

Class B Autoclave

STB-B18-3C

STB-B23-3C



Features

- ◆ Based on the new class B, have 3 pulsating vacuum, vacuum up to -0.9bar (-0.09 MPa). Residual humidity is $<0.2\%$. Suitable to sterilizing wrap, unwrap, solid, porous, hollow device.
- ◆ Use imported & advanced 16-bit microprocessor, easy to operate. Suitable for the Dept of Stomatology, Ophthalmology, Surgery and Lab.
- ◆ Equipped with B&D test and vacuum test procedures. To test the penetrability.
- ◆ Chamber punched by stainless steel (#304, thickness: 2.5mm), together with the jet type of steam generator, ensures the efficient sterilizing. With alarm system for waste water tank, it avoid the waste water entering into the sterilizing circulation and make the sterilization completely.
- Precise LCD display and advanced self-test system ensure you get the working data freely.
- ◆ Double lock door system for safety during operation.
- ◆ The new design of water tank is on the top, easy to clean.
- ◆ Built-in printer.
- ◆ Optional USB function.

Specifications

Model	STB-B18-3C	STB-B23-3C
Power	1800 W	2000 W
Voltage	AC220V/110V $\pm 10\%$	AC220V/110V $\pm 10\%$
Frequency	50/60Hz $\pm 1\text{Hz}$	50/60Hz $\pm 1\text{Hz}$
Tank Capacity	18Litres	23Litres
Display Accuracy	$\pm 0.5\text{ }^{\circ}\text{C}$	$\pm 0.5\text{ }^{\circ}\text{C}$
Recording Accuracy	$\pm 0.5\text{ }^{\circ}\text{C}$	$\pm 0.5\text{ }^{\circ}\text{C}$
Sensor Accuracy	0.01 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$
Appearance Size (mm)	480 \times 560 \times 420	480 \times 630 \times 420
Inside Dimension (mm)	$\Phi 249 \times 355$	$\Phi 249 \times 450$
Shipping Dimension (W*D*H) (mm)	670 \times 580 \times 520	730 \times 600 \times 500
N.W. / G.W. (kg)	40/47	47/52