

BCS-P-TIP14FSR3L3-Ai1

Index: **13069** GTIN13/EAN13: 5904890716933

URL: <https://bcs.pl/gb/4mpx/4687-bcs-p-tip14fsr3l3-ai1-5904890716933.html>



BCS-P-TIP14FSR3L3-Ai1

Product Details

Product	BCS-P-TIP14FSR3L3-Ai1
Brand	BCS POINT
NDAA	National Defense Authorization Act
Camera type	Bullet
Resolution	4 Mpx
Sensor	1/3" CMOS
Scanning system	Progressive Scan
Pixels	2688(H)×1520(V)
Lens	fixed
Focal length	2.8 mm
Aperture	F1.6
Focus	fixed
Iris	fixed
Angle of view	H: 97° V: 52.2° D: 107.5°
DORI	Detect 63m / Observe 25.2m / Recognize 12.6m / Identify 6.3m
Min illumination	0.003Lux(F1.6,AGC) 0Lux(B/W,IR)
S/N ratio	52dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	2D/3D DNR
Roi	Region of Interest
Defog	Digital
Image rotate	Mirror, Flip 0°/90°/180°/270°
Stream support	2
Resolutions	4M(2688×1520)(2560×1440) / 3M(2304×1296) / 2M(1920×1080) / 720P(1280×720) / D1(720×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
Main stream	2688×1520@25fps 2560×1440@25fps 2304×1296@30fps 1920×1080@30fps 1280×720@30fps
Second stream	720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
Bitrate	128Kbps~16Mbps
Video compression	H.265 / H.265+ / H.264 / MJPEG
Day/night	ICR
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
NightColor	Yes
Microphone	Yes
Loudspeaker	Yes
Audio compression	G.711A / G.711U
Storage	NAS(NFS)

Memory card slot	microSD 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP, QoS
Network security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic/digest authentication RTSP, Digest authentication HTTP, TLS 1.2, WSSE/digest authentication ONVIF
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 9W
Housing color	White
IP class	IP67
Surge protection	4kV
Working environment	-30°C~+60°C max 95% RH
Dimensions	192×75×74mm
Weight	0.4kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Recognition of people entering the area and crossing the line reduces false alarms.
Ai - SMD - Smart Motion Detection	Intelligent Ultra Motion Detection with human/vehicle recognition

BCS-P-TIP14FSR3L3-Ai1

Accessories

BCS-P-A81



BCS-ADU100



BCS-ADU125

