

AML760/760

Operating Lamp

(LED Shadowless)



Features

- Uniform, homogeneous lighting in surface and deep cavity procedures thanks to 760 LED's innovative shadow control
- Our ergonomic, sterile operating concept allows for the simple and flexible control of all functions by the surgical team.
- Almost unlimited LED life expectancy delivers tremendous product reliability and investment protection.
- Environmentally proactive: low power consumption and durable LEDs minimize the impact on our precious resources.

Technical Specifications

PARAMETER	SPECIFICATION
Illuminance	$\geq 160,000\text{Lux}$ / $\geq 160,000\text{Lux}$
Color Temperature	4500 \pm 200K
Color Reduction Index (Ra)	96 \pm 2
Illuminance Depth	700mm / 700mm
Total Irradiance	510W/m ²
Size of Light Field	180~260mm
Lamp Head Diameter	760mm / 760mm
Rated Power of Bulb	3.2V/1W
Service Life of Illuminant	50,000h
Power Supply Voltage	AC110-240v, 50/60Hz
Lowest Height of Installatio	2900mm
Total Power Consumption	200W
Total LED Bulb Quantity	262pcs



Add: Block B, CC Park, No.728 Lanzhou Road, Baohe Industrial Zone, Hefei, China.

Tel: 0086-551-63802963

Fax: 0086-551-63802920

Web: www.ari-cn.com

Email: sales@ari-cn.com