

 **algaflex**
Connection lines

- Wide range of connection lines to meet all your needs



Features & benefits

DESIGNED FOR 1200 PSI (83 BARS) OR 300 PSI (21 BARS)

- For low and high pressure injections

LENGTHS

- From 30 cm to 200 cm

NYLON BRAIDED, PU OR PVC

ROTATING, FIXED OR SPINLOCK ADAPTORS

References

High pressure lines (1200 psi)

References	Length (cm)	Designation	Packaging
0163NA	50	Nylon braided Polyurethane (PU) lines Rotating male Luer-lock + Inner diameter: 1.8mm	30/box
0163NB	75		
0163NC	100		
0163ND	120		
0163TP	150		
0163TU	200		
0163NF	75	Nylon braided Polyurethane (PU) lines Fixed male Luer-lock + Inner diameter: 1.8mm	
0163NH	120		
0163TR	150		
0163TM	180		

References	Length (cm)	Designation	Packaging
0209NF	50	Polyurethane (PU) lines Rotating male Luer lock + Inner diameter: 1.7mm	30/box
0209NG	75		
0209NH	100		
0209NK	120		
0209NL	150		
0209NM	180		

Low pressure lines (300 psi)

References	Length (cm)	Designation	Packaging
0163PP	30	Polyvinyl chloride (PVC) lines + Spinlock male Luer-lock Inner diameter: 2.0mm	50/box
0163PQ	50		
0163PR	75		
0163PM	100		
0163PS	150		
0163NP	30	Polyvinyl chloride (PVC) lines + Fixed male Luer-lock + Inner diameter: 2.0mm	
0163NR	40		
0163NT	100		
0163PL	150		
0163NQ	180		

Low pressure coiled lines (300 psi)

References	Length (cm)	Designation	Packaging
0163QA	150	Polyvinyl chloride (PVC) line Fixed male Luer-lock + Inner diameter: 1.4mm	50/box
0163QD	150	Polyvinyl chloride (PVC) line with non-return valve Fixed male Luer-lock + Inner diameter: 1.4mm	

Please read carefully the Instructions For Use. The CE conformity assessment has been conducted by LNE-GMED (0459).