



FAZZINI

Your Health is Our Aim

Fazzini srl
S.S. Padana Superiore, 317-20055
Vimodrone-Milano-ITALY
Tel. 022651521 - Fax 0226515221
info@fazzini.it - www.fazzini.it

HIGH VACUUM SUCTION PUMP WITH MANUAL CHANGEOVER VALVE

F-100R	2 x 2 lt.
F-100R/F	2 x 2 lt. Footswitch
F-100R/4	2 x 4 lt.
F-100R/F4	2 x 4 lt. Footswitch



DIMENSIONS:

Length: 46 cm

Height: 42 cm

Width: 48 cm

Weight: 18 kg

STANDARD ACCESSORIES:

Two autoclavable jars with overflow valve, capacity 2 or 4 lt (cod.05.0002 or 05.0004)

Disposable antibacterial hydrophobic filter (cod.05.0016)

Set of silicone tubes (code 05.00077)

Connector (cod.05.00063)

Disposable suction catheter size CH18 (cod. 05.0014)

Power cable

User manual

Foot pedal predisposition (Foot switch pedal optional)

GENERAL FEATURES:

High vacuum mobile suction machine for professional use, with powerful double piston metal motor.
ABS anti-shock case. Four antistatic castors, two of which with brakes.

Vacuum gauge for the control of vacuum.

Vacuum regulator.

Standard configuration with two jars of 2 lt. capacity made of Makrolon autoclavable.

Each jar with overflow valve.

Independent use of each jar.

Supplied with disposable antibacterial hydrophobic filter and set of silicon tubes.

TECHNICAL FEATURES:

Motor: Maintenance Oil free piston pump

Power supply: 230V/50-60Hz (414 VA)

Suction power: 80 l/min

Max vacuum: from 0 to -0,90 bar / 675 mmHg / -90 kPa

CONFORMITY:

93/42/CEE - 2007/47/CE CND Z120105

CEI EN 60601-1 CEI EN 60601-1-2