

POWERSTAR TRUCKS INDUSTRY CO., LIMITED



ISUZU Garbage Compactor Truck Specification

Vehicle Brand	POWERSTAR		Chassis brand: ISUZU ELF	
Vehicle Main	Overall dimensions (L x W x H) mm		6800x2400x3500	
Dimensions	Wheelbase (mm)		3815	
Weight in KGS	Gross Weight		13000	
	Payload Weight		10 Tons	
	Front /Rear axles loading capacity		4000 / 7000	
Cab	ISUZU 3D cab, with A/C and 2 seats, Forward control, all steel welded construction. Manual tilt, Mechanical suspension			
Driving type	4x2 left hand drive, 6 wheels			
Engine	Model		ISUZU 4HK1	
	Horse Power (HP)		190 HP	
	Emission standard		Euro 6(5.19L)	
Gearbox	MLD 6-shift transmission, Manual, 6-speed forward, 1 reverse gears			
Fuel tank (L)	140L			
Tire	235/75R17.5 tire 6 pcs including one spare tire			
Upper body				
Body Capacity	10 CBM	Hopper Capacity		1.5 cbm
Body Material	Weather Resisting Steel	Sewage Tank		200L + 100L
Compressing Ration	≥ 1:3.4	Working zone Lighting		2 lamps
Dust Bin Lifter	2 bins 240L	Control		Siemens Automatic-PLC system
	Optional 1100L,660L			Manual, semi-automatic, automatic
Loading Cycle Time	15 ~ 20 sec	Foot Stands		2 sets
Discharging Time	10 ∼18 sec	Painting		Two primers, and one final paint coating
Discharging system	Horizontal ejection	Color and Logo		According to wish
Standard equipment	"U" shape Sub Frame, Hydraulic system, Ejector panel, Safety protection, Rotating Lamp, Working Lamp, Hand holds.			

























Tailgate lifting



Slide Plate & Scraper







PLC Modular control box



