

Tracheal Tube

Cuffed

- ▶ For both oral and nasal intubation
- ▶ Atraumatic, soft rounded, beveled tip
- ▶ Murphy eye
- ▶ Accurate positioning depth marks
- ▶ Radiopaque line
- ▶ Standard volume, low pressure cuff
- ▶ Special cuff design provides an efficient low pressure seal
- ▶ Valve integrated pilot pressure cuff with designated size and nominal outside diameter markings
- ▶ Standard connector
- ▶ Pre-assembled stylet option for easier intubation of the tracheal tube

| Ref            |             | Size | I.D. (mm) | O.D. (mm) |
|----------------|-------------|------|-----------|-----------|
| Without Stylet | With Stylet |      |           |           |
| 551 0030 1     | 551 1030 1  | 3.0  | 3.0       | 4.5       |
| 551 0035 1     | 551 1035 1  | 3.5  | 3.5       | 5.2       |
| 551 0040 1     | 551 1040 1  | 4.0  | 4.0       | 5.9       |
| 551 0045 1     | 551 1045 1  | 4.5  | 4.5       | 6.5       |
| 551 0050 1     | 551 1050 1  | 5.0  | 5.0       | 7.1       |
| 551 0055 1     | 551 1055 1  | 5.5  | 5.5       | 7.7       |
| 551 0060 1     | 551 1060 1  | 6.0  | 6.0       | 8.4       |
| 551 0065 1     | 551 1065 1  | 6.5  | 6.5       | 9.1       |
| 551 0070 1     | 551 1070 1  | 7.0  | 7.0       | 9.8       |
| 551 0075 1     | 551 1075 1  | 7.5  | 7.5       | 10.3      |
| 551 0080 1     | 551 1080 1  | 8.0  | 8.0       | 11.0      |
| 551 0085 1     | 551 1085 1  | 8.5  | 8.5       | 11.4      |
| 551 0090 1     | 551 1090 1  | 9.0  | 9.0       | 12.0      |
| 551 0095 1     | 551 1095 1  | 9.5  | 9.5       | 12.6      |
| 551 0100 1     | 551 1100 1  | 10.0 | 10.0      | 13.3      |



Tracheal Tube

Uncuffed

- ▶ For both oral and nasal intubation
- ▶ Atraumatic, soft rounded, beveled tip
- ▶ Murphy eye
- ▶ Accurate positioning depth marks
- ▶ Vocal cord markings
- ▶ Radiopaque line
- ▶ Standard connector

| Ref        | Size | I.D. (mm) | O.D. (mm) |
|------------|------|-----------|-----------|
| 550 0020 1 | 2.0  | 2.0       | 3.0       |
| 550 0025 1 | 2.5  | 2.5       | 3.8       |
| 550 0030 1 | 3.0  | 3.0       | 4.5       |
| 550 0035 1 | 3.5  | 3.5       | 5.2       |
| 550 0040 1 | 4.0  | 4.0       | 5.9       |
| 550 0045 1 | 4.5  | 4.5       | 6.5       |
| 550 0050 1 | 5.0  | 5.0       | 7.1       |
| 550 0055 1 | 5.5  | 5.5       | 7.7       |
| 550 0060 1 | 6.0  | 6.0       | 8.4       |
| 550 0065 1 | 6.5  | 6.5       | 9.1       |
| 550 0070 1 | 7.0  | 7.0       | 9.8       |



## Tracheostomy Tube

### Cuffed

- ▶ Swivel 15 mm connector provides easy handling
- ▶ Flexible neckplate with slits for strap insertion providing secure positioning
- ▶ Designated size and nominal outside diameter markings on the neckplate
- ▶ Reliable inflation apparatus comprising of inflating tube, pilot balloon, and a check-valve with luer connection
- ▶ Soft, thin-walled, high-volume, low-pressure cuff
- ▶ Atraumatic, soft rounded tip, transparent, curved cannula
- ▶ Clear radiopaque line facilitates to help spatial positioning
- ▶ Obturator to prevent tissue drag and lumen obstruction



| Ref        | Size | Length (mm) |
|------------|------|-------------|
| 555 0050 1 | 5.0  | 57          |
| 555 0055 1 | 5.5  | 57          |
| 555 0060 1 | 6.0  | 55          |
| 555 0065 1 | 6.5  | 61          |
| 555 0070 1 | 7.0  | 67          |
| 555 0075 1 | 7.5  | 73          |
| 555 0080 1 | 8.0  | 80          |
| 555 0085 1 | 8.5  | 84          |
| 555 0090 1 | 9.0  | 91          |
| 555 0095 1 | 9.5  | 94          |
| 555 0100 1 | 10.0 | 94          |

## Tracheostomy Tube

### Uncuffed

- ▶ Swivel 15 mm connector provides easy handling
- ▶ Flexible neckplate with slits for strap insertion providing secure positioning
- ▶ Designated size and nominal outside diameter markings on the neckplate
- ▶ Atraumatic, soft rounded tip, transparent, curved cannula
- ▶ Clear radiopaque line facilitates to help spatial positioning
- ▶ Obturator to prevent tissue drag and lumen obstruction



| Ref        | Size | Length (mm) |
|------------|------|-------------|
| 556 0050 1 | 5.0  | 57          |
| 556 0055 1 | 5.5  | 57          |
| 556 0060 1 | 6.0  | 55          |
| 556 0065 1 | 6.5  | 61          |
| 556 0070 1 | 7.0  | 67          |
| 556 0075 1 | 7.5  | 73          |
| 556 0080 1 | 8.0  | 80          |
| 556 0085 1 | 8.5  | 84          |
| 556 0090 1 | 9.0  | 91          |
| 556 0095 1 | 9.5  | 94          |
| 556 0100 1 | 10.0 | 94          |

## Thoracic Catheter

### With Trocar, Standard Tip

- ▶ Trocar with tri-faceted cutting tip
- ▶ Flexible tubing wall provides leak proof tissue/tubing interface and easy milking
- ▶ Tapered tip for easy and safe insertion
- ▶ Cross side eyes to prevent tissue aspiration
- ▶ Radiopaque line
- ▶ Accurate positioning depth marks at each cm starting 2 cm from the distal end
- ▶ Integral large bore tapered connector



| Ref        | Size  | Length |
|------------|-------|--------|
| 184 1201 1 | 12 Ch | 225 mm |
| 184 1601 1 | 16 Ch | 235 mm |
| 184 2001 1 | 20 Ch | 390 mm |
| 184 2401 1 | 24 Ch | 390 mm |
| 184 2801 1 | 28 Ch | 390 mm |
| 184 3201 1 | 32 Ch | 390 mm |



## Thoracic Catheter

- ▶ Flexible tubing wall provides leak proof tissue/tubing interface
- ▶ Atraumatic, rounded, open distal tip
- ▶ Easy to milk
- ▶ Cross side eyes to prevent tissue aspiration
- ▶ Radiopaque line
- ▶ Accurate positioning depth marks at each cm starting 2 cm from the distal end
- ▶ Flared end to accept different sized connectors
- ▶ Straight or right angled design
- ▶ Length: 52 cm

| Ref        |            | Size  |
|------------|------------|-------|
| Straight   | Angled     |       |
| 180 1201 1 | 182 1201 1 | 12 Ch |
| 180 1601 1 | 182 1601 1 | 16 Ch |
| 180 2001 1 | 182 2001 1 | 20 Ch |
| 180 2401 1 | 182 2401 1 | 24 Ch |
| 180 2801 1 | 182 2801 1 | 28 Ch |
| 180 3201 1 | 182 3201 1 | 32 Ch |
| 180 3601 1 | 182 3601 1 | 36 Ch |
| 180 4001 1 | 182 4001 1 | 40 Ch |



## Vaginal Speculum II

- ▶ Designed for patient comfort and easy to use
- ▶ Clear body providing good visualization of the cervix
- ▶ Wide aperture with support frame
- ▶ Aperture  $\geq 3\text{cm}$
- ▶ Secure stepped locking mechanism
- ▶ Ergonomic design with anti-pinch gaps and smooth rounded blades
- ▶ Retains an opening force of 45N
- ▶ Color coded size indication



| Ref        |             | Size   |
|------------|-------------|--------|
| Sterile    | Non-Sterile |        |
| 595 1021 1 | 595 1021 2  | Small  |
| 595 1022 1 | 595 1022 2  | Medium |
| 595 1023 1 | 595 1023 2  | Large  |

## Umbilical Cord Clamp

- ▶ Lock security to prevent accidental opening
- ▶ Solid grip with toothed design
- ▶ Rounded edges to prevent skin irritation



| Ref        |
|------------|
| 230 0001 1 |

## Three Way Stopcock

- ▶ For pressures up to 5 bar (72 PSI)
- ▶ 360° rotation
- ▶ Color coded arrows indicating flow direction
- ▶ Transparent housing
- ▶ Rotating male luer lock and two female luer lock connectors
- ▶ Lipid Resistance

| Ref        | Color                                                                                   |
|------------|-----------------------------------------------------------------------------------------|
| 760 3011 1 | White  |
| 760 3031 1 | Blue   |
| 760 3041 1 | Red    |



## Three Way Stopcock

1200 PSI

- ▶ For pressures up to 83 bar (1200 PSI)
- ▶ 180° rotation
- ▶ Arrows indicating flow direction
- ▶ Transparent housing
- ▶ Rotating male luer lock and two female luer lock connectors



| Ref        |
|------------|
| 760 3111 1 |

## Manifold

- ▶ Flat with cross handle
- ▶ Pressure tested
- ▶ Arrows to indicate the direction of flow
- ▶ Clear housing for maximal visual inspection
- ▶ Color coded
- ▶ Female luer connectors

| Ref        |        |
|------------|--------|
| 765 0301 1 | Trio   |
| 765 0501 1 | Quinto |



## Manifold

Pressure

- ▶ For pressures up to 41 bar (600 PSI)
- ▶ Arrows to indicate the direction of flow
- ▶ Clear housing for maximal visual inspection
- ▶ Rotating male luer and female luer connectors



| Ref        | Position |
|------------|----------|
| 765 1301 1 | Right    |

## Extension Line

### 250 PSI

- ▶ For pressures up to 17 bar (250 PSI)
- ▶ Ø 3.0 x 4.1 mm tubing
- ▶ Luer lock connector



| Ref        |            | Length |
|------------|------------|--------|
| M/F        | M/M        |        |
| 120 1030 1 | 120 2030 1 | 30 cm  |
| 120 1050 1 | 120 2050 1 | 50 cm  |
| 120 1060 1 | 120 2060 1 | 60 cm  |
| 120 1075 1 | 120 2075 1 | 75 cm  |
| 120 1090 1 | 120 2090 1 | 90 cm  |
| 120 1100 1 | 120 2100 1 | 100 cm |
| 120 1120 1 | 120 2120 1 | 120 cm |
| 120 1145 1 | 120 2145 1 | 145 cm |
| 120 1150 1 | 120 2150 1 | 150 cm |

## Extension Line

### Smallbore - 250 PSI

- ▶ For pressures up to 17 bar (250 PSI)
- ▶ Ø 1.2 x 2.5 mm tubing
- ▶ Luer lock connector



| Ref        |            | Length |
|------------|------------|--------|
| M/F        | M/M        |        |
| 012 7050 1 | 012 8050 1 | 50 cm  |
| 012 7100 1 | 012 8100 1 | 100 cm |
| 012 7150 1 | 012 8150 1 | 150 cm |