

HBY-4 HOSPITAL BED WITH 4 MOTORS TECHNICAL DETAILS

- Overall Length :2200 mm
- Overall Width : 1100 mm
- Height Range : 4000-760 mm
- Trendelenburg (Max) : 16,5°
- Reverse trendelenburg (Max): 17,5°
- Backrest angle (Max) 71°
- Legrest Angle (Max.): 30°
- Castor Diameter : 125 mm
- Safe working load: 230 kg

SPECIFICATIONS

- Electrical operated backrest, height and legrest adjustment.
- Electrical operated trendelenburg, reverse trendelenburg, fowler and vascular position.
- Patient handset.
- Nurse control unit. Blocking patient control (O)*
- Auto-CPR. (O)*
- Hygienic design (PP), lockable and tuck away siderails.
- Profile frame with easy removable ABS plastic covers.
- Removable head and foot ends.
- Cross lockable castors
- Electrostatic painted metal frame.
- Central brake castors (O)*
- Height adjustable serum holder
- Easy adjustable knee break position.
- Plastic crash bumpers.
- Battery Back-uo. (O)*
- Dual sided manual CPR at backrest. (O)*
- Cardiac chair position with one button. (O)*
- Shock position with one button. (O)*
- Bed exit position with one button.
- Examination position with one button.
- Washable / orthopedic mattresses
- Dual sided control panel on side -rails. (O)*
- Lifting Pole. (O)*
- X-Ray translucent backrest and cassette carrier. (O)*
- Underbed light. (O)*



(O) : Opsiyonel

HBY-4 HOSPITAL BED WITH 4 MOTORS

SPECIFICATIONS

- Built-in manual CPR function on both side.
- Height adjustment min. 40-76 cm.
- Side grid integrated control for the nurse on the outside of the side grid and for the patient on the inside of the side grid.
- Indication of the lowest position determination on the controller or intelligent night light that clearly indicates the lowest position.
- Autocontour function (raising/lowering the backrest also automatically raises / lower the upper leg to prevent the patient from slipping on the bed).
- When raising / lowering the backrest, the automatic rise / lower of the upper leg starts with backrest movement.
- Side grilles with a plastic surface running along the length of the bed.
- Auto regression function (when raising the backrest, the pelvic part moves horizontally at least towards the the head) min. 10cm.
- Split spring grilles with gas spring damping, which allow one-handed opening without the use separate release.
- The space required to lower the side grilles next to the bed is max. 4 cm.
- Battery-operated with built-in battery.
- Bed structure desing with powder-coated or frame-painted metal.
- The lying surface is washable and disinfected plastic and / or metal.
- Removable headboards.
- Roller stops at the 4 corners.

SPECIFICATIONS

- The removable back of the bed can latterbe replaced at any time by the staff on the back with an integrated X-ray cassette holder, which allows chest X-rays to be taken.
- Removable headboards.
- Lying surface or electric bed extension that can be extended without separate removal of a thumbscrew or other fastening element, extent of extension min. 20cm.
- Bed extension min. Can be fxd in 4 position in addition to the basic lenght or electric bed extension.
- Bed enclosure size max. 220 x 100 cm.
- Wheel diameter min 15 cm.
- If necessary, the wheels can be replaced by removing them horizontally from the axle.
- Foot-operated central three position brake pedal.
- Backrest angle display and trendelenburg angle display integrated in the side grille on both side of the bed.
- Mattress delimeters integrated n the bed surface,adjustable to the width of mattresses of different size.
- Training for fastening straps.
- Bed capacity min. 220 kg.
- Lying surface size min. 195 x 85 cm.
- Min. per page 4 urine bag holders that can be moved on the medical rail system on the bed frame.



(O) : Opsiyonel

HBY-4 HOSPITAL BED WITH 4 MOTORS

MANDATORY ACCESSORIES PER BED

- Visco mattress thickness range: min. 12cm.
- Infusion stand with 4 hooks, minimum load capacity 8kg (2-2 kg per hook).
-



(O) : Opsiyonel