




Manufacturer: BAS STEEL PROFILE SRL str.Vozcalinaia 28, Taraclia, Moldova Phone:+373 78 436 481		A01	MILL'S TEST CERTIFICATE (ACC.TO EN10204 / 3.1)		A02	Transport: A10 				
Customer: BIMETCOM		A06	No. 1312 Date: 20.02.2023		A03	AIT023/A023IT				
Contract No. 4C-22 Specification № 0010/4C-22 Order No. 0012/4C-22 Destination Moldova		A07	B03-B06 Welded cold sized tubes STEEL Grade S235JRH, Direct welded Package wrapped with 6 straps through the side 100% NDT on the weld seam. NDT on the weld seam acc. EN ISO 1088 , Plain ends, straight cut from mill		B03-B06	B12	Total weight, Kg 23228	Total Length, m 10 098,00 (meters)	B08 Pieces: 1683	Bundles: 22
						EN 10219-1/2 S235JRH		 2174		


		B09		B10	Steel	B07	Heat	Mechanical Test		C11	C12	C13	D02	D03
Dimension(mm)		W.T.(mm)		Grade	Nr. Bundles		Direction of the	C02	C03	ReH	Rm	A	Ra	Hydraulic
							test pieces	temperature	Test				µm	sure, bar,min.
40x25		2	S235JRH	0857	V23		1212308	L	ambient	304	407	29	-	
40x25		2	S235JRH	0795	V23		130053	L	ambient	289	417	30	-	
40x25		2	S235JRH	0856	V23		1212291	L	ambient	343	451	25	-	
50x50		2	S235JRH	1162	V23		122526-9	L	ambient	319	427	31	-	
50x50		2	S235JRH	1149	V23		122426-9	L	ambient	289	412	28	-	
50x50		2	S235JRH	1150	V23		122526-9	L	ambient	319	427	31	-	
50x50		2	S235JRH	1151	V23		122426	L	ambient	294	412	27	-	
50x50		2	S235JRH	1152	V23		122426	L	ambient	294	412	27	-	
50x50		2	S235JRH	1153	V23		122426	L	ambient	294	412	27	-	
50x50		2	S235JRH	1154	V23		122426	L	ambient	294	412	27	-	
50x50		2	S235JRH	1155	V23		122426-9	L	ambient	289	412	28	-	
40x40		2	S235JRH	1276	V23		130111-9	L	ambient	314	397	30	-	
40x40		2	S235JRH	1275	V23		130111-9	L	ambient	314	397	30	-	
40x40		2	S235JRH	1274	V23		130111-9	L	ambient	314	397	30	-	
40x40		2	S235JRH	1216	V23		130111-9	L	ambient	314	397	30	-	
40x40		2	S235JRH	1215	V23		130161	L	ambient	289	397	29	-	
40x40		2	S235JRH	1214	V23		130111-9	L	ambient	314	397	30	-	
40x40		2	S235JRH	1213	V23		130111-9	L	ambient	314	397	30	-	
40x40		2	S235JRH	1212	V23		130111-9	L	ambient	314	397	30	-	
40x40		2	S235JRH	1209	V23		130161	L	ambient	289	397	29	-	
40x40		2	S235JRH	1208	V23		713026	L	ambient	284	412	33	-	
40x40		2	S235JRH	1207	V23		713026	L	ambient	284	412	33	-	



We state on our sole responsibility that the delivered products are in conformity with production standards or with contract Addendums.
 Visual inspection: checked without any objection
 Tolerances on dimensions and shape: pass

Drawn up,
 Eng.Filip Nicolai






Signature of the OCD representative,
 Eng.Mekit Yuzii



Manufacturer: BAS STEEL PROFILE SRL str.Vozalinalia 28, Taraclia, Moldova Phone:+373 78 436 481		MILL'S TEST CERTIFICATE (ACC.TO EN10204 / 3.1)		Transport: A10 A03 A1023/A023IT									
Customer: BIMETCOM		No. 1312 Date: 20.02.2023		B03-B06		B12 Total weight, Kg 23228		Total Length, m 10 098,00 (meters)		B08 Pieces: 1683		Bundles: 22	
Contract No. 4C-22 Specification № 0010/4C-22 Order No. Destination Moldova		0012/4C-22		A06 Welded cold sized tubes STEEL Grade S235JRH, Direct welded		A07 Package wrapped with 6 straps through the side 100% NDT on the weld seam. NDT on the weld seam acc. EN ISO 1088 ,		EN 10219-1/2 S235JRH		 2174			
				Plain ends, straight cut from mill									

				Chemical Composition					C71-C92						
B09	B08	Steel	B07	Heat	C	Si	Mn	S	P	Cr	Ni	Cu	As	N	Al
Dimension(mm)	W.T.(mm)	Grade	Nr. Bundles		x100	x100	x100	x1000	x1000	x100	x100	x100	x100	x1000	x1000
40x25		2 S235JRH	0857\23	1212308	11,0	1,8	44,0	32,0	14,0	6,0	1,0	1,0	x100	x1000	x1000
40x25		2 S235JRH	0795\23	130053	12,0	1,5	43,0	24,0	26,0	5,0	2,0	1,0		9	
40x25		2 S235JRH	0856\23	1212291	13,0	1,3	48,0	30,0	30,0	5,0	1,0	1,0		9	
50x50		2 S235JRH	1162\23	122526-9	13,0	1,4	44,0	34,0	20,0	5,0	1,0	1,0		9	
50x50		2 S235JRH	1149\23	122426-9	12,0	1,6	45,0	31,0	22,0	4,0	1,0	1,0		9	
50x50		2 S235JRH	1150\23	122526-9	13,0	1,4	44,0	34,0	20,0	5,0	1,0	1,0		9	
50x50		2 S235JRH	1151\23	122426	12,0	1,6	45,0	31,0	22,0	4,0	1,0	1,0		9	
50x50		2 S235JRH	1152\23	122426	12,0	1,6	45,0	31,0	22,0	4,0	1,0	1,0		9	
50x50		2 S235JRH	1153\23	122426	12,0	1,6	45,0	31,0	22,0	4,0	1,0	1,0		9	
50x50		2 S235JRH	1154\23	122426	12,0	1,6	45,0	31,0	22,0	4,0	1,0	1,0		9	
50x50		2 S235JRH	1155\23	122426-9	12,0	1,6	45,0	31,0	22,0	4,0	1,0	1,0		9	
40x40		2 S235JRH	1276\23	130111-9	10,0	1,8	40,0	32,0	19,0	7,0	2,0	2,0		9	
40x40		2 S235JRH	1275\23	130111-9	10,0	1,8	40,0	32,0	19,0	7,0	2,0	2,0		9	
40x40		2 S235JRH	1274\23	130111-9	10,0	1,8	40,0	32,0	19,0	7,0	2,0	2,0		9	
40x40		2 S235JRH	1216\23	130111-9	10,0	1,8	40,0	32,0	19,0	7,0	2,0	2,0		9	
40x40		2 S235JRH	1215\23	130161	10,0	1,6	38,0	32,0	25,0	6,0	1,0	1,0		9	
40x40		2 S235JRH	1214\23	130111-9	10,0	1,8	40,0	32,0	19,0	7,0	2,0	2,0		9	
40x40		2 S235JRH	1213\23	130111-9	10,0	1,8	40,0	32,0	19,0	7,0	2,0	2,0		9	
40x40		2 S235JRH	1212\23	130111-9	10,0	1,8	40,0	32,0	19,0	7,0	2,0	2,0		9	
40x40		2 S235JRH	1209\23	130161	10,0	1,6	38,0	32,0	25,0	6,0	1,0	1,0		9	
40x40		2 S235JRH	1208\23	713026	13,0	1,7	43,0	25,0	23,0	6,0	2,0	1,0		9	
40x40		2 S235JRH	1207\23	713026	13,0	1,7	43,0	25,0	23,0	6,0	2,0	1,0		9	



Manufacturer: BAS STEEL PROFILE SRL str.Vozcalinaia 28, Taraclia, Moldova Phone:+373 78 436 481		MILL'S TEST CERTIFICATE (ACC.TO EN10204 / 3.1)		Transport: A10 A03 AIT023/A023IT							
Customer: BIMETCOM		No. 1312 Date: 20.02.2023		B03-B06		B12 Total weight, Kg 23228		Total Length, m 10 098,00 (meters)		B08 Pieces: 1683 Bundles: 22	
Contract No. 4C-22 Specification № 0010/4C-22 Order No. Destination Moldova		A06 Welded cold sized tubes STEEL Grade S235JRH, Direct welded		A07 Package wrapped with 6 straps through the side 100% NDT on the weld seam. NDT on the weld seam acc. EN ISO 1088 ,		EN 10219-1/2 S235JRH				2174	

Product description

Nr.	B07		Product	B01-B02	B09	B10	B11	Deviation	B08		B12	B13
	Nr. Bundles	Heat							Bundles	Pieces	Netto Weight (Kg)	Brutto weight, kg
1	0857/23	1212308	S235JRH-EN 10219-1/2	40x25	2	6 000	+50/-0	1	108	1134	-	648
2	0795/23	130053	S235JRH-EN 10219-1/2	40x25	2	6 000	+50/-0	1	108	1170	-	648
3	0856/23	1212291	S235JRH-EN 10219-1/2	40x25	2	6 000	+50/-0	1	108	1150	-	648
4	1162/23	122526-9	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	38	632	-	228
5	1149/23	122426-9	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	63	1066	-	378
6	1150/23	122526-9	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	63	1038	-	378
7	1151/23	122426	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	63	1050	-	378
8	1152/23	122426	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	63	1057	-	378
9	1153/23	122426	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	63	1052	-	378
10	1154/23	122426	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	63	1053	-	378
11	1155/23	122426-9	S235JRH-EN 10219-1/2	50x50	2	6 000	+50/-0	1	63	1042	-	378
12	1276/23	130111-9	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1072	-	480
13	1275/23	130111-9	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1078	-	480
14	1274/23	130111-9	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1062	-	480
15	1216/23	130111-9	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1079	-	480
16	1215/23	130161	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1072	-	480
17	1214/23	130111-9	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1071	-	480
18	1213/23	130111-9	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1070	-	480
19	1212/23	130111-9	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1076	-	480
20	1209/23	130161	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1074	-	480
21	1208/23	713026	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1075	-	480
22	1207/23	713026	S235JRH-EN 10219-1/2	40x40	2	6 000	+50/-0	1	80	1055	-	480

