

imageRUNNER ADVANCE DX C3700 Series

EVOLVE YOUR BUSINESS' DIGITISATION WITH AUTOMATED WORKFLOWS FROM SMART COLOUR A3 MULTIFUNCTION DEVICES




Canon uniFLOW Online
Outstanding Cloud Output Management Solution



New to the Line

MAIN CONFIGURATION OPTIONS



This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online [product configurator](#).

The Unified Firmware Platform (UFP) ensures that the latest feature upgrades and protection are available, for an enhanced user experience across the entire iR ADVANCE DX portfolio.

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C3700 Series

MAIN UNIT

Machine type	A3 Colour Laser Multifunctional
Core functions	Print, Copy, Scan, Send, Store and Optional Fax
Processor	1.75GHz Dual Core Processor
Control Panel	10.1" TFT LCD WSVGA Colour Touch panel
Memory	Standard: 3.0GB RAM
Hard Disk drive	Standard*: 320 GB (available disk space: 250 GB), Optional: 250GB, 1TB * A different initial HDD may be used.
Interface Connection	NETWORK Standard: 100Base-T/100Base-TX/10Base-T, Wireless LAN(IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy OTHERS Standard: USB 2.0(Host) x1, USB 3.0(Host) x1, USB 2.0(Device) x1 Optional: Serial Interface, Copy Control Interface
Paper Supply Capacity (A4, 80gsm)	Standard: 1,200 sheets 2 x 550-sheet cassettes 100-sheet multi-purpose tray Maximum: 2,300 sheets (with Cassette Feeding Unit-AP1)
Paper output capacity (A4, 80gsm)	Standard: 250 sheets Maximum: 3,450 sheets (with Staple Finisher-AA1/Booklet Finisher-AA1 and Copy Tray-J2)
Finishing capabilities	With options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand
Supported media types	Multi-purpose tray: Thin, Plain, Heavy*, Recycled, Coated*, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Envelope * SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm) paper. Paper Cassettes (Upper): Thin, Plain, Heavy*, Recycled, Coated*, Colour, Tracing, Bond, Transparency, Pre-punched, Envelope * SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm) paper. Paper Cassettes (Lower): Thin, Plain, Heavy, Recycled, Color, Bond, Transparency, Pre-punched, Envelope* * Envelope Feeder Attachment A is required.
Supported media sizes	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Free size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Envelopes: COM10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm Envelopes: ISO-C5 Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes*: COM10 No.10, Monarch, DL * Envelope Attachment A (standard) is required.
Supported media weights	Multi-purpose tray: 52 to 300 gsm* *SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm) paper. Paper Cassettes (Upper/Lower): 52 to 220 gsm Duplex: 52 to 220 gsm
Warm-up Time	Quick startup mode: 4 seconds or less* *Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 10 Seconds or Less From Power On: 10 seconds or less* *Time from device power-on, until copy ready (not print reservation)
Dimensions (W x D x H)	With Platen Cover-Y2: 565 x 692 x 777 mm With Single Pass DADF-C1: 565 x 722 x 887 mm With DADF-BA1: 565 x 719 x 880 mm
Installation Space(W x D)	Basic: 978 x 1,118 mm (with Single Pass DADF-C1 + right cover open + Multi-purpose tray extension extended + paper cassette open) 978 x 1,115 mm (with DADF-BA1 + right cover open + Multi-purpose tray extension extended + Paper cassette open) Fully Configured: 1,651 x 1,118 mm with Single Pass DADF-C1 + Booklet Finisher-AA1/Staple Finisher-AA1 + Copy Tray-J2 extension extended + paper cassette open 1,651 x 1,115 mm (with DADF-BA1 + Booklet Finisher-AA1/Staple Finisher-AA1 + Copy Tray-J2 extension extended + paper cassette open)
Weight	With Platen Cover-Y2: Approx. 66.7kg including toner With DADF-BA1: Approx. 73.1 kg including toner With Single Pass DADF-C1: Approx. 79.6 kg including toner
PRINT SPECIFICATIONS	
Print Speed (BW/CL)	iR-ADV DX C3730i: Up to 30 ppm (A4,A5,A5R,A6R), Up to 15 ppm (A3), Up to 20 ppm (A4R) iR-ADV DX C3725i: Up to 25 ppm (A4,A5,A5R,A6R) , Up to 15 ppm (A3), Up to 20 ppm (A4R) iR-ADV DX C3720i: Up to 20 ppm (A4,A5,A5R,A6R) , Up to 15 ppm (A3), Up to 20 ppm (A4R)
Print Resolution (dpi)	600×600, 1200×1200 (half-speed)
Page description languages	Standard: UFR II, PCL6, Adobe® PostScript®3™
Direct Print	Supported file types: PDF, EPS, TIFF/JPEG and XPS
Printing from mobile and cloud	AirPrint, Mopria, Google Cloud Print, Canon PRINT Business, and uniFLOW Online A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information

Fonts

PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT
J/K/S/T*¹ (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts*²

*¹ Optional PCL International Font Set-A1 is required.
**² Optional Barcode Printing Kit-D1 is required.

Print Features

Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer

Operating System

UFR II: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later)

PCL: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019

PS: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later)

PPD: Windows®7/8.1/10, Mac OS X(10.9 or later)
McAfee Embedded Control Software
As of July,2019.

COPY SPECIFICATIONS

Copy Speed (BW/CL)

iR-ADV DX C3730i:
Up to 30 ppm (A4,A5,A5R,A6R), Up to 15 ppm (A3), Up to 20 ppm (A4R)

iR-ADV DX C3725i:
Up to 25 ppm (A4,A5,A5R,A6R) , Up to 15 ppm (A3), Up to 20 ppm (A4R)

iR-ADV DX C3720i:
Up to 20 ppm (A4,A5,A5R,A6R) , Up to 15 ppm (A3), Up to 20 ppm (A4R)

First-Copy-Out Time (A4; BW/ CL)

Approx. 5.9/8.2 seconds or less

Copy resolution (dpi)

600 x 600

Multiple Copies

Up to 999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25% to 400% (1% Increments)
Preset reduction/enlargement: 25%, 50%, 70%, 110% (1:1), 141%, 200%, 400%

Copy Features

Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Mirror Image, Copy ID Card, Skip Blank Pages, Free Size Original, Colour Mode, Reserved copy, Copy Sample

SCAN SPECIFICATIONS

Type

Standard: Colour Platen
Optional: Platen cover, Single Pass DADF-C1 or DADF-B1 2-sided to 2-sided (Automatic with DADF)*

*Detect Feeder Multi Sheet Feed is supported
DADF: Duplexing Automatic Document Feeder

Document Feeder Paper Capacity (80 gsm)

Single Pass DADF-C1: up to 200 Sheets
DADF-BA1: up to 100 Sheets

Acceptable originals and weights

Platen: Sheet, Book, and 3-Dimensional objects
Document Feeder media weight:
Single Pass DADF-C1*

1-sided scanning: 38 to 220 gsm (BW/CL)

2-sided scanning: 38 to 220 gsm (BW/CL)

*An acceptable weight of A6R or smaller is 50 to 220gsm.

DADF-BA1 :

1-sided scanning: 38 to 128 gsm (BW), 64 to 128 gsm (CL)

2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)

Supported media sizes

Platen: max. scanning size up to 297.0 x 431.8 mm

Single Pass DADF-C1:

A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,

Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm

DADF-BA1:

A3, A4, A4R, A5, A5R, B4, B5, B5R, B6,

Custom size: 139.7 x 128 mm to 297.0 x 431.8 mm

Scan Speed (ipm: BW/CL,A4)

Single Pass DADF-C1:

1-sided Scanning: 135/135 (300 x 300 dpi, send),

51/51 (600 x 600 dpi, copy)

2-sided Scanning: 270/270 (300 x 300 dpi, send),

51/51 (600 x 600 dpi, copy)

DADF-BA1:

1-sided Scanning: 70/70 (300 x 300 dpi, send),

51/51 (600 x 600 dpi, copy)

2-sided Scanning: 35/35 (300 x 300 dpi, send),

25.5/25.5 (600 x 600 dpi, copy)

Scan Resolution (dpi)

Scan for Copy: 600 x 600

Scan for Send: (Push) up to 600 x 600

(SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600

Scan for Fax: 600 x 600

Pull Scan Specifications

Colour Network ScanGear2. For both TWAIN and WIA

Supported OS: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server 2016

Scan Method

Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile device, Scan to cloud (uniFLOW Online)



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C3700 Series

SEND SPECIFICATIONS

Destination	Standard: E-mail/Internet FAX (SMTP) SMB3.0 FTP WebDAV Mail Box Optional: Super G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send resolution (dpi)	Push: up to 600 x 600(SMB/FTP/WebDAV/IFAX) Pull: up to 600 x 600
Communication protocol	File: FTP(TCP/IP), SMB3.0 (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF/A-lb, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals

FAX SPECIFICATIONS

Maximum Number of Connection Lines	2
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)
Sending and Receiving Size	Sending: A3, A4, A4R, A5 ¹ , A5R ¹ , B4, B5 ² , B5R ¹ Receiving: A3, A4, A4R, A5R, B4, B5, B5R ¹ Sent as A4 ² Sent as B4 short
FAX memory	Up to 30,000 pages (2,000 jobs)
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log

STORE SPECIFICATIONS

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 10,000 Pages (2,000 jobs) Stored
Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 8.1/10 Concurrent Connections (Max.): SMB:64, WebDAV:3
Advanced Space available disc space	Standard:16 GB (With option: max. 480GB.)
Advanced Space Features	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore

SECURITY SPECIFICATIONS

Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print ¹), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) ¹ Requires uniFLOW Online / uniFLOW
Network Security	TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), Communication Line Separation (G3 FAX, USB Port, Advanced Space, Scan and Send -Virus Concerns for E-mail Reception)

Device Security

Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Comply IEEE2600.2 (Common Criteria Certification) (TBD)

Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

Device Management and Auditing

ENVIRONMENTAL SPECIFICATIONS

Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity)
Power source	220-240V 50/60Hz 4A
Power consumption	Maximum: Approx. 1,500 W Copying (with DADF continuous scan): Approx. 546.4 W ¹ Standby: Approx. 45.1 W ¹ Sleep mode: Approx. 0.8 W ² ¹ Reference value: measured one unit ² 0.8W sleep mode is not available in all circumstances due to certain settings. Typical Electricity Consumption (TEC)** : iR-ADV DX C3730i: 0.35 kWh iR-ADV DX C3725i: 0.29 kWh iR-ADV DX C3720i: 0.25 kWh **As per USA Energy Star 3.0

Noise levels

Sound Power Level (LWA)m)
Active (1-sided)
iR-ADV DX C3730i: 6.2 B, Kv 0.3 B
iR-ADV DX C3725i: 6.2 B, Kv 0.3 B
iR-ADV DX C3720i: 6.1 B, Kv 0.3 B
^{*}Reference value: measured only one unit with ISO7779, described with ISO9296 (2017).
Sound Pressure (LpAm)
Bystander's position:
Active(BW/CL)(1-sided):
iR-ADV DX C3730i: 48 dB* / 49 dB*
iR-ADV DX C3725i: 48 dB* / 48 dB*
iR-ADV DX C3720i: 47 dB* / 47 dB*
Standby:
iR-ADV DX C3730i/C3725i/C3720i: 10 dB*
^{*}Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)

Standards

Blue Angel

CONSUMABLES

Toner Cartridges	C-EXV 49 TONER BK/C/M/Y
Toner (Estimated Yield @ 5% Coverage)	C-EXV 49 TONER BK: 36,000 pages C-EXV 49 TONER C/M/Y: 19,000 pages

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting	For detailed information please visit our website https://www.canon-europe.com/business/ Universal Login Manager (ULM) uniFLOW Online Express* [*] For more information, please refer to uniFLOW Online Express/uniFLOW Online Technical Datasheets
Remote management tools	iW Management Console eMaintenance Content Delivery System
Scanning software	Network ScanGear
Optimisation tools	Canon Driver Configuration Tool NetSpot Device Installer
Platform	MEAP (Multifunctional Embedded Application Platform)
Document Administration	Kofax Power PDF (Optional)

PAPER SUPPLY OPTIONS

Cassette Feeding Unit-AP1	Paper Capacity: 550 sheets x 2 (1,100 sheets) (80 gsm) Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched Paper Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Paper Weight: 52 to 220 gsm Power Source: From the Main Unit Dimensions (W x D x H): 565 x 615 x 248 mm Weight: Approx. 16.0 kg
----------------------------------	---



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C3700 Series

OUTPUT OPTIONS*

Copy Tray-J2

*Paper capacity may vary with different paper type/sizes.

Capacity: 100 sheets (80 gsm)
Dimensions (W x D x H): 444 x 373 x 176 mm (attached to the main unit, when the extension tray is extended)

Inner 2way Tray-J1

Tray Capacity (with 80 gsm paper)
Upper tray: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Custom size (98.4 x 139.7 mm to 320.0 x 457.2 mm): 100 sheets
Lower tray: A4, A5, A5R, A6R, B5, B5R: up to 250 sheets
SRA3, A3, A4R, B4, Custom Size (98.4x139.7 to 320.0x457.2 mm): 100 sheets
Paper Weight: 52 to 300 gsm
Dimensions (W x D x H): 426 x 407 x 76 mm
Weight: 0.7 kg

Inner Finisher-K1

Tray Capacity (with 80gsm paper):
Upper Tray: A4, A5, A5R, B5: 100 sheets
SRA3, A3, A4R, A6R, B4, B5R: 50 sheets
Lower Tray: A4, A5, A5R, B5: 500 sheets
SRA3, A3, A4R, B4, B5R: 250 sheets
A6R: 30 sheets
Paper Weight: 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity :
A4/B5: 50 sheets (52 to 90 gsm)
A3/A4R/B4: 30 sheets (52 to 90 gsm)
Eco Staple:
A3/A4/B4/B5: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)
Staple On Demand: approx. 40 sheets (80 gsm)
Power supply: From the main unit
Dimensions (W x D x H): 634 x 525 x 188 mm
(when the extension tray is extended)
Weight: Approx. 8.0 kg

Staple Finisher-AA1

Tray Capacity (with 80gsm paper):
Upper Tray: A4, A5, A5R, A6R, B5: 250 sheets
SRA3, A3, A4R, B4, B5R: 125 sheets
Lower Tray: A4, A5, A5R, B5: 3,000 sheets
SRA3, A3, A4R, B4, B5R: 1,500 sheets
A6R: 250 sheets
Envelope: Monarch 30 sheets, COM10 No.10, DL, ISO-C5: 100 sheets
Paper Weight:
Upper Tray: 52 to 256 gsm
Lower Tray: 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity: A4/B5: 50 sheets (52 to 90 gsm)
A3/A4R/B4: 30 sheets (52 to 90 gsm)
Eco Staple:
A3/A4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (82 to 105 gsm)
Staple On Demand: 50 sheets
Power supply: From the main unit
Dimensions (W x D x H): 637 x 623 x 1,016 mm
(when the extension tray is extended)
Weight: Approx. 30.0 kg

Booklet Finisher-AA1

(Includes the above Staple Finisher-AA1 basic staple specifications.)
Saddle Stitch paper size: A3, A4R, B4
Saddle Stitch Staple Capacity: 20 sheets x 10 sets (52 to 81.4 gsm)
(including 1 cover sheet up to 256gsm)
Non Staple Folded Bunch Capacity: up to 3 sheets (52 to 105 gsm)
Power supply: From main unit
Dimensions (W x D x H): 637 x 623 x 1016 mm
(when the extension tray is extended)
Weight: Approx. 53.0 kg

2/4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1)
Two or Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Two holes A3, A4, A4R, A5, B4, B5, B5R, Four holes A3, A4
Power Source: From the Finisher

4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1)
Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size: Four holes A3, A4, A4R, A5, B4, B5, B5R
Power Source: From the Finisher

HARDWARE ACCESSORIES

Card Readers

Various card readers available e.g. MiCard Plus.
Please contact local Canon Office for more details.
Copy Card Reader-F1
Copy Card Reader Attachment-B7

Others

Utility Tray-B1
Numeric Keypad-A1
Platen Cover-Y2

SECURITY OPTIONS

Data Security

2.5inch/1TB HDD-P1

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A

Barcode Printing

Barcode Printing Kit-D1

System Accessories

Copy Control Interface Kit-A1
Serial Interface Kit-K3
Connection Kit-A2 for Bluetooth LE
NFC Kit-E1

Fax Accessories

Super G3 FAX Board-AZ1
Super G3 2nd Line Fax Board-AU1
Remote Fax Kit-A1
IP FAX Expansion Kit-B1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1
Voice Guidance Kit-G1
Voice Operation Kit-D1

Staple Cartridge

Staple-P1
Staple Cartridge-Y1

Software & Solutions



Certifications and compatibility



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2020