

Specificații tehnice (F4.1)

Numărul licitației:	ocds-b3wdp1-MD-1540212555580	Data: 09.11.2018	Alternativa nr.: nu se aplică
Denumirea licitației:	Echipament și accesorii pentru computer:	Lot: 4	Pagina: 1 din 3

Cod CPV	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standard e de referință
1	2	3	4	5	6	7	8
30210000-4	Servere	868703-B21	EU (Czech Republic)	HP Enterprise	Server	868703-B21 HPE ProLiant DL380 Gen10 8SFF Configure-to-order Server	Conform
					Rack mount, 2U, 19" rack mount	Rack mount, 2U, 19" rack mount	Conform
					Processor min. two (2 x) processors; min. 18 core; min 36 threads; min. 2.3 Ghz; min. cache 45Mb; memory 2400Mhz.	1x 826878-L21 HPE DL380 Gen10 Intel Xeon-Gold 6140 (2.3GHz/18-core/150W) FIO Processor Kit 1x 826878-B21 HPE DL380 Gen10 Intel Xeon-Gold 6140 (2.3GHz/18-core/150W) Processor Kit	Conform
					Memory min. 256 GB (8 x 32 Gb); DDR4 PC4-19200 2400 MHz; min 24 slots or more	8x 815100-B21 HPE 32GB (1x32GB) Dual Rank x4 DDR4-2666 CAS-19-19-19 Registered Smart Memory Kit 24x DIMM slots	Conform
					RAID controller Hardware Controller; RAID 0/1/5/10/50/60; Cache 4Gb.	1x 804338-B21 HPE Smart Array P816i-a SR Gen10 (16 Internal Lanes/4GB Cache/SmartCache) 12G SAS Modular Controller 1x P01366-B21 HPE 96W Smart Storage Battery (up to 20 Devices) with 145mm Cable Kit RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM (Advanced Data Mirroring)	Conform
					Drive bays min. 16x 2.5" SAS/SATA (front) with drive bays;	16x front drive bays 1x 8 SFF cage standard	Conform

						1x 826691-B21 HPE DL38X Gen10 SFF Box1/2 Cage/Backplane Kit 1x 826708-B21 HPE DL38X Gen10 Universal Media Bay Kit	
					Hard drives: min. two (2x) 2,5"; min. 400 GB; Enterprise Performance SAS SSD; 12Gbps; hot-plug.	2x 872374-B21 HPE 400GB SAS 12G Mixed Use SFF (2.5in) SC Digitally Signed Firmware SSD	Conform
					Optic drive: Internal DVD drive	1x 726537-B21 HPE 9.5mm SATA DVD-RW Optical Drive	Conform
					Cooling system: Redundant hot plug	6x standard redundant hot plug fans	Conform
					Power supply: Redundant hot plug power supplies; min. 900W; Two (2x) Power cables, PDU connection	2x 865414-B21 HPE 800W Flex Slot Platinum Hot Plug Redundant Low Halogen Power Supply Kit; with PDU power cables	Conform
					Expansion slots: 1x Full PCIe x16; min 3x Full PCIe x8	2x PCIe x16 full-height full-length; 2x PCIe x8 full-height full-length; 2x PCIe x8 full-height half-length Slots	Conform
					Network interfaces Two (2x) - Gigabit Ethernet NIC with four (4x) ports 100/1000	1x HPE 1Gb Ethernet 4-Port 331i Adapter standard 1x 665240-B21 HPE Ethernet 1Gb 4-port 366FLR Adapter	Conform
					Additional cards: Two (2x) - FC HBA cards 8Gbit FC port	1x P9D94AHPE StoreFabric SN1100Q 16Gb Dual Port Fibre Channel Host Bus Adapter	Conform
					Porturi: 1x front VGA (15 pin/female); 1x back end VGA (15pin/female); 1x Management port; 8 x RJ-45; min. 4 x USB 2.0	1x front VGA/DisplayPort; 1x Rear VGA port; 1x iLO Remote Management Port; 1x Front iLO Service port; 5x USB 3.0: 3 front, 2 rear, 2 internal (secure); 1x Micro SD Slot; 8x RJ-45	Conform
					Diagnostic panel: LCD panel on front panel must displays: status information, system error messages.	LEDs on front panel, status information, system error messages.	Conform
					Server management (SM): Dedicated Ethernet NIC for management. Local and remote control of system resources (manage, diagnose and monitor). Remote power control, remote firmware updating, remote presence, capture of OS failure screen (BSOD) via web interface, virtual media attachment to a server of USB drive, CD/DVD drive	1x BD505A HPE iLO Advanced 1-server License Local and remote control of system resources (manage, diagnose and monitor). Remote power control, remote firmware updating, remote presence, capture of OS failure screen (BSOD) via web interface, virtual media attachment to server of USB drive, CD/DVD drive	Conform

				Serial over LAN, DHCP, IPMI V2.0, CIM, SNMP, email alerts LDAP user authentication Browser based administration with full control over the remote host server's display, keyboard, and mouse, including host OS graphical interface. Virtual media option that provides virtual CD drive and remote image mounting. SM & server diagnostics logging. SSL or SSH encryption.	Serial over LAN, DHCP, IPMI V2.0, CIM, SNMP, email alerts LDAP user authentication Browser based administration with full control over the remote host server's display, keyboard, and mouse, including host OS graphical interface. Virtual media option that provides virtual CD drive and remote image mounting. SM & server diagnostics logging. SSL or SSH encryption.	
				Rack mounting rails: Rails with full extraction, Cable management arm	1x 733664-B21 HPE 2U Cable Management Arm for Easy Install Rail Kit 1x 733660-B21 HPE 2U Small Form Factor Easy Install Rail Kit	Conform
				Operating Systems Supported MS Windows Server 2008 R2, 2012 R2 x86 (64-bit), Microsoft Hyper-V server 2012 R2, Microsoft Hyper-V Server 2016, SUSE Linux Enterprise Server x86 (64-bit)	Windows Server 2008 R2; Windows Server 2012 R2; Windows Server 2016; Microsoft Hyper-V; VMware ESXi 6.0 U3; VMware ESXi 6.5 and U1; CentOS; Red Hat Enterprise Linux (RHEL) 6.9 and 7.3; SUSE Linux Enterprise Server (SLES) 11 SP4 and 12 SP2; Canonical Ubuntu; ClearOS	Conform
				Installation, cabling and configuration: Including all necessary parts and specialists	Included all necessary parts and specialists for Installation, cabling and configuration	Conform
				Warranty 5 years parts/labor/onsite, repair next business-day	1 H7J32A5 HPE 5Y Foundation Care NBD SVC 5 years support NBD included	Conform

Semnatar: _____

Numele, Prenumele: Iurii Svera

În calitate de: Key Account Manager

Ofertantul: **BASS SYSTEMS SRL**

Adresa: Calea Ieșilor 8, Chișinău, MD-2069, Republica Moldova