

DECLARACION DE CONFORMIDAD / DECLARATION OF CONFORMITY S/ EN 10.204.-2.1																																																	
CLIENTE / CUSTOMER:				Nº PEDIDO / PURCHASE Nº:			FECHA / DATE: 01/07/2019																																										
CARACTERISTICAS DE PRODUCTO / PRODUCT CHARACTERISTICS 1/1																																																	
PRODUCTO / PRODUCT																																																	
ALAMBRE ACERO BAJO CARBONO DURO / GALVANIZED LOW CARBON STEEL WIRE (HARD)																																																	
CARACTERISTICAS DEL ACERO / STEEL CHARACTERISTICS:																																																	
TIPO / TYPE: C4D/C9D				NORMA / STANDARD: ISO 16120-2																																													
C (%)	Mn (%)	Si (%)	P (%)	S (%)																																													
≤ 0.08	0.35 ÷ 0.60	0.10 ÷ 0.30	≤ 0.040	≤ 0.040																																													
CARACTERISTICAS DEL RECUBRIMIENTO DE ZINC / ZINC COATING CHARACTERISTICS :																																																	
TIPO / TYPE: (Z1) de 99.995% Min.				TIPO DE ZINC S/NORMA / ZINC ACORDING WITH: EN 1179																																													
MASA DE ZINC / WEIGHT COATING: (g/m ²): Ver características de los alambres/ See Wire characteristics				MASA DE ZINC S/NORMA / WEIGHT COATING ACORDING WITH: EN 10244-2																																													
CARACTERISTICAS DE LOS ALAMBRES/WIRE CHARACTERISTICS:																																																	
<table border="1"> <thead> <tr> <th rowspan="3">DIÁMETRO NOMINAL NOMINAL DIAMETER "D" (mm)</th> <th colspan="4">G/REFORZADO HARD WIRE COMERCIAL GALV. TO EN10244-2 QUALITY A</th> </tr> <tr> <th rowspan="2">MASA DE ZINC WEIGHT COATING (gr/m²)</th> <th colspan="2">RESISTENCIA A LA TRACCIÓN TENSILE STRENGTH</th> <th rowspan="2">CARGA DE ROTURA BREAK LOAD N</th> </tr> <tr> <th>N/mm²</th> <th>Kpsi</th> </tr> </thead> <tbody> <tr> <td>1.80</td> <td>≥ 260</td> <td>740÷940</td> <td>107÷136</td> <td>1.882÷2.391</td> </tr> <tr> <td>2.00</td> <td>≥ 260</td> <td>730÷930</td> <td>106÷135</td> <td>2.292÷2.920</td> </tr> <tr> <td>2.20</td> <td>≥ 260</td> <td>680÷920</td> <td>99÷134</td> <td>2.584÷3.495</td> </tr> <tr> <td>2.40</td> <td>≥ 260</td> <td>680÷920</td> <td>99÷134</td> <td>3.075÷4.160</td> </tr> <tr> <td>2.70</td> <td>≥ 260</td> <td>660÷860</td> <td>96÷125</td> <td>3.777÷4.921</td> </tr> <tr> <td>3.00</td> <td>≥ 260</td> <td>640÷840</td> <td>93÷122</td> <td>4.522÷5.935</td> </tr> </tbody> </table>									DIÁMETRO NOMINAL NOMINAL DIAMETER "D" (mm)	G/REFORZADO HARD WIRE COMERCIAL GALV. TO EN10244-2 QUALITY A				MASA DE ZINC WEIGHT COATING (gr/m ²)	RESISTENCIA A LA TRACCIÓN TENSILE STRENGTH		CARGA DE ROTURA BREAK LOAD N	N/mm ²	Kpsi	1.80	≥ 260	740÷940	107÷136	1.882÷2.391	2.00	≥ 260	730÷930	106÷135	2.292÷2.920	2.20	≥ 260	680÷920	99÷134	2.584÷3.495	2.40	≥ 260	680÷920	99÷134	3.075÷4.160	2.70	≥ 260	660÷860	96÷125	3.777÷4.921	3.00	≥ 260	640÷840	93÷122	4.522÷5.935
DIÁMETRO NOMINAL NOMINAL DIAMETER "D" (mm)	G/REFORZADO HARD WIRE COMERCIAL GALV. TO EN10244-2 QUALITY A																																																
	MASA DE ZINC WEIGHT COATING (gr/m ²)	RESISTENCIA A LA TRACCIÓN TENSILE STRENGTH		CARGA DE ROTURA BREAK LOAD N																																													
		N/mm ²	Kpsi																																														
1.80	≥ 260	740÷940	107÷136	1.882÷2.391																																													
2.00	≥ 260	730÷930	106÷135	2.292÷2.920																																													
2.20	≥ 260	680÷920	99÷134	2.584÷3.495																																													
2.40	≥ 260	680÷920	99÷134	3.075÷4.160																																													
2.70	≥ 260	660÷860	96÷125	3.777÷4.921																																													
3.00	≥ 260	640÷840	93÷122	4.522÷5.935																																													
TOLERANCIA/TOLERANCE: Acorde a:/ According to: UNE-EN 10218-2																																																	
FORMA DE ENTREGA/ PACKAGING: Rollos o fardos/Rolls																																																	