

Specificații tehnice (F4.1)

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5.]

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1710775408690 din 18 martie 2024
Obiectul achiziției: Echipament audiovizual și de televiziune

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Tara de origine	Producătorul	Specificarea tehnică deplină solicitată decătore autoritatea contractantă	Specificarea tehnică deplină propusă decătore ofertant	Standarde de referință
1	2	3	4	5	6	7
1.Video Switcher	Blackmagic Design ATEM Television Studio HD8 + Blackmagic Design GPI and Tally Interface	Indonezia	Blackmagic Design	<p>Connections</p> <p>SDI Video Inputs - 8</p> <p>SDI Video Outputs - 12</p> <p>SDI Rates - 1.5G, 3G</p> <p>HDMI Video Outputs - 1</p> <p>Total Audio Inputs - 2 x XLR balanced analog audio, 1 x BNC 32 Ch MADI digital audio, 2 x RCA stereo analog audio, 1 x 5 pin XLR Talkback.</p> <p>Total Audio Outputs - 4 x 1/4 inch Jack analog audio, 1 x BNC 64 Ch MADI digital audio, up to 50 active, 1 x 5 pin XLR Talkback.</p> <p>SDI Audio Inputs - 4 Ch embedded audio on all SDI inputs.</p> <p>SDI Audio Outputs - 2 Ch embedded audio on all SDI outputs.</p> <p>Timecode Connections - 1 x BNC In, 1 x BNC Out.</p> <p>Reference Input - 1 x BNC In, 1 x BNC Out. (Tri-Sync or Black Burst)</p> <p>Video Input Re-Sync - On all 8 inputs.</p> <p>Frame Rate and Format Converters - On all 8 inputs.</p> <p>SDI Aux Outputs - 2</p> <p>SDI Program Outputs - 1</p> <p>Webcam Output - 2 x USB-C supporting 720p or 1080p at PGM frame rate.</p> <p>Total Multi Views - 1 x 3G-SDI, 1 x HDMI</p> <p>Remote - RJ12 supports RS-422</p> <p>Control Panel Connection Ethernet. Direct connection between panel and chassis, or via network.</p> <p>Internal Timecode Generator - Yes</p> <p>Talkback - RJ45 for 3rd party talkback systems.</p> <p>Ethernet - 4 x RJ45 with internet network switch.</p> <p>Supports 10/100/1000 BASE-T.</p> <p>Computer Interface - 2 x USB-C supports USB 2.0 for external drive recording, webcam out, software control, software updates and switcher connection.</p> <p>Standards</p> <p>Video Sampling - 4:2:2</p> <p>Color Precision - 10-bit.</p> <p>Color Space - REC 709</p> <p>SDI Auto Switching - Automatically detects between 1.5G-SDI and level A or level B 3G-SDI.</p> <p>Number of Mix Effects Rows - 1</p> <p>Direct Cross Points - 10</p> <p>Shifted Cross Points - 20</p> <p>Crosspoint Button Type - Tri-Color LED</p> <p>Crosspoint Label - 6 rows 24 character LCD</p> <p>Preview Transition - 1</p> <p>Source Select Bus - 1</p> <p>Dedicated Macro Buttons - 10 plus shift 10</p> <p>Transition Type Buttons - 5</p> <p>Transition Rate - Set via system LCD menu display</p> <p>Key Buttons - 8</p> <p>AUX Buttons - 12</p> <p>Fader Bar - 1</p> <p>Record Buttons - 2</p> <p>Stream Buttons - 2</p> <p>DSK Transition Selectors - 6</p> <p>Upstream Keyers - 4</p> <p>Downstream Keyers - 2</p> <p>Advanced Chroma Keyers - 4</p> <p>SuperSource - 1</p> <p>DVEs - 2</p> <p>Linear/Luma Keyers - 7</p> <p>Transition Keyer (Stinger/DVE) - 1 Stinger, 1 DVE.</p> <p>Total Number of Layers - 8</p> <p>Control Panel - Integrated panel with full control of switching and settings.</p> <p>Routable Windows - 16</p> <p>Tally - Red for program and green for preview indication.</p> <p>Recording</p> <p>Direct Recording Video and Audio - USB-C expansion port can record directly to external media.</p> <p>Video Recording - Program recorded as a H.264 .mp4 file at the streaming quality setting and at the video standard with AAC audio.</p> <p>Media Format - Supports media formatted ExFAT (Windows/Mac). APFS or HFS+ (Mac).</p> <p>Include: GPI and Tally Interface</p> <p>Contact Closure - 25 pin D-type connector providing 8 opto isolated inputs and 8 relay contact closure outputs.</p> <p>Computer Interface - 1 x USB 2.0 high speed interface for configuration and firmware updates.</p> <p>Inputs - Optical isolators triggered by connection to ground. Max 5V at 14mA.</p> <p>Outputs - Mechanical relay contact closure to ground. Max 30V at 1A.</p> <p>Ethernet - 10/100 BaseT with loop through for connecting to other ethernet enabled equipment.</p> <p>Warranty hardware 2 years</p>	<p>Connections</p> <p>SDI Video Inputs - 8</p> <p>SDI Video Outputs - 12</p> <p>SDI Rates - 1.5G, 3G</p> <p>HDMI Video Outputs - 1</p> <p>Total Audio Inputs - 2 x XLR balanced analog audio, 1 x BNC 32 Ch MADI digital audio, 2 x RCA stereo analog audio, 1 x 5 pin XLR Talkback.</p> <p>Total Audio Outputs - 4 x 1/4 inch Jack analog audio, 1 x BNC 64 Ch MADI digital audio, up to 50 active, 1 x 5 pin XLR Talkback.</p> <p>SDI Audio Inputs - 4 Ch embedded audio on all SDI inputs.</p> <p>SDI Audio Outputs - 2 Ch embedded audio on all SDI outputs.</p> <p>Timecode Connections - 1 x BNC In, 1 x BNC Out.</p> <p>Reference Input - 1 x BNC In, 1 x BNC Out. (Tri-Sync or Black Burst)</p> <p>Video Input Re-Sync - On all 8 inputs.</p> <p>Frame Rate and Format Converters - On all 8 inputs.</p> <p>SDI Aux Outputs - 2</p> <p>SDI Program Outputs - 1</p> <p>Webcam Output - 2 x USB-C supporting 720p or 1080p at PGM frame rate.</p> <p>Total Multi Views - 1 x 3G-SDI, 1 x HDMI</p> <p>Remote - RJ12 supports RS-422</p> <p>Control Panel Connection Ethernet. Direct connection between panel and chassis, or via network.</p> <p>Internal Timecode Generator - Yes</p> <p>Talkback - RJ45 for 3rd party talkback systems.</p> <p>Ethernet - 4 x RJ45 with internet network switch.</p> <p>Supports 10/100/1000 BASE-T.</p> <p>Computer Interface - 2 x USB-C supports USB 2.0 for external drive recording, webcam out, software control, software updates and switcher connection.</p> <p>Standards</p> <p>Video Sampling - 4:2:2</p> <p>Color Precision - 10-bit.</p> <p>Color Space - REC 709</p> <p>SDI Auto Switching - Automatically detects between 1.5G-SDI and level A or level B 3G-SDI.</p> <p>Number of Mix Effects Rows - 1</p> <p>Direct Cross Points - 10</p> <p>Shifted Cross Points - 20</p> <p>Crosspoint Button Type - Tri-Color LED</p> <p>Crosspoint Label - 6 rows 24 character LCD</p> <p>Preview Transition - 1</p> <p>Source Select Bus - 1</p> <p>Dedicated Macro Buttons - 10 plus shift 10</p> <p>Transition Type Buttons - 5</p> <p>Transition Rate - Set via system LCD menu display</p> <p>Key Buttons - 8</p> <p>AUX Buttons - 12</p> <p>Fader Bar - 1</p> <p>Record Buttons - 2</p> <p>Stream Buttons - 2</p> <p>DSK Transition Selectors - 6</p> <p>Upstream Keyers - 4</p> <p>Downstream Keyers - 2</p> <p>Advanced Chroma Keyers - 4</p> <p>SuperSource - 1</p> <p>DVEs - 2</p> <p>Linear/Luma Keyers - 7</p> <p>Transition Keyer (Stinger/DVE) - 1 Stinger, 1 DVE.</p> <p>Total Number of Layers - 8</p> <p>Control Panel - Integrated panel with full control of switching and settings.</p> <p>Routable Windows - 16</p> <p>Tally - Red for program and green for preview indication.</p> <p>Recording</p> <p>Direct Recording Video and Audio - USB-C expansion port can record directly to external media.</p> <p>Video Recording - Program recorded as a H.264 .mp4 file at the streaming quality setting and at the video standard with AAC audio.</p> <p>Media Format - Supports media formatted ExFAT (Windows/Mac). APFS or HFS+ (Mac).</p> <p>Include: GPI and Tally Interface</p> <p>Contact Closure - 25 pin D-type connector providing 8 opto isolated inputs and 8 relay contact closure outputs.</p> <p>Computer Interface - 1 x USB 2.0 high speed interface for configuration and firmware updates.</p> <p>Inputs - Optical isolators triggered by connection to ground. Max 5V at 14mA.</p> <p>Outputs - Mechanical relay contact closure to ground. Max 30V at 1A.</p> <p>Ethernet - 10/100 BaseT with loop through for connecting to other ethernet enabled equipment.</p> <p>Warranty hardware 2 years</p>	

Semnat: Semnat electronic
 Nume/prenume: Pantehovschi Vadim
 Funcția în cadrul firmei: Director
 Ofertantul: SRL "FALENAT"