



ANNEX

EU TYPE EXAMINATION CERTIFICATE Nr. 032/2022/1079

1. Applicant

Ansell Healthcare Europe NV/SA
Riverside Business Park - Block J Boulevard International 55
1070 Brussels
Belgium

2. Description

EN 14605:2005+A1:2009



Typ PB[4]

class 6 for the abrasion resistance
class 6 for the flex resistance
class X for the flex resistance @ -30°C
class 3 for the tearing resistance
class 3 for the tensile strength
class for 2 the puncture resistance
class 6 for the permeation of H₂SO₄ 30 % and NaOH 10%
class X for the resistance to ignition
seam strength: not applicable, the apron has no seam

3. Materials and accessories

Outer fabric

- The aprons 56-100 PVC-45G and 56-101 PVC-45W

4. Technical documentation

Summary test results

EN ISO 13688:2013+A1:2021 Outer fabric

The aprons 56-100 PVC-45G and 56-101 PVC-45W

Method	Description	Result	Class
ISO 3071:2020, Textile	pH	PASS	
ISO 3071:2020, Textile	pH	PASS	
ISO 14362(-1/3):2017, Textiles	Arylamines	PASS	
ISO 5077:2007, Textiles	Dimensional stability	/	/

EN 14605:2005+A1:2009 Outer fabric

The aprons 56-100 PVC-45G and 56-101 PVC-45W

Method	Description	Result	Class
ISO 6330	Pre-treatment	/	/
ISO 15797	Pre-treatment	/	/
ISO 9073-4	Tear resistance trapezoidal	PASS	Class 3
EN ISO 13934-1	Tensile strength and elongation	PASS	Class 3
EN 530 Methode 2	Abrasion resistance	/	/
EN 863	Puncture resistance	PASS	Class 2
EN ISO 7854 methode 2	Flex cracking resistance	PASS	Class 6
EN ISO 7854 methode B -30°C	Flex cracking resistance at -30°C	/	/
EN 374-3 or EN ISO6529 A or B	Resistance to permeation by chemicals for NaOH 50%	PASS	Class 6
EN 374-3 or EN ISO6529 A or B	Resistance to permeation by chemicals for H2SO4 50 %	PASS	Class 6

Description/Picture of article

Article **The aprons PVC-45G (56-100) and PVC-45W (56-101)**



The above picture is a general picture of the article. Possible variations of the above article can be present in the technical file.

Note :

Any modification in material, design, or other technical features must be brought to the attention of the Notified Body.