

[Acest tabel va fi completat de către **ofertant în coloanele 2, 3, 4, 6, 7**, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție: Informația o găsiți în SIA RSAP, ocids-b3wdp1-MD-1749471765615							
Obiectul achiziției: <u>Echipamente de radioteleviziune</u>							
Nr. d/o conf anuntului	Denumirea bunurilor/serviciilor	Denumirea modelului bunului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
0	1	2	3	4	5	6	7

Lotul nr. 8 - Light Meter

	Light Meter	Light Meter Sekonic Speedmaster L-858D-U	JP, USA	Sekonic	Meter Type Ambient, Cine, Flash, Spot Spot Metering 1° Spot Flash Metering Cordless Light Reading Method Incident, Reflected Light Readings Candelas per Meter Squared (cd/m²), Foot Lamberts (fl), Footcandle, Lux Measuring Modes Aperture Priority, FPS Metering, Flash Duration Analysis, HSS Flash, Shutter Priority Aperture Range Flash, Incident: f/0.5 to 128.9 at ISO 100; Flash Reflected: f/1 to 128.9 at ISO 100; f/0.5 to 161.2 (1, 1/2, 1/3-Step Increments) at ISO 100 EV Range Ambient, Incident: -5 to 22.9 EV at ISO 100; Ambient, Reflected: -1 to 24.4 EV at ISO 100 ISO Range 3 to 13,107,200 (1/3-Step Increments), Plus 850 Shutter Speed Range 1/64,000 to 30 Minutes (1, 1/2, 1/3-Step Increments), Plus 1/400, 1/200	Meter Type Ambient, Cine, Flash, Spot Spot Metering 1° Spot Flash Metering Cordless Light Reading Method Incident, Reflected Light Readings Candelas per Meter Squared (cd/m²), Foot Lamberts (fl), Footcandle, Lux Measuring Modes Aperture Priority, FPS Metering, Flash Duration Analysis, HSS Flash, Shutter Priority Aperture Range Flash, Incident: f/0.5 to 128.9 at ISO 100; Flash Reflected: f/1 to 128.9 at ISO 100; f/0.5 to 161.2 (1, 1/2, 1/3-Step Increments) at ISO 100 EV Range Ambient, Incident: -5 to 22.9 EV at ISO 100; Ambient, Reflected: -1 to 24.4 EV at ISO 100 ISO Range 3 to 13,107,200 (1/3-Step Increments), Plus 850 Shutter Speed Range 1/64,000 to 30 Minutes (1, 1/2, 1/3-Step Increments), Plus 1/400, 1/200	CE
--	-------------	--	---------	---------	--	--	----

					Max Flash Sync Speed 1/16,000 Illuminance Range 0.1 to 2,000,000 Lux / 0.01 to 180,000 fc Luminance Range 0.3 to 290,000 fL / 0.1 to 980,000 cd/m ² Cine Speed / Shutter Angle 0.001 to 1000 fps at 1 to 358° Diffuser Adjustable Spherical to Flat Display 6.9 cm Color Touchscreen LCD Battery 2x AA	Max Flash Sync Speed 1/16,000 Illuminance Range 0.1 to 2,000,000 Lux / 0.01 to 180,000 fc Luminance Range 0.3 to 290,000 fL / 0.1 to 980,000 cd/m ² Cine Speed / Shutter Angle 0.001 to 1000 fps at 1 to 358° Diffuser Adjustable Spherical to Flat Display 6.9 cm Color Touchscreen LCD Battery 2x AA	
--	--	--	--	--	---	---	--

LOTUL 9

	9.1. Stage Platform	Stage Platform - platforme scenice 2x1m Alustage	PL	Alustage	Technical specs: Load capacity: 750 kg/m ² Length: 2000 mm; Width: 1000 mm ; Height: 90 mm Weight: 32,00 kg New plugs for round & square feet from 48,3 to 60mm Advantages of the stage platforms: High load capacity High quality aluminium frame Easy & quick installation Compatible to many decks from other brands Compatible with existing podium Duratruss 750	Technical specs: Load capacity: 750 kg/m ² Length: 2000 mm; Width: 1000 mm ; Height: 90 mm Weight: 32,00 kg New plugs for round & square feet from 48,3 to 60mm Advantages of the stage platforms: High load capacity High quality aluminium frame Easy & quick installation Compatible to many decks from other brands Compatible with existing podium Duratruss 750	CE
	9.2. Leg set	Leg set - set din 4 picioare fixe de 30cm	PL	Alustage	4 pcs. fixed square stage deck legs made of aluminium. Technical specs load capacity: Height: 600 mm; Width: 60 mm; Depth: 60 mm. Compatible with existing podium Duratruss 750	4 pcs. fixed square stage deck legs made of aluminium. Technical specs load capacity: Height: 600 mm; Width: 60 mm; Depth: 60 mm. Compatible with existing podium Duratruss 750	CE

	9.3. Leg set	Leg set - set din 4 picioare fixe de 60cm	PL	Alustage	4 pcs. fixed square stage deck legs made of aluminium. Technical specs load capacity: Height: 300 mm; Width: 60 mm; Depth: 60 mm. Compatible with existing podium Duratruss 750	4 pcs. fixed square stage deck legs made of aluminium. Technical specs load capacity: Height: 300 mm; Width: 60 mm; Depth: 60 mm. Compatible with existing podium Duratruss 750	CE
--	--------------	---	----	----------	---	---	----

Semnat: **electronic** Numele, Prenumele: **Svetlana Faina** În calitate de: **Director**

data completarii 30.06.25

Ofertantul: **FAINA LUMINA SRL SC** Adresa: **MD-2043, mun. Chişinăum str. Hr. Botev 27, of.1A**