

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

NORD-TEST Kontrastrot U 88 Spray

Further trade names

Article no. (user):
121.300.201

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Inspection of metals

1.3. Details of the supplier of the safety data sheet

Company name:	Helling GmbH	
Street:	Spoekerdamm 2	
Place:	D-25436 Heidgraben	
Telephone:	+49-4122-922-0	Telefax: +49-4122-922-201
e-mail:	info@helling.de	
Internet:	www.helling.de	

1.4. Emergency telephone number:

GIZ Nord Göttingen +49-(0)551-19240
(Information in German and English)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Aerosol: Aerosol 1
Skin corrosion/irritation: Skin Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes skin irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Distillates (petroleum), hydrotreated light, Kerosine - unspecified

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 2 of 13

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P302+P352	IF ON SKIN: Wash with plenty of water.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to industrial incineration plant.

Special labelling of certain mixtures

EUH208	Contains Solvent red dye, Solvent red Dye. May produce an allergic reaction.
--------	--

Additional advice on labelling

The marking of aspiration hazard (Asp. Tox. 1; H304) is not required for aerosols and for containers with a sealed spray attachment (Regulation (EC) No 1272/20, Annex I 1.3.3).

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
106-97-8	butane			35 - 45 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1; H220			
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified			35 - 45 %
	265-149-8	649-422-00-2	01-2119484819-18	
	Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H315 H336 H304 H411			
74-98-6	propane			6 - 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			
56358-09-9	Solvent red dye			0 - 0,75 %
	260-124-8			
	Skin Irrit. 2, Skin Sens. 1, STOT RE 2; H315 H317 H373			
57712-94-4	Solvent red Dye			0 - 0,75 %
	260-913-7			
	Skin Irrit. 2, Skin Sens. 1, STOT RE 2; H315 H317 H373			
	Hydrocarbons, C10, aromatics, > 1% naphthalene			0 - 0,65 %
	919-284-0		01-2119463588-24	
	Carc. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H351 H336 H304 H411			
	Hydrocarbons, C10-C13, aromatics, > 1% naphthalene			0 - 0,65 %
	926-273-4		01-2119451151-53	
	Carc. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H351 H336 H304 H411			

Full text of H and EUH statements: see section 16.

Further Information

EC No. 919-284-0 & 926-273-4:

The amount of these two components will not exceed 1 % content within the product.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration! Medical treatment necessary.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 4 of 13

4.2. Most important symptoms and effects, both acute and delayed

Following eye contact: Conjunctival redness.
After skin contact: erythema (redness)
after ingestion: vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Foam. Extinguishing powder. Atomized water.
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.
Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Oxidizing agents.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 5 of 13

7.3. Specific end use(s)

In case of special use, contact supplier.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 6 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified			
Consumer DNEL, long-term		oral	systemic	19 mg/kg bw/day
56358-09-9	Solvent red dye			
Worker DNEL, long-term		dermal	systemic	0,53 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	1,88 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,27 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,46 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,27 mg/kg bw/day
57712-94-4	Solvent red Dye			
Worker DNEL, long-term		dermal	systemic	0,53 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	1,88 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,27 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,46 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,27 mg/kg bw/day
	Hydrocarbons, C10, aromatics, > 1% naphthalene			
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	150 mg/m ³
Consumer DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m ³
Consumer DNEL, long-term		oral	systemic	7,5 mg/kg bw/day
	Hydrocarbons, C10-C13, aromatics, > 1% naphthalene			
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	151 mg/m ³
Consumer DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m ³
Consumer DNEL, long-term		oral	systemic	7,5 mg/kg bw/day

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 7 of 13

Eye/face protection

Wear eye/face protection.

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended protective gloves brand: neoprene NBR (Nitrile rubber).

Protect skin by using skin protective cream.

Skin protection

Body protection: not required.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	red
Odour:	characteristic
pH-Value:	not applicable

Changes in the physical state

Melting point:	not applicable
Initial boiling point and boiling range:	not applicable
Flash point:	not applicable

Flammability

Solid:	not applicable
Gas:	not determined

Explosive properties

Heating causes rise in pressure with risk of bursting. Vapours may form explosive mixtures with air.

Lower explosion limits:	1,4 vol. %
Upper explosion limits:	10,8 vol. %

Auto-ignition temperature

Solid:	not applicable
Gas:	not determined

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: 3100 hPa
(at 20 °C)

Density: not determined

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 8 of 13

Partition coefficient: not determined
 Vapour density: not determined
 Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention.

10.2. Chemical stability

No risks worthy of mention.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Remove all sources of ignition. Keep away from heat.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
106-97-8	butane				
	inhalation (4 h) aerosol	LC50 658 mg/l	Rat		
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) aerosol	LC50 5,28 mg/l	Rat		
74-98-6	propane				
	inhalation (4 h) vapour	LC50 > 20 mg/l	Rat		
	Hydrocarbons, C10, aromatics, > 1% naphthalene				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	Hydrocarbons, C10-C13, aromatics, > 1% naphthalene				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 9 of 13

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Contains Solvent red dye, Solvent red Dye. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Distillates (petroleum), hydrotreated light, Kerosine - unspecified)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Caution if victim vomits: Risk of aspiration!

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified					
	Fish toxicity	NOEC mg/l	0,098	14 d		
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	> 100	96 h		
	Acute algae toxicity	ErC50 mg/l	> 100			
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h		
	Hydrocarbons, C10, aromatics, > 1% naphthalene					
	Acute fish toxicity	LC50 mg/l	2,0 - 5,0	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	4,0 - 11,0	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1,0 - 10,0	48 h	Daphnia magna	
	Hydrocarbons, C10-C13, aromatics, > 1% naphthalene					
	Acute fish toxicity	LC50 mg/l	2,0 - 5,0	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	4,0 - 11,0	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1,0 - 10,0	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 10 of 13

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Transport category:	2
Tunnel restriction code:	D

Other applicable information (land transport)

EQ: E0

Inland waterways transport (ADN)

14.1. UN number:	UN 1950
-------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 11 of 13

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Other applicable information (inland waterways transport)

EQ: E0

Marine transport (IMDG)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277

EmS: F-D, S-U

Other applicable information (marine transport)

EQ: E0

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

Passenger-LQ: Y203

EQ: E0

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 12 of 13

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: butane

2004/42/EC (VOC): 47,4 %

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Distillates (petroleum), hydrotreated light, Kerosine - unspecified

Hydrocarbons, C10, aromatics, > 1% naphthalene

Hydrocarbons, C10-C13, aromatics, > 1% naphthalene

SECTION 16: Other information**Changes**

section 9

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains Solvent red dye, Solvent red Dye. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NORD-TEST Kontrastrot U 88 Spray

Revision date: 23.06.2020

Page 13 of 13

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)