# HEXOL INTERNATIONAL LTD

## HEXOL

### TECHNICAL DATA SHEET

#### **HEXOL ATF UNIVERSAL**

GFAR OIL

#### PRODUCT DESCRIPTION

HEXOL Universal ATF is a high quality transmission oil, for use in semi-automatic and automatic transmissions installations equipping industrial equipment and vehicles, in power steering systems.

Hexol ATF Universal is formulated from mineral base oils combined with specific additives, recommended for use throughout the year to automatic transmission systems, industrial equipment and vehicles, or any transmissions where specified using a such oil.

#### PERFORMANCE FEATURES

- meets requirements according to GM Type A Suffix A (tasa) MAN 339.A, Allison C-3 (10350289), Volvo 97325 and other types of vehicles whose manufacturers recommend that classification;
- ensures a long life of components subject to wear;
- has good thermal stability;
- excellent oxidative stability, providing protection against corrosion or sediment deposits.

#### **APPLICATION**

- recommended for all semi-automatic and automatic transmission systems equipping industrial equipment and vehicles requiring an oil corresponding to GM Type A Suffix A standard:
- recommended for hydraulic systems requiring anti-wear oils with good fluidity even at low temperatures.

#### **PROPERTIES**

Viscosity Grade SAE	20
Density at 15°C [kg/m³]	850 - 880
Kinematic Viscosity at 40°C [mm²/s]	41.4-50
Viscosity index	110
Flash Point [°C]min	200
Pour Point [°C ]max	-30
Colour	red

#### **PACKAGING**

0.4Kg	☐ 1Kg	4Kg	□ 15Kg	☐ 180Kg	
0.23L	0.45L	0.5L	0.6L	0.9L	3L
4L			≥ 20L		