

DATE	28.03.2025
DOC.NO	FRM-KLT-BYM-069
PAGE NO	1
REV.NO	
REV.DATE	

		"we work	TECHNICAL DATE CHEET		
TECHNICAL DATA SHEET PRODUCT: Sterile disposable cryoablation set					
- 11	торест.	Sterne disposable cryo	vaniativii Sti		
85 Sterile disposable cryoablation set					
			1) 1 pc.: 3-way OFF ramp, for high pressure, "wing" valves, with straight "male" type rotator adapter; transparent chamber, resistant to at least 35 bar; Luer Lock connection. 35 bar	1	
			2) 1 pc.: High pressure tubing – minimum 1200 psi, transparent, internal/external diameter 1.7mm / 3.6mm	1	
			2 /3.6mm; minimum length 50 cm; material for (mandatory), Luer Lock connection. uzunluk 50 cm 3 3) 1 pc.: Y connector mono-, 9.5F, with rotator adapter and Tuohy-Borst valve, with insertion device.	1	
			4) 3 pcs.: High pressure resistant infusion set, for administering gravity infusions under pressure with infusion pumps; resistant to 2 bar pressure; minimum length 1800mm; 15mcm filter for uzunluk 1800mm	3	
			protection; Luer Lock connection.		
			5 5) 50 pcs.: Gauze pad, absorbent, minimum 10x10cm, minimum 8 layers. 10x10 cm 6) 1 pc.: 1 pc.: 2500 ml tray, round, polypropylene, colored, with "wings", minimum height 9cm 2500 mL	50	
Description of Product:		oduct:	(±1cm). uzunluk min 9 cm		
			7 7) 1 pc.: 12 ml angiographic syringe, transparent. 8 1) 1 pc.: 20 ml Luer Lock syringe, green plunger. Syringe tip with special design for dosing accuracy 20 mL	1	
			or approximately 0.01 ml. Smooth, non-jerky piston sliding. 9) 2 one 20 ml. light John Swiping, transparent Double scaling plus to prevent accidental leakage.		
			Smooth, non-jerky piston sliding.	2	
			jerky piston sliding.	4	
			11) 2 pcs.: 2 ml Luer Lock syringe. Double sealing cap to prevent accidental leakage. Smooth, non- jerky piston sliding. 2 mL	2	
			12 12 1 pc.: 800 ml renal-type bowl made of polypropylene. 800 mL 13 1 pc.: 2-layer sterile field: a) absorbent layer on the entire surface; b) 100% waterproof layer -	1	
			13 15 1 pc.: 2-layer stenie field: a) absorbent layer on the entire surface; b) 100% waterproof layer - 100x150 cm minimum dimensions 100 x 150cm.	1	
	P	• •		-	
	Raw Mater Product Col		Biflex Medical Phys		
	Reference C		Medical Blue SP-01001-67		
	Weight in G		Biflex 56 gsm		
	Package		Flat Pouch		
	P	roduct: Medical Devic	ce Directive MDR 2017/745 ECC ANNEX XI A ALL VERSIONS. / Products and materials used do not contain metal.		
			Product Shelf Life - 5 Years		
	Product M Unit / Siz		PROPERTIES		
			1 2 3 4		
1	***	35 bar			
1	***	1.7mm /3.6mm			
1	20.00.00	uzunluk 50 cm			
1	***				
		1	5 6 7 8		
3	***	length 1800mm			
F0	***				
50	***	10x10 cm	THE PARTY OF THE P		
1	***	2500 mL			
_		length min 9			
1	***	12 mL	9 10 11 12		
	1				
1	***	20 mL			
2	***	20 mL			
۷	- and - and -	ZU IIIL			
4	***	5 mL	42		
			13		
2	***	2 mL			
		000 7			
1	***	800 mL			
1	Biflex	100x150 cm			
To	lerances:	+/- 2% cm	Package Information		
	asurement:	cm			
			The products in the sterilization bag are double-packaged to reduce all risks during transportation. Double packaged pr	roducts are put into	
			Baymed's standard sized carton; dimensions are as follows:		
			Height = 44 cm; Length = 40 cm ve Width = 60 cm.		
	Preparation	Date	OHALITY CONTROL APPROVAL		
	гтерагацоп	Date	QUALITY CONTROL APPROVAL		