

Name Bezel color Type-model Panel Viewable image size Max view area (W x H) Native resolution Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD) Power supply Weight Limited warranty Available date	T23i Wide Flat Panel Monitor Black 61ABMAR1US / 61ABMAT1EU TFT-LCD, In-Plane Switching (IPS), White LED backlight 23" (584.2mm) diagonal 20.36" x 11.92" (517.2mm x 302.8mm) 1920x1080 16:9 0.2652 x 0.2652 mm 95.8 dpi 250 nits or cd/m² (typical) 1000:1 (typical) 6ms (typical) 72% 178° (+/- 89°) horizontal, 178° (+/- 89°) vertical Tilt, swivel, pivot, and height adjustable stand <i>Sides:</i> 0.08" (2.0mm) 13.3" H x 20.56" W x 10.4" D; 337.7mm H x 522.2mm W x 264.2mm D 16 watts typical, 45 watts maximum (with USB 3.0 hub), <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 10.85 lb; 4.92 kg 3 year (includes backlight) April 2017	Features • Widescreen 23-inch monitor • Supports 1920x1080 resolution • Supports ThinkCentre Tiny Clamp Bracket • Includes dual input connection for attachment to two systems concurrently • EPEAT Gold certified • Microsoft® Windows® 7 certified • Microsoft Windows 10 certified				
VESA-compliant Power management Ergonomics Emission standards Environmental	VESA DDC2B/CI ENERGY STAR® qualified ISO 9241-307 FCC Class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT™ Silver rating	 ThinkVision T23i Wide Monitor				
Preset resolutions	VGA: 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900 WSXGA+: 1680x1050 Full HD: 1920x1080					
Presets display modes	HDMI: 18; DP: 18					
Viewing adjustments Rotating screen On screen display Control features USB hub Multiple input Monitor connectors	<i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Direct access (buttons on front) for power, menu, input source select and brightness and automatic image setup USB 3.0 Hub: 1 port into PC (USB 3.0); 4 ports for accessories (4 USB 3.0) Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant					
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter					
Mounting features Security	Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)					
Ship group	Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter USB signal cable, 1.8 meter black power cord					
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281						
Accessories <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr></table> See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision			Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582					
Kensington Twin Head Cable Lock	45K1620					