

CERTIFICATE

Quality Austria - Trainings, Zertifizierungs und Begutachtungs GmbH awards this **qualityaustria** certificate to the following organisation:

This **qualityaustria** certificate confirms the application and further development of an effective

 **EGGER**

Fritz Egger GmbH & Co. OG.
A-6380 St. Johann, Weibersdorf 20

QUALITY MANAGEMENT SYSTEM
complying with the requirements of standard
ISO 9001:2015

Sites: see Appendix

Production of wood-based materials, laminates,
glues and impregnation resins, recycling

Registration No.: Q-00184/0

Date of initial issue: 22 March 1994

Valid until: 26 August 2027



 **qualityaustria**

MEMBER OF



Vienna, 20 August 2024

The validity of the **qualityaustria** certificate will be maintained by annual surveillance audits and one renewal audit after three years.

Quality Austria - Trainings, Zertifizierungs und Begutachtungs GmbH,
AT-1010 Vienna, Zelinkagasse 10/3



Mag. Christoph Mondl
CEO



Mag. Dr. Werner Paar
CEO



Ing. Christoph Baumgartner, MSc, MBA
Authorised representative,
management Customer Service Center

Quality Austria - Trainings, Zertifizierungs und Begutachtungs GmbH is accredited according to the Austrian Accreditation Act by the BMWFV (Federal Ministry of Science, Research and Economy).

Quality Austria is accredited as an organisation for environmental verification by the BMLFUW (Federal Ministry of Agriculture, Forestry, Environment and Water Management).

Quality Austria is authorized by the VDA (Association of the Automotive Industry).

For accreditation registration details please refer to the applicable decisions or recognition documents.

Quality Austria is the Austrian member of IQNet (International Certification Network).

Dok. Nr. FO_24_028

aadf8c78-0afd-4973-9bc3-849a6c7090b5

The current validity of the certificate is documented exclusively on the Internet under <http://www.qualityaustria.com/en/cert>

Annex

**to the certificate, registration number: Q-00184/0
ISO 9001 : 2015**

**Fritz Egger GmbH & Co. OG.
AT-6380 St. Johann, Weiberndorf 20**

Barony	EGGER UK Ltd.
Bevern	EGGER Beschichtungswerk M. GmbH & Co.KG
Biscupiec	EGGER Biskupiec sp. z o.o.
Gifhorn	EGGER Kunststoffe GmbH & Co. KG
Brilon	EGGER Brilon Service GmbH EGGER Holzwerkstoffe Brilon GmbH & Co. KG EGGER Holzwerkstoffe Wismar GmbH & Co. KG (Werk Brilon)
Brilon Sägewerk	EGGER Sägewerk Brilon GmbH
Bünde	EGGER Holzwerkstoffe Brilon GmbH & Co. KG
Campact Glue Factory	Campact Limited
Gagarin	OOO EGGGER Drevprodukt Gagarin
Gebze	EGGER Dekor A.Ş EGGER Orman Ürünleri A.Ş Roma Plastik Sanayi Ve Ticaret A.S.
Hexham	EGGER UK Ltd.
Lexington	EGGER Wood Products, LLC.
Mariemünster	EGGER Beschichtungswerk M. GmbH & Co.KG
Radauti	EGGER Romania SRL.
Radauti Glue Factory	EGGER Technologia SRL.
Rambervillers	EGGER Panneaux & Décors SAS, Rambervillers
Rion	EGGER Panneaux & Décors SAS, Rion
Shuya	OOO EGGGER Drevprodukt Shuya
St. Johann in Tirol	Fritz EGGGER GmbH & Co. OG
Unterradlberg	Fritz EGGGER GmbH & Co. OG
Wismar	EGGER Holzw. Wismar GmbH & Co. KG LTPRO GmbH (Leimfabrik)
Wörgl	Fritz EGGGER GmbH & Co. OG
Caorso (PC)	SAIB S.P.A.

This annex is only valid in connection with the above-mentioned certificate.

Environmental & Health Data Sheet

Self-declaration according to ISO 14021

EGGER Laminate

EGGER laminates are decorative laminates based on curable resins. They have a multilayer structure and consist of melamine resin impregnated decorative paper and one or more layers of soda kraft paper impregnated with phenolic resins, which are laminated under high pressure and heat. EGGER laminates are non-weight-bearing materials and suitable for indoor applications only. The laminates are used for the lamination of wood-based materials or other core boards as composite elements for indoor applications in furniture construction and interior design.

Raw Materials & Primary Products

Wood origin for paper production

Our plants are certified according to the standard ISO 38200:2018, all paper can be referred to the ISO 38200:2018 statements. On request and in agreement with your contact person at the EGGER sales department, our products can be declared on our sales documents also with other certification claims, depending on the availability at the production site. Please inquire availability details from your sales or certificates and an up-to-date list of the regional origin and wood species used in the product, see document available for download at www.egger.com/environment:

Manufacturer's Declaration – Timber origins (Pdf)

- Manufacturer Declaration – Sustainable Forestry (Pdf)
- Certificate ISO 38200:2018 (Pdf)
- Further 3rd party certificates of sustainable wood procurement (Pdf) (Pdf)

Renewable content

	Renewable content	Fossil-based content
EGGER Laminate	60 %	40 %

Average renewable resource content by dry weight, in relation to all constituent materials (incl. glue, resin and others). Figures may vary between thicknesses.

Recycled content

	Virgin material	Co-products	Pre-consumer recycling material	Post-consumer recycling material
EGGER Laminate	100 %	0 %	0 %	0 %

Average recycling content by dry weight, in relation to all constituent materials (incl. glue, resin and others). Figures may vary between thicknesses.

Carbon Footprint

	Global warming potential
1 m ² EGGER Laminate	2.03 kg CO ₂ -equivalent

A negative amount indicates that carbon is stored in the product. Data on carbon storage in products (carbon footprint) is taken from the Life Cycle Assessment (LCA) in the Environmental Product Declaration (EPD). GWP 100 (global warming potential over 100 years), cradle-to-gate.

Constituent materials

EGGER laminates are constructed by fusing multiple layers and consists of melamine resin impregnated decor paper and several phenolic resin impregnated core layers. The table below contains 99.9% of the primary products, measured by weight. Proportions may vary between individual product thicknesses. Listed is the average across all thicknesses in one production year. All chemicals have been evaluated and are disclosed down to 1000 ppm.

Proportion		Function	Composition / Add. info
64 -68	%	Paper core layers, decorative layer and overlay	1% overlay paper, 17% decorative paper, 13 % parchment paper (core layers), 69% soda kraft paper (core layers) Average cellulose content 91%
18 - 21	%	Phenole formaldehyde resin	Polymer on a melamine, phenole and formaldehyde basis/ <i>During the pressing process, the aminoplastic resin hardens fully. Under normal conditions , it is bound to the paper and chemically stable</i>
9 - 11	%	Melamine- formaldehyde resin	Polymer on a melamine formaldehyde basis / <i>During the pressing process, the aminoplastic resin hardens fully. Under normal conditions , it is bound to the wood and chemically stable</i>
3 - 4	%	Flexibilizer	Di-ethylene glycole
< 2	%	Hardener	Amine salt in water/ <i>chloride-free</i>
< 1	%	High abrasive wear layer (ingredient of overlay)	Corund (high abrasive mineral)
< 1	%	pH Catalyst	PTS acid
< 1	%	Release agent	Blend of ethoxylated and modified alcohols

Manufacturing

Production plants & their certifications

The product is manufactured at the following locations. You find the plant certifications available for download at www.egger.com/environment. For production plant's address kindly see footnotes at the end of this document.

Plant ⁱ	Certifications ⁱⁱ obtained by this plant			
	Quality	Environment	Energy	Wood origin
Gifhorn, D	ISO 9001	ISO 14001	ISO 50001	ISO 32800

Processing

Safety

This product is not hazardous in the form in which it is shipped by the manufacturer. Dust may be generated during processing. There is a risk of sensitization of the skin and respiratory tract. Depending on the processing and the particle size, especially when inhaling dust, there may be further health risks. The formation of dust must be taken into account when assessing risks in the workplace. In particular in the case of machining processes (e.g. sawing, planing, milling), an effective extraction system must be used in accordance with the applicable health and safety regulations. If there is no adequate suction, suitable respiratory protection must be worn.

Technical data

See Technical Datasheets available at the product download area at www.egger.com/products

Use

Product certification

- TÜV ProfiCert Product Interior PREMIUM

On request the products can be labelled with a certification claim according to:

- ISO 38200:2018
- Further 3rd party certificates of sustainable wood procurement

To download certificates, see EGGER environmental downloads at www.egger.com/environment and product category's downloads at www.egger.com/products.

Product emissions & Health aspects

Natural wood constituents may be released in small quantities. Minor amounts of formaldehyde can be detected. During the EGGER Laminate's manufacturing processes, heat and pressure is applied in a short cyclepress. All resins cure completely into a solid material. In the use phase, the product is chemically stable under normal conditions. There are no known health hazards or health effects to be expected under normal conditions, when the product is used as intended.

The product is subjected to annual tests within the scope of TÜV PROFICERT-product Interior surveillance by an independent third party. Please note: requirements listed as met "via TÜV PROFICERT" are NOT CERTIFIED stand-alone in this category!

The following table contains an overview of requirements, on which the product has been tested by an independent third party and fulfills the emission requirements. See Annex for limit values and further details.

Substance / indicator	Product has been tested and fulfils emission requirement	Requirement	Requirement details ⁱⁱ
Formaldehyde	✓	E1	Formaldehyde class E1, according to EN DIN EN 16516, external testing
Formaldehyde	✓	E1 DE 2020 \triangleq E1E05	German ChemVerbotsVO Formaldehyde class E1 from 1.1.2020, external testing
VOC, Formaldehyde, Carcinogens, Ammonia, Nitrosamines	✓	TÜV PROFICERT-product Interior PREMIUM	Common Label for the Health and Quality Assessment of Interior Products
VOC, Carcinogens	✓	AgBB 2018	via TÜV PROFICERT (see above)
VOC	✓	French VOC regulation, emission class A+	via TÜV PROFICERT (see above)
VOC	✓	Belgian VOC regulation	via TÜV PROFICERT (see above)
VOC, Formaldehyde, Carcinogens, harmful substances	✓	CAM Italy	via TÜV PROFICERT (see above)
VOC, Formaldehyde, Carcinogens	✓	BREEAM Exemplary Level	via TÜV PROFICERT (see above)
VOC	✓	Finnish M1 classification	via TÜV PROFICERT (see above)
Formaldehyde, VOC Carcinogens, harmful substances	✓	DE-UZ 76 (Blue Angel)	via TÜV PROFICERT (see above)
Formaldehyde	✓	LEED v4 (outside North America)	via TÜV PROFICERT (see above)

Substance / indicator	Product has been tested and fulfils emission requirement	Requirement	Requirement details ⁱⁱ
Formaldehyde Melamine	✓	Food safety	European Plastics Regulation (EU) No 10/2011, Guidelines on testing conditions for articles in contact with foodstuffs
Antimony, arsenic, barium, cadmium, chromium, lead, mercury, selenium	✓	Safety of toys	DIN EN 71-3: Safety of toys

End of life – Waste treatment

Reuse

Since laminates are usually used as composite materials, reuse is not possible.

Recycling – Material use

Laminate itself cannot be recycled for the same use. But if it is applied on a chipboard carrier, the laminated chipboards still can be recycled and are actively used for the production of new chipboards.

Incineration – Energetic use

After its utilization phase, the product should be separated and routed to an energetic recovery, due to its high calorific value of approx. **15 – 16 MJ/kg**. Upon incineration, kindly observe all locally applicable legal requirements for the correct dimensions, required filter technologies, operating conditions, and legal permissions for burning the core board, on which the EGGER Laminate is glued.

Waste code according to European Waste Catalogue, depending on type and volume of the core board, on which the EGGER Laminate is glued:

- 17 02 01 Construction & Demolition Waste: Wood
- 03 01 03 Construction & Demolition Waste: Plastic

The product itself is not classified as hazardous waste. If the wood composites, that are covered by EGGER Laminate also do not contain wood reservatives and halogenated compounds, the waste can be classified as glued, laminated waste wood without halogenated compounds in the lamination layer and without wood preservatives.

See also document available for download at www.egger.com/environment:

- Manufacturer's Declaration – Wood preservatives (Pdf)
- Manufacturer's Declaration – Halogenated organic compounds (Pdf)

Environmental life cycle assessment

The product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804.

- EPD Laminate (Pdf)
available for download at www.egger.com/environment



Compliance with LEED v4

The EGGER Laminate is compliant with the prerequisites for use in LEED certified buildings outside the U.S. Beyond that the usage of a EGGER Laminate contributes to gather additional points within the LEED scoring system. The following table shows all LEED credits which are applicable to the usage of our product. As the actually achievable number of points depends on the attributes of all used materials in the LEED building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see LEED credit library at www.usbc.org.

Projects outside U.S.

LEED v4 Requirements for Building Design + Construction (BD+C) New Construction, Core and Shell, Schools, Retail, Healthcare, Data Centers, Hospitality, Warehouses and Distribution Centers			Product contributions
LEED v4 Requirements for Interior Design + Construction (ID+C) Commercial Interiors, Retail, Hospitality			
Chapter	Requirement summary	Maximum Points	
Material and Resources	Building Product Disclosure and Optimization - Environmental Product Declarations Option 1. Environmental Product Declaration (EPD)	1 Point	This product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804. See <ul style="list-style-type: none"> EPD Laminate (Pdf) available for download at www.egger.com/environment
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 1.:Raw material source and extraction reporting Third-party verified corporate sustainability reports (CSR) according to an accepted framework.	2 Points	An annual Sustainability report is published in accordance with the GRI standards: "Core" option, and is audited by an independent party. See <ul style="list-style-type: none"> Sustainability report (Pdf) available for download at www.egger.com/environment .
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.3: Wood products must be certified by the Forest Stewardship Council® (FSC®) or USGBC-approved equivalent.		Yes, the product can be purchased in 3 rd party certified qualities on request . Use delivery receipt as evidence document. See also chapter "Wood origin" of this document.
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.5: Recycled content is the sum of postconsumer recycled content plus one-half the preconsumer recycled content	1 Point	<i>This product does not contain any recycled material. See "Constituent materials" section above to obtain further information.</i>
Material and Resources	Building Product Disclosure and Optimization - Material Ingredients Option 1: Declare.	1 Point	The manufacturer has screened the product to at least 1,000 ppm and has provided a publicly available inventory. See "Constituent materials" section above to obtain further information.
Indoor Environmental Quality	Low-emitting Materials- VOC emissions evaluation (product categories ceilings, walls, acoustic insulation only) Product complies with the LCI values of the German AgBB Testing and Evaluation Scheme	3 Points	Product complies with the LCI values of the German AgBB scheme. See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> TÜV PROFICERT-product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .
Indoor Environmental Quality	Low-emitting Materials- Formaldehyde emissions evaluation For projects outside the U.S. , composite wood must be documented not to exceed a concentration limit of 0.05 ppm of formaldehyde.		Product is tested per EN 717-1:2014 for formaldehyde emissions and complies with emissions class E1 DE 2020. See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> TÜV PROFICERT-product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .

Projects inside U.S.

Please note that formaldehyde emission requirements in LEED v4 are deviating for projects **inside the U.S.**

LEED v4 Requirements for Building Design + Construction (BD+C) New Construction, Core and Shell, Schools, Retail, Healthcare, Data Centers, Hospitality, Warehouses and Distribution Centers			Product contributions
LEED v4 Requirements for Interior Design + Construction (ID+C) Commercial Interiors, Retail, Hospitality			
Chapter	Requirement summary	Maximum Points	
Material and Resources	Building Product Disclosure and Optimization - Environmental Product Declarations Option 1. Environmental Product Declaration (EPD)	1 Point	This product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804. See <ul style="list-style-type: none"> EPD Laminate (Pdf) available for download at www.egger.com/environment
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 1: Raw material source and extraction reporting Third-party verified corporate sustainability reports (CSR) according to an accepted framework.	2 Point	An annual Sustainability report is published in accordance with the GRI standards: "Core" option, and is audited by an independent party. See <ul style="list-style-type: none"> Sustainability report (Pdf) available for download at www.egger.com/environment .
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.3: Wood products must be certified by the Forest Stewardship Council® (FSC®) or USGBC-approved equivalent.		Yes, the product can be purchased in 3 rd party certified qualities on request . Use delivery receipt as evidence document. See also chapter "Wood origin" of this document.
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.5: Recycled content is the sum of postconsumer recycled content plus one-half the preconsumer recycled content, based on cost.	1 Point	<i>This product does not contain any recycled material. See "Constituent materials" section above to obtain further information.</i>
Material and Resources	Building Product Disclosure and Optimization - Material Ingredients Option 1: Declare.	1 Point	The manufacturer has screened the product to at least 1,000 ppm and has provided a publicly available inventory. See "Constituent materials" section above to obtain further information.
Indoor Environmental Quality	Low-emitting Materials- Formaldehyde emissions evaluation: Composite wood must be documented to have low formaldehyde emissions that meet the requirements for ultra-low-emitting formaldehyde (ULEF) resins or no added formaldehyde resins.		<i>The product does not fulfil ULEF requirements. Resin on a formaldehyde basis is used.</i>

Compliance with WELL Building Standard v2™

EGGER Laminate is compliant with the preconditions for use in WELL v2™ certified buildings. Beyond that the usage of this product may contribute to gather additional points within the WELL scoring system. The following table shows all WELL features which are applicable to the usage of our product. *Requirements given in italics are currently not met by the product.* As the actually achievable number of points depends on the attributes of all used materials in the WELL building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see WELL feature library at www.wellcertified.com.

Requirements			Product contributions
Chapter	Requirement summary	Maximum Points	
X01 Material Precautions	Restrict asbestos, mercury and lead.	Precondition	<p>The product complies with this precautions. See Manufacturer's Declaration – Asbestos (Pdf) available for download at www.egger.com/environment. Use</p> <ul style="list-style-type: none"> TÜV PROFICERT-product Interior PREMIUM as evidence document for healthy living products, available for download at www.egger.com/downloads.
X05 Enhanced Material Restrictions	Part 2a Select Compliant Architectural and Interior Products: Flooring products, ceiling and wall panels contain halogenated flame retardants (HFR) at less than 100 ppm.	1 Point	<p>The product complies with this requirement. No halogenated flame retardants (HFR) are used in this product. See "Constituent materials" section above for your documentation. Please get in touch with the EGGER product sustainability & compliance team at environment@egger.com to get Manufacturer's declaration on the use of halogenated compounds (Pdf).</p>
X05 Enhanced Material Restrictions	Part 2a Select Compliant Architectural and Interior Products: Newly installed floorings and furniture contain Orthophthalates at less than 100 ppm.		<p>In general, no softening agents are used in the production of , laminates in particular no phthalates. See "Constituent materials" section above for your documentation.</p>
X06 Volatile Compound reduction	Part 2a Restrict VOC Emissions from Furniture, Architectural and Interior Products: Furniture and wall panels tested per AgBB or CDPH method and VOC emission threshold established.	2 Points	<p>Product complies with the LCI values of the German AgBB scheme. See "Product emissions & Health aspects" section above for further information. Use</p> <ul style="list-style-type: none"> TÜV PROFICERT-product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads.
X06 Volatile Compound reduction	Part 2c2 Restrict VOC Emissions from Furniture, Architectural and Interior Products: Composite wood panels meet the formaldehyde standards European E1, TSCA, F*** or LEED v4.1		<p>Product is tested per EN 717-1:2014 for formaldehyde emissions and complies with emissions class E1 DE 2020. See "Product emissions & Health aspects" section above for further information. Use</p> <ul style="list-style-type: none"> TÜV PROFICERT-product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads.
X07 Material Transparency	Part 1: Select Products with Disclosed Ingredients: Promote ingredient disclosure with ingredients identified and disclosed to 1,000 ppm.	1 Point	<p>The product is screened to at least 1,000 ppm and the manufacturer has provided a publicly available inventory within this document. See "Constituent materials" section above for your documentation.</p>
X08 Materials Optimization	Part 1 Select Material with Enhanced Chemical Restrictions: Newly installed furnishings, built-in furniture, interior finishes and finish materials comply with some combination of the listed programs (e.g. Living Building Challenge Red List Free)	2 Points	<p><i>Currently our product does not participate in any of the listed programs. It does not contribute to achieve points for this requirement.</i></p>
X08 Materials Optimization	Part 2 Select Optimized Products: Product is certified by one of the listed programs (e.g. Cradle to Cradle)		<p><i>Currently our product does not participate in any of the listed programs. It does not contribute to achieve points for this requirement.</i></p>

Compliance with BREEAM International New Construction 2016

EGGER Laminate is compliant with the preconditions for use in BREEAM 2016 certified buildings and fulfils the emission requirements at exemplary level. Beyond that the usage of this product may contribute to gather additional points within the BREEAM scoring system. *Requirements given in italics are currently not met by the product.* The following table shows all BREEAM credits which are applicable to the usage of our product. As the actually achievable number of credits depends on the attributes of all used materials in the BREEAM building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see BREEAM manual at www.breeam.com.

Requirements			Product contributions
Chapter	Requirement summary	Maximum Credits	
Mat 01 Life cycle impacts	Environmental product declarations (EPD) – product installed by Post-Construction Stage is covered by verified EPD	1 Credit	This product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804. See <ul style="list-style-type: none"> ▪ EPD Laminate (Pdf) available for download at www.egger.com/environment
Mat 03 Responsible sourcing of construction products	All timber-based products used on the project are legally harvested and traded timber.	Prerequisite	The product is verified by the ISO 38200 : 2018 statements. The standard considers all legality requirements in the respective purchasing or production country and all environmental and social criteria known in the ISO system. See also chapter “Wood origin” of this document. Additionally, the product can be purchased in other 3 rd party certified qualities on request. Use delivery receipt as evidence document.
Hea 02 Indoor air quality	Avoidance of asbestos.	Prerequisite	The product complies with this prerequisite. See Manufacturer’s Declaration – Asbestos (Pdf) available for download at www.egger.com/environment
Hea 02 Indoor air quality	Minimising sources of pollution - Emissions from building products. Product should meet the exemplary level emission criteria Formaldehyde $\leq 0.01 \text{ mg/m}^3$ TVOC $\leq 0.3 \text{ mg/m}^3$ TSVOC $\leq 0,001 \text{ mg/m}^3$ Category 1A and 1B carcinogens $\leq 0.001 \text{ mg/m}^3$	2 Credits	Product meets the exemplary level emissions criteria. Use <ul style="list-style-type: none"> ▪ TÜV ProfiCert Product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .

Compliance with DGNB System Version 2020 International – New buildings criteria set

The DGNB Silver, Gold and Platinum ratings result from the overall level of fulfillment of the building project. Which quality levels EGGER Laminate fulfills according to the DGNB system and where you can find the required verifications can be found in the following table. The contributions to the overall degree of fulfillment resulting from this according to the DGNB point system depend, among other things, on the relevance of the product group for the overall building. Please note that other criteria are also relevant for the overall rating of the building. We can therefore not guarantee a score to be obtained through the use of EGGER Laminate.

Requirements			Product contributions
Topic	Requirement summary	Quality level	
ENV1.1 Building life cycle assessment	The building life cycle assessment requires building material data. Specific and verified life cycle assessment data (e.g. Environmental Product Declaration, EPD) should be preferred over general, generic life cycle assessment data.	General requirement	This product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804. See <ul style="list-style-type: none"> EPD Laminate (Pdf) available for download at www.egger.com/environment
ENV1.2 Local environmental impact	Wood materials equipped with flame retardents: Boron compounds ≤ 0.1%	4	Surveillance of boron compounds is covered by the TÜV PROFICERT product Interior PREMIUM certificate. See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> TÜV PROFICERT-product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads
ENV1.2 Local environmental impact	Interior walls, floor and ceiling coverings (such as fibreboards): Asbestos free	4	The product complies with this requirement. See Manufacturer's Declaration – Asbestos (Pdf) available for download at www.egger.com/environment
ENV1.2 Local environmental impact	Documentation of emission: Certification (by a laboratory accredited in accordance with ISO 17025 that the product or system complies with the AgBB criteria	4	Product complies with the LCI values of the German AgBB scheme. See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> TÜV PROFICERT-product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .
ENV1.2 Local environmental impact	No chemical wood preservative in the interior.	4	During the production of EGGER Laminate no wood preservatives are added. See Manufacturer's declaration Wood Preservatives (Pdf) available for download at www.egger.com/environment .
ENV1.3 Sustainable resource extraction	Certified sustainable resource extraction	1.3	The product is verified by the ISO 38200 : 2018 statements. See also chapter "Wood origin" of this document. Additionally, the product can be purchased in other 3 rd party certified qualities on request. Use delivery receipt as evidence document.

Compliance with Nordic Swan Ecolabel

Small houses, apartment buildings and buildings for schools and pre-schools

The product EGGER Laminate is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings (Portal Nordic Ecolabelling) under the Manufacturer's name Egger, Fritz GmbH & Co. As an applicant for an Ecolabelled building, please inform your Nordic Swan certifier about the product listing. For the use of EGGER Laminate no other documents are necessary for your application.

Furniture and Fitments, version 4.15

If you are planning to certify a furniture product with the Nordic Swan Ecolabel, we as your supplier are happy to provide you with the required evidence documents, as shown below. From our current knowledge, all other requirements beyond this list are not applicable to this product from the raw material supplier. When in doubt, please always take the original criteria version as a reference at the official Nordic Swan website.

Requirements		Product contributions
Chapter	Requirement summary	
R11 Origin and traceability	Written procedure ensuring traceability to the origin of the raw materials	The product complies with the requirement. The following evidence document can be used: <ul style="list-style-type: none"> ▪ Certificate ISO 38200:2018 (Pdf) available for download at www.egger.com/environment .
R12 Chemical products and additives	Chemical products and additives/constituent substances used in the production of wood-based panels must satisfy the requirements of R3, R4 and R5 in Chapter 2.1.	The product complies with the requirement. Please get in touch with the EGGER product sustainability & compliance team at environment@egger.com to get Form 2a documents and safety data sheets for each chemical product and additive/ constituent substance.
R13 Formaldehyde	Average emissions of formaldehyde must not exceed 0.07 mg/m ³ air as determined by the current version of EN 717-1	Product is tested per EN 717-1:2014 for formaldehyde emissions and complies with emissions class E1 DE 2020. See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> ▪ TÜV PROFICERT-product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .

Compliance with other labels & regulations

Additional information in the form of manufacturer declarations, EPDs and brochures is available at

- www.egger.com/environment

Your label or regulation is missing? The EGGER product sustainability & compliance team is happy to support you with suitable information on the requirements. Please get in touch with

- environment@egger.com

or contact your EGGER sales contact or distributor, who are happy to forward the inquiry.

Footnotes

i

Production plant	Address
Gifhorn., D	EGGER Kunststoffe Gifhorn GmbH & Co. KG, Im Weilandmoor 2, 38518 Gifhorn (D)

ii

Product Certifications	
ISO 38200:2018	ISO 38200:2018 Chain of Custody of wood and wood-based products
TÜV PROFICERT PREMIUM	TÜV PROFICERT-product Interior PREMIUM certification criteria V1.3

iii

Substance	Requirement	Norm reference	Limit value	Testing method
Formaldehyde	E1	Chemicals Act (Chemicals Prohibition Ordinance; German: Chemikalien-Verbotsverordnung, ChemVerbotsV), Appendix 1 to Section 3, Entry 1: "Formaldehyde" Clause 2(1)	0.1 ppm	DIN EN 16516
Formaldehyde	E1 DE 2020 ≙ E1E05	Chemicals Act (Chemicals Prohibition Ordinance; German: Chemikalien-Verbotsverordnung, ChemVerbotsV), Appendix 1 to Section 3, Entry 1: "Formaldehyde" Clause 2(1)	0.1 ppm [test result x factor 2]	DIN EN 717-1
TVOC TSVOC Tolouene Formaldehyde Acetaldehyde CMR substances 1A & 1B R value TVOC w/o LCI	AgBB 2018	AgBB 2018 evaluation scheme for VOC emissions from construction products, Committee for Health-related Evaluation of Building Products (German: Ausschuss zur gesundheitlichen Bewertung von Bauprodukten AgBB)	≤ 1000 µg/m ³ ≤ 100 µg/m ³ 2900 µg/m ^{3*}) 100 µg/m ^{3*}) 1200 µg/m ^{3*}) ≤ 1 µg/m ³ ≤ 1 ≤ 100 µg/m ³ *) NIK, LCI, CLI	DIN ISO 16000-3, -6, 9, -11, DIN EN 16516
TVOC (AgBB) TVOC (DIN EN 16516) TSVOC	TÜV PROFICERT PREMIUM	TÜV PROFICERT-product Interior PREMIUM v. 1.3 for details see	< 300 µg/ m ³ (28d) ≤ 200 µg/ m ² h (28d) ≤ 100 µg/ m ³ (28d)	ISO 16000 parts 3, 6, 9, 11/ EN 16516

VOC R value Formaldehyde 1,4-Dichlorobenzol Trichlorethylene DEHP DBP Carcinogenic, mutagenic substances and substances toxic to reproduction (EU-category 1A and 1B according to CLP Regulation (EC) No 1272/2008) Ammoniac Nitrosamines Formaldehyde according to "ChemVerbotsV E1 DE 2020 (DIN EN 717-1, result with factor 2) Formaldehyde according to "ChemVerbotsV E1 DE 2020 (DIN EN 16516)		proficert.de	< 100 µg/ m³ (28d) < 1.0 µg/ m³ (28d) < 10 µg/ m³ (28d) < 60 µg/ m³ (28d) ≤ 1 µg/ m³ (28d) ≤ 1 µg/ m³ (28d) ≤ 1 µg/ m³ (28d) ≤ 1 µg/ m³ (28d) ≤ 24 µg/ m³ (28d) ≤ 0.2 µg/ m³ (28d) ≤ 0.1 ppm (28d) ≤ 0.1 ppm (28d)	
VOC Carcinogens	German AgBB	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
VOC	French A+	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
VOC	Belgian VOC regulation	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
Formaldehyde VOC	Minimum Environmental Criteria CAM Italy	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
VOC Formaldehyde Carcinogens	BREEAM International, Exemplary Level	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
VOC	Finnish M1 classification	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
VOC Formaldehyde Carcinogens	DE-UZ 76 (Blue Angel)	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
VOC Carcinogens	Annex 8 MVV TB/ ABG, 2019/1	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
Formaldehyde VOC	LEED v4 (outside North America)	covered by TÜV PROFICERT-product Interior PREMIUM	see TÜV PROFICERT	see TÜV PROFICERT
Σ PAK/ PAH	AfPS GS 2014:01 PAK	AfPS GS 2014:01 PAK	< 1 mg/kg	AfPS GS 2014:01

Revision: 05
Approved: 22.01.2024

Manufacturer Declaration Stockholm Convention on Persistent Organic Pollutants (POP)

The Stockholm Convention on Persistent Organic Pollutants is an environmental treaty, signed on 2001 and effective from May 2004. This treaty aims to eliminate or restrict the production and use of specific persistent organic pollutants (POPs). The treaty was adopted to EU legislation EC 850/2004 and was recast by the regulation EU 2019/1021 in June 2019. Initially the regulation covered twelve substances, but the list was modified and extended.

We hereby confirm, that no listed substances (POP) are actively used in the production of EGGER products and that EGGER fully complies with legislation EU1029/1021.

A handwritten signature in black ink, appearing to be "Alexander Krimbacher".

Alexander Krimbacher
Product Compliance
EGGER group
22.01.2024, St. Johann in Tyrol

Fritz EGGER GmbH & Co. OG
Weiberndorf 20
6380 St. Johann in Tyrol
Austria

MINISTERUL SĂNĂTĂȚII AL REPUBLICII MOLDOVA
МИНИСТЕРСТВО ЗДРАВООХРАНЕНИЯ
РЕСПУБЛИКИ МОЛДОВА
AGENȚIA NAȚIONALĂ PENTRU SĂNĂTATE PUBLICĂ
НАЦИОНАЛЬНОЕ АГЕНТСТВО ОБЩЕСТВЕННОГО
ЗДОРОВЬЯ

MD-2028, mun. Chișinău, str. Gheorghe. Asachi, 67 a
Tel. + 373 22 574501, fax + 373 22 729725
IDNO 1018601000021
e-mail: office@ansp.gov.md

DOCUMENTAȚIE MEDICALĂ/ Медицинская документация
FORMULAR/ Форма Nr. 303-2/c
APROBAT DE MS al RM / Утверждена МЗ РМ Nr. 828
от 31.10.11
Centrul de încercări de laborator acreditat de către Centrul
Național de Acreditare din Republica Moldova MOLDAC
Испытательный лабораторный центр аккредитованный
Национальным Аккредитационным Центром РМ MOLDAC
Certificat nr. LI-044 din 17.02.2018 valabil până la 16.02.2026

AVIZ SANITAR
PENTRU PRODUSELE ALIMENTARE ȘI NEALIMENTARE Nr. P-22313/2025
Санитарное заключение для пищевых и непищевых продуктов
din/от 31 iulie 2025

Prin prezentul aviz sanitar se confirmă că producerea, importul, utilizarea și desfacerea produselor / echipamentelor
Настоящим санитарным заключением подтверждается что производство, ввоз, использование и реализация продукции / оборудования
Veselă și accesorii de bucătărie m.c."MAESTRO"

sunt conforme **Regulamentului (lor) sanitar (e) / соответствуют санитарному (ым) регламенту (ам) (se va indica denumirea completă a**
Regulamentului (lor) sanitar (e) / указать полное наименование санитарного (ых) регламента (ов))
Regulamentului sanitar privind materialele și obiectele destinate să vină în contact cu produsele alimentare
aprobat prin HG 308/2011

Organizația-producătoare/importatoare, țara de origine / организация произв./импортер, страна происхождения
China, "M.C.MAESTRO"; Polonia, Splash sp. z o.o. - furnizor

Destinatarul avizului sanitar / получатель санитарного заключения
"SIGHIȘOARA" S.R.L., Republica Moldova, mun. Chișinău, sec. Botanica, str. Sarmizegetusa, 1

Temei pentru recunoașterea conformității produselor Regulamentului (lor) sanitar (e) menționat (e) a servit /
Основанием для признания продукции указанному (ым) санитарному (ым) регламенту (ам) послужило
Demers, contract nr.1 din 04.01.2013, invoice nr.F00008/2025 din 05.06.2025, aviz sanitar nr.P-20073/2024
(a enumera documentele de însoțire, buletinele de analiză / перечислить сопроводительные док., протоколы исслед.)

Caracteristica sanitară a produselor / санитарная характеристика продукции:
Parametrii (factorii) / показатели (факторы) **Normativul sanitar / санитарный норматив**
Vesela în corespundere cu Regulamentul 1935/2004, HG 308/2011 admisă pentru contact cu produse alimentare

Domeniu de utilizare / Область применения:
contact produse alimentare

Condițiile necesare de utilizare, depozitare, transportare, măsurile de securitate / Необходимые условия использования, хранения,
транспортировки, меры безопасности:
plasarea pe piață în condițiile respectării legislației în vigoare în Republica Moldova

AVIZUL SANITAR este valabil pînă la / Санитарное заключение действительно до: 30.07.2028

DIRECTORUL AGENȚIEI NAȚIONALE PENTRU SĂNĂTATE PUBLICĂ

Vasile Gustiuc

Digitally signed by Guștiuc Vasile
Date: 2025.07.31 13:18:44 EEST
Reason: MoldSign Signature
Location: Moldova
MOLDOVA EUROPEANĂ





Marcegaglia
59880 -Ergene Tekirdag-Turchia
phone + 90 282 693 5900
www.marcegaglia.com
Ergene Plant:
elise me Mah. Barajyolu, Kume Evleri, Pelitlik Mevkii Sanayi
Bölgesi No:108 59880 Ergene / Tekirdag
turkiye@marcegaglia.com

Type Inspection Certificate 3.1 EN 10204 THIS DOCUMENT WAS PRODUCED AUTOMATICALLY AND IS VALID WITHOUT SIGNATURE Number 59026000315 Issued On 29/01/2026

Customer Code: 0000057645 Consignee Delivery Nn 8042865069 Quality Control Q.M.D./Q.M. Murat Gezer Pages 1/1
Of 29/01/2026
Delivery note nr 0059000156 Plant Of Ergene

Material 59320286 Test specification: Stainless steel grade: TP 304L 1.4307/1.4301 X2CrNi18-9/X5CrNi18-10 Welding process HIGH FREQUENCY INDUCTION WELDING Order Nr 6059034/130 Client Order .
Description TXQ_TU 30x30x1,20x6000 TP304 HF SPZ Tolerances: EN10305-5 EN10219-2 ASTM A554 Part Number Client Date 4/07/2025

Item	Identification Nr	Heat	Quantity MTL	Quantity KG	Quantity PZZ	Delivery conditions	Reworks
1	26S1000362	Y250330F20C-6	600	611	100		BRUSHED

WE CERTIFY THAT THE ABOVE MENTIONED PRODUCTS COMPLY WITH THE TERMS OF ORDER CONTRACT AND THE STANDARDS RECALLED IN THE PRESENT TEST CERTIFICATE

Identification Nr	Chemical Type	C (%)	Si (%)	Mn (%)	P (%)	S (%)	N (%)	Cr (%)	Ni (%)
26S1000362	RAW_MATERIAL	.015	.359	1.058	.0282	.0036	.0495	18.157	8.066

Identification Nr	Type of mechanical test	Rp 0.2 [MPa]	Rp 1.0 [MPa]	Rm [MPa]	A5 (%)
26S1000362	TUBES	372	407	603	47.3

NON DESTRUCTIVE TESTS
ANTIMIXING TEST: CONFORM
VISUAL INSPECTION AND DIMENSIONAL CONTROLS: CONFORM

DESTRUCTIVE TESTS
FLATTENING TEST ACCORDING TO EN ISO 8492:2004: CONFORM
TENSILE TEST ACCORDING TO EN ISO 6892-1:2009

Marking

Remarks:
THE CHEMICAL COMPOSITION REFERS TO THE RAW MATERIAL USED ACCORDING TO EN 10088-2 AND 10028-7



METINOX INTERNATIONAL ,

Tel: 00852-2735 7759 Fax: 00852-2730 0946

Quality Manufacturer and exporter of Stainless Steel Coils, Sheets, Circles, Plates and Tubes
www.intexportsteel.com

TEST CERTIFICATE - INSPECTION CERTIFICATE

Customer	UCAS PASLANMAZ CELIK IC VE DIS TIC.A.S.	Date of Issue	11-Aug-25
Manufacturer	METINOX INTERNATIONAL .		
Description of Goods	COLD ROLLED STAINLESS STEEL COILS - PRIME		
Test Certificate No.	HXL-525119-TC		
Test Certificate No.	UPDATE LATER		
LC Date (If any)		LC Issuing Bank:	UPDATE LATER

Our Ref	GRADE	Thick (mm)	Width (mm)	Length (mm)	N.W. (MT)	Package No.	Contract No.	Heat Number	C	Si	Mn	P	S	Ni	Cr	Cu	Mo	N	Hardness (HV)	屈服强度	抗拉强度	伸长率
																				Yield Strength	Tensile strength	
																				N/mm ²		E.L.%
1	304	1.0	1250	COIL	10.915	XD1571584B	MTX-2025068	537519	0.042	0.37	1.028	0.042	0.01	8.100	18.02	-	-	-	181	285	660	56
2	304	1.2	1250	COIL	10.911	XD1571571B	MTX-2025068	537520	0.041	0.44	0.998	0.045	0.02	8.220	18.12	-	-	-	188	290	670	57
3	304	3.0	1250	COIL	10.500	XD3570973A	MTX-2025068	537519	0.042	0.37	1.028	0.042	0.01	8.100	18.02	-	-	-	181	285	660	56
4	304	1.5	1250	COIL	10.668	XD3571623A	MTX-2025068	537520	0.041	0.44	0.998	0.045	0.02	8.220	18.12	-	-	-	188	290	670	57
5	304	1.5	1250	COIL	11.137	XD3571622B	MTX-2025068	537519	0.042	0.37	1.028	0.042	0.01	8.100	18.02	-	-	-	181	285	660	56
6	304	2.0	1250	COIL	10.714	XD3571672A	MTX-2025068	537520	0.041	0.44	0.998	0.045	0.02	8.220	18.12	-	-	-	188	290	670	57
TOTAL:					64.845																	

Remarks:
1) Actual test result may vary +/- 5% from above figures

Statement	Through inspection and testing, the quality of these products conform to the stipulations of the related contract and	Stamp by Department Of Quality Assurance
-----------	---	---

For and on behalf of
METINOX INTERNATIONAL
Moh
Authorized Signatures