



LUBRICANTS
COMPANY

Bulevardul Chimiei 14, 700293 Iasi, Romania
Tel.: 0040 232 254153 / 0040 726 757951
Email: info@vipoil.ro / vipoil@yahoo.com

RAPORT DE ANALIZA / CERTIFICATE OF ANALYSIS

NUME PRODUS : PRODUCT NAME :	MARCA / BRAND : VIPOIL PRODUS / PRODUCT : TP-22 C
NR CERTIFICAT : CERTIFICATE NO :	588
DATA : DATE :	29.04.2025
CLIENT : CLIENT :	SECTIA BLENDING – VIPOIL SRL
COD PROBA / LOT : SAMPLE CODE / BATCH :	588 / 29.04.2025

Nr. No.	Caracteristici Characteristics	Metoda de incercare Test method	Limite admise Limits	Determinat Determined
1.	Clasa de viscozitate Viscosity grade	VG	32	
2.	Culoare ASTM Color	ASTM D 6045	5	1,5
3.	Densitate la 15°C, g/cm ³ Density at 15°C, g/cm ³	ASTM D 4052	0,900	0,872
4.	Viscozitate cinematică la 40°C, mm ² /s Kinematic viscosity at 40°C, mm ² /s	ASTM D 445	29,8 – 35,2	33.79
5.	Viscozitate cinematică la 50°C, mm ² /s Kinematic viscosity at 50°C, mm ² /s	ASTM D 445	raportat report	22.66
6.	Indice de viscozitate Viscosity Index	ASTM D 2270	90	105
7.	Punct de inflamabilitate, °C Flash Point °C	ASTM D 92	190	210
8.	Punct de curgere, °C Pour point °C	ASTM D 97	-12	-15
9.	Proprietati de spumare, cm ³ -la 24°C / Sequence I -la 93,5°C / Sequence II -la 24°C, după revenire / Sequence III Foam Characteristics, cm ³	ASTM D 892	50-0 50-0 50-0	10-0 10-0 10-0
10.				

Observatii (Remarks):

*Acest raport de analiza se refera numai la proba supusa incercarii / The certificate refers only to the tested sample

**Acest raport de analiza nu va fi reprodus de alte parti fara permisiune / The certificate will not be reproduced by other parties without permission

Aprobat de
Approved by

Nume / Semnatura
Name / Signature

