Data Sheet

OceanStor Dorado 5000/6000 All-Flash Storage Systems



OceanStor Dorado 5000/6000 All-Flash Storage Systems

Leading Performance with Innovative Hardware

30% higher performance than the previous generation

E2E NVMe for 0.05 ms of ultra-low latency FlashLink® intelligent algorithms

SCM intelligent cache acceleration for 60% lower latency

Distributed file system OceanFS with 30% higher performance

Efficient O&M with Intelligent Edge-Cloud Synergy

3-layer intelligent management:

- 365-day capacity trends prediction
- 60-day performance bottleneck prediction
- 14-day disk fault prediction

• Immediate solutions for 93% of problems SAN&NAS&object convergence, and crossgen device convergence for efficient resource utilization

FlashEver: No data migration over 10 years for cross-gen systems

Always-On Applications with 5-Layer Reliability

Component reliability: Wear leveling and anti-wear leveling

Architecture and product reliability: 0 data loss in the event of failures of controllers, disk enclosures, or three disks Solution and cloud reliability: The industry's only A-A solution for SAN and NAS, geo-redundant 3DC/4DC solution, The industry's only SOCC solution and gateway-free cloud backup Huawei OceanStor Dorado 5000/6000 are mid-range storage systems in the OceanStor Dorado all-flash series, and are designed to provide excellent data service experience for enterprises. Both products are equipped with innovative hardware platform, intelligent FlashLink® algorithms, and an end-to-end (E2E) NVMe architecture, ensuring the storage systems deliver a 30% higher performance than the previous generation, and achieve the latency down to just 0.05 ms. The intelligent algorithms are built into the storage system to make storage more intelligent during the application operations. Furthermore, the five-level reliability design ensures the continuity of core business.

Excelling in scenarios such as OLTP/OLAP databases, server virtualization, VDI, and resource consolidation, OceanStor Dorado 5000/6000 all-flash systems are smart choices for medium and large enterprises, and have already been widely adopted in the finance, government, healthcare, education, energy, and manufacturing fields. The storage systems are ready to maximize your return on investment (ROI) and benefit diverse industries.

Product Features

Ever Fast Performance with Innovative Hardware

Innovative hardware platform:

The hardware platform of Huawei storage enables E2E data acceleration, improving the system performance by 30% compared to the previous generation.

- ✓ The intelligent multi-protocol interface module hosts the protocol parsing previously performed by the general-purpose CPU, expediting the front-end access performance by 20%.
- √ The computing platform offers industry-leading performance with
 25% higher computing power than the industry average.
- ✓ The intelligent accelerator module analyzes and understands I/O rules of multiple application models based on machine learning

Data Sheet


OceanStor Dorado 5000/6000 All-Flash Storage Systems



FlashLink[®]

Controller





frameworks to implement intelligent prefetching of memory space. This improves the read cache hit ratio by 50%.

- ✓ SmartCache + SCM intelligent multi-tier caching identify whether or not the data is hot and uses different media to store it, reducing the latency by 60% in OLTP (100% reads) scenarios.
- ✓ The intelligent SSD hosts the core Flash Translation Layer (FTL) algorithm, accelerating data access in SSDs and reducing the write latency by half.
- ✓ The intelligent hardware has a built-in Huawei storage fault library that accelerates component fault location and diagnosis, and shortens the fault recovery time from 2 hours to just 10 minutes.

Intelligent algorithms:

Most flash vendors lack E2E innate capabilities to ensure full performance from their SSDs. OceanStor Dorado 5000/6000 runs industry-leading FlashLink® intelligent algorithms based on self-developed controllers, disk enclosures, and operating systems.

- Many-core balancing algorithm: Taps into the many-core computing power of a controller to maximize the data processing capability.
- ✓ Service splitting algorithm: Offloads reconstruction services from the controller enclosure to the smart SSD enclosure to ease the load pressure of the controller enclosure for more efficient I/O processing.
- Cache acceleration algorithm: Accelerates batch processing with the intelligent module to bring intelligence to storage systems during application operations.

The data layout between SSDs and controllers is coordinated synchronously.

- Large-block sequential write algorithm: Aggregates multiple discrete data blocks into a unified big data block for disk flushing, reducing write amplification and ensuring stable performance.
- Independent metadata partitioning algorithm: Effectively controls the performance compromise caused by garbage collection for stable performance.
- ✓ I/O priority adjustment algorithm: Ensures that read and write I/Os are always prioritized, shortening the access latency.

FlashLink[®] intelligent algorithms give full play to all flash memory and help Huawei OceanStor Dorado achieve unparalleled performance for a smoother service experience.

E2E NVMe architecture for full series:

All-flash storage has been widely adopted by enterprises to upgrade existing IT systems, but always-on service models continue to push IT system performance boundaries to a new level. Conventional SAS-based all-flash storage cannot break the bottleneck of 0.5 ms latency. NVMe all-flash storage, on the other hand, is a future-proof architecture that implements direct communication between the CPU and SSDs, shortening the transmission path.



 Image: A marked bit in the system

 Image: A marked bit in the system

 Controller 1
 Controller 2

 Controller 3
 Controller 4

Global resource pool

In addition, the quantity of concurrencies is increased by 65,536 times, and the protocol interaction is reduced from four times to two, which doubles the write request processing. Huawei is a pioneer in adopting end-to-end NVMe architecture across the entire series. OceanStor Dorado 5000/6000 all-flash systems use the industry-leading 32 Gb FC-NVMe/100 Gb RoCE protocols at the front end and adopt Huawei-developed link-layer protocols to implement failover within seconds and plug-and-play, thus improving the reliability and O&M. It also uses a 100 Gb RDMA protocol at the back end for E2E data acceleration. This enables latency as low as 0.05 ms and 10x faster transmission than SAS all-flash storage.

Globally shared distributed file system OceanFS:

The OceanStor Dorado 5000/6000 all-flash storage systems support the NAS function and use the globally shared distributed file systems to ensure ever-fast NAS performance. To make full use of computing power, the many-core processors in a controller process services concurrently. In addition, intelligent data prefetching and layout further shorten the access latency, achieving over 30% higher NAS performance than the industry benchmark.

OceanFS supports the NAS migration function of servers that do not need to be migrated. It provides minutes-level downtime and GB-level migration services, shortening NAS migration time and improving migration experience. File data can be tiered to OceanStor V3/V5 NAS storage and OceanStor Pacific object storage, reducing the TCO throughout the data lifecycle.

Linear increase of performance and capacity:

Unpredictable business growth requires storage to provide simple linear increases in performance as more capacity is added to keep up with ever-changing business needs. OceanStor Dorado 5000/6000 support the scale-out up to 32 controllers, and IOPS increases linearly as the quantity of controller enclosures increases, matching the performance needs of the future business development.

Efficient O&M with Intelligent Edge-Cloud Synergy

Extreme convergence:

Huawei OceanStor Dorado 5000/6000 all-flash storage systems provide multiple functions to meet diversified service requirements, improve storage resource utilization, and effectively reduce the TCO. The storage systems provide both SAN and NAS services and support parallel access, ensuring the optimal path for dual-service access. NAS and S3 convergence, support file and object interworking in a single instance, and smooth evolution to object; The convergence of cross-generation devices allows data to flow freely, simplifying O&M and reducing IT purchasing costs.

On and off-cloud synergy:

Huawei OceanStor Dorado 5000/6000 all-flash systems combine general-purpose cloud intelligence with customized edge intelligence over a built-in intelligent hardware platform, providing incremental training and deep



Data Sheet

OceanStor Dorado 5000/6000 All-Flash Storage Systems



learning for a personalized customer experience. The DME-IQ intelligent O&M and management platform collects and analyzes over 190,000 device patterns on the live network in real time, extracts general rules, and enhances basic O&M.

Intelligence throughout service lifecycle:

Intelligent management covers resource planning, provisioning, system tuning, risk prediction, and fault location, and enables 60-day and 14-day predictions of performance bottleneck and disk faults respectively, and immediate solutions for 93% of problems detected.

Anti-Ransomware:

Ransomware is a major threat to cyber security. Huawei's OceanStor Dorado all-flash storage systems take ransomware protection to a whole new level, with three layers of ransomware interception, as well as secure snapshot and isolation zone-based recovery. These storage systems incorporate Huaweiexclusive detection and analysis engines to support ransom file interception (pre-event), real-time ransom detection (in-event), and intelligent detection (post-event). With a ransomware detection rate of 99.9%, detection capabilities have been enhanced from post-remediation to pre-event prevention. OceanStor Dorado also recovers in seconds with secure snapshots, mitigating the impact of ransomware attacks.

FlashEver:


The intelligent flexible architecture implements component-based upgrades without the need for data migration within 10 years. Users can enjoy latestgeneration software and hardware capabilities without investing again in the related storage software features.

Always-On Applications with 5-Layer Reliability

Industries such as finance, manufacturing, and carriers are upgrading to intelligent service systems to meet the strategy of sustainable development. This will likely lead to diverse services and data types that require better IT architecture. Huawei OceanStor Dorado all-flash storage is an ideal choice for customers who need robust IT systems that consolidate multiple types of services for stable, always on services. It ensures end-to-end reliability at all levels, from component, architecture, product, solution, all the way to cloud, supporting data consolidation scenarios with 99.9999% availability.

Benchmark-Setting 5-Layer Reliability Component – SSDs:

Reliability has always been a top concern in the development of SSDs, and Huawei SSDs are a prime example of this. Leveraging global wear-leveling technology, Huawei SSDs can balance their loads for a longer lifespan of each SSD. In addition, Huawei's patented anti-wear leveling technology prevents simultaneous multi-SSD failures and improves the reliability of the entire system.





SSD



Architecture - fully interconnected design:

Huawei OceanStor Dorado 5000/6000 adopt the intelligent matrix architecture (multi-controller) within a fully symmetric active-active (A-A) design to eliminate single points of failure and achieve high system availability.

Application servers can access LUNs through any controller, instead of just a single controller. Multiple controllers share workload pressure using the load balancing algorithm. If a controller fails, other controllers take over services smoothly without any service interruption.


Product – enhanced hardware and software:

Product design is a systematic process. Before a stable storage system is commercially released, it must ensure that it meets the demands from both software and hardware, and can faultlessly host key enterprise applications. The OceanStor Dorado 5000/6000 are equipped with hardware that adopts a fully redundant architecture and supports dual-port NVMe and hot swap, preventing single points of failure. The innovative 9.5 mm palm-sized SSDs and biplanar orthogonal backplane design provide 44% higher capacity density and 25% improved heat dissipation capability, and ensure stable operations of 2U 36-slot SSD enclosures. The smart SSD enclosure is the first ever to feature built-in intelligent hardware that offloads reconstruction from the controller to the smart SSD enclosure. Backed up by RAID-TP technology, the smart SSD enclosure can tolerate simultaneous failures of three SSDs and reconstruct 1 TB of data within 25 minutes. In addition, the storage systems offer comprehensive enterprise-grade features, such as 3-second periodic snapshots, that set a new standard for storage product reliability.

Solution – gateway-free active-active solution:

Flash storage is designed for enterprise applications that require zero data loss or zero application interruption. OceanStor Dorado 5000/6000 use a gatewayfree A-A solution for SAN and NAS to prevent node failures, simplify deployment, and improve system reliability. In addition, the A-A solution implements A-A mirroring for load balancing and cross-site takeover without service interruption, ensuring that core applications are not affected by system breakdown. The all-flash systems provide the industry's only A-A solution for NAS, ensuring efficient, reliable NAS performance. They also offer the industry's first all-IP active-active solution for SAN, which uses long-distance RoCE transmission to improve performance by 50% compared with traditional IP solutions. The industry's only Storage + Optical Connection Coordination(SOCC) solution ensures efficient mitigation of active-active/replication link sub-health issues and completes link switchover within 2 seconds. In addition, the solution can be smoothly upgraded to the geo-redundant 3DC/4DC solution for highlevel data protection. Huawei OceanStor Dorado 5000/6000 provides a professional container CDR DR plug-in to support cross-site active-active DR, cross-container cluster active/standby DR, and cross-storage integrated backup and restoration for container applications in a single cluster.

HyperMetro







Cloud-level reliability – gateway-free migration to the cloud: With the rise of public clouds, more backup services use public cloud object

With the rise of public clouds, more backup services use public cloud object storage as their backup storage for higher cost-effectiveness and more reliable remote backup. The CloudBackup feature of Huawei OceanStor Dorado 5000/6000 follows this trend and eliminates the need to purchase backup storage devices and backup software, thereby reducing purchase and maintenance costs. The backup service supports interworking with HUAWEI CLOUD Object Storage Service (OBS) and AWS S3, incremental backup, fullcopy recovery, and file-level fine-grained recovery, delivering cloud-level reliability.



Technical Specifications

Data Sheet

Model	OceanStor Dorado 5000	OceanStor Dorado 6000
Hardware Specifications	, and the second se	
Maximum Number of Controllers	32	32
System Cache	256 GB-8 TB	1TB~24TB*
Supported Storage Protocols	FC, iSCSI, FC-NVMe, NVMe over RoCE,NFS, CIFS, NDMP, S3*, NFS over RDMA	
Front-End Port Types	8/16/32 Gbps FC/FC-NVMe, 10/25/40/100 GbE, 25/100 Gbps NVMe over RoCE/NFS over RDMA	
Back-End Port Types	SAS 3.0/ 100Gb RDMA	
Maximum Number of Hot-Swappable I/O Modules per Controller Enclosure	12	
Maximum Number of Front-End Ports per Controller Enclosure	48	
Maximum Number of SSDs	3,200	4,800
SSDs	1.92 TB/3.84 TB/7.68 TB/15.36TB/30.72TB palm-sized NVMe SSD, 960 GB/1.92 TB/3.84 TB/7.68 TB/15.36 TB SAS SSD	
SCM Supported	800GB/1.6TB SCM*	
Software Specifications		
Supported RAID Levels	RAID 5, RAID 6, RAID 10*, and RAID-TP (tolerates simultaneous failures of 3 SSDs)	
Number of LUNs	16,384	32,768
Value-Added Features	SmartDedupe, SmartVirtualization, SmartCompression, SmartMigration, SmartThin, SmartQoS, SmartTier*, SmartCache, SmartQuota,SmartMulti-Tenant, SmartMigration for NAS, SmartMobility for NAS, SmartMobility for Object, SmartMove, HyperSnap, HyperReplication, HyperClone, HyperMetro, HyperCDP, HyperLock, HyperEncryption, HyperDetect*, HyperLink, CloudVxLAN, CloudBackup*	
Storage Management Software	DeviceManager UltraPath DME-IQ	
Physical Specifications		
Power Supply	SAS SSD enclosure: 100V–240V AC±10%, 192V–288V DC, -48V to -60V DC Controller enclosure/Smart SAS disk enclosure/Smart NVMe SSD enclosure: 200V–240V AC±10%, 100–240V AC ±10%,192V–288V DC, 260V–400V DC, -48V to -60V DC	
Dimensions (H x W x D)	SAS controller enclosure: 86.1 mm × 447 mm × 820 mm NVMe controller enclosure: 86.1 mm × 447 mm × 920 mm SAS SSD enclosure: 86.1 mm × 447 mm × 410 mm Smart SAS SSD enclosure: 86.1 mm x 447 mm x 520 mm NVMe SSD enclosure: 86.1 mm x 447 mm x 620 mm	
Weight(with disks)	SAS controller enclosure: \leq 45 kg NVMe controller enclosure: \leq 50 kg SAS SSD enclosure: \leq 20 kg Smart SAS SSD enclosure: \leq 30 kg Smart NVMe SSD enclosure: \leq 35 kg	
Operating Temperature	–60 m to +1800 m altitude: 5°C to 35°C (bay) or 40°C (enclosure) 1800 m to 3000 m altitude: The max. temperature threshold decreases by 1°C for every altitude increase of 220 m	
Operating Humidity	10% RH to 90% RH	

*For further details on specifications with an asterisk for a specific project, please contact Huawei sales.

For More Information

To learn more about Huawei storage, please contact your local Huawei office or visit the Huawei Enterprise website: http://e.huawei.com/en/.



Huawei Enterprise APP



Huawei IT

Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without the prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

ψ_{HUAWEI}, HUAWEI</sub>, and _{ψ₀} are trademarks or registered trademarks of Huawei Technologies Co., Ltd. Other trademarks, product, service and company names mentioned are the property of their respective holders.

Disclaimer

The content of this manual is provided "as is". Except as required by applicable laws, no warranties of any kind, either express or implied, including but not limited to, the implied warranties of merchantability and fitness for a particular purpose, are made in relation to the accuracy, reliability or contents of this manual.

To the maximum extent permitted by applicable law, in no case shall Huawei Technologies Co., Ltd be liable for any special, incidental, indirect, or consequential damages, or lost profits, business, revenue, data, goodwill or anticipated savings arising out of, or in connection with, the use of this manual.

Huawei Technologies Co., Ltd Bantian Longgang District

f in У You Tube

Shenzhen 518129, P.R. China Tel: +86-755-28780808

www.huawei.com