

# PRODUCT

## VLS 354A AC ICELINED REFRIGERATOR

Probably the most energy efficient icelined refrigerator available today. A sustainable solution constructed with hydrocarbon refrigerant, cyclopentane insulation and recyclable components. Net capacity is increased by at least 40 % due to the specially developed integrated icelining, which is covered with a prepainted aluminium inner liner surface. Reliability and usability is secured through the self-regulating cooling system.

The junction box further from safeguard the electrical parts, aases services as well as maintenance on the appiance. In addition the appliance now is supplied with an appliance socket.

### SPECIFICATIONS

|  |             |
|--|-------------|
| Gross volume, litres (cu. ft.)           | 209 (7.38)  |
| Net volume, litres (cu. ft.)             | 127 (4.48)  |
| Temperature range (43°C AMB)             | +2° to +8°C |
| Hold-over time, hours                    | 54.7        |
| Energy consumption - stable, kWh/24h     | 0.62        |
| Energy consumption- cool down, kWh/24h   | 0.64        |
| Refrigerant                              | R600a       |
| Freeze protection, grade                 | A           |
| Climate class                            | T           |
| Energy supply needed per 24 hours, hours | 4           |

### WHO SPECIFICATIONS

|                           |               |
|---------------------------|---------------|
| Test procedure            | E003/RF03-VP3 |
| Performance specification | E003/RF03.4   |
| PQS code                  | E003/111      |

### FEATURES

|                     |           |
|---------------------|-----------|
| Storage baskets, no | 7         |
| Temperature control | Automatic |
| Lock + keys         | YES       |
| Junction box        | YES       |
| Adjustable legs     | YES       |



### DIMENSIONS

|                                |               |
|--------------------------------|---------------|
| Height, mm (inches)            | 905 (35.62)   |
| Width, mm (inches)             | 1.120 (44.09) |
| Depth, mm (inches) with handle | 700 (27.56)   |
| Gross weight, kg (lbs)         | 103 (227)     |
| Net weight, kg (lbs)           | 82 (180)      |

### LOADING QUANTITIES

|                              |         |
|------------------------------|---------|
| Qty. per 20' / 40' container | 26 / 60 |
| Qty. per truck (EU standard) | 76      |

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



**COLD CHAIN SOLUTIONS**

**VESTFROST**  
SOLUTIONS

**A/S Vestfrost**  
Falkevej 12  
DK-6705 Esbjerg Ø  
www.vestfrostolutions.com