











Constructie modulara 6058mm x 6015mm x 3050mm.

1)Partea de jos este formata de jos in sus din:

- structura metalica zincata profilata la rece (2,5 mm) cu piese de colt (2 - 10 mm), acoperita cu grund si vopsea (RAL 7016)
- tabla zincata (0,5 mm)
- spuma poliuretanică (50-80 mm)
- folei protectie (100 mkr)
- vata minerala (50 mm)
- OSB-3 (18 mm)
- linoleu PVC Tarkett

2) Acoperisul este format de sus in jos din:

- structura metalica zincata profilata la rece (2,5 mm) cu piese de colt (2 - 10 mm), acoperita cu grund si vopsea (RAL 7016)
- tabla zincata dublu faltuita (0,5 mm)
- spuma poliuretanică (80-100 mm)
- folei protectie (200 mkr)
- vata minerala (50 mm)
- PAL laminat (18 mm)

3) Stalpi sustinere acoperis:

- structura metalica zincata profilata la rece (3,0 mm), acoperita cu grund si vopsea (RAL 7016)
- vata minerala (100 mm)
- teava PVC pentru scurgerea apei

4)Peretii sunt formati din (conform schita tehnica si 3D):

- panouri sandwich cu spuma poliuretanică (ext.RAL 7016 - int.RAL 9002 / ext.100 mm - int.60mm)
- usi si geamuri PVC:
 - laminare antracit (exterior)
 - sticla multifunctionala 4S (3 sticle/42mm)

5)Instalatie electrica (conform standardelor):

- tablou sigurante automate – 2 buc.
- prize cu impamantare – 9 buc.
- comutator 10A IP 20 – 4 buc.
- priza exterioara 32A – 3 buc.
- LED – 6 buc.

