

YC-525L

🚓 Real Air Cooling

The multi-duct vortex refrigeration system and finned evaporator can prevent frosting completely and improve temperature uniformity to a large extent.

W Real Energy Saving

The refrigerator is equipped with "M + Energy Core" power management system and complete air cooling design, improving energy saving efficiency by more than 40%.

Real Visibility

The electrical heating + LOW-E design with double considerations can achieve a better anti-condensation effect for the glass door.

🔍 Real Safety

Seven temperature probes can ensure high precision of temperature control with nearly no fluctuation and thus can improve safety.



<u>(</u>





Data Storage

• Equipped with a USB export interface, which can be used for exporting data in PDF;

When a U-disk is connected, temperature data can be stored continuously and automatically (data can be stored for 100,000 sets of data); The printer is optional.



Human-oriented


 Equipped with high-quality shelves made from PVC-coated steel wire with tag cards and classification marks, which are easy to clean;
 Equipped with invisible door handle, ensuring elegance of appearance;

Equipped with testing port, bringing convenience to users in testing temperature inside the cabinet.


Scope of Application

Suitable for storage of biological products, vaccines, drugs, reagents, etc. Suitable for use in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc.

Performance Data / Cooling Curve



🗠 External Dimensions









M Specification Chart

2~8°C Pharmacy Refrigerator	
Model	YC-525L
Cabinet Type	Upright
Capacity(L)	525
Internal Size(W*D*H)mm	610*685*1264
External Size(W*D*H)mm	720*810*1973
Package Size(W*D*H)mm	774*862*2120
NW/GW(Kgs)	148/178
Performance	
Temperature Range	2~8°C
Ambient Temperature	16-32°C
Cooling Performance	5°C
Climate Class	Ν
Controller	Microprocessor
Display	Digital display
Refrigeration	
Compressor	1pc
Cooling Method	Air cooling
Defrost Mode	Automatic
Refrigerant	R290
Insulation Thickness(mm)	55
Construction	
External Material	Spray cold rolled steel plate
Inner Material	Aluminum plate with spraying (optional Stainless steel)
Shelves	6(coated steel wired shelf)
Door Lock with Key	Yes
Lighting	
	LED
Access Port	1pc. Ø 25 mm
Access Port Casters	
	1pc. Ø 25 mm
Casters	1pc. Ø 25 mm 4 (2 casters with brake)
Casters Data Logging/Interval/Recording Time	1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years
Casters Data Logging/Interval/Recording Time Door with heater	1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years
Casters Data Logging/Interval/Recording Time Door with heater Alarm	1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature	1pc. Ø 25 mm4 (2 casters with brake)USB/Record every 10 minutes / 2 yearsYesHigh/Low temperature,High ambient temperature,Condenser overheating
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature Electrical	 1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes High/Low temperature,High ambient temperature,Condenser overheating Power failure , Low battery
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature Electrical System	 1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes High/Low temperature,High ambient temperature,Condenser overheating Power failure , Low battery
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Rated Power(W)	 1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes High/Low temperature,High ambient temperature,Condenser overheating Power failure , Low battery Sensor failure,Door ajar, Built-in USB datalogger failure, Communication failure
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Rated Power(W) Power Consumption(KWh/24h)	 1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes High/Low temperature,High ambient temperature,Condenser overheating Power failure , Low battery Sensor failure,Door ajar, Built-in USB datalogger failure, Communication failure 220-240~/50 310 3.63
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Rated Power(W)	 1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes High/Low temperature,High ambient temperature,Condenser overheating Power failure , Low battery Sensor failure,Door ajar, Built-in USB datalogger failure, Communication failure 220-240~/50 310
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Rated Power(W) Power Consumption(KWh/24h)	 1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes High/Low temperature,High ambient temperature,Condenser overheating Power failure , Low battery Sensor failure,Door ajar, Built-in USB datalogger failure, Communication failure 220-240~/50 310 3.63 2.49
Casters Data Logging/Interval/Recording Time Door with heater Alarm Temperature Electrical System Electrical Power Supply(V/HZ) Rated Power(W) Power Consumption(KWh/24h) Rated Current(A)	 1pc. Ø 25 mm 4 (2 casters with brake) USB/Record every 10 minutes / 2 years Yes High/Low temperature,High ambient temperature,Condenser overheating Power failure , Low battery Sensor failure,Door ajar, Built-in USB datalogger failure, Communication failure 220-240~/50 310 3.63

*The model, parameters and performance specified in this brochure may be ch nged without prior notice because of product upgrading.

*There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.

