

DS-K4H258S One-Door Magnetic Lock



The DS-K4H258S One-Door magnetic lock is designed for wooden door, glass door, and steel door with the opening angle of 90°. The maximum thrust of the lock is 280 kg (617 Lbs). It can be used for controlling door opening/closing, and the indicator shows the door status.

- Magnetic lock supports static linear thrust of 280 kg (617 Lbs)
- Power supply can be 12VDC or 24VDC, (default voltage is 12VDC)
- Suitable for wooden door, glass door, metal door and fireproof door
- LED indicator displays door lock status
- Abrasion-proof materials

▪ Specification

| General | |
|---------------------|--|
| Indicator | Green: Working Status |
| Power supply | 12 VDC, 340 mA × 2 |
| Working temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| Working humidity | 0 to 95 % (relative humidity) |
| Dimensions | Lock Body: 238 mm × 45 mm × 25 mm (9.4" × 1.8" × 1.0") Armature Plate: 182 mm × 38 mm × 12.5 mm (7.2" × 1.5" × 0.5") |
| Weight | 2.1 kg (4.6 lb) |
| Material | Shell: hard Anodizing Electroplating Operated Lock Body: eco-friendly Nickel Electroplating Operated Armature Plate: eco-friendly Zinc Electroplating Operated |
| Thrust | Max. 280 kg (617 lb) |
| Door type | Single leaf, double leaf, wooden door, glass door, metal door, fireproof door |
| Magnetic Lock | |
| Unlock method | Current Interruption |
| Surface temperature | ≤ Ambient Temperature +20 °C (68 °F) |

▪ Available Model

DS-K4H258S

▪ Accessory

▪ Optional

| DS-K4H258-LZ Value Series Magnetic Lock Bracket | DS-KAS261 Fingerprint Terminal Kit |
|---|--|
|  |  |

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

