



Veriton X


































Power On By Monitor

Veriton X2660G **SPECIFICATIONS**





Product views	1. Power button 6. Microphone-in jack 2. One button recovery 7. Two USB 3.1 Gen 1 po 3. Optical media drive 8. Two USB 3.1 Gen 2 po		16. Ethernet (RJ-45) port17. Power connector
	 Status LEDs Headphone/speaker jack HDM[®] port 	 COM (Serial) port VGA port 	
Operating system ^{1, 2}	Windows 10 Pro 64-bit Windows 10 Home 64-bit Endless OS	.w. vo.,port	
CPU and chipset ¹	8th Generation Intel® Core™ i7 processors, Intel® UHD Graphics 630 8th Generation Intel® Core™ i5 processors, Intel® UHD Graphics 630 8th Generation Intel® Core™ i3 processors, Intel® UHD Graphics 630 Intel® Pentium® Gold processors, Intel® UHD Graphics 630 / 610 Intel® Celeron® processors, Intel® UHD Graphics 610 Chipset: Intel® B360 Express Chipset		
Memory ^{1, 3, 4}	16 GB / 8 GB / 4 GB DDR4 2666 MHz UDIMM Up to 32 GB of Dual-channel DDR4 2666 MHz		
Storage ^{1,5}	Hard disk drive • 2 TB / 1 TB 3.5-inch 7200 RPM • 1 TB 2.5-inch 5400 RPM, 7 mm high • 500 GB 2.5-inch 5400 RPM • 512 GB / 256 GB M.2 2280 PCI-E SSD		
Optical media drive	8X DVD-RW drive, 9.0 mm slim, tray-load, M-DISC Ready™		
Graphics ⁶	NVIDIA® GeForce® GT 720 with 2 GB of DDR3 AMD Radeon™ R7 430, 2 GB GDDR5		
Audio	Integrated high-definition, 5.1-channel surround sound		
Communication	WLAN 802.11ac/a/b/g/n, aggregate bandwidth up to 1.73 Gbps Bluetooth® 5.0	LAN Gigabit Ethernet	
Expansion slot(s)	PCIe x16 slot: 1 PCIe x1 slot: 2 PCI slot: 1	M.2 slot (for SSD): 1 M.2 slot (for WLAN): 1	
Windows Desktop Apps ⁷	Acer Office Manager Acer Control Center	 Acer ProShield CyberLink[®] PowerDVDTM 	
Commercial features	One-button recovery (OBR) Kensington lock slot 2-in-1 cable and padlock slot Hard drive password protection (via BIOS)	PXE (Preboot eXecution Environme WOL (Wake On Lan) ASF (Alert Standard Format) 2.0 Intrusion alert (via BIOS)	ent)
Commercial selected options ⁸	Parallel (printer) port COM (Series) port SD card reader module Dual-channel memory support	DisplayPort™-to-DVI adapter DisplayPort™-to-VGA adapter Internal speaker Dust filter	
	TPM v2.0 (Trusted Platform Module)		
Dimensions	102 (W) x 305.08 (D) x 330 (H) mm (4.02 x 12.01 x 12.99 inches)		
Power supply and battery	250 W PFC, auto-sensing, 80PLUS# Platinum, TFX 180 W PFC, auto-sensing, 80PLUS# Platinum, TFX 180 W PFC, auto-sensing, 80PLUS# Bronze, TFX		
System compliance	RoHS, DMI, GS, ENERGY STAR®, PC2001		
Certification	BSMI, CE, FCC, CB		
 A 64-bit operating syst Memory speed may var 1 GB is 1 billion bytes. A and operating environment 	ired to enjoy the advantages of 64-bit processing. em is required to enjoy the ultimate performance of 4 GB or higher memory. y, depending on the CPU, chipset or memory fitted. Actual formatted capacity is less and may vary depending on preloaded materials nent. Recovery Management uses a portion of the stated hard disk capacity as	 Bundled software may vary depending on it. For systems with a dual-channel configuratidentical, including raw card, size, type, and 	hardware configuration, OS and regional availability. ition, the two memory modules inserted must be d speed.
 dedicated backup space Total available graphics 	e. s memory comprises dedicated video memory, system memory, and shared		

In a continuing effort to improve the quality of our products, information in this document is subject to change without notice. Images shown are only representations of some of the configurations available for this model. Availability may vary depending on region. As a phenomenon known to thin-film transistors (TFTs), liquid crystal displays (LCDs) commonly exhibit a small number of discoloration dots, as so-called "non-conforming pixels." This phenomenon is a limitation of TFT LCD technology, not a product defect, and as such is not covered by Acer's warranty.

© 2018. All rights reserved.

Microsoft and Windows are registered trademarks of Microsoft Corporation.

Intel, Intel Core, Core Inside, Pentium, and Pentium Inside are trademarks of intel Corporation in the U.S. and other countries.

Total available graphics memory comprises dedicated video memory, system memory, and shared system memory. This figure will vary depending on system memory, installed drivers, BIOS settings and

6.

other factors.