

Model No.: CET-122



PARAMETERS

| Model | CET-122 | CET-122 | CET-122 | CET-122 | CET-122 | CET-122 |
|---------------|---|------------|------------|------------|------------|------------|
| Lamp Power | 50W | 100W | 150W | 200W | 250W | 300W |
| Lamp Size(mm) | 460x315x90 | 540x315x90 | 620x315x90 | 700x315x90 | 780x315x90 | 860x315x90 |
| Pole Diameter | Φ60mm | Φ60mm | Φ60mm | Φ60mm | Φ60mm | Φ60mm |
| Material | Die-cast Aluminium+PC Lens | | | | | |
| Lamp Flux | 90-100LM/1W, 100-120LM/1W, 130-140LM/1W | | | | | |
| Power Factor | >0.9 | | | | | |
| LED Color | 3000-3500K, 4000-4500K, 5000-5500K, 6000-6500K | | | | | |
| IP Grade | IP65 | | | | | |
| CRI | Ra>70 | | | | | |
| Life Time | 50000H | | | | | |
| SPD | 2.5KV-4KV-6KV-10KV | | | | | |
| Input Voltage | AC85-305V or AC165-277V | | | | | |
| Body Color | Black or Grey, The product can choose to install Photocell Sensor | | | | | |
| Certificate | BIS ,SASO ,CE-LVD-EMC ,RoHS ,IES ,TUV ,EAC ,ISO9001 ,SAA ,Intertek ,TIR | | | | | |

PACKING DETAILS

| Lamp Power | 50W | 100W | 150W | 200W | 250W | 300W |
|------------------|----------|----------|----------|----------|----------|----------|
| Packing Size(cm) | 48*32*11 | 55*32*11 | 66*32*11 | 72*32*11 | 78*32*11 | 88*32*11 |
| PCS/CTN | 1 | 1 | 1 | 1 | 1 | 1 |
| CBM/CTN | 0.017 | 0.019 | 0.023 | 0.025 | 0.027 | 0.031 |

DIAGRAMS

