



DN	L	B	C	D	t	n-h	f	d
DN15	35	φ 95	φ 65	φ 45	10	4-M12	2	φ 15
DN20	38	φ 105	φ 75	φ 55	11	4-M12	2	φ 20
DN25	42	φ 115	φ 85	φ 65	12	4-M12	2	φ 24
DN32	55	φ 135	φ 100	φ 78	14.5	4-M16	2	φ 30
DN40	62	φ 145	φ 110	φ 85	15	4-M16	2	φ 36
DN50	73	φ 160	φ 125	φ 100	16.5	4-M16	2	φ 46
DN65	95	φ 180	φ 145	φ 120	18	4-M16	2	φ 57
DN80	118	φ 195	φ 160	φ 135	18.5	8-M16	2	φ 73
DN100	140	φ 215	φ 180	φ 155	18.5	8-M16	2.5	φ 90
DN125	165	φ 245	φ 210	φ 182	20.5	8-M16	2.5	φ 110
DN150	192	φ 280	φ 240	φ 206	22	8-M20	2.5	φ 125



Performance Specification		
No.minal Pressure	PN16	Test Medium
Shell Test	(2.4MPa)	Water
Seal Test	(1.8MPa)	
Air Seal Test	(0.6MPa)	Air
Suitable Temperature	-30~120℃	
Suitable Media	Water/Steam/Oil/Gas	

14	Nut	201
13	Washer	201
12	Lever	201
11	Gland	201
10	Screw	201
9	Nut	201
8	PacKing	PTFE
7	GasKet	PTFE
6	Stem	201
5	Ball	201
4	SeatSeal	PTFE
3	Bonnet	WCB
2	Gasket	PTFE
1	Body	WCB
No.	Parts	Material

Float ball valve

TYPE:IN-GAZ FLF