



EMSAS®

MEDICAL COOLING & HEATING SYSTEMS

www.emsas-as.com.tr



EKT Serie (0°C / +15°C)

- The outer surface of the device is made of galvanized steel, painted with electrostatic paint to protect against rust. The inner surface is produced of stainless steel.
- The device operates with 195-230 V/50 Hz network voltage.
- The door of the device has double thermal glazing, it can be locked and has magnetic seal rings. Thus, it provides an opportunity to trace the stocks.
- There is a plastic covered wire shelves in the device that can be adjusted according to the user request.
- Operates between +0/+15°C and it is set to +4°C.
- Provides equal temperature distribution with the strengthened fan system it contains..
- In order to prevent the temperature rising up speedily , Interior fans shut down when door is opened
- Works smoothly and quietly.
- In order to protect the productivity of the device cooling evaporator, there is full-automatic defrosting system.
- The lightening of the inner cabin of the device is carried out with LED lightening.
- A user-friendly digital control panel with a micro processor has been used on the device. This system can keep the data in memory for 30 days.
- There is a USB socket to transfer the cabinet temperature information to the computer when requested. In this way, the 10 year old temperature records can be transferred to the PC in excel format.
- The thermostat at the control panel of the device can make measurements with 0.1 degree sensitivity.
- There is an accumulator system charged automatically at the control panel of the device. This system allows the control panel and thermal printer (if available) to operate for 24 hours when the electricity cuts off.
- While the refrigerator is working the device gives alerts with the visual and audio signal when the lower and upper temperature limits are exceeded, the door of the device is left open, and there is electricity cut off or low voltage problems.
- The cooling system and the insulation system of the device do not contain CFC gas that is harmful for OZONE.
- High quality well known brand compressor is used which is hermetically sealed and air-cooled
- There are two braked and two regular castors under the device that provide easy portability.
- Our devices can be connected to heat tracking system.
- All medical devices produced by EMSAS A.S. are guaranteed for 2 years.
- As per the request of the user, a thermal printer can be installed at the device. The numerical and graphical printout of the data recorded with the thermal printer can be taken.
- All of our products are produced in line with the ISO 9001:2008, TSE service place competence certificates. The device has CE certificates and barcode.

EKT 425



**OPTIONAL BLOCK
3XGLASS DOOR**



**OPTIONAL CHROME
SHELVES**




**OPTIONAL GRAPHICAL
CHART RECORDER**



**OPTIONAL THERMAL
PRINTER**



**OPTIONAL TOUCH
SCREEN DISPLAY**



**OPTIONAL VACCINE TRACKING
SYSTEM**

EKT-B Serie (0°C / +15°C)

- EKT-B Serie has same features with EKT Serie only the difference; door system is designed as polyurethane pressed block (solid) door.

LABORATORY / PHARMACY REFRIGERATOR

EKT 80
(0 °C/+15 °C)



EKT 150
(0 °C/+15 °C)



EKT 175
(0 °C/+15 °C)



OPTIONAL BLOCK DOOR

EKT 250
(0 °C/+15 °C)



EKT 425
(0 °C/+15 °C)



EKT 725
(0 °C/+15 °C)



EKT 1450
(0 °C/+15 °C)



MODEL	EKT 80 - EKT-B 80	EKT 150 - EKT-B 150	EKT 175 - EKT-B 175	EKT 250 - EKT-B 250	EKT 425 - EKT-B 425	EKT 725 - EKT-B 725	EKT 1450 - EKT-B 1450
Temperature Range	0 / +15 °C						
Set Point	+4°C						
External Dimensions (WxLxH) mm	450x600x750	765x823x900	600x660x1446	600x660x1720	600x660x2020	765x820x2040	1450x821x2030
Internal Dimensions Net (WxLxH) mm	368x365x520	660x462x622	516x472x797	515x472x1070	515x472x1350	662x654x1390	1370x715x1346
Volume	70 L	190 L	225 L	300 L	388 L	637 L	1320 L
Polyurethane (mm)	41 mm	50 mm	42,5 mm	42,5 mm	42,5 mm	51,5	40 mm
Packaged Dimensions (WxLxH)mm	470x675x785 mm	825x875x1050 mm	700x750x1550 mm	700x750x1950 mm	700x740x2100 mm	800x850x2120 mm	1550x900x2090 mm
Gross KG	60 Kg	107 Kg	105 Kg	115 Kg	156 Kg	220 Kg	320 Kg
Interior Lighting	+	+	+	+	+	+	+
Door Lock	+	+	+	+	+	+	+
Alarm	+	+	+	+	+	+	+
Internal Surface	Stainless Steel Cr-Ni 304						
External Surface	Galvanized sheet with electrostatic paint						
Heating / Cooling System	Fan System	Fan System	Fan System	Fan System	Fan System	Fan System	Fan System
Insulation	CFC Free - Polyurethane						
Shelves	2 Pcs	3 Pcs	3 Pcs	4 Pcs	5 Pcs	5 Pcs	12 Pcs
Chrome Shelf	Optional						
Thermal Printer	Optional						
Basket	Optional						
SMS and E-MAIL MODULE	Optional						
PC Connection	USB						
Castors	2 Braked , 2 Regular						
Temperature Sensor	NTC						
Control System	Microprocessor Control						
Voltage	220v-50hz						
Cooling Gas	R134a						
Power	230 Watt	230 Watt	230 Watt	230 Watt	277 Watt	277 Watt	400 Watt
Natural Gas	Optional						



MEDICAL COOLING & HEATING SYSTEMS



www.emsas-as.com.tr
www.kandolabi.com
www.asidolabi.com
ISO 9001:2008
ISO 13485



Muradiye Sanayi Bölgesi Muradiye Mahallesi
28 Sokak No:6 Yunusemre - MANİSA / TURKEY
Tel: +90 (236) 214 03 96 - 97 - 98 Fax: +90 (236) 214 07 06
izmir Tel: +90 (232) 479 55 22 - 479 55 23
mail: export1@emsas-as.com.tr
www.emsas-as.com.tr