

PM-7000D

Multi-parameter Patient Monitor



zoncare
FDA MC CE ISO9001

WUHAN ZONCARE BIO-MEDICAL ELECTRONICS CO.,LTD.

Add: Zoncare Building, No. 380, High-tech 2nd Road, Eastlake High-tech
Development Zone, Wuhan, Hubei 430206 P. R. China.
Tel: +86-27-8777 0581 Fax: +86-27-8777 0203

Email: info@zoncare.com <http://www.zoncare.com>
2015 Wuhan Zoncare Bio-Medical Electronics Co.,Ltd. All rights reserved. Specifications subject to changes without
prior notice.

<http://www.zoncare.com>



PM-7000D

Multi-parameter Patient Monitor

8 Core Advantages

- Global original ATN adaptive central monitoring network, no need settings, no need arrangement of wire, just plugs and play, stable signal.
- Original perfusion index(PI) and show signal quality of blood oxygen infusion.
- Having been Activated EtCO2 port, optional EtCO2 module, can plug and play. One key reset alarm preset values
- Arrythmia analysis, S-T segment analysis and drug concentration and titration table calculation, ST base dot automatically adjust
- Defibrillation and resistance electrome design
- Excellent workmanship and materials accessories
- Powerful storage function: 2000 NIBP measured value, 200 Alarm events, 1000 hour trend chart review, 1000 hour trend table review, 120 minutes dynamic trend,
- 8 minutes SpO2 figures and 48 hours Holographic waveform

Six Interfaces

Standard interface, all leads display interface, trend coexistence interface, large font Interface, NIBP review interface and respiratory oxygenation map interface.
large font interface is applied to long-distance monitoring.



Accessories

We elaborate selected the materials, extremely attention to every detail of the design, and strive to make you satisfied.



Split type 5-lead ECG cable, import TPU wire, wipe disinfection 2000 remains the same color gold plated electrodes, more stable signal acquisition.



Removable internal capsule design, convenience for wash, import PU fabric, comfortable tactile impression, easy cleaning and disinfection to avoid cross infection.



Split type SpO2 cable, shading design, strong ability resistance to Interference.

Standard Configuration:

ECG, HR (Heart Rate), NIBP, SpO2, PR (Pulse Rate), Dual-TMP (Including TMP probes), EtCO2 (Excluding EtCO2 module), Touch Screen, Lithium Battery.

Optional Configuration:

3-ch Recorder, Wall bracket, Trolley, Double lithium battery, VGA port, ATN Networking module, WIFI module, Nellcor SpO2 module, Suntech blood pressure module.

