

## M-14D2

### MOTOR OIL FOR DIESEL LOCOMOTIVES AND HIGH PRESSURE DIESELS WITH SUPERCHARGING.

#### SPECIFICATIONS:

SAE 40

#### DESCRIPTION:

Intended for use in diesel locomotives, as well as in high-pressure diesels with supercharging of quarry dump trucks, where the use of engine oil corresponding to API CD or earlier specifications is required.

It is made on the basis of mineral base oils with the addition of a package of high-quality additives. It has a high operational potential with neutralizing abilities, cleaning properties, resistance to high-temperature oxidation, anti-wear properties.

#### CONFORMITY:

TY Y 19.2-31852954-061:2013

#### BENEFITS:

- Provides an increase in mileage without changing the oil and an increase in the service life of fine-cleaning filter elements;
- Has excellent antioxidant, anti-wear and anti-corrosion characteristics;
- Has good washing and dispersing properties, even when using fuels with a high sulfur content;
- The product is stable at high temperatures.

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	13,5-15,0
Viscosity index, min	90
Flash point in open crucible, °C, min	242
Pour point, °C	-15
Density at 20°C, kg/m <sup>3</sup>	903
TBN mg KOH/g	13,7
Ash content, %	1,9

Packing	Vendor code	Barcode
Barrel metal 200l	009772	482007024483