

ANUNȚ DE PARTICIPARE

privind achiziționarea *Echipament audio*

prin procedura de achiziție *Licitație Deschisă*

1. Denumirea autorității contractante: *IP Compania „Teleradio-Moldova”*
2. IDNO: *1004600050558*
3. Adresa: *str. Miorița 1, mun. Chișinău, MD-2028*
4. Numărul de telefon/fax: *022 721047, 022 723352*
5. Adresa de e-mail și pagina web oficială ale autorității contractante: trm@trm.md, www.trm.md
6. Adresa de e-mail sau pagina web oficială de la care se va putea obține accesul la documentația de atribuire: *documentația de atribuire este anexată în cadrul procedurii în SIA RSAP*
7. Tipul autorității contractante și obiectul principal de activitate (dacă este cazul, mențiunea că autoritatea contractantă este o autoritate centrală de achiziție sau că achiziția implică o altă formă de achiziție comună): *Instituție Publică*
8. Cumpărătorul invită operatorii economici interesați, care îi pot satisface necesitățile, să participe la procedura de achiziție privind livrarea bunuri:

Nr Lot	Cod CPV	Denumirea bunului	Un. de m	Cant	Descrierea bunurilor și specificarea tehnică (cerințe minime tehnice)	Preț Fără TVA (lei)
1	32323100-4	Digital Audio Mixer	set	1	<p>48-Channel Digital Mixer 19" Rack mountable With 96 kHz FPGA processing 17 Faders / 6 Layers 12 x Stereo mixes (perfect for in-ear monitoring setups) + LR 3 x Stereo matrix 8 x Internal stereo FX engines with stereo returns DEEP processing enables the integration of plug-ins directly into the mixer inputs and mix channels 7" Touch screen SLink port for remote audio networking 64ch I/O port for audio networking 32 x 32 USB audio interface SQ-Drive direct recording to USB AES output Chromatic channel metering Integrated LED illumination per fader Dedicated physical controls 8 assignable SoftKeys Channel LCD displays <i>Include SLink Network Interface Card</i> <i>Include tablet (equivalent Tab S8+)</i> Size 12.4" inches Super AMOLED, 120Hz Resolution 2800 x 1752 pixels, 16:10 ratio (~266 ppi density) Protection Corning Gorilla Glass 5 Chipset Qualcomm SM8450 Snapdragon 8 Gen 1 (4 nm) CPU Octa-core, GPU Adreno 730 Internal min 128GB 8GB RAM stereo speakers (4 speakers) Wi-Fi 802.11 a/b/g/n/ac/ax 2.4G+5GHz+6GHz, HE160, MIMO, 1024-QAM Bluetooth 5.2, A2DP, AVRCP, DI, HFP, HID, HOGP, HSP, MAP, OPP, PAN, PBAP Positioning GPS, Glonass, Beidou, Galileo, QZSS USB Type-C 3.2 Sensors Accelerometer, Fingerprint Sensor, Gyro Sensor, Geomagnetic Sensor, Hall Sensor. BATTERY 10090 mAh.</p>	104166,67

					<p>Stylus, 6.2ms latency (Bluetooth integration, accelerometer, gyro) Colors Graphite Include tablet case book, gray or black color, magnetic closure. <i>Include Cat5e Cable</i> Length: 50 m On cable reel with winding assistance 2x RJ45 Hirose connector with Neutrik NE8MX1 4x 2x AWG26 / 7 double shielded with foil metal braided shield Cable can be unwound completely Housing / Bushing shielded by contact with metal plug Warranty hardware 2 years</p>	
2	32323100-4	Combo de chitară electrică	buc.	1	<p>Combo for Electric Guitar Power: 40 W @ 5 Ohm Equipped with: 1x 10" Speaker Valvetronix tube preamp 11 Amp models (20 when using Tone Room - editor/librarian software): Deluxe CL, Tweed 4x10, Vox AC30, Boutique OD, VOX AC30TB, Brit 800, Brit OR MKII, Double Rec, Boutique CL. Effects: Pedal 1-type: 4 (Comp, Chorus, Overdrive, Distortion) Pedal 2-type: 4 (Flanger, Phaser, Tremolo, Delay) Reverb type: 4 (Room, Spring, Hall, Plate) Memory slots: 33 (60 when using Tone Room - editor/librarian software) User programs: 8 (2 banks x 4 channels) 6.3 mm Jack input, AUX in Headphone connector Foot pedal connector Mini USB port (type B) Including power adapter Warranty hardware 2 years</p>	5250,00
3	32323100-4	Combo de chitară electrică	buc.	1	<p>Bass Combo Power: 25 Watt 1x 8" Loudspeaker 15 Amplifier models 20 Effects, 50 Factory and 30 user presets Gain, Bass, Mid, Treble, Master controls Preset Select, Back, Save Button, Menu Button, Tap Tempo/Tuner Button USB Output for recording and firmware updates Stereo aux Headphone output Foot-switch connection Warranty hardware 2 years</p>	4166,67
4	32323100-4	Combo de chitară electrică	buc.	1	<p>Electric Guitar Modelling Combo 40 W Speaker configuration: 1x 10" 5 Amp voicings, incl. Clean, Crunch, Lead, OD1 and OD2 4 Fully programmable presets Multi-FX DSP with 5 individual digital effects: Reverb, Delay, Chorus, Tremolo and Phaser, each with adjustable parameters Controls for gain, volume, treble, mid, bass and FX as well as a master volume Mini-jack connection for aux line and headphones Bluetooth audio receiver for playing backing tracks from an external source Digital guitar tuner with LED display Output for external speaker 240 V 50/60 HZ switching power supply 12 mm wooden cabinet Warranty hardware 2 years</p>	2416,67
5	32323100-4	Microfon set pentru tobe	Set	1	<p>Drum microphone set PG Alta Series 1x PGA52 bass drum microphone 3x PGA56 snare / tom microphones 1x PGA57 snare microphone 2x PGA81 overhead microphones 3x Tom mounts 7x 4.6 m XLR cables Case Warranty hardware 2 years</p>	10833,33
6	32323100-4	Microfon dinamic	Buc.	2	<p>Dynamic large diaphragm vocals microphone (Equivalent EV ND76) Polar pattern: Cardioid Frequency range: 70 - 17,000 Hz Max. SPL: 140 dB 2.4 mV / Pascal Impedance: 350 Ohm Black zinc diecast housing</p>	5000,00

					ABS polycarbonate Incl. microphone holder and bag Warranty hardware 2 years	
7	32323100-4	Microfon vocal	Buc.	2	Vocal Microphone (Equivalent EV RE520) Working principle: Condensor Directional characteristic: Supercardioid Frequency range: 40 - 20,000 Hz Max. Sound pressure level: 150 dB Output impedance: 200 ohms Sensitivity: 5.6 mV / Pa (-45 dBV / Pa) @ 1 kHz Requires +48 V phantom power Includes bag Warranty hardware 2 years	12083,33
8	32323100-4	Microfon vocal	Buc.	2	Microphone (Equivalent XS1) Form Factor - Handheld Sound Field - Mono Capsule - 1 x Dynamic Polar Pattern - Cardioid Orientation - End Address High-Pass Filter - None On-Board Controls - Mic Mute Performance Frequency Range - 55 Hz to 16 kHz Impedance - 300 Ohms Load Impedance - 1 Kilohms Sensitivity - 1.8 mV/Pa Connectivity Output Connectors (Analog) - 1 x XLR Mounting - Mic Clip/Stand Adapter (Included) Construction Material - Metal Warranty hardware 2 years	2083,33
9	32323100-4	Microfon vocal	Buc.	6	Condenser vocal microphone (Equivalent Beta87A) -Supercardioid polar pattern -Linear transmission range for precise, detailed and true to original song and speech. -Extremely precise supercardioid characteristic over the entire frequency range for the greatest possible feedback resistance with maximum amplification. -Built-in, three-layer wind protection minimizes pop and breathing noises. -Operation with phantom power -Frequency range: 50 Hz - 20 kHz -Output impedance: 100 ohms -Idle sensitivity: -54 dBV / Pa (2 mV) -Maximum sound pressure level: 140.5 dB SPL -Inherent self-noise (equivalent sound pressure): 23.5 dB (A) -Includes microphone clip and storage bag Warranty hardware 2 years	35000,00
10	32323100-4	Cablu Multicore	Buc.	1	Studio Multicore Cables 4x Female XLR in the stagebox 4x Balanced 6.3 mm female jack (socket) in stagebox 4x Male XLR on fanout cable 4x Balanced 6.3 mm male jack (plug) in the fanout cable Length: 10 m	2416,67
11	32323100-4	Cablu pentru instrument muzical	Buc.	6	Double sided 6.3mm mono jack Metal connectors Textile coated Colour: Black Length: min 9 m	1250,00
12	32323100-4	Saundcard USB	Buc.	1	4-Channel audio Interface (Equivalent Universal Audio Volt 476) 24 bit / 192 kHz 2 microphone preamps +48 V phantom power Switchable air function 2 Mic/Instrument/Line inputs: XLR/6.3 mm jack combo balanced 2 Line inputs: 6.3 mm jack 4 Line outputs: 6.3 mm jack balanced Stereo headphone output: 6.3 mm jack MIDI input and output USB-C connection <i>Incl. USB cable (type C to A)</i> <i>Include brand computer, Small Form Factor</i> Minimum requirements: Operating System: Windows 11 Pro 64-bit English;	26666,67

					<p>Processor: 6C/12T, up to 4.6 GHz Cache: 18MB, equivalent i5-12500; Memory: 16 GB DDR4; Hard Drive: SSD 512 GB for System; Graphics Card: Integrated Graphics; Network interface: Integrated 10/100/1000 Gigabit Ethernet LAN, Bluetooth; External I/O Ports: Front: 2 USB2.0 port, 1 USB3.2, 1 USB3.2 Type-C® port, 1 audio jack; Rear: 3+1 USB3.2 ports, 2 USB2.0 ports, 2 DisplayPort1.4 ports, 1 line-out/in audio port, 3 SATA3.0 slots for 3.5/2.5-inch HDD, and optical drive, 1 PCIe x16 slot, 1 PCIe x4 slot; Keyboard: USB Wireless Mouse and Keyboard (Eng/Ru); Optical drive, SD card slot; Warranty: 2 years.</p>	
13	32323100-4	Microfon	Buc.	4	<p>Microphone (Equivalent SM7B) - Dynamic Speaker and Recording Microphone - Polar pattern: Cardioid - Frequency range: 50 – 20,000 Hz - Sensitivity -59.0 dB (1.12 mV) - Bass roll-off switch - Mid-boost switch - Impedance: 150 ohms - Shielding against electromagnetic interference - Swivel mount - XLR connector - Includes switch cover plate and windscreen Microphone Arm (Equivalent Gator Frameworks Deluxe) - Table microphone arm with cable guide - Cables up to 8mm in diameter can be attached to the underside of the arms with a clip system - Aluminium construction - Locking centre joint - 3/8» Rhreaded connection with 5/8» adapter - Table clamp up to 56 mm or table feed-through up to 45 mm (20 mm hole) - Length upper arm: 43 cm - Length lower arm: 43 cm - Colour: Black - Microphone Cable Length: 3 m (equivalent Mogami xlr cable)</p>	31666,67
14	32323100-4	Microphone Stand	Buc.	1	<p>Microphone Stand (Equivalent Roadworx Mic Stand Round Base Boom) With boom arm and round metal base Length from approx. 92 to 150 cm Boom arm length: 70 cm Threads: 3/8" with 5/8" adapter Base diameter 290 mm Weight: 3.7 kg</p>	791,67
15	32323100-4	Level Amplifier	Buc.	1	<p>1-Channel Level Amplifier (Equivalent cloudlifter) +25 dB for dynamic or passive ribbon microphones To be used in conjunction with a microphone amplifier with standard phantom power on mixers/preamplifiers/audio interfaces with mic input Requires phantom power XLR input and output Metal casing included band for fixing to microphone stand Warranty hardware 2 years.</p>	3041,67
16	32323100-4	Portable Speaker	Set	2	<p>Portable Speaker (Equivalent Boombox 3) Transducers: 189 x 114mm Subwoofer, 2 x 80.9 x 80.9mm Midrange/2 x 2.75 inch, 2 x 20mm Tweeter/2 x 0.75 inch. Output power: 1 x 80W RMS-subwoofer + 2 x 40W RMS-midrange + 2 x 10W RMS-tweeter (AC mode), 1x60W RMS-subwoofer + 2x30W, RMS-midrange + 2x8W RMS-tweeter, (Battery mode) Frequency response: 40Hz – 20kHz Signal-to-noise ratio: >80dB Battery type: Li-ion polymer 72.6Wh Connection ports: AC-in, USB-A, Aux-in USB charge out: 5V/2A Bluetooth® version: 5.3. IP67 dust and water proof, black. Portable Speaker (Equivalent Charge 5) Transducer: 52mm x 90mm woofer, 20mm tweeter; Rated output power: 30W RMS for woofer, 10W RMS for tweeter Frequency response: 60Hz – 20kHz Signal-to-noise ratio: >80dB Battery type: Li-ion polymer 27 Wh USB port: Type C USB rating: 5V/2A Bluetooth® version: 5.1</p>	25000,00

					IP67 dust and water proof, black. Warranty 2 years.	
17	32323100-4	Microfon	Buc.	6	General Specifications (Equivalent AKG C417 PP) Type Pre-polarized condenser microphone Polar Pattern Omnidirectional Audio frequency bandwidth 20 - 20000 Hz Equivalent noise level 34 dB-A Sensitivity 7 mV/Pa Signal to Noise 60 dB-A Electrical impedance 200 Ohms Recommended load impedance 1000 Ohms Cable length 1.5 m (5 ft.) Type XLR Gender Female Contacts 3-pin Current 2 mA Warranty hardware 2 years.	18750,00
18	32323100-4	Microfon	Buc.	3	OMNIDIRECTIONAL CONDENSER MICROPHONE (equivalent OMNI1) Technical specifications: Type: Condenser microphone (permanently biased 10mm capsule) Polar pattern: Omni Frequency response: 20-20000Hz +-1dB Phantom power: 12 - 48V Current consumption: 4 mA Impedance: <100 Ohm Sensitivity: 8mV/PA -42dB S/N ratio (DIN A-weighted/CCIR): 76dB/66dB Noise level: 18dB(A) Max SPL: 133dB @0.5% THD (130dB@24V, 120dB @ 12V) Connector: XLR Warranty hardware 2 years	10500,00
19	32323100-4	Microfon	Buc.	6	CARDIOID CONDENSER MICROPHONE (equivalent CM4) Technical specifications: Type: Condenser microphone (permanently biased capsule) Polar pattern: Cardioid (slightly wide cardioid) Frequency response: 20-20000Hz (100-16000Hz+-1dB on axis, at 1m, 23C, MLS noise stimuli, 1/12 oct narrow smoothing) Phantom power: 12 - 48V current consumption: <4 mA Impedance: <100 Ohm Sensitivity: 8mV/PA -42dB S/N ratio (DIN A-weighted/CCIR): 78dB/68dB Noise level: 16dB(A) Max SPL: 140dB, 135dB@ 0.5% THD (130dB@24V, 120dB @ 12V) Connector: XLR Warranty hardware 2 years	23333,33
20	32323100-4	Microfon	Buc.	4	Condenser Microphone (equivalent AKG C414 XLII) Microphone Frequency Range - 20 Hz to 20 kHz Primary Applications - Live Sound, Studio Recording Form Factor - Large Diaphragm Mic / Stand/Boom Mount Intended Sound Sources - Vocals, Instrument Sound Field - Mono Operating Principle - Pressure Gradient Capsule - Condenser Diaphragm - 1" / 25.4 mm Polar Pattern - Cardioid, Figure-8, Hypercardioid, Omnidirectional, Subcardioid/Wide Pattern Selection - Switched Orientation - Side Address Circuitry - Solid-State Pad - -6 dB, -12 dB, -18 dB High-Pass Filter - 40 Hz, 12 dB/Octave, 80 Hz, 12 dB/Octave, 160 Hz, 6 dB/Octave Indicators - 13 x Single LED On-Board Controls - High-Pass Filter, Pad, Polar Pattern Windscreens - Foam (Included) Output Connectors (Analog) - 1 x XLR 3-Pin Male (on Mic) Mounting - Shockmount (Included) Included Case - Hard Case Included Filters - Pop Filter Construction Material - Metal Warranty hardware 2 years	53333,33

21	32323100-4	Microfon	Buc.	6	<p>Mic type small diaphragm condenser (Equivalent Oktava MK-012-01)</p> <p>Polar Pattern Cardioid Freq. Response 20-20000Hz Phantom voltage required 48 +- 2V Full impedance, module less than 300 ohms Weighted SPL 18 dBA Maximum SPL in 250-8000Hz range, (less than 0.5% THD) 130 db Free field sensitivity at 1KHz 10 mV/Pa Free field sensitivity roll off from 40Hz to 20KHz should not exceed +- 3 db Length, mm 128 Max diameter/width, mm 23 Shockmount Warranty hardware 2 years</p>	45000,00
22	32323100-4	Căști Monitor	Buc.	10	<p>Monitor Headphones (equivalent DT-770 M)</p> <p>TECHNICAL SPECIFICATIONS Transducer type - Dynamic Operating principle - Closed Nominal frequency response - 5 - 30,000 Hz Nominal impedance - 80-250 Ω per cartridge Nominal SPL - 105 dB SPL Nominal T.H.D. - < 0.2% Power handling capacity - 100 mW Sound coupling to ear - Circumaural Ambient noise isolation - approx. 35 dB(A) Nominal headband pressure - approx. 6.5 N Length and type of cable - 3 m / straight cable Cable with in-line volume control Connection - Gold plated mini stereo jack plug (3.5 mm) and 1/4" adapter (6.35 mm) Warranty hardware 2 years</p>	26666,67
23	32323100-4	Microfon fără fir, bluetooth	Buc	1	<p>Wireless Mics (Pair) for Smartphones/DSLR (Equivalent Sabinetek Smartmike+)</p> <p>Wireless Technology - Digital Bluetooth RF Channel Scanning - Auto-Scan Max Transmitters per Band - 2 Bluetooth - 5.0 Sample Rate/Resolution - 44.1 kHz Latency - 60 to 100 ms Transmitter Type Clip-On with Microphone Audio I/O - 1 x 3.5 mm TRRS Female Output Power Requirements - Battery, Bus Power (USB) Internal Battery Capacity - 110 mAh USB/Lightning I/O - 1 x Micro-USB (Bus Power, Charging) Display & Indicators - LED (Recharging) Microphone Type - Integrated Color - Black</p> <p><i>Include bluetooth Earbuds</i> (equivalent Buds 2 Pro) Speaker custom Coaxial 2-way (Tweeter + Woofer) 24bit Hi-Fi, 360 Audio with Direct Multi-Channel ANC + High SNR Microphone (2 outer + 1 inner) Voice Detect Up to 5 hours / Total up to 18 hours (ANC on) play time Up to 8 hours / Total up to 29 hours (ANC off) play time Battery Capacity Case 515 mAh Bluetooth 5.3, Auto Switching IPX7 water resistance Sensors Accelerometer,Gyro Sensor,Hall Sensor,Proximity Sensor,Touch Sensor,VPU Color: Graphite Warranty - 2 years</p>	8333,33
24	32323100-4	Microfon fără fir, bluetooth	Buc	1	<p>Wireless Mics (Pair) for Smartphones/DSLR (Equivalent Sabinetek Smartmike+)</p> <p>Wireless Technology - Digital Bluetooth RF Channel Scanning - Auto-Scan Max Transmitters per Band - 2 Bluetooth - 5.0 Sample Rate/Resolution - 44.1 kHz Latency - 60 to 100 ms Transmitter Type Clip-On with Microphone Audio I/O - 1 x 3.5 mm TRRS Female Output Power Requirements - Battery, Bus Power (USB) Internal Battery Capacity - 110 mAh USB/Lightning I/O - 1 x Micro-USB (Bus Power, Charging) Display & Indicators - LED (Recharging) Microphone Type - Integrated Color - White</p>	8333,33

					<p><i>Include bluetooth Earbuds (equivalent Buds 2 Pro)</i> Speaker custom Coaxial 2-way (Tweeter + Woofer) 24bit Hi-Fi, 360 Audio with Direct Multi-Channel ANC + High SNR Microphone (2 outer + 1 inner) Voice Detect Up to 5 hours / Total up to 18 hours (ANC on) play time Up to 8 hours / Total up to 29 hours (ANC off) play time Battery Capacity Case 515 mAh Bluetooth 5.3, Auto Switching IPX7 water resistance Sensors Accelerometer,Gyro Sensor,Hall Sensor,Proximity Sensor,Touch Sensor,VPU Color: White Warranty - 2 years</p>	
25	32324300-3	Teleprompter	set	2	<p>Teleprompter for fixing the tablet or phone Articulating Arm: Load Capacity Up to 2.72 kg Construction Durable aluminum construction Length, Fully Extended 28 cm Weight 0.2 kg Arm Length 21.1 cm (joint-to-joint length) Mount CompatibilityTop: 1/4"-20 male screw Bottom: cold shoe 1/4"-20 female thread (with spacer piece attached) 1/4"-20 male screw (with spacer removed) TAB GRABBER universal tablet cradle for ultralight teleprompters Compatible Display 23 cm to 30 cm (9.25 to 11.75") Include Remote control Wireless remote control (teleprompter pad remote) Wireless remote (application with IOS/Android included) WIRELESS BLUETOOTH REMOTE FOR TELEPROMPTER APPLE/ANDROID Work distance 10 meter Include Battery <i>Include phone (equivalent S23)</i> Size 6.1 inches Dynamic AMOLED 2X, 120Hz, HDR10+, 1200 nits (HBM), 1750 nits (peak) Resolution 1080 x 2340 pixels, 19.5:9 ratio (~425 ppi density) Protection Corning Gorilla Glass Victus 2 Always-on display Chipset Qualcomm SM8550-AC Snapdragon 8 Gen 2 (4 nm) CPU Octa-core, GPU Adreno 740 Internal min 256GB 8GB RAM MAIN CAMERA 50 MP, f/1.8, 24mm (wide), 1/1.56", 1.0µm, Dual Pixel PDAF, OIS 10 MP, f/2.4, 70mm (telephoto), 1/3.94", 1.0µm, PDAF, OIS, 3x optical zoom 12 MP, f/2.2, 13mm, 120° (ultrawide), 1/2.55" 1.4µm, Super. Video 8K@24/30fps, 4K@30/60fps, 1080p@30/60/240fps, 1080p@960fps, HDR10+, stereo sound rec., gyro- EIS. Wi-Fi 802.11 a/b/g/n/ac/6e, tri-band, Wi-Fi Direct Bluetooth 5.3, A2DP, LE USB Type-C 3.2, OTG BATTERY 3900 mAh Colors Black Warranty hardware 2 years</p>	50833,33
26	32324300-3	Tablet	buc	1	<p>Tablet (equivalent Galaxy Tab S8 8/128GB) Network GSM/HSPA/LTE/5G Dimensions 253.8 x 165.3 x 6.3 mm Stylus, 6.2ms latency (Bluetooth integration, accelerometer, gyro) DISPLAY TFT LCD, 120Hz Size 11.0 inches Resolution 1600 x 2560 pixels, 16:10 ratio (~274 ppi density) Protection Corning Gorilla Glass 5 PLATFORM OS Android 12 Chipset Qualcomm SM8450 Snapdragon 8 Gen 1 (4 nm) CPU Octa-core (1x3.00 GHz Cortex-X2 & 3x2.50 GHz Cortex-A710 & 4x1.80 GHz Cortex- A510) GPU Adreno 730 MEMORY Card slot microSDXC (dedicated slot) Internal min 128GB 8GB RAM MAIN CAMERA Dual 13 MP, f/2.0, 26mm (wide), 1/3.4", 1.0µm, AF 6 MP, f/2.2, (ultrawide) Features LED flash, HDR, panorama Video 4K@30/60fps, 1080p@30fps SELFIE CAMERA Dual 12 MP, f/2.4, 120° (ultrawide) Features HDR Video 4K@30/60fps, 1080p@30fps</p>	15833,33

					<p>SOUND Loudspeaker Yes, with stereo speakers (4 speakers) 3.5mm jack No COMMS WLAN Wi-Fi 802.11 a/b/g/n/ac/6e, dual-band, Wi-Fi Direct Bluetooth 5.2, A2DP, LE Positioning GPS, GLONASS, BDS, GALILEO USB USB Type-C 3.2, magnetic connector FEATURES Sensors Fingerprint (side-mounted), accelerometer, gyro, proximity, compass BATTERY Type Li-Po 8000 mAh Color: Graphite Charging 45W wired <i>Include Remote control</i> Wireless remote control (teleprompter pad remote) Wireless remote (application with IOS/Android included) WIRELESS BLUETOOTH REMOTE FOR TELEPROMPTER APPLE/ANDROID Work distance 10 meter Include Battery</p>	
27	32323100-4	Microfon radio	Buc.	3	<p>System Microfon (Equivalent EW 135P G4-E) Wireless Technology Analog UHF Number of RF Channel Frequencies 1680 Included Transmitters 1 x Bodypack with Microphone Diversity Antenna Diversity RF Frequency Band 566 to 608 MHz RF Bandwidth 42 MHz Frequency Step Size 25 kHz Max Operating Range 330' / 100.6 m (Line of Sight) Max Transmitters per Band 12 Deviation 48 kHz (Peak) Modulation Wideband FM Receiver Type Camera-Mount Mounting Options Shoe-Mount (with Included Hardware) Antenna 1 x Flexible Whip, Fixed Number of Audio Channels 1 Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable) Gain Range 42 dB (6 dB Steps) Audio Output Level +12 dBu Squelch 5 to 25 dBµV Adjacent Channel Isolation >65 dB Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level) Transmitter Type Handheld RF Output Power 30 mW Audio I/O None Audio Input Level 3 V RMS (Max) Gain Range 48 dB (6 dB Steps) Frequency Response 80 Hz to 18 kHz (Mic) 80 Hz to 18 kHz (Line) Sync Method IR Antenna 1 x Internal Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength) Microphone Microphone Type Handheld Capsule Sound Field Mono Capsule Dynamic Polar Pattern Cardioid Maximum SPL 154 dB SPL Peak Sensitivity 2.1 mV/Pa Warranty hardware 2 years</p>	32500,00
28	32323100-4	Microfon pentru instrument	Buc.	4	<p>Microphone (Equivalent Sennheiser MD 421-II) Operating Principal Pressure Gradient Capsule Dynamic Polar Pattern Cardioid Frequency Range 30 Hz to 17 kHz Impedance 200 Ohms Sensitivity in free field, no load (1kHz) 2 mV/Pa +- 3 dB Connectivity Output Connectors (Analog) 1 x XLR 3-Pin Warranty hardware 2 years</p>	30000,00

29	32323100-4	Microfon	Buc	1	<p>Dynamic Podcast microphone (Equivalent MV7B) Control of microphone gain, headphone level, monitor mixing,mute over touch panel interface Individual adjustments via the ShurePlus motif desktop app possible (e.g., amplification, compression and EQ presets) Internal shockmount Directional characteristics: unidirectional (cardioid) A / D converter: 16/24 bit, 44.1 / 48 kHz Frequency range: 50 - 16,000 Hz Adjustable gain: 0 to +36 DB Sensitivity: XLR -55 DBV / PA (1.78 mV) at 1 kHz USB -47 DBFS / PA at 1 kHz (with minimal reinforcement Flat Mode 1 Pa = 94 DB SPL) USB Maximum SPL 132 DB SPL DSP modes (presets): near / far, dark / natural / bright Power supply via USB or LIGHTNING connection MFI certified XLR output impedance: 314 ohms at 1 kHz 5/8" Thread XLR output Micro USB output 3.5 mm Jack headphone output Warranty hardware 2 years</p>	5833,33
30	32323100-4	Double Ear Intercom Headset	Buc.	10	<p>Double Ear Intercom Headset (equivalent HMD685) Professional intercom headsets with flexible anti-vibration gooseneck boom microphones. The headset is lightweight, provides extra soft ear cushions and headband paddings for outstanding wearing comfort even during extra soft ear cushions Headset is provided with a dynamic vocal unidirectional patterned microphone, featuring excellent acoustic performance and a reliable noise suppression. HEADPHONE Transducer principle : dynamic, closed Ear coupling : Circumaural Frequency response : 20~20,000 Hz Impedance Double-ear: 200 Ω Sensitivity : 96 dB SPL at 1 kHz, 1 mW Max. Input Power : 100 mW Caliper pressure : approx. 4.5 N Connector : 1.5-meter (4.92') straight cord, 4-pin XLR female plug MICROPHONE Transducer principle : dynamic, cardioid Frequency response : 50~15,000 Hz Polar Pattern : cardioid Sensitivity : -64 dBV/Pa (0.6 mV/Pa) at 1 kHz Impedance : 250 Ω</p>	16666,67
31	32323100-4	Lavalier microphone system	set	2	<p>System Wireless Technology - Digital UHF Number of RF Channel Frequencies - 2240 Included Receivers - 5 x Receivers Included Transmitters - 5 x Bodypack Included Splitters – 1 x Active Antenna Splitter Diversity - Intelligent Switching Diversity RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Max Transmitters per Band - 90 Bluetooth - 5.1 Sample Rate/Resolution - 24-Bit Receiver 5 pcs (equivalent EW-D EM Y1-3) Frequency range U1/5: 1785.2-1799.8 MHz Receiver Type - Tabletop / Rackmount Mounting Options - Rackmount, Tabletop Rackmount Size - 1 RU (1/2 Rack) Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount) Number of Audio Channels - 1 Audio I/O - XLR 3-Pin Male Balanced Output (Lockable), 1/4" TRS Female Unbalanced Output Gain Range - -3 to +42 dB (3 dB Steps) Audio Output Level-XLR Output:+18dBu (Balanced), 1/4"Output:+12 dB (Unbalanced) Frequency Response - 20 Hz to 20 kHz ±3 dB Power Requirements - AC/DC Power Adapter AC/DC Power Adapter - 11 to 13 VDC at 300 mA (Included) AC Input Power - 100 to 240 VAC, 50 / 60 Hz Display & Indicators - Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter)</p>	155083,34

				<p>Transmitter 5 pcs (EW-D SK) Transmitter Type - Bodypack RF Output Power - 10 mW (ERP) Audio I/O - 1 x 3.5 mm TRS Female Input (Lockable) Muting - Mute Switch Audio Input Level - 2 to 4.35 V RMS Sync Method - Bluetooth Antenna - 1 x Flexible Whip, Fixed (Belt-pack) Power Requirements - Battery Microphone 5 pcs (equivalent ME-2) Microphone Type Lavalier Sound Field Mono Capsule Electret Condenser Polar Pattern Omnidirectional Frequency Range 50 Hz to 18 kHz Equivalent Noise Level 32 dB Maximum SPL 130 dB SPL Sensitivity 17 mV/Pa at 1 kHz Output Connectors 1 x 1/8" / 3.5 mm TRS Male (Lockable) Cable Length 5.2' / 1.6 m Operating Voltage 7.5 V Active Antenna Splitter 1 pcs (equivalent EW-D ASA X-Y) Active Antenna Splitter (Dual 1:4) with DC Voltage Distribution For the UHF-range from 1350-1805 MHz Incl. 1x power supply NT 12-35 CS and 8x BNC connection cable Half-wave dipole rod antenna 2 pcs Frequency range - Y: 1785 - 1805 MHz Connection - BNC</p>		
32	32323100-4	Handheld Microphone System	set	1	<p>System Frequency range Y1-3: 1785.2 - 1799.8 MHz Wireless Technology - Digital UHF Number of RF Channel Frequencies - 2240 Included Transmitters - 3 x Handheld Diversity - Intelligent Switching Diversity RF Channel Scanning - Auto-Scan Max Operating Range - 100 m Max Transmitters per Band - 90 Bluetooth - 5.1 Sample Rate/Resolution - 24-Bit Receiver 3 pcs (equivalent EW-D EM Y1-3) Frequency range Y1-3: 1785.2 - 1799.8 MHz Receiver Type - Tabletop / Rackmount Mounting Options - Rackmount, Tabletop Rackmount Size - 1 RU (1/2 Rack) Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount) Number of Audio Channels - 1 Audio I/O-XLR 3-Pin Male Balanced Output (Lockable), 1/4" TRS Female Unbalanced Gain Range - -3 to +42 dB (3 dB Steps) Audio Output Level- XLR Output: +18 dBu (Balanced), 1/4" Output: +12 dB (Unbalanced) Frequency Response - 20 Hz to 20 kHz ±3 dB Power Requirements - AC/DC Power Adapter AC/DC Power Adapter - 11 to 13 VDC at 300 mA (Included) AC Input Power - 100 to 240 VAC, 50 / 60 Hz Display & Indicators - 1 x Backlit OLED (AF Level, Frequency, Mute, RF Level). Transmitter 3 pcs (equivalent EW-D SKM-S) Transmitter Type - Handheld RF Output Power - 10 mW (ERP) Muting - Mute Switch Audio Input Level - 2 to 4.35 V RMS Auto-Level Control - No Antenna - 1 x Internal (Handheld) Power Requirements - Battery Battery Type - 2 x AA (Included) Display & Indicators - 1 x LED (Mute); 1 x LED (Sync) Microphone 6 pcs (equivalent MMD 835 capsule) Microphone Type - Handheld Capsule Sound Field - Mono Capsule - Dynamic Polar Pattern - Cardioid Equivalent Noise Level - 32 dB Maximum SPL - 154 dB SPL Sensitivity - 2.1 mV/Pa</p>	60000,00

				Active Antenna Splitter 1 pcs (equivalent EW-D ASA X-Y) Active Antenna Splitter (Dual 1:4) with DC Voltage Distribution For the UHF-range from 1350-1805 MHz Incl. 1x power supply NT 12-35 CS and 8x BNC connection cable Half-wave dipole rod antenna 2 pcs Frequency range - Y: 1785 - 1805 MHz Connection – BNC Include EW-D Color Coding Set	
Suma totală estimativă (fără TVA)					832833,34

9. În cazul procedurilor de preselecție se indică numărul minim al candidaților și, dacă este cazul, numărul maxim al acestora.-----

10. În cazul în care contractul este împărțit pe loturi un operator economic poate depune oferta (se va selecta):

- 1) Pentru un singur lot;
- 2) **Pentru mai multe loturi;**
- 3) Pentru toate loturile;
- 4) Alte limitări privind numărul de loturi care pot fi atribuite aceluiași ofertant _____

11. Admiterea sau interzicerea ofertelor alternative: *nu se admite*

12. Termenii și condițiile de livrare/prestare solicitată: *Livrarea bunurilor în decurs de 40 de zile de la semnarea contractului.*

13. Termenul de valabilitate a contractului: **31.12.2023**

14. Contract de achiziție rezervat atelierelor protejate sau că acesta poate fi executat numai în cadrul unor programe de angajare protejată (după caz): *Nu*

15. Prestarea serviciului este rezervată unei anumite profesii în temeiul unor legi sau al unor acte administrative (după caz): *Nu*

16. Scurta descriere a criteriilor privind eligibilitatea operatorilor economici care pot determina eliminarea acestora și a criteriilor de selecție/de preselecție; nivelul minim (nivelurile minime) al (ale) cerințelor eventual impuse; se menționează informațiile solicitate (DUAE, documentație):

Scurtă descriere a criteriilor de selecție		Nivelul minim/ Obligatorietatea
Specificații tehnice completată în conformitate cu Anexa nr. 22	- în original semnat electronic;	Obligatoriu
Specificații de preț completată în conformitate cu Anexa nr. 23	- în original semnat electronic;	Obligatoriu
Garanția pentru ofertă 1% – formularul garanției bancare completată în conformitate cu Anexa nr. 9	- în original, garanție bancară în original, emisă de o bancă comercială; sau - Transfer pe contul IP Compania „Teleradio-Moldova”, Beneficiarul plății: IP Compania „Teleradio-Moldova” <i>Denumirea Băncii: BC „Moldindconbank” SA</i> <i>Codul fiscal: 1004600050558</i> <i>Contul de decontare: MD47ML000000002251206328</i> <i>Contul bancar: MOLDM2X306</i> Termenul de valabilitate al garanției să fie valabil pe perioada de valabilitate a ofertei – 30 zile din ziua depunerii ofertelor;	Obligatoriu
Document unic de achiziții european	- în original semnat electronic;	Obligatoriu
Cerere de participare completată în conformitate cu Anexa nr. 7	- în original semnat electronic;	Obligatoriu

Declarație privind valabilitatea ofertei completată în conformitate cu Anexa nr. 8	- în original semnat electronic;	Obligatoriu
Acte solicitate prin DUAE, conform art. 20 alin.8, Legea nr. 131 din 03.07.2015, privind achizițiile publice, ofertantul clasat pe primul loc va prezenta (prin mijloace electronice, cu aplicarea semnăturii electronice) în termen de 3 zile, la solicitarea autorității contractante, documentele justificative actualizate prin care va demonstra îndeplinirea tuturor criteriilor de calificare și selecție.		
Dovada înregistrării juridice	emis de organul abilitat – în original/copie semnat electronic;	Obligatoriu
Certificat de atribuire al contului bancar	eliberat de banca deținătoare de cont, în original/copie semnat electronic;	Obligatoriu
Situație financiară	raportul financiar în original/copie pentru ultimul an, aprobat de către Direcția Generală pentru Statistică sau însoțite de recipisa de primire de către Direcția Generală pentru Statistică autentificat prin semnătură electronică	Obligatoriu
Declarație privind lista principalelor livrări/prestări efectuate în ultimii 3 ani de activitate completată în conformitate cu Anexa nr. 12	în original semnat electronic;	Obligatoriu
Numărul de înregistrare	Numărul de înregistrare din „Lista producătorilor” conform Regulamentului privind deșeurile de echipamente electrice și electronice aprobat prin H.G. nr. 212 din 07.03.2018	Obligatoriu
Declarație privind confirmarea identității beneficiarilor efectivi și neîncadrarea acestora în situația condamnării pentru participarea la activități ale unei organizații sau grupări criminale, pentru corupție, fraudă și/sau spălare de bani.	Aprobat prin Ordinul MF nr. 145 din 24.11.2020, completată în conformitate cu Formularul - în original semnat electronic; <i>*Se va prezenta în termen de 5 zile de către operatorul economic desemnat câștigător.</i>	Obligatoriu
Garanția de bună execuție a contractului 5% din valoarea contractului inclusiv TVA	<u>Transfer la contul I.P. Compania „Teleradio-Moldova”, Beneficiarul plății: I.P. Compania „Teleradio-Moldova”</u> <u>Denumirea Băncii: B.C. „Moldindconbank” SA</u> <u>Codul fiscal: 1004600050558</u> <u>Contul de decontare: MD47ML00000002251206328</u> <u>Contul bancar: MOLDM2X306</u> <i>*Se va prezenta până la semnarea contractului.</i>	Obligatoriu

- 17. Garanția pentru ofertă, după caz Da , cuantumul 1% din valoarea ofertei fără TVA.**
- 18. Garanția de bună execuție a contractului, după caz Da, cuantumul 5% din valoarea contractului inclusiv TVA.**
- 19. Motivul recurgerii la procedura accelerată (în cazul licitației deschise, restrânse și a procedurii negociate), după caz-----**
- 20. Tehnici și instrumente specifice de atribuire (dacă este cazul specificați dacă se va utiliza acordul-cadru, sistemul dinamic de achiziție sau licitația electronică):** licitație electronică, 3 runde, valoarea pasului minim 1 %
- 21. Condiții speciale de care depinde îndeplinirea contractului (indicați după caz): -----**
- 22. Ofertele se prezintă în valuta LEI MDL**
- 23. Criteriul de evaluare aplicat pentru atribuirea contractului: *prețul cel mai scăzut și corespunderea cerințelor caietului de sarcini.***
- 24. Termenul limită de depunere/deschidere a ofertelor:**
- conform SIA RSAP
- 25. Adresa la care trebuie transmise ofertele sau cererile de participare:**

Ofertele sau cererile de participare vor fi depuse electronic prin intermediul SIA RSAP

26. Termenul de valabilitate a ofertelor: *30 de zile*
27. Locul deschiderii ofertelor: **SIA RSAP**
Ofertele întârziate vor fi respinse.
28. Persoanele autorizate să asiste la deschiderea ofertelor:
Ofertanții sau reprezentanții acestora au dreptul să participe la deschiderea ofertelor, cu excepția cazului când ofertele au fost depuse prin SIA RSAP.
29. Limba sau limbile în care trebuie redactate ofertele sau cererile de participare: **limba română**
30. Respectivul contract se referă la un proiect și/sau program finanțat din fonduri ale Uniunii Europene: -----
31. Denumirea și adresa organismului competent de soluționare a contestațiilor:
Agenția Națională pentru Soluționarea Contestațiilor
Adresa: mun. Chișinău, bd. Ștefan cel Mare și Sfânt nr.124 (et.4), MD 2001;
Tel/Fax/email:022-820 652, 022 820-651, contestatii@ansc.md
32. Data (datele) și referința (referințele) publicărilor anterioare în Jurnalul Oficial al Uniunii Europene privind contractul (contractele) la care se referă anunțul respectiv (dacă este cazul):-

33. În cazul achizițiilor periodice, calendarul estimat pentru publicarea anunțurilor viitoare:-----
34. Data publicării anunțului de intenție sau, după caz, precizarea că nu a fost publicat un astfel de anunț: **BAP nr. 21 din 14.03.2023**
35. Data transmiterii spre publicare a anunțului de participare: **Conform SIA RSAP**
36. În cadrul procedurii de achiziție publică se va utiliza/accepta:
- | Denumirea instrumentului electronic | Se va utiliza/accepta sau nu |
|--|------------------------------|
| Depunerea electronică a ofertelor sau a cererilor de participare | da |
| Sistemul de comenzi electronice | nu |
| Facturarea electronică | da |
| Plățile electronice | da |
37. Contractul intră sub incidența Acordului privind achizițiile guvernamentale al Organizației Mondiale a Comerțului (numai în cazul anunțurilor transmise spre publicare în Jurnalul Oficial al Uniunii Europene): **Nu**

Președintele grupului de lucru

Ion Stratulat