



New design of stainless steel inner tank made in a single piece free of welds, coupled to an outer metal cabinet with epoxy coating.

Main features incorporated in the equipment:

- 1 | Digital selection of parameters with display of actual operating temperature and time.
- 2 | Continuous operation or operation in programmed periods, with acoustic signal at the end of the selected time.

- 3 | Acoustic signal indicating overheating of the bath when the bath temperature exceeds the selected temperature by 10°C.
- 4 | Airtight membrane keypad protected against splashing
- 5 | Including lid with holes (11 cm) and reducing rings (8 and 5 cm)
- 6 | Electric drainage pump with drainage outlet (except model 601/3)



Code: JDD001
Model: 601/3
Capacity: 3L



Code: JDD002
Model: 601/5
Capacity: 6L



Code: JDD003
Model: 601/12
Capacity: 12L



Code: JDD004
Model: 601/19
Capacity: 18L

Code	JDD001	JDD002	JDD003	JDD004
Model	601/3	601/5	601/12	601/19
Capacity	3 L	6 L	12 L	18 L
Temperature range	RT – 100°C			
Resolution	0.1 °C			
Timer	1 - 9999 min			
Holes	1	2	4	6
Dimensions(mm)	160x160x130	305x160x130	305x305x130	470x305x130
Weight	3 kg	4 kg	6 kg	8 kg