

TECHNICAL FEATURES

| THERAPIC 9400 TH1313 | | |
|---|----------------------|--|
| Main voltage: | | 230 Vac, 50-60Hz, ±10% |
| | | 115 Vac, 50-60Hz, ±10% * |
| Max. Power absorption: | THERAPIC 9400 | 65 VA |
| Double delay type (T) mains fuse protection: | THERAPIC 9400 | 315 mA - T - 5 x 20 mm for alimentation 230Vac 630 mA - T - 5 x 20 mm for alimentation 115Vac |
| Backlit LCD Display, to visualise and control operating parameters | | Colour graphic 320 x 240 pixel touch screen +encoder |
| Programmable treatment time | | up to 60 minutes |
| <u>Class of isolation/parts applied according to the rule EN 60601-1</u> | | <u>I / BF</u> |
| <u>Classification in compliance with the directive 93/42/CEE</u> | | <u>II B</u> |
| <u>Degree of protection against the input of liquids according to the UNI EN 60601-1 standard</u> | | <u>IPX0</u> |
| Emission frequency | THERAPIC 9400 | All low and medium frequency currents , 25 Waveforms total number |
| Functioning: | THERAPIC 9400 | Voltage Costant Current Costant |
| Peak current (Load resistance 1KOhm) | Pulse current | 100 mA |
| | Diadynamic current | 70 mA |
| | Continuous current | 50 mA |
| Peak voltage (Load resistance 1KOhm) | Pulse current | 100 V |

TECHNICAL FEATURES

| | | |
|---|----------------------|------------------|
| | Diadynamic current | 70 V |
| | Continuos current | 50V |
| Channel output: | THERAPIC 9400 | 4 independents |
| Protocols in memory | THERAPIC 9400 | 126 |
| Number of protocols that can be saved in the user memory | | 200 |
| Sequences that can be saved in the user memory | | 10 |
| <u>Curve I/t that can be saved in the user memory</u> | | 100 |
| <u>Value of reobase/cronaxya that can be saved in the user memory</u> | | 100 |
| Number of protocols that can be saved in the smart-card | | 50 |
| Sequences that can be saved in the smart-card | | 10 |
| <u>Curve I/t that can be saved in the smart-card</u> | | 20 |
| <u>Value of reobase/cronaxya that can be saved in the smart-card</u> | | 10 |
| Table container in plastic, external size (width x height x depth) | | 39 x H14 x 30 cm |
| Unit body weight | THERAPIC 9400 | 6,2 Kg |

TECHNICAL FEATURES

| | | |
|--|-----------------------------|--|
| <u>Conditions for use</u> | <u>Room temperature</u> | <u>(+10 : +40) °C</u> |
| | <u>Relative humidity</u> | <u>(10 : 80) % without condensation</u> |
| <u>Conditions for stocking / transport</u> | <u>Room temperature</u> | <u>(-40 : +70) °C</u> |
| | <u>Relative humidity</u> | <u>(10 : 100) % without condensation</u> |
| | <u>Atmospheric pressure</u> | <u>(500 : 1060) hPa</u> |

*upon request