# **EB-PU2113W**

# EPSON

### DATASHEET / BROCHURE



## The EB-PU2113W is a high lumens 3LCD projector that's ultralightweight and compact.

The EB-PU2113W offers users significant advantages including much reduced size and weight, easier installation and set-up, simplified maintenance and great image quality. This ultra-lightweight, compact laser projector has been designed for use in large auditoriums, live events, concerts, conference rooms where it delivers high-impact immersive experiences.

### Compact and lightweight

The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

### Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.

### Flexibility

The EB-PU2113W's functionality enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

### Reliability

Includes outstanding dust resistance as the hermetically sealed optical engine, and laser light source unit, ensure stable brightness output over long periods, even in high dust environments.

### **KEY FEATURES**

- Ultra-lightweight and compact Easy to store, transport and install
- Stunning image displays 13,000lm, 4K Enhancement technology, WUXGA resolution
- Easy to use Simple installation, stacking, lens flexibility and control
- Fit-and-forget reliability Enhanced dust resistant construction -IP5X certified
- Environmental benefits Lower power consumption, reduced packaging, reduced weight



### **PRODUCT SPECIFICATIONS**

TECHNOLOGY		
Projection System	3LCD Technology	
LCD Panel	1.03 inch with C2 Fine	
IMAGE		
Color Light Output	13,000 Lumen- 9,100 Lumen (economy) In accordance with IDMS15.4	
White Light Output	13,000 Lumen - 9,100 Lumen (economy) In accordance with ISO 21118:2020	
Resolution	WUXGA	
High Definition	4K enhancement	
Aspect Ratio	16:10	
Contrast Ratio	Over 2,500,000 : 1	
Native Contrast	2,000 : 1	
Light source	Laser	
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco	
Colour Video Processing	10 Bits	
Colour Reproduction	Upto 1.07 billion colours	
HDR support	HDR10, HLG	
OPTICAL		
Throw Ratio	0.35 - 7.41:1	
Zoom	Motorized, Factor: 1 - 1.6	
Lens	varies by lens	
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %, varies by lens	
Lens position memory	10 positions	
Screen Size	60 inches - 1,000 inches, varies by lens	
Projection Distance Wide	)varies by lens	
Projection Distance Tele	)varies by lens	
Projection Lens F Number	varies by lens	
Projection Lens Focal Length		
Projection Lens Focus	Motorized	
Interchangeable Lens	Yes	
Standard Lens	Not included	
CONNECTIVITY Interfaces	USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet Interface (1000 Base-T/ 100	
Interfaces		
	Base TX/ 10-Base-T), VGA in, DVI in, HDMI in, HDBaseT, Jack plug out, Wireless LAN IEEE 802.11a/b/g/n (optional), Near Field Communication (NFC), USB content playback, Remote	
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink	
ADVANCED FEATURES	Kansington look Security for Desculard look Mireless I AN unit look Mireless I AN security	
Security	Kensington lock, Security bar, Password lock, Wireless LAN unit lock, Wireless LAN security,	
Other features	Password protection	
Other features	21:9 aspect ratio support, 4K enhancement, A/V mute, Auto Power On, Auto source search,	
	Direct Power on/off, Edge Blending, Lens position memory, Long light source life, OSD copy	
	function, Point correction, Power on button, Quick Corner, Schedule Function, Split-Screen-	
	Function, Super resolution, Web Control, Web Remote, iProjection App	
Video Color Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709	
Projector control	via: AMX, Crestron, Extron	
Sealed Light Source Module	Yes, IP5X rated	
Sealed Optical Engine	Yes, IPox rated	
Sealed Optical Engine	Yes, IP5X rated	

### EB-PU2113W

### WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- User manual
- Warranty document



### PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	686 Watt - On mode power consumption (Normal)
	864 Watt (Peak), 633 Watt (Eco), 0.4 Watt (Energy saving standby)
Heat Dissipation	2,938 BTU/hour (max)
Supply Voltage	AC 200 V - 240 V, 50 Hz - 60 Hz
Product dimensions	586 x 492 x 218 mm (Width x Depth x Height)
Product weight	23.8 kg
Noise Level	Normal: 34 dB (A) - Economy: 29 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
Included Software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Config Tool, Epson
	Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool
Options	Camera module, Ceiling mount, Wireless LAN unit
Positioning	Ceiling Mounted, Desktop, Flying Frame
Colour	White
OTHER	
Warranty	36 months Carry in
	Optional warranty extension available

### EB-PU2113W

### WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- User manual
- Warranty document



### **OPTIONAL ACCESSORIES**

- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Camera Unit ELPEC01 V12HA46010
- Ceiling Mount ELPMB68
- V12H006AE0
- Extension Pole ELPMB70 For ELPMB68 V12H006AG0
- Truss Adaptor ELPMB71 For ELPMB68 V12H006AH0
- Stacking Frame ELPMB59 EB-PU2200 Series (EVO) V12H996B59

### **OPTIONAL LENSES**

- Lens ELPLL08 Long throw EB-PU Series V12H004L08
- Lens ELPLM10 Mid throw 3 EB-PU Series V12H004M0A
- Lens ELPLM11 Mid throw 4 EB-PU Series V12H004M0B
- Lens ELPLM15 Mid throw EB-PU Series V12H004M0F
- Lens ELPLU03S Short throw off axis 1 EB-PU Series V12H004UA3
- Lens ELPLU04 Short throw off axis 2 EB-PU Series V12H004U04
- Lens ELPLW05 Wide zoom 1 EB-PU Series V12H004W05
- Lens ELPLW06 Wide zoom 2 EB-PU Series V12H004W06
- Lens ELPLW08 Wide throw EB-PU2000 Series V12H004W08
- Lens ELPLX02S UST EB-PU2000 Series V12H004X0B
- Lens ELPLX02WS UST EB-PU2000 Series V12H004Y0B

### LOGISTICS INFORMATION

SKU	V11HA65940
EAN code	8715946703190
Country of Origin	China
Layer	1 Units



\* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

### **EB-PU2113W**

**EPSON**<sup>®</sup>