## ITEM 2 Laboratory Freezer

|    | Minimum Technical Requirement                                      | Bidder's Offer                       |        |   |  |
|----|--|--------------------------------------|--------|---|--|
| No |  | Conformity                           |        |   |  |
|    |  | Yes                                  | Yes No |   | Remarks  |
| 1  | Model  | DW-HL340                             |        |   | Advandages of product 1/ Standary: RS485, remote alarm contact, backup battery 2/ Options Chart recorder Printer CO2 backup system 3/ Alarm systems High/Low temperature, High ambient temperature, Low battery, Power failure, Sensor failure, Condenser overheating, Door ajar, Built-in datalogger USB failure Main board communication error |
| 2  | Country of Origin  | CHINA                                |        |   |  |
| 3  | Name of Manufacture  | ZHONGKE MEILING CRYOGENICS CO., LTD. |        | _ |  |
| 4  | Laboratory application   | Yes                                  |        |   |  |
| 5  | Volume from 250 to 300 L   | Yes                                  |        |   | 340L   |
| 6  | Stainless steel test chambers and corrosion-resistant outer casing | Yes                                  |        |   | Inner Material:Stainless steel   |
| 7  | Configuration - on wheels  | Yes                                  |        |   | 4 casters  |
|    | Number of doors-1 door   | Yes                                  |        |   | 1 exterior door, 4 inner doors   |
| _  | Max temperature range -20 ° C, min80 ° C                           | Yes                                  | +      |   | -40~-86C(adjustable)   |
|    | Greenhouse gases / technology (energy saving)                      | Yes                                  |        |   |  |
| 11 | Noise reduction by speed controlled fan compressor                 | Yes                                  |        |   |  |
| 12 | Possibility of calibration and validation                          | Yes                                  |        |   |  |
| 13 | Temperature setting accuracy: 0.1 ° C                              | Yes                                  |        |   |  |
| 14 | Humidity setting accuracy: 0.5%                                    | Yes                                  |        |   |  |
| _  | Number of stainless steel shelves: at least 2                      | Yes                                  |        |   | 3 shelves:stainless steel  |
| 16 | Communication interfaces: LAN, USB                                 | Yes                                  |        |   | USB/Record every 10 minute / 2 years   |
| 17 | Self-diagnosis and temperature and humidity control system: yes    | Yes                                  |        |   |  |
| 18 | 220V-230V electrical connection, 50-60 Hz                          | Yes                                  |        |   |  |
| 19 | Warranty 24 months   | Yes                                  |        |   | Warranty for whole machine 24 months Warranty for compressor 36 months   |