

EXCELL MCDSe



Electrosurgical unit for monopolar and bipolar surgery

EXCELL MCDSe are electrocautery units for advanced surgery, indicated for all monopolar, bipolar and monopolar techniques with Argon gas flow.

They are available in 5 models:

- **EXCELL 400 MCDSe, EXCELL 350 MCDSe, EXCELL 250 MCDSe, EXCELL 200 MCDSe** for electrosurgery
- **EXCELL 400/A MCDSe** both for electrosurgery and for electrosurgery with Argon gas, being equipped with an integrated Argon module

CURRENTS

MONOPOLAR CURRENTS

PURE	Pure cut without any coagulating effect
BLEND 1	Coagulating cut with medium haemostatic effect
BLEND 2	Coagulating cut with strong haemostatic effect, spray type
ENDO	Coagulating cut with cut phases alternated to coagulation phases, for flexible endoscopy

FULG FORCED	Coagulation with strong superficial and deep effect
PINPOINT CONTACT	Coagulation similar to the previous one, but softer
SOFT	Very delicate coagulation, with soft superficial effect and strong deep action
SPRAY	Coagulation without any contact and a very strong superficial effect

BIPOLAR CURRENTS

PURE	Pure cut with minimum coagulating effect
BLEND	Coagulating cut with strong coagulating effect
MICRO	Very delicate coagulation, Micro Precise type, with minimum sticking effect of tissue on the tips of the forceps
MICRO AUTO	Coagulation identical to Micro, but with Impedance Sensing automatic Auto Start/Auto Stop
MACRO	Coagulation Standard type, very rapid and efficacious, ideal for forceps with bigger section (for example, for laparoscopy)



TECHNICAL FEATURES

HF generator compliant with	IEC 60601-1 and IEC 60601-2-2
CE Classification	IIB
IEC 60601-1 classification and type	I CF
IEC 60601-2-2 output circuit	Floating - protected for the use of a defibrillator (HF dispersion <150 mA)
Monopolar and bipolar working frequency	440 kHz
Operation check	Complete self-diagnosis by means of a double microprocessor which performs: - Main Self-check when turned on - Standard Self-check during operation and, if any, operation lock (within 100 milliseconds), with alarm signalling to operators through specific Error Codes, in the event of problems concerning: - general operation or activation errors (General Error Control) - output power (Output Error Control) - HF Leakage Control: continuous verification, by means of a specific circuit, of any HF current dispersion to earth and possible automatic power reduction by means of an alarm signal - Storage of the last 32 Error Codes
Power self-adjustment	By microprocessor with: - ADC System - Constant power: self-adjusts power, controlling voltage and current, based on real-time feedback (7000 checks/sec) between device and patient's tissue
Operation memorisation	10 programs
Outputs	2 Monopolar and 1 Bipolar
Foot-operated controls	The EXCELL MCDSe can be equipped with: • A double pedal control selectable for monopolar or bipolar functions. • Two double pedal controls, one for monopolar and one for bipolar functions. The pedals are compliant with IEC 60601-2-2, waterproof (IP67), electric with 12 VDC low voltage power supply.
Micro/macro power adjustment	Monopolar: 0-30 W = 1 W, 30-100 W = 2 W, 100-200 W = 5 W, over 200 W = 10 W Bipolar: 0-10 W = 0.5 W, 10-30 W = 1 W, 30-100 W = 2 W, over 100 W = 5 W
Panel	Smooth, with digital displays and keys
Neutral electrode safety circuit NPCC System	Control of the connection of the neutral electrode - and of the quality of the contact using double section/split electrodes - with alarm signal and possible lock of delivered power.
Power supply	230 or 115 V - 50/60 Hz
Power consumption at 230 V	Max power 3.6 A = 828 VA, Stand-by 0.4 A = 92 VA
Cooling	Convection, without fan
Equipotential bonding	Standard DIN 42801 plug
Size (LxDxH) and weight	EXCELL 400/A MCDSe: 38x38x16 cm – 16 Kg EXCELL 400 MCDSe, EXCELL 350 MCDSe, EXCELL 250 MCDSe, EXCELL 200 MCDSe: 38x35x16 cm – 15 Kg
Argon gas section (only in the EXCELL 400/A MCDSe model)	
Supply	One 5 litre cylinder or with centralised system
Flow	Max 15 l/min
Pressure	Inlet 2.5 atm / Outlet 1 atm
Flow check with Constant flow System	From 1 to 15 l/min by means of an electronic sensor with adjustment buttons and visual control on the LED bar. Automatic self-compensation based on the type of electrode used. Alarm if gas is absent.
Pressure check in the Safety gas System circuit	Two-stage pressure reducer (on the cylinder and inside, with safety valve). Pressure sensor connected to the electronic control system, with Auto-Check when the gas section is switched on.
Protection of the supplied gas flow	Gas outlet equipped with antibacterial filter.

OUTPUT POWERS

Monopolar currents	EXCELL 400 MCDSe	EXCELL 350 MCDSe	EXCELL 250 MCDSe	EXCELL 200 MCDSe	EXCELL 400/A MCDSe
PURE	400 W – 350 Ω 3450 Vpp – CF: 1.6 M: no – D: no	350 W – 350 Ω 3450 Vpp – CF: 1.6 M: no – D: no	280 W – 350 Ω 3450 Vpp – CF: 1.6 M: no – D: no	200 W – 350 Ω 3450 Vpp – CF: 1.6 M: no – D: no	400 W – 350 Ω 3450 Vpp – CF: 1.6 M: no – D: no
BLEND 1	300 W – 350 Ω 3600 Vpp – CF: 2.3 M: 29 kHz – D: 65%	300 W – 350 Ω 3600 Vpp – CF: 2.3 M: 29 kHz – D: 65%	280 W – 350 Ω 3540 Vpp – CF: 2.3 M: 29 kHz – D: 65%	200 W – 350 Ω 3500 Vpp – CF: 2.3 M: 29 kHz – D: 65%	300 W – 350 Ω 3600 Vpp – CF: 2.3 M: 29 kHz – D: 65%
BLEND 2	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%
ENDO	250 W – 350 Ω 1880 Vpp – CF: 2.2 50% Pure / 50% Coag	250 W – 350 Ω 1880 Vpp – CF: 2.2 50% Pure / 50% Coag	220 W – 350 Ω 1880 Vpp – CF: 2.2 50% Pure / 50% Coag	200 W – 350 Ω 1880 Vpp – CF: 2.2 50% Pure / 50% Coag	250 W – 350 Ω 1880 Vpp – CF: 2.2 50% Pure / 50% Coag
FULG FORCED	150 W – 350 Ω 4700 Vpp – CF: 4.5 M: 78 kHz – D: 35%	150 W – 350 Ω 4700 Vpp – CF: 4.5 M: 78 kHz – D: 35%	150 W – 350 Ω 4700 Vpp – CF: 4.5 M: 78 kHz – D: 35%	150 W – 350 Ω 4700 Vpp – CF: 4.5 M: 78 kHz – D: 35%	150 W – 350 Ω 4700 Vpp – CF: 4.5 M: 78 kHz – D: 35%
PINPOINT CONTACT	250 W – 250 Ω 3460 Vpp – CF: 2.6 M: 29 kHz – D: 56%	250 W – 250 Ω 3460 Vpp – CF: 2.6 M: 29 kHz – D: 56%	250 W – 250 Ω 3460 Vpp – CF: 2.6 M: 29 kHz – D: 56%	200 W – 250 Ω 3400 Vpp – CF: 2.6 M: 29 kHz – D: 56%	250 W – 250 Ω 3460 Vpp – CF: 2.6 M: 29 kHz – D: 56%
SOFT	280 W – 250 Ω 3440 Vpp – CF: 2.5 M: 29 kHz – D: 56%	280 W – 250 Ω 3440 Vpp – CF: 2.5 M: 29 kHz – D: 56%	280 W – 250 Ω 3440 Vpp – CF: 2.5 M: 29 kHz – D: 56%	200 W – 250 Ω 3020 Vpp – CF: 2.5 M: 29 kHz – D: 56%	280 W – 250 Ω 3440 Vpp – CF: 2.5 M: 29 kHz – D: 56%
SPRAY	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%	140 W – 600 Ω 7600 Vpp – CF: 8.1 M: 19 kHz – D: 9%
Argon Coag					SPRAY + ARGON GAS
Bipolar currents	EXCELL 400 MCDSe	EXCELL 350 MCDSe	EXCELL 250 MCDSe	EXCELL 200 MCDSe	EXCELL 400/A MCDSe
PURE	140 W – 300 Ω 790 Vpp – CF: 1.5 M: no – D: no	140 W – 300 Ω 790 Vpp – CF: 1.5 M: no – D: no	140 W – 300 Ω 790 Vpp – CF: 1.5 M: no – D: no	140 W – 300 Ω 790 Vpp – CF: 1.5 M: no – D: no	140 W – 300 Ω 790 Vpp – CF: 1.5 M: no – D: no
BLEND	120 W – 300 Ω 980 Vpp – CF: 1.8 M: 29 kHz – D: 75%	120 W – 300 Ω 980 Vpp – CF: 1.8 M: 29 kHz – D: 75%	120 W – 300 Ω 980 Vpp – CF: 1.8 M: 29 kHz – D: 75%	120 W – 300 Ω 980 Vpp – CF: 1.8 M: 29 kHz – D: 75%	120 W – 300 Ω 980 Vpp – CF: 1.8 M: 29 kHz – D: 75%
MICRO	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no
MICRO AUTO	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 450 Vpp – CF: 1.7 M: no – D: no
MACRO	120 W – 100 Ω 760 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 760 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 760 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 760 Vpp – CF: 1.7 M: no – D: no	120 W – 100 Ω 760 Vpp – CF: 1.7 M: no – D: no

KEY

W: DELIVERED POWER

Ω: NOMINAL LOADS

Vpp: PEAK/NO-LOAD PEAK VOLTAGES

CF: CREST FACTORS

M: MODULATION

D: DUTY CYCLE

GENERAL LIST OF ACCESSORIES

■ REUSABLE NEUTRAL ELECTRODES

- EIP/9 Stainless steel electrode (16x6 cm), 3 m cable
- NP/A Stainless steel electrode (25x12 cm), 3 m cable
- NP/GA Conductive flexible rubber electrode (25x15 cm), 4.5 m cable
- NP/GP Conductive flexible rubber electrode (15x8 cm), 4.5 m cable
- EIP/S Manual neutral electrode, 2 m cable
- FFE Elastic belt for fixing electrodes, with double button, L. 50 cm (*)
- FGE Elastic belt for fixing electrodes, with double button, L. 150 cm (*)



■ DISPOSABLE ADHESIVE NEUTRAL ELECTRODES

- CMS/E Reusable connection cable, 3 m
- CMS/E5 As above, 5 m
- EIP/DA Single section non Split adhesive electrode for adults (25-pc pack) (*)
- EIP/SA As above, Split type with double section (25-pc pack) (*)
- EIP/DP Single section non Split paediatric adhesive electrode (25-pc pack) (*)
- EIP/SP As above, Split type with double section (25-pc pack) (*)

■ HANDLES FOR USE WITH FOOT CONTROLS

- MPE/F Autoclavable handle, 2.5 m cable
- MPE/E Sterilisable electrode holder handle, 3.5 m cable
- MPE/E5 As above, 5 m cable
- MLD/F Needle holder microsurgery handpiece, autoclavable, 2 m cable

■ HANDLES WITH DOUBLE BUTTON MANUAL CONTROLS

- MPE/CMS Electrode holder handle with blade electrode, 3 m cable (100 times sterilisable)
- MPE/CMS5 As above, 5 m cable

■ ACTIVE ELECTRODES stainless steel, insulated stem $\varnothing$ 2.3 ÷ 2.4 mm, sterilisable SHORT TYPE, L. 70 mm

- E1 Blade electrode, straight
- E1/I Blade electrode, straight, all insulated except the last 5 mm
- E3 Blade electrode, angled
- E1/L Lancet electrode, straight
- E3/L As above, angled
- E5 Thick needle electrode, straight
- E6 As above, angled
- E7 Thin needle electrode, straight
- E7/I Thin needle electrode, straight, all insulated except the last 5 mm
- E8 Thin needle electrode, angled
- E10 Ultra-thin needle electrode, 0.40 mm diam.
- E12 Ball electrode, straight, $\varnothing$ 2.5 mm
- E13 As above, angled
- E14 Ball electrode, straight, $\varnothing$ 4 mm
- E15 As above, angled
- E16 Ball electrode, straight, $\varnothing$ 6 mm
- E17 As above, angled
- E18 Loop electrode (diamond-shaped 5x10 mm)
- E19 As above, diamond-shaped 10x10 mm
- E21 Loop electrode (wire, round $\varnothing$ 5 mm)
- E23 As above, $\varnothing$ 10 mm
- E25 As above, $\varnothing$ 15 mm
- E23/N Loop electrode (ribbon, round $\varnothing$ 10 mm)
- E25/N As above, $\varnothing$ 15 mm
- E26 Plate electrode
- EXT/15 Extension l. 15 cm for all electrodes with stem $\varnothing$ 2.3 ÷ 2.4 mm
- LONG TYPE, L. 130 mm
- E40 Blade electrode, straight
- E40/I Blade electrode, straight, all insulated except the last 5 mm
- E41 Thick needle electrode, straight
- E42 Thin needle electrode, straight
- E42/I Thin needle electrode, straight, all insulated except the last 5 mm
- E43 Loop electrode, straight (wire, round $\varnothing$ 5 mm)
- E44 As above, $\varnothing$ 10 mm
- E45 As above, $\varnothing$ 15 mm
- E46 Ball electrode, straight, $\varnothing$ 2.5 mm
- E47 As above, $\varnothing$ 4 mm
- E47/6 As above, $\varnothing$ 6 mm



ELECTRODES FOR GYNECOLOGY L. 130 mm

E48 Round loop electrode, 20x15 mm

E49 As above, 10x7 mm

E50 As above, 10x10 mm

E51 As above, 15x12 mm

E52 As above, 15x10 mm

E53 As above, 20x8 mm

E54 As above, 20x10 mm

E55 As above, 20x20 mm

E56 Square loop electrode, 10x5 mm

E57 As above, 10x8 mm

E58 As above, 10x10 mm

E59 As above, 5x5 mm

ELECTRODES FOR MICROSURGERY, STERILISABLE

MID Needle reducer (for all electrode handles)

SAD Series of 10 needles, Ø 0.10 mm

SAD/1 As above, Ø 0.15 mm

SAD/2 As above, Ø 0.20 mm

SAD/3 As above, Ø 0.40 mm

INSULATED MONOPOLAR FORCEPS FOR COAGULATION, WITHOUT CONNECTION CABLES TO THE EQUIPMENT, STERILISABLE

PIC/1 Straight forceps (Cushing/Potts-Smith) ("grasping" tips 1 mm - L. 18 cm)

PIC/1-25 As above, L. 25 cm

PIC/2 Straight forceps (Cushing/Potts-Smith) ("grasping" tips 2 mm - L. 25 cm)

INSULATED MONOPOLAR FORCEPS FOR COAGULATION, WITH CONNECTION CABLES TO THE EQUIPMENT, STERILISABLE

CPI Connection cable for PMI, L. 3.5 m

CPI/5 As above, L. 5 m

PMI/1 Straight forceps (Cushing/Potts-Smith) ("grasping" tips 1 mm - L. 18 cm)

PMI/1-20 As above, L. 20 cm

PMI/1-25 As above, L. 25 cm

PMI/2 Straight forceps (Cushing/Potts-Smith) ("grasping" tips 2 mm - L. 25 cm)

PMI/B Bayonet forceps (Jansen/Yasargil) ("grasping" tips 2 mm - L. cm. 20 cm)

MONOPOLAR ACCESSORIES FOR LAPAROSCOPY, request specific details.

CONNECTION CABLES FOR MONOPOLAR INSTRUMENTS FOR LAPAROSCOPY

CPE Connection cable for instruments with male or female connector Ø 4 mm, L. 3.5 m

CPE/5 As above, L. 5 m

CABLES FOR FLEXIBLE ENDOSCOPY, request specific details.

CONNECTION CABLES FOR BIPOLAR FORCEPS OR ELECTRODES AND FOR HOOKS, FORCEPS AND BIPOLAR SCISSORS FOR LAPAROSCOPY, STERILISABLE

CPB/E Connection cable, 3 m

CPB/E5 As above, L. 5 m

RIGID BIPOLAR INSULATED CLAMPS AND ELECTRODES, STERILISABLE

Standard forceps for bipolar coagulation

PMC/JR Straight forceps (Jeweler) (straight tips 0.5 mm - L. 11.5/12 cm)

PMC/JC As above, angled tips

PMC/RS Straight forceps (Cushing/Potts-Smith) (straight tips 0.7 mm - L. 15.5 / 16 cm)

PMC/CS As above, angled tips

PMC/R Straight forceps (Cushing/Potts-Smith) (straight tips 1 mm - L. 20 cm)

PMC/C As above, angled tips

PBC/R Straight forceps (Cushing/Potts-Smith) (straight tips 2 mm - L. 20 cm)

PBC/C As above, angled tips

PMC/R25 Straight forceps (Cushing/Potts-Smith) (straight tips 1 mm - L. 25 cm)

PMC/C25 As above, angled tips

PBC/R25 Straight forceps (Cushing/Potts-Smith) (straight tips 2 mm - L. 25 cm)

PBC/C25 As above, angled tips

PMC/RSB Bayonet forceps (Jensen/Yasargil) (straight tips 0.7 mm - L. 16.5 / 17 cm)

PMC/B Bayonet forceps (Jensen/Yasargil) (straight tips 1 mm - L. 20 cm)

PMC/BCD As above, angled tips pointing down

PMC/BCU As above, angled tips pointing up

PBC/B Bayonet forceps (Jensen/Yasargil) (straight tips 2 mm - L. 20 cm)

PBC/BCD As above, angled tips pointing down

PBC/BCU As above, angled tips pointing up

