


COLONOVIDEOSCOPE

# CF-H170L/I

A powerful tool for routine colonoscopy - with HDTV image quality and improved insertability




# **OLYMPUS CF-H170L/I**



#### **Main Features**


# **HDTV** Image Quality

HDTV captures and displays clear images with precise details and accurate colors, helping you to perform more advanced procedures.



### **NBI** (Narrow Band Imaging)

NBI facilitates observation of capillaries and other structures on the mucosal surface. It helps identify suspicious areas.



#### Close Focus

Close focus enables you to obtain an enlarged, close-up image by moving the scope tip as close as 2 mm from the mucosa.

# Variable Stiffness

Variable stiffness helps to avoid re-loop of the endoscope, for example at the sigmoid colon, and also allows the stiffness of the scope to be adjusted on a case-by-case basis in order to meet the unique anatomical needs of each patient or the handling preferences of the physician.

#### Water Jet

This technology removes mucus and debris inside the colon at the press of a button on the scope or the footswitch unit, providing a clear view.

# Waterproof Connector

The newly designed connector is fully submersible and therefore eliminates the need for a water-resistant cap, while minimizing the risk of damage due to accidental immersion.



#### **Specifications**

	Field of view	140°
Optical System	Direction of view	Forward viewing
	Depth of field	2-100 mm
	Distal end outer diameter	12.8 mm
	Distal end enlarged	
	Objective Lens	Up Air/Water Nozzle
Insertion Section	Right	Auxiliary Water Channel Left
	Instrument Channel Outlet	Light-guide Lens
	Down	
	Insertion tube outer diameter 12.8 mm	
	Working length	L: 1680 mm I: 1330 mm

Instrument Channel	Channel inner diameter	3.7 mm
	Minimum visible distance	5.0 mm from the distal end
	Direction from which endotherapy accessories enter and exit the endoscopic image	
High-frequency	Cauterization treatment	Available
Bending Section	Angulation range	Up 180°
		Down 180°
		Right 160°
		Left 160°
Total Length	L: 2005 mm 1: 1655 mm	

Specifications, design and accessories are subject to change without any notice or obligation on the part of the manufacturer.

