

## Table Top Autoclave Class N Series



LCD Display



USB Port



Printer (Optional)



Chamber



Aluminum Tray (Standard)



Stainless Steel Tray (Optional)

### Introduction:

BKM-K18/23N sterilizer series is an N-level sterilizer. It discharges the cold air in the sterilization chamber by gravity displacement, saturates the internal steam, and reaches the set pressure and temperature. To achieve the purpose of sterilizing the items to be sterilized. Suitable for stomatology, ophthalmology, beauty, operating room and other places. It is suitable for sterilization of glassware, bare metal utensils, and unencapsulated solid instruments.

### Features:

- \* High-quality material: The sterilization chamber is made of high-quality S30408 stainless steel electropolished.
- \* Steam generation method: The main body is heated, no external steam source is required.
- \* Operation interface: 3.5-inch capacitive color display screen is used to display pressure, temperature, time, alarm code and other information in real time, which is convenient for users to observe. When the sterilization cycle is over, a buzzer will sound.
- \* Sterilization record: Standard USB interface, optional printer, record program data.
- \* New storage rack: Increase the utilization space of the sterilization chamber, and the selection space for sterilization load is larger.
- \* Control system: controlled by single chip microcomputer, automatic control of heating, sterilization and exhaust, without too much manual operation.
- \* One-key start on the operation panel, using mechanical keys, the number of actions  $\geq 100,000$  times.

### Safety Protection:

Over-temperature automatic protection, heating tube anti-dry protection, safety interlock device, double over-voltage protection, over-current leakage safety protection, door detection protection.

### Technical Parameters:

Model	BKM-K18N	BKM-K23N
Capacity	18L	23L
Door	Manual	
Designed Pressure	0.28Mpa	
Working Pressure	0.23Mpa	
Working Temp.	121/134°C	
Chamber Material	S30408	
Power Supply	AC220±10%, 50/60Hz (Standard); 110V, 60Hz (Optional)	
Consumption	1.8KW	
Altitude	≤2500m	
Chamber Size(φ*L)	φ250*350mm	φ250*450mm
Standard Accessories	Tray, USB port	
Optional Accessories	Printer	
External Size(W*D*H)	650*495*410mm	700*495*410mm
Package Size(W*D*H)	810*610*590mm	
Net Weight(kg)	32	36
Gross Weight(kg)	47	50