



'MADAM CORINNE " ULTRA PAD - CERTIFICATE OF ANALYSIS

NAME OF MANUFACTURER	: ARKAN GRUP SAGLIK URUNLERI A.S.
COUNTRY OF MANUFACTURE	: TURKEY
NAME OF PRODUCT	'MADAM CORINNE " ULTRA NIGHT 6x48
PIECES OF PACK	: 6
SIZE	:NIGHT
DATE OF PRODUCTION	: 26.12.2020
EXPIRATION DATE	: 26.12.2025
LOT NO	: U-6
THE AMOUNT OF SAMPLE FOR TESTING	: 10 PACKAGE
DATE OF QUALITY TEST	: 26.12.2020
LABORATORY NAME	: BABY DIAPER and SANITARY PAD - QUALITY CONTROL LABORATORY

CERTIFICATE OF ANALYSES

As a result of the below analysis, it has been seen that "MADAM CORINNE " NIGHT Ultra Pads doesn't contain any harmful substance to human health and this product is produced following row materials.

1- Airlaid (Contain SAP)	3- Hot Melt	5- Perforated Polyethylene	7-Ink	9-Hydrophilic Transfer Layer
2- Closing Tape	4- Polyethylene	6-Silicon Paper	8-Single Wrap	

RESULT OF ANALYSES

	TARGET	AVERAGE	TEST RESULT MAX.	TEST RESULT MIN.
PAD GRAMAJ	6,65 (±1 gr)	6,65 gr	7,34 gr	6,59 gr
SANITARY PAD DIAMETER	165 (± 5 mm)	165 mm	166 mm	160 mm
SANITARY PAD LENGHT	310 (± 5 mm)	310 mm	315 mm	305 mm

RESULT OF ANALYSES

TEST PARAMETERS	ACCEPTANCE LIMITS	RESULT
Classification	All materials used in the sanitary pad manufacture shall have no harmful effect during normal use.	Approved
	shall be made of an absorbent material which gives a feeling of comfort during use.	Approved
Filling	shall be free of protrusions, oil spots, dirty, or any other foreign matter, and shall have no harmful effect.	Approved
	shall be arranged in a way to allow the distribution of menstrual flow in the absorbent material, and prevent it from leaking to any side.	Approved
Porous fabric	This fabric, if present shall be placed between the filling and outer layer.	Approved
Base layer	Shall be a thin layer of plastic or any other leak-proof material that is placed at the back side of the pad.	Approved
Adhesive tapes	One or several lines of adhesive substances shall be made on the back of the pad to secure it in place on the underwear when used. The adhesive shall be covered with a protective cover.	Approved
	The adhesive shall leave no traces on clothes when the pad is removed.	Approved
ABSORBENCY (LIQUID)	Overall absorbency shall not be less than 30 ml /pad	39 ml
ABSORPTION TIME	≤15 seconds	5 seconds
PH	Ph shall vary between 5,5 and 9,5 according to International Standart ISO 6588-1	6,5
Absorbency Capacity (ml)	No Leakage	39 ml
ANAEROBIC/AEOROBIC BACTERIA COUNT(cfu/mg)	≤10 cfu/mg	Absent
STAOHYLOCOCCUS AUREUS(cfu/mg)	Not Found	Absent
CANDIDA ALBICANS(cfu/mg)	Not Found	Absent
PSEUDOMONAS AUREGINOSA(cfu/mg)	Not Found	Absent
E-COLI(cfu/mg)	Not Found	Absent

ARKAN GRUP SAGLIK URUNLERI A.S.
QUALITY CONTROL DEPARTMENT