

# Vertical autoclaves without drying

## Accessories

### PREMIUM CASTERS (2 WITH BRAKES)



- Although all AES Series autoclaves include casters, this accessory offers the option of upgrading them with a more resistant and higher quality casters that include brakes.
  - Enables an easier movement of the equipment between different locations.
  - Must be installed in our facilities.
- Reference: **4WHBR**

### TRANSPORT TROLLEY



- Auxiliary trolley to assist the loading and unloading of the autoclave.
  - Built in chromed iron and plastic.
  - The surface of each shelf is textured to prevent the load from shifting.
  - Rubber coated wheels to reduce noise.
  - Dimensions (LxDxH): 730 x 490 x 700 mm.
- Reference: **TR-TR**

### CONDENSATES BOTTLE



- 12L bottle with tap to collect condensates during purge phase and also to collect water while cleaning the sterilization chamber. Useful in situations where no easy drainage is available.
- Reference: **TANK-AE**

### CABLE GLANDS




- Installation of up to 8 cable glands within the sterilization chamber walls to enable external temperature probe access in multiple locations for autoclave calibration and validation procedures.
  - These ports can either be of 2 or 4 mm of diameter.
- References:  
**PRENSACLAV** (8 holes  $\varnothing$  2mm),  
**PRENSACLAV2** (8 holes  $\varnothing$  4mm).

### SW7000 SOFTWARE



- Communication software between the equipment and the PC that allows the real-time and posterior visualization and registry of each cycle. Cycles can also be exported to Excel or printed.
  - Connection to PC via RS-232.
  - Supplied with a RS-232 cable, an USB stick that includes the software and installation drivers and a RS-232 to USB adapter.
- Reference: **SW7000**

### STERILIZATION CONTROL TAPE



**20 min 121°C**  
Color change.

- Class 1 indicator for steam sterilization. The change of color indicates that the materials have been processed, without being a guarantee of proper sterilization, additional methods are needed such as biological indicators (EN ISO 11138).
  - Tape roll of 50 m x 19 mm.
- Reference: **TEST-CT**