



Variable speed drives

Altivar Process for Cabinet Integration

Quick access to product information

Get technical information about your product

References

Modicon TM3
I/O expansion modules for Modicon controllers
Analog I/O modules

Reference	Modicon analog input modules	Number of channels	Input range	Output range	Resolution	Input terminal	Reference	Weight (g)
TM3A0X	2 analog inputs	-10...+10VDC	-10...+10VDC	-10...+10VDC	16 bits or sign	1.0501.2	TM3A0X	0.190
TM3A0M	2 analog inputs	-2...+20mA	-2...+20mA	-2...+20mA	16 bits or sign	1.0501.2	TM3A0M	0.200
TM3A1X	4 analog inputs	-10...+10VDC	-10...+10VDC	-10...+10VDC	16 bits or sign	1.0501.15	TM3A1X	0.200
TM3A1M	4 analog inputs	-2...+20mA	-2...+20mA	-2...+20mA	16 bits or sign	1.0501.15	TM3A1M	0.200
TM3A2X	4 analog or temperature inputs	(A, K, J, S, T, N, E, C)	-10...+10VDC	-10...+10VDC	16 bits or sign	1.0501.15	TM3A2X	0.200
TM3A2M	4 analog or temperature inputs	(A, K, J, S, T, N, E, C)	-2...+10VDC	-2...+10VDC	16 bits or sign	1.0501.15	TM3A2M	0.200
TM3D1X	4 differential temperature inputs	(J, K, R, S, B, T, N, E, C)	-10...+10VDC	-10...+10VDC	16 bits or sign	1.0501.15	TM3D1X	0.200
TM3D1M	4 differential temperature inputs	(J, K, R, S, B, T, N, E, C)	-10...+10VDC	-10...+10VDC	16 bits or sign	1.0501.15	TM3D1M	0.200
TM3A3X	8 thermocouple inputs	-10...+10VDC	-10...+10VDC	-10...+10VDC	12 bits or sign	1.0501.15	TM3A3X	0.190

Each commercial reference presented in a catalog contains a hyperlink. Click on it to obtain the technical information of the product:

- Characteristics, Dimensions and drawings, Mounting and clearance, Connections and schemas, Performance curves
- Product image, Instruction sheet, User guide, Product certifications, End of life manual

The screenshot shows a detailed product page for the TM3A12H module. It features a main product image, a table of technical characteristics, and sections for 'Related Software' and 'Product Datasheet', 'User guide', 'Catalogue', and 'CAD Document'.

Find your catalog

The screenshot displays the Digi-Cat Online platform, which allows users to search for and browse through various industrial automation components and libraries.

- With just 3 clicks, you can access the Industrial Automation and Control catalogs, in both English and French
- Consult digital automation catalogs at [Digi-Cat Online](#)

The screenshot shows the General Catalog interface, specifically the Industrial Automation section. It includes a search bar and a list of product categories such as Pneumatics, Hydraulics, Power Supplies, Drives, Cables & Interfaces, Signaling Devices, HMI Terminals and Industrial PCs, Sensors & RFID System, Motor Starters and Load Management, Components for Motor Starters, Variable Speed Drives & Soft Starters, Motor Control & Robotics, and Interface, Measurement & Control Relays.

- Up-to-date catalogs
- Embedded product selectors, 360° pictures
- Optimized search by commercial references

Select your training



- Find the right [Training](#) for your needs on our Global website
- Locate the training center with the selector tool, using this [link](#)

The screenshot shows the 'Training and courses' section of the Schneider Electric website. It includes a search bar and a grid of course categories such as Electrical Installation and Safety, Data Center, and Industrial Automation.

Life Is On

Schneider
Electric



Altivar

Discover Altivar

Variable speed drives and soft starters

Altivar variable speed drives and soft starters deliver top performance in motor control applications across machines, processes, and buildings. With built-in intelligence, these smart connected devices gather and share data to improve operational efficiency, safety, and reliability.

Explore our offer

- [Altivar Process](#)
- [Altivar Machine](#)
- [Altivar Building](#)
- [Altivar Soft Starters](#)

Life Is On

Schneider
Electric

Green Premium™

Enhance sustainability with Altivar™ Process drives

Superior environmental performance thanks to upgradability and modernization solutions.

Altivar Process is **RoHS** and **REACH** compliant

- Transparent environment information
- Life Cycle Analysis, compliant with ISO14025
- Circular instructions

Altivar Process drives brings key benefits to our end users in achieving **superior sustainable performance** by enhancing its functionality, performance of capacity, for both, hardware and software.

The **additional hardware options** and the **firmware upgradability** capabilities of the Altivar process help our customers to maximize the process continuity and operation, as well as reducing the operational expenses, by avoiding the change of their drive or the modification of the existing installation, as a retrofit.

Benefits

- Maximize **process continuity and operation**
- Reduce your **OPEX**
- Easy **scalability** of your Automation system
- **Future-ready** solution for **Industry 4.0**
- Improve **power quality** of your system with a low investment
- Improve the **safety, integration, and performance** of your application
- Optimize your **maintenance cost** and the **Drives Lifetime**



 **Green Premium™**

Sustainable
performance,
by design



Experience the difference today at
se.com/green-premium

Communication & Wi Fi Modules

The additional communication modules allow our customers to easily integrate Altivar Process drives in their scalable Automation system. Together with the Wi Fi access point, brings easy access to the real data provided by the drive, helping the digitalization and the easy integration of the drive in the Industry 4.0 technologies.

Passive Filters*

The optional passive filter of the Altivar Process brings to customers the possibility to improve their installation's power quality by reducing the harmonics levels, even keeping their existing drives installed.

Additional I/O & Safety modules*

The additional I/O and the safety modules help our customers to extend the performance and integration of their application, enhancing at the same time the operators' and machines' safeness.

Firmware Update & Service expertise

Thanks to our global network of service experts, our customers have the possibility of upgrading the Drive's firmware and modernizing its hardware to extend the Drives lifetime.

* For more information regarding the compatibility of these options, please visit us in se.com/drives

Contents

■ General presentation.....	page 2
Altivar Process Modular drives for cabinet integration selection guide.....	
■ Altivar Process variable speed drives presentation	page 6
■ Altivar Process Modular offer structure	
□ Presentation	page 10
□ Description	page 18
■ Altivar Process Modular variable speed drives	
■ Sub-assemblies and accessories	
□ Power modules.....	page 23
□ Control units	page 24
□ Housings	page 25
□ Control cables.....	page 26
□ Power busbar kits	page 27
□ Fuses.....	page 28
□ Mechanical mounting kits	page 29
□ Additional modules for liquid-cooled drives.....	page 30
□ Braking modules.....	page 31
□ Control units for braking unit	page 32
■ Options.....	page 33
■ Drives for cabinet integration	
□ Presentation	page 34
□ Architectures	page 35
□ 400...480 V 50/60 Hz supply Standard drives	page 36
□ 500...690 V 50/60 Hz supply Standard drives	page 37
□ 400...480 V 50/60 Hz supply Low Harmonic/Regen drives	page 38
□ 500...690 V 50/60 Hz supply Low Harmonic/Regen drives	page 39
□ 400...480 V 50/60 Hz supply Standard Liquid-cooled drives	page 40
□ 500...690 V 50/60 Hz supply Standard Liquid-cooled drives	page 41
□ Braking unit references.....	page 42
□ Combinations	page 43
■ Motor starters	
□ Applications	page 44
□ Combinations	page 45
■ Services	
■ A whole world of services for your drives.....	page 46
■ Index	
■ Product reference index.....	page 47

Variable speed drives

Altivar Process

Business optimization, process efficiency

Altivar Process

Provides the efficiency you deserve

Altivar Process is the new comprehensive range of variable speed drives from Schneider Electric, covering the majority of industrial applications with two series:

- > ATV600: drives focused on fluid management and processing and energy saving
- > ATV900: drives focused on maximum productivity with exceptional motor control and connectivity

Depending on customer requirements, Altivar Process drives are available as wall-mounting, floor-standing, and optimized solutions for integration in cabinets.



Wall-mounting drives
from 0.75 kW up to 315 kW
(1...500 HP)




Enclosed drive solutions
from 0.75 kW up to 2,600 kW
(1...2,600 HP)




Drives for cabinet integration
from 0.75 kW up to 2,600 kW
(1...2,600 HP)

Altivar Process range



Pump monitoring display



«Stop & go» function



Calculate your level of energy efficiency
with the Altivar Efficiency Calculator

Business optimization

Optimum monitoring of your process

- > Instant reaction if pump efficiency drops thanks to embedded pump monitoring
- > Notification of critical operating points without additional sensors
- > Process integration with pressure, flow, and level control including compensation of flow losses

Energy-saving drive solution

- > Up to 30% energy saving when on standby due to the innovative "Stop & Go" operation without additional costs
- > Smart control of the internal fans depending on operation
- > Optimum energy efficiency over the whole life cycle
- > Data logging and graphic display of the power consumption

Process efficiency

Motor performance and connectivity

- > Excellent motor performance on any type of motor
- > Ethernet dual port offers maximum services such as connection to the control room and process transparency
- > Network service helps ensure operation continuity even in case of connection breakdown
- > Web server and data logging help to reduce downtime through fast troubleshooting and preventive maintenance

Altivar Efficiency Calculator

This tool calculates the level of energy efficiency of your variable speed drive according to the Ecodesign standard EN/IEC 61800-9-2.

> Drive Efficiency (CDM Complete Drive Module)

Drive performance is determined according to 8 operating points considering torque and speed

> System Efficiency (PDS Power Drive System)

System performance is determined according to 8 operating points considering torque and speed. This includes the efficiency of the variable speed drive and its motor.



Saving energy with variable speed drives



Achilles™ Level2 certified



ODVA organization:
Supports network
technologies based on
EtherNet/IP



FDT Technology:
A widely-accepted
international standard in
the automation industry

Real-time intelligence

Web server and services via Ethernet


- Embedded Web server interface based on the Ethernet network gives you process monitoring with your daily working tools.
- Local and remote access to energy use and customized dashboards means your energy is visible anywhere, any time, on PC, tablet, or smartphone.

User-friendliness

Simple integration in controller environments

- Easy integration thanks to standardized FDT/DTM and ODVA technology
- Supported by predefined EcoStruxure Control Expert libraries
- Easy access via PC, tablet, or smartphone
- Secure connection via “cyber-secure Ethernet”

EcoStruxure for Industry



Scanning the QR code from a smartphone or tablet



Instant access to online help

Sophisticated service concept

- Modular design provides easy spare parts logistics
- Optimized maintenance costs due to dynamic maintenance schedule, with integrated monitoring of individual components
- Simple exchange of power modules and fans
- Quick assistance with dynamic QR codes and Customer Care app

Green product

Designed to have a smaller carbon footprint

- The Green Premium product label, Schneider Electric's eco-mark, indicates your compliance with international environmental standards such as:
 - RoHS according to European Directive 2011/65 and the delegated Directive (EU) 2015/863
 - REACH according to EU regulation 1907/2006
 - IEC 62635: The end-of-life instructions comply with the latest recycling rules, up to 85% of the product components can be recycled.

(1) The Schneider Electric industrial software business and AVEVA have merged to trade as AVEVA Group plc, a UK listed company. The Schneider Electric and Life is On trademarks are owned by Schneider Electric and are being licensed to AVEVA by Schneider Electric.



Best-in-class service concept



Variable speed drives

Altivar Process Modular

Modularity

Consolidate a powerful range

The Altivar Process Modular offer is designed for easy and cost-effective integration of power-intensive drives into cabinets. From a few number of standard components it is possible to build a large range of air- and liquid cooled drives from 75 up to 2600 kW (125 up to 2,600 HP) in different integration types.


Customers using our Altivar Process Modular offer benefit from all the advanced features of service-oriented Altivar Process ATV600 and ATV900 drives developed for industrial applications such as water & wastewater, mining, minerals & metals, oil & gas, and consumer packaged goods (CPG).

- > ATV600 drives focused on fluid management and processing and energy saving
- > ATV900 drives focused on maximum productivity with exceptional motor control and connectivity

Modularity

Get more than just a drive with the Altivar Process Modular offer:

- > Standardized and cost-efficient integration
- > Flexibility in cabinet design such as protection rating and incoming supply equipment
- > Prewired, tested electric core components
- > Integrated category C3 EMC filter
- > Reduced harmonics with integrated line choke for Standard drives and less than 3% THDi for Low Harmonic/Regen drives
- > Integrated high-efficiency motor filter reducing the risk of motor winding insulation aging and motor damage even for longer motor cables
- > Ready-to-connect line supply terminals on top and motor terminals at the bottom
- > Reduced downtime of assets thanks to easily changeable electric core components such as power module with wheel (for Standard/Reduced Height drives) and power fan (for Low Harmonic/Regen, Standard and Reduced Height drives) inside a drawer accessible from the front face



Standardized integrated cabinet design



Easy and standardized cabinet integration



Cost-saving solution due to standardization and local production

Cabinet integration

Standardization of integration design for ATV600 and ATV900 solutions

- ATV600 and ATV900 drive solutions by simply changing the control unit
- Larger application scope with power rating through module paralleling up to 1800 kW/2500 HP at 400 V supply voltage and up to 2,600 kW/2,600 HP at 690 V supply voltage
- Reduced engineering workload thanks to standardization
- Optimized supply chain with standard sub-assembly and kits available ex stock



Local production

- Assembly of Modular drive architectures on sites of qualified partners belonging to Schneider Electric network
- Altivar Process Modular partners have access to dedicated selection tools, drawings, EPLAN macros, integration manuals, videos, and training material
- Options and accessories may be supplied by Schneider Electric or manufactured locally

Fast construction of power connections and control cabling

Main benefits

- Cost-saving solution with reduced integration workload (lighter and less space-consuming) and simplified purchasing (optimized number of parts covering all architectures)
- Reduce lead time to end users thanks to standardized integration design and simple adaptation as per application requirement
- Enlarge your business scope thanks to simple maintenance of the Altivar Process Modular offer



Compact compared with a standard product

Variable speed drives

Altivar Process Modular
Drives for cabinet integration

Market segments	<ul style="list-style-type: none"> ■ Water & wastewater ■ Oil & gas ■ Mining, minerals & metals ■ Consumer packaged goods (CPG) 				
			<ul style="list-style-type: none"> ■ Water & wastewater ■ Oil & gas ■ Mining, minerals & metals 		
Mounting type	Cabinet integration				
Drive type	Drive products for cabinet integration	Modular Standard drives	Modular Low Harmonic/Regen drives	Modular Liquid-cooled drives	
Degree of protection		IP20	IP00		
Power range for 50...60 Hz line supply	Three phase: 380...480 V (kW/HP) Three-phase: 400 V (kW) Three-phase: 440 V (kW) Three-phase: 480 V (HP) Three-phase: 500 (kW) Three-phase: 600 (HP) Three-phase: 690 (kW)	0.75...90/1...120 – – – – – – –	– 110...1000 110...1000 150...1400 75...800 125...1200 110...1200	– 110...1800 110...1800 150...2500 110...1900 150...2600 160...2600	
Drive	Output frequency	Standard constant torque, variable standard torque, optimized torque mode			
	Control type	Asynchronous motor			
		Synchronous motor			
Functions	Advanced functions				
	Including all the advanced features of ATV600 drives: <ul style="list-style-type: none"> ■ Accurate measurement for monitoring system energy consumption (deviation < 5%) ■ Installation energy drift detection ■ Embedded Ethernet with direct access to system configuration and monitoring ■ Integration of actual pump curves to optimize the system operating point ■ Optimized pump monitoring based on actual operating point ■ Sensorless estimated flow rate ■ Measurements expressed in working units (e.g. m³/h, kWh/m³) ■ Limitation of overvoltage at the motor terminals ■ Contextual access to technical documentation through dynamic QR code ■ Continuous and historical real-time measurements with customizable dashboards ■ Predictive and preventive maintenance tracking functions (e.g. temperatures with PT100/1000 probe, fan monitoring) ■ Easy setting of drive identification for Altivar Process Modular drives 				
	1: STO (Safe Torque Off) SIL3				
	16				
Number of integrated I/O	Analog inputs Digital inputs Digital output Analog outputs Relay outputs Safety function inputs				
	3: Configurable as voltage (0...10 V) or current (0-20 mA/4-20 mA), 2 of them including probes (PTC, PT100, PT1000, or KTY84)				
	6: Voltage 24 V ... (positive or negative logic)				
	–				
	2: Configurable as voltage (0...10 V) or current (0-20 mA)				
	3: 1 with NO/NC contacts and 2 with NO contacts				
	2: For safety function STO				
Extended I/O module (optional)	Analog inputs Digital inputs Digital outputs				
	2 differential analog inputs configurable via software as voltage (0...±10 V) or current (0-20 mA/4-20 mA), or for PTC, PT100, or PT1000 2- or 3-wire probes				
	6: Voltage 24 V ... (positive or negative logic)				
	2: Assignable				
Extended relay module (optional)	Relay outputs				
	3: NO contacts				
Communication	Integrated Option modules				
	Modbus/TCP, Modbus serial link				
	Ethernet/IP, Modbus TCP and MD-Link dual port, CANopen daisy chain, SUB-D, and screw terminal block, PROFINET, PROFIBUS DP V1, DeviceNet, BACnet MS/TP, POWERLINK				
Configuration and runtime tools	Graphic display terminal, embedded Web server, DTM (Device Type Manager), SoMove software				
Standards and certifications	86/188/EEC, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, EN/IEC 61800-3, EN/IEC 61800-5-1, IEC 61000-3-12, IEC 60721-3, IEC 61508, IEC 13849-1, TÜV certification, CE marking, ATEX 2/22, ATEX 1/21			86/188/EEC, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, EN/IEC 61800-3, EN/IEC 61800-5-1, IEC 60721-3, IEC 13849-1, TÜV certification, CE marking, cULus, IEC 61508, Marine certification (DNV-GL, ABS, RINA, BV, LR) (1), ATEX 2/22, ATEX 1/21,	
References	ATV630•••N4Z	ATV6A0•••••	ATV6B0•••••	ATV6L0•••••	
Page	–	36	48	60	

(1) For marine product certificate, please contact your Schneider Electric representative.

More technical information on www.se.comMore technical information on www.se.com

Variable speed drives

Altivar Process Modular Drives for cabinet integration

(1) For marine product certificate, please contact your Schneider Electric representative.



More technical information on www.se.com



More technical information on www.se.com




Altivar Process Modular range

Process

Altivar Process drives are specifically designed to meet the requirements of the following market segments:

- Water & wastewater
- Oil & gas
- Mining, minerals & metals
- Consumer packaged goods (CPG)



Altivar Process in EcoStruxure Foxboro DCS architecture



Water & wastewater applications

- Pumping
- Drilling
- Suction
- Dosing
- Odor control
- Ventilation
- Gas compression
- Treatment plant
- Wastewater treatment
- Sludge removal

Use

- Pumping station and storage tank
- Irrigation
- Treatment plant
- Desalination plant
- Storage and booster station
- Housing
- Wastewater lift station
- Wastewater treatment
- Discharge back into the environment, land application
- Decanter



Process (continued)

Oil & gas applications

- Hydrocarbon production:
- Drilling
- Offshore and onshore extraction
- Water treatment and re-injection
- Crude oil storage
- Separation
- Pipeline pumping
- Storage
- Refining
- DOF (digital oil field)

Use

- Pumps:
- Submersible
- Hydraulic
- Pipeline
- Reverse flow
- Water injection
- Kerosene
- PCP (progressive cavity pump)
- ESP (electrical submersible pump)
- Rod pump
- Mud pump
- Rotary table, top drive
- Draw works
- Regasification compressors
- Refining:
- Fans
- Compressors



Mining, minerals & metals applications

- Flotation and thickening
- Rinsing and filtration
- Mine shaft pumping
- Preheater fan
- Waste gas evacuation
- Cooling fan
- Separator for vertical roller mill
- Storage and loading
- Water supply
- Pumping
- Drying fans
- Open-pit or underground mining
- Stockpiling/homogenization
- Concentration/mineral separation
- Solid-liquid separation
- Final handling/transport
- Clinker production
- Cement production

Use


- Conveyors
- Grinders
- Mixers
- Pumps
- Tunnel boring machines
- Long-distance heavy conveying
- Bucket wheel excavator
- Special cranes:
- Gantry cranes
- Grab cranes
- Grinding mills (ball mills, SAG and AG mills)
- Spiral and magnetic separators
- Reclaimers and stackers
- Ship loaders
- Mobile mining machines
- Vibro feeders
- Crushers
- Long belt conveyors
- Kiln main drives
- Separators for VRM (vertical roller mills)

Variable speed drives

Altivar Process Modular



Modular drive architecture with 2 power modules from 200 kW to 315 kW on 400 V supply



IP21/UL Type1 integration with a common cooling air flow

Process (continued)

Consumer packaged goods (CPG) applications

- Pumping
- Drying fans
- Dairy beverage
- Agribusiness

Use

- Conveyors
- Mixers
- Centrifuges
- Pumps
- Extruders
- Shredders
- Centrifuges
- Hot rotary dryers

General presentation of the offer

Altivar Process drives can help improve equipment performance and reduce operating costs by optimizing energy consumption and user comfort.

Altivar Process drives provide a wide range of integrated functions, such as:

- Safety and automation functions that meet the requirements of some of the most demanding applications
- Various optional communication modules available for seamless integration into the main automation architectures
- Numerous configurable I/O as standard to facilitate adaptation to specific applications
- Intuitive commissioning using the graphic display terminal and SoMove commissioning software
- Local and remote access and monitoring using the embedded Web server
- Energy savings and protection of the grid by means of integrated harmonic filters
- Installation EMC conformity by means of integrated EMC filters

Altivar Process Modular drives are designed for IT systems.

Modular drive


Altivar Process Modular is ready to build into cabinets to create high-power drive solutions with minimum dimensions that withstand harsh environments.

Altivar Process Modular brings a new approach with sub-assemblies to build drives locally:

- A power module section to be combined in different drive architectures. Each architecture covers several drive power ranges, set at the discretion of the integrator by using SoMove commissioning software
- Control units that make the drive family differentiation of the power architecture between ATV600 and ATV900 families
- Optional kits and accessories that can be supplied by Schneider Electric or manufactured locally
- Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets
- Liquid-cooled modules to create high-power drive solutions that withstand harsh environments

Altivar Process Modular drives are designed to operate on IT and corner-grounded (1) systems.

Altivar Process Modular drives can also be supplied as Engineered Drive System variants from 75 to 2600 kW (125...2600 HP), developed by Schneider Electric based on customer specifications. For more information, please contact your Schneider Electric supplier.



IP54/UL Type 12 integration with a separate cooling air flow

General presentation of the offer (continued)

Cabinet integration (air-cooled)


Altivar Process Modular brings flexible solutions for special integration constraints as well as standard integration in 2 m/6.56 ft height and 600 mm/23.62 in. depth cabinets with IP21 (UL Type 1)/IP54 (UL Type 12) protection rating.

The Altivar Process Modular drives offer consists of:

- Drive power and control modules
- Semiconductor protection fuses
- Line chokes to limit THDi levels for the Standard version and less than 3% THDi for the Low Harmonic/Regen version
- A filter to help protect the motor against the effects of dv/dt
- Accessible terminals to simplify the motor wiring and power wiring

IP21 (UL Type 1) integration type creates a common cooling air flow for the power and control sections.

The IP54 (UL Type 12) integration mechanical kit introduces a system for separating the cooling air flow between the power and control sections, allowing operation in a highly polluted environment as well as optimum management of thermal stress in the plant room.



IP23 air-cooled design with internal liquid/air heat exchanger

IP23 with external air heat exchanger


Cabinet integration (liquid-cooled)

Altivar Process liquid-cooled drives for cabinet integration offer a modular high-power solution for installation in cabinets and separate enclosures. Thanks to the optimized liquid cooling concept, these drives are suitable for operation in a very harsh environment.

The integrated liquid cooling allows optimal dissipation of the heat losses and therefore optimizes the encapsulation of the whole drive unit. Its robust design meets the requirements for applications in harsh environments and provides protection up to IP66.

Ideally suited to customer needs with flexible cooling concepts:

- Air-cooled drive with internal liquid/air heat exchanger
- Air-cooled drive with external liquid/air heat exchanger to dissipate the heat losses out of the operating room
- Liquid-cooled drive with liquid/liquid heat exchanger, encapsulated solution for harsh environment and "low noise" requirements



Up to IP66 with liquid/liquid heat exchanger

Optimized cabinet design

Altivar Process Modular liquid-cooled drives bring flexible solutions for special integration constraints with a 6- or 12-pulse supply and robust design with two offers:

- **Universal:** Suitable for all kind of grids with integrated mains choke (THDi ≤ 48% at 6-pulse or THDi ≤ 9% at 12-pulse supply at 80 to 100% load)
- **Compact:** Optimized with dedicated transformer for most compact dimensions


(1) Only Standard Modular drives for 380...480 V supply are compatible with corner-grounded systems.

Variable speed drives


Altivar Process Modular



Low Harmonic/Regen drive architecture with 2 power modules



2-level technology



3-level technology



Braking unit module

General presentation of the offer (continued)

Low Harmonic/Regen drives

The Low Harmonic/Regenerative drives are used when drives need to generate particularly low harmonics on the mains.

In addition, Low Harmonic/Regen drives are capable of feeding energy back to the mains, enabling a 4Q operation and improving overall application efficiency.

In comparison with commonly-used 2-level AFE (active front end) architectures, the 3-level technology of Altivar Process Modular Low Harmonic/Regen drives allows this new technology to reach a total distortion factor (THDi) of around 2% and thus fulfills the requirements of standard IEEE 519 for a THDi < 5% in case of distorted mains. Additionally, the $\cos \Phi \approx 1$ in each load situation (from 30 % Pn) helps to reduce the line supply load.

The Low Harmonic/Regen drives range is an optimum solution for energy efficiency and process optimization.

Device features

Enhanced motor service life due to the 3-level concept

The 3-level AIC (active infeed converter) technology reduces the voltage load at the motor significantly, compared with other low harmonic frequency inverters. The fluctuating adaptation of the DC link voltage helps to extend the motor service life.

Reduced losses due to the 3-level concept

In comparison with the traditional circuit structure of active mains rectifiers, the switching frequency is increased and the current load is reduced at the same time when using 3-level technology.

Compact dimensions due to the 3-level concept

A significant advantage of the 3-level technology is the reduced size of the integrated filter. Due to the increased switching frequency and its location inside the forced cooling air channel, the dimensions of the filter can be almost halved.

Braking units

Same integration process as standard power module

Braking units and standard power modules have the same frame and size. They use the same integration kits and DC bus bar kits.

Compliant with Standard and Low Harmonic/Regen drives

Braking units can be built for APM Standard drives, APM Reduced Height drives and Low Harmonic/Regen APM drives with an ATV900 control unit.

Compliant with any APM integration type

- Standard integration in 2 m/6.56 ft high cabinets
- Reduced Height integration in 1.6 m/5.25 ft high cabinets
- IP21/UL Type 1 with a common cooling air flow
- IP54/UL Type 12 with a separate cooling air flow

Advanced functions with ATV900

- With Standard drives:
 - Full braking torque also in overload range
 - Shortening and monitoring of deceleration time, such as for long travel application
 - Temporary regenerative load, such as for hoist applications
- With Low Harmonic/Regen drives:
 - Braking operation when Energy regeneration is not possible

Variable speed drives

Altivar Process Modular

The screenshot shows the Schneider Electric Panel Builder - Selection tool interface. At the top, it says "Panel Builder - Selection tool" and "Life is On". The "Drive selection" section shows the following parameters:

- Select Drive type: ATV 600
- Voltage: 440 V
- Typical motor rating Pn (N/D/HO): 160/132 kW
- Integration IP rating: IP 54

Below this, it says "Selected Drive: ATV6A0C16R4". The main area displays a table titled "Bill of Material (BOM)" with columns for Item, Description, Quantity, and Part Number. The table includes rows for various components like Power modules, Control units, and Mechanical accessories.

Selection tool for Altivar Process Modular

General presentation of the offer (continued)

Selection tool for Altivar Process Modular

The Selection tool is an intuitive guide for defining the parts list and specification list to build Altivar Process Modular drives.


It is used to:

- Design the correct Modular drive architecture according to the application needs by simply choosing the drive type, protection rating, cabinet type and supplier, supply voltage, and power rating
- Obtain the parts list containing the power modules, control units, mechanical accessories, options, and specifications and their required quantity
- Customize the parts list with project details and additional materials

The tool is accessible to registered partners of Altivar Process Modular through the download area of [mySchneider partner portal](#).

Altivar Process Modular

Drive Integration Partner Program




Altivar Process Modular Partner Program

The Altivar Process Modular offer is dedicated to partners building ATV600 and ATV900 high-power drive solutions.

This offer enhances our partners as they are able to:

- Build customized panels and high-power drive solutions by paralleling drive modules up to 1800 kW (2500 HP) in 380...480 V supply voltage and 2600 kW (2600 HP) in 500...690 V supply voltage
- Assemble the final drive and perform panel integration
- Benefit from the standardized way of drive integration using the modular concept
- Perform the final power setting and drive registration
- Order/produce mechanical options for integration locally
- Access the download area of the partner portal and find all the relevant technical documents, including mechanical specifications
- Access service training material for commissioning, assembly, and after-sales services
- Become a Schneider Electric recognized trained and registered drive integration partner




Altivar Process drive THDI

Rugged

Altivar Process Modular drives are designed to adapt to the harshest environments.

- Ambient operating temperature
- Temperature without derating:
-10...40 °C/14...104 °F for Altivar Process Modular Standard (air- and liquid-cooled)
-5...40 °C/23...104 °F for Altivar Process Modular Low Harmonic/Regen
- Temperature with derating of output power: < 50 °C/< 122 °F
- Relative humidity without condensing: 5...95%
- Storage and transport temperature: -40...+70 °C/-40...+158 °F
- Operating altitude:
0...1,000 m/0...3,300 ft without derating
1,000...4,800 m/3,300...15,740 ft with derating of 1% per 100 m/330 ft
- Withstand to harsh environments:
□ Chemical class 3C3 conforming to IEC/EN 60721-3-3
□ Mechanical class 3S3 conforming to IEC/EN 60721-3-3
□ Climatic class 3K3 conforming to IEC/EN 60721-3-3
□ Printed circuit boards with protective coating
□ IP00 to integrate in an enclosure



"Stop & go" function

General presentation of the offer (continued)

Energy

Altivar Process drives help to optimize power consumption by reducing the rms input current for the same load.

- Standard offer:
 - THDi ≤ 48% for 80 to 100% load on the most common operating range maintaining an optimum power factor
 - Embedded line choke technology
- Low Harmonic offer:
 - Compatible with standard IEEE 519

In addition, thanks to the "Stop & go" function, Altivar Process drives can reduce power consumption by up to 30% during system stop phases by disabling some functions automatically (the power section, fans, backlighting, etc.). On a system restart request, the Altivar Process drive takes less than 2 seconds to restart the motor.

Integrated as standard, the "Stop & go" function can be enabled and disabled in the drive parameters.

Environment

The Altivar Process Modular drives offer has been developed to meet the requirements of directives regarding protection of the environment and to anticipate future changes in regulations:

- REACH (1) + solution for REACH Substitute It Now (halogen-free wiring and plastics)
- PEP (Product Environmental Profile) eco-passport program for reducing the carbon footprint and conserving raw materials
- EoLI (End of Life Instruction) (2)

Electromagnetic compatibility (EMC)

Compliance with electromagnetic compatibility requirements has been incorporated into the design of Altivar Process Modular drives, which simplifies installation and provides an economical means of helping to ensure equipment meets CE marking requirements.

Altivar Process Modular drives have category C3 EMC filters that allow 300 m/980 ft of shielded motor cables.

(1) European regulation 1907/2006.

(2) According to IEC 62635 Enhanced Guidelines.

General presentation of the offer (continued)

Installation/Maintenance

Altivar Process Modular drives are ergonomically designed to adapt to any type of installation:

- IP00 modules that can be integrated in cabinets with an IP21 (UL Type 1) or IP54 (UL Type 12) protection rating as a standard integration and up to IP66 with liquid-cooled modules
- Easy installation of products and systems:
 - Color code for connections to the removable terminal blocks on the HMI block
 - Long cable: Highly efficient integrated motor filters for dv/dt and common mode reduction and voltage peak limitation allow motor cable lengths up to 300 m/980 ft with shielded cable (category C3 environment) and 500 m/1,640 ft with unshielded cable (category C4 environment)
 - Sinus filter option: contact your local Schneider Electric sales office for support
- Asynchronous or synchronous drive in open loop from 0.1...500 Hz for ATV600 and 0.1...599 Hz for ATV900 output frequency
- Special motors: Submersible, synchronous reluctance, and tapered rotor motors
- Lower maintenance costs due to drive's ergonomic design:
 - Fans can be replaced in less than 5 minutes thanks to access from front face and drawer design
 - Wheel on standard drive power module for easy removal
 - Limited number of parts and integrated power auxiliaries
- Embedded Web server:
 - Compatible process elements for easier implementation
 - Direct worldwide access to monitoring and maintenance functions:
 - Reading values
 - Modifying data
 - Configuring parameters
 - Changing controller status

Integrated functions

Altivar Process Modular drives include numerous advanced functions for more complex applications in each market segment.

For more information, please refer to the Altivar Process ATV600 and Altivar Process ATV900 catalogs.



Altivar Process catalogs
Click to open the documents



Altivar Process Modular Standard architecture from 1 to 6 modules



Altivar Process Modular Low Harmonic/Regen architecture from 1 to 6 modules



Altivar Process Modular Standard Reduced Height architecture from 1 to 6 modules



Altivar Process Modular - Liquid-cooled architecture from 1 to 6 modules

Altivar Process Modular offer structure

Presentation

The Altivar Process Modular drives offer is composed of sub-assemblies and accessories that are integrated into cabinets to create modular drive solutions.

These separate elements can be ordered from our Schneider Electric Partner Network. For more information on the references, see [page 20](#).

Numerous drive solutions can be built using these modular parts. For more information on the characteristics of these configurations, see [page 36](#).

Altivar Process Modular offer structure (continued)

Description

The Altivar Process Modular drives offer consists of sub-assemblies and accessories:


- 1 Power module, braking unit, or mains module
- 2 Front face cover
- 3 Control units for ATV600 and ATV900 or braking unit

Accessories

Optional extensions: Communication, I/O expansion, and encoder modules



Altivar Process Modular standard drives



Altivar Process Modular Low Harmonic/Regen drives




Braking units



Altivar Process Modular standard Reduced Height drives



Altivar Process Modular power connection kit



Altivar Process Modular - Liquid-cooled drives

Accessories comprise:

- Power connection kits
- Digi-Link cables
- Mechanical mounting kits



Altivar Process Modular Digi-Link cables

For more information, please contact your Schneider Electric supplier.

Variable speed drives


Altivar Process Modular Sub-assemblies and accessories



APM1A0C16N401



APM1A0C16N4RH



APMCA03LCN4RH




APM1LOC28V6


Power modules		
Description	Reference	Weight kg/lb
Standard architectures		
Standard power module		
Power module 160 kW - 380...480 V IP00:	APM1A0C16N401	155/ 342
■ 1 x standard power unit		
■ 1 x standard mains unit		
■ 3 x fuse holder with screws and washers for the fuse		
■ 2 x brackets with nuts for front mechanical connection		
Power module 200 kW - 500...690 V IP00:	APM1A0C20Y6	168/ 370
■ 1 x standard power unit		
■ 1 x standard mains unit		
■ 3 x fuse holder with screws and washers for the fuse		
■ 2 x brackets with nuts for front mechanical connection		
Low Harmonic/Regen power module		
Power module 160 kW - 380...480 V IP00:	APM1B0C16N4	260/ 574
■ 1 x power module for Low Harmonic/Regen APM drives		
■ 3 x fuse holder with screws and washers for the fuse		
Power module 200 kW - 500...690 V IP00:	APM1B0C20Y6	290/ 639
■ 1 x power module for Low Harmonic/Regen APM drives		
■ 3 x fuse holder with screws and washers for the fuse		
Reduced Height architectures		
Standard power module (Reduced Height integration)		
Power module for Reduced Height 160 kW - 380...480 V IP00:	APM1A0C16N4RH	100/ 220
■ 1 x power module		
Power module for Reduced Height 200 kW - 500...690 V IP00:	APM1A0C20Y6RH	100/ 220
■ 1 x power module		
Liquid-cooled architectures		
Standard power module liquid-cooled		
Standard power module 200 kW - 380...480V IP00:	APM1L0C20N4	82.5/ 182
■ 1 x standard power unit with embedded 6/12-pulse rectifier		
■ 1 x integrated water/water heat exchanger		
Standard power module 315 kW - 380...480V IP00	APM1L0C31N4	82.5/ 182
■ 1 x standard power unit with embedded 6/12-pulse rectifier		
■ 1 x integrated water/water heat exchanger		
Standard power module 280 kW - 500...690V IP00:	APM1L0C28Y6	82.5/ 182
■ 1 x standard power unit with embedded 6/12-pulse rectifier		
■ 1 x integrated water/water heat exchanger		
Standard power module 450 kW - 500...690V IP00	APM1L0C45Y6	82.5/ 182
■ 1 x standard power unit with embedded 6/12-pulse rectifier		
■ 1 x integrated water/water heat exchanger		
Overall dimensions		
Reference	W x H x D	
	mm	in.
APM1A0C16N401	230 x 1705 x 510	9.10 x 67.12 x 20.08
APM1A0C20Y6		
APM1B0C16N4	450 x 1692 x 508	17.72 x 66.61 x 20
APM1B0C20Y6		
APM1A0C16N4RH	230 x 1230 x 509	9.10 x 48.43 x 20
APM1A0C20Y6RH		
APM1L0C20N4	232 x 1080 x 526	9.13 x 40.08 x 20.71
APM1L0C31N4		
APM1L0C28Y6		
APM1L0C45Y6		

Variable speed drives

Altivar Process Modular Sub-assemblies and accessories



APMCA02LCN4RH



APMCA03LCY6RH

Power modules		Reference	Weight kg/lb
Description			
Reduced Height architectures (continued)			
Mains module (Reduced Height integration)			
Mains module 1 line choke - 380...480V - IP00: For combination with 1 standard power module. ■ 1 x mains module for APM Standard Reduced Height 380...480V		APMCA01LCN4RH	103/ 227
■ Components for power fan management: Controller, 48 VDC power supply, 2 x relays and 2 x relay holders, 3 x fuses and 3 x fuse holders			
Mains module 2 line chokes - 380...480V - IP00: For combination with 2 x standard power modules. ■ 1 x mains module for APM Standard Reduced Height 380...480V		APMCA02LCN4RH	160/ 353
■ Components for power fan management: Controller, 48 VDC power supply, 2 x relays and 2 x relay holders, 3 x fuses and 3 x fuse holders			
Mains module 3 line chokes - 380...480V - IP00: For combination with 3 x standard power modules. ■ 1 x mains module for APM Standard Reduced Height 380...480V		APMCA03LCN4RH	217/ 478
■ Components for power fan management: Controller, 48 VDC power supply, 2 x relays and 2 x relay holders, 3 x fuses and 3 x fuse holders			
Mains module 1 line choke - 500...690V - IP00: For combination with 1 standard power module. ■ 1 x mains module for APM Standard Reduced Height 500...690V		APMCA01LCY6RH	116/ 256
■ Components for power fan management: Controller, 48 VDC power supply, 2 x relays and 2 x relay holders, 3 x fuses and 3 x fuse holders			
Mains module 2 line chokes - 500...690V - IP00: For combination with 2 x standard power modules. ■ 1 x mains module for APM Standard Reduced Height 500...690V		APMCA02LCY6RH	186/ 410
■ Components for power fan management: Controller, 48 VDC power supply, 2 x relays and 2 x relay holders, 3 x fuses and 3 x fuse holders			
Mains module 3 line chokes - 500...690V - IP00: For combination with 3 x standard power modules. ■ 1 x mains module for APM Standard Reduced Height 500...690V		APMCA03LCY6RH	256/ 564
■ Components for power fan management: Controller, 48 VDC power supply, 2 x relays and 2 x relay holders, 3 x fuses and 3 x fuse holders			

Overall dimensions		
Reference	W x H x D mm	in.
APMCA01LCN4RH	269 x 1248 x 506	10.60 x 49.10 x 19.92
APMCA02LCN4RH		
APMCA03LCN4RH		
APMCA01LCY6RH		
APMCA02LCY6RH		
APMCA03LCY6RH		

Variable speed drives

Altivar Process Modular Sub-assemblies and accessories



ATV6A0CTLN401
APM6A0CTLN401



ATV6B0CTLY6
APM6B0CTLY6



ATV9L0CTLY6
APM9L0CTLY6

Control units for power module

Description	Reference	Weight kg/lb
ATV600 (1)		
Standard module 380...480 V	APM6A0CTLN401	6.750/ 14.880
Standard module 500...690 V	APM6A0CTLY6	6.750/ 14.880
Low Harmonic 380...480 V	APM6B0CTLN4	8.000/ 17.640
Low Harmonic 500...690 V	APM6B0CTLY6	4.800/ 10.580
Liquid-cooled 380...480 V	APM6L0CTLN4	6.500/ 14.330
Liquid-cooled 500...690 V	APM6L0CTLY6	6.500/ 14.330
ATV900 (1)		
Standard module 380...480 V	APM9A0CTLN401	6.750/ 14.880
Standard module 500...690 V	APM9A0CTLY6	6.750/ 14.880
Low Harmonic/Regen 380...480 V	APM9B0CTLN4	8.000/ 17.640
Low Harmonic/Regen 500...690 V	APM9B0CTLY6	4.800/ 10.580
Liquid-cooled 380...480 V	APM9L0CTLN4	6.500/ 14.330
Liquid-cooled 500...690 V	APM9L0CTLY6	6.500/ 14.330

Overall dimensions

Reference	W x H x D	
	mm	in.
APM6A0CTLN401	230 x 678 x 108	9.10 x 16.80 x 4.30
APM9A0CTLN401		
APM6A0CTLY6		
APM9A0CTLY6		
APM6L0CTLN4	230 x 510 x 131	9.10 x 20.08 x 5.16
APM6L0CTLY6		
APM6B0CTLN4	450 x 520 x 105	17.72 x 20.47 x 4.13
APM6B0CTLY6		
APM9B0CTLN4		
APM9B0CTLY6		
APM9L0CTLN4	230 x 510 x 131	9.10 x 20.08 x 5.16
APM9L0CTLY6		

(1) All control units include 1 control unit (metal housing + control block + power board), 1 graphic display terminal, 1 Digi-Link cable, 1 cable for 24 V supply, and cables for voltage measurement (mains, DC, motor).

Variable speed drives

Altivar Process Modular Sub-assemblies and accessories



Housings			
Description	Reference	Weight kg/lb	
Standard front face cover	VW3A97A01	5.000/ 11.000	
Low Harmonic/Regen front face cover	VW3A97B01	5.900/ 13.000	
Overall dimensions			
Reference	W x H x D		
	mm	in.	
VW3A97A01	230 x 678 x 108	9.06 x 26.70 x 4.25	
VW3A97B01	450 x 520 x 105	17.72 x 20.47 x 4.13	
Control cables			
Description	Reference	Weight kg/lb	
RJ45 module-link cable 1.5 m/4.92 ft	VW3A83BMR015	0.120/ 0.264	
RJ45 module-link cable 5 m/16.4 ft	VW3A83BMR050	0.230/ 0.507	
Digi-Link cable 2 m/6.56 ft	VW3A83CDG020	0.100/ 0.220	
Digi-Link cable 3 m/9.84 ft	VW3A83CDG030	0.140/ 0.309	
Digi-Link cable 5 m/16.4 ft	VW3A83CDG050	0.230/ 0.507	
Digi-Link cable 10 m/33 ft	VW3A83CDG100	0.430/ 0.948	

Variable speed drives

Altivar Process Modular

Sub-assemblies and accessories



VW3A98ABMAAA



VW3A98ABMCAB



VW3A98ABMCAC



VW3A98ABMDCE



VW3A98ABMDCF



VW3A98ABPDCE1



VW3A98ABPDCE1



VW3A98ABPDCE1



VW3A98BBMAAB



VW3A98BBMCAD



VW3A98BBMDCG



VW3A98BBPC



VW3A98BBPDCG



VW3A98BBPDCK



VW3A98CTM01



VW3A98CTM02



VW3A98CF3169



VW3A98CF4040

Power busbar kits

Description	Reference	Weight kg/lb
Power busbar kit to connect 1 standalone power module in a 400 mm/15.75 in. width cabinet.	VW3A98ABMAAA	4.500/ 9.920
Power busbar kit to connect 2 side-by-side power modules in a 600 mm/23.62 in. width cabinet	VW3A98ABMCAB	8.000/ 17.637
Power busbar kit to connect 3 side-by-side power modules in a 800 mm/31.50 in. width cabinet	VW3A98ABMCAC	12.000/ 26.455
Power busbar kit to connect 2 remote power modules integrated in side-by-side cabinet columns of: ■ 600 mm + 600 mm (23.62 in. + 23.62 in.) width or ■ 800 mm + 600 mm (31.50 in. + 23.62 in.) width	VW3A98ABMDCE	2.500/ 5.512
Power busbar kit to connect 2 remote power modules integrated in side-by-side cabinet columns of 800 mm + 800 mm (31.50 in. + 31.50 in.) width	VW3A98ABMDCF	2.000/ 4.409
Power busbar kit to connect: ■ 2 side-by-side standard power modules or ■ 1 side-by-side standard power module + 1 braking unit	VW3A98ABPC1	1.000/ 2.204
Power busbar kit to connect: ■ 2 remote standard power modules or ■ 1 remote standard power module and 1 braking unit In side-by-side cabinet columns of: ■ 600 mm + 600 mm (23.62 in. + 23.62 in.) width or ■ 800 mm + 600 mm (31.50 in. + 23.62 in.) width	VW3A98ABPDCE1	2.600/ 5.730
Power busbar kit to connect 2 power modules integrated in side-by-side cabinet columns of 800 mm+ 800 mm (31.50 in. + 31.50 in.) width	VW3A98ABPDCE1	2.000/ 4.409
Power busbar kit to connect 1 standalone Low Harmonic power module integrated in a 600 mm/23.62 in. width cabinet	VW3A98BBMAAB	8.400/ 18.519
Power busbar kit to connect 2 side-by-side Low Harmonic power modules integrated in a 1,000 mm/39.37 in. width cabinet	VW3A98BBMCAD	16.500/ 36.376
Power busbar kit to connect 2 remote Low Harmonic power modules integrated in side-by-side cabinet columns of: ■ 600 mm + 1,000 mm (23.62 in. + 39.37 in.) width or ■ 1,000 mm + 1,000 mm (39.37 in. + 39.37 in.) width	VW3A98BBMDCG	1.800/ 3.968
Power busbar kit to connect 2 side-by-side Low Harmonic power modules	VW3A98BBPC	2.000/ 4.409
Power busbar kit to connect 2 remote Low Harmonic power modules integrated in side-by-side cabinet columns of: ■ 600 mm + 1,000 mm (23.62 in. + 39.37 in.) width or ■ 1,000 mm + 1,000 mm (39.37 in. + 39.37 in.) width	VW3A98BBPDCG	2.500/ 5.511
Power busbar kit to connect 1 Low Harmonic/Regen power module with 1 braking unit integrated in side-by-side cabinet columns of: ■ 400 mm + 600 mm (15.75 in. + 23.62 in.) width or ■ 400 mm + 1,000 mm (15.75 in. + 39.37 in.) width	VW3A98BBPDCK	1.000/ 2.204
Power busbar mounting kit	VW3A98CTM01	0.500/ 1.102
Power terminal kit	VW3A98CTM02	7.500/ 16.535

Fuses

Description	Reference	Weight kg/lb
Set of 3 fuses 315 A	VW3A98CF3169	0.750/ 1.653
Set of 3 fuses 400 A, UL certified	VW3A98CF4040	0.750/ 1.653

References (continued)

Variable speed drives

Altivar Process Modular Sub-assemblies and accessories



VW3A99ACFAA



VW3A99AR01



VW3A99ACFCB02



VW3A99ACA11



Mechanical mounting kits

Description	Cabinet	Reference	Weight kg/lb
Mounting kits			
Mains terminal extension plates for drives architectures with UL certification	SF/TS8/VX25	VW3A98CTM03	6.450/ 14.220
Mains bar support for a required SCR rating > 50 kA	SF/TS8/VX25	VW3A98CTM04	0.200/ 0.440
Mechanical mounting kit for integration of: ■ 1 standard power module in a 400 mm/15.75 in. width cabinet	SF/TS8 VX25	VW3A99ACFAA VW3A99ACFAA01	6.600/ 14.550
Mechanical mounting kit for integration of: ■ 2 standard power modules in a 600 mm/23.62 in. width cabinet	SF/TS8 VX25	VW3A99ACFCB VW3A99ACFCB01	9.500/ 20.944
Mechanical mounting kit for integration of: ■ 3 standard power modules in a 800 mm/31.50 in. width cabinet.	SF/TS8 VX25	VW3A99ACFEC VW3A99ACFEC01	14.000/ 30.865
Removable support	SF/TS8/VX25	VW3A99AR01	2.200/ 4.850
Mechanical mounting kit for integration of: ■ 1 Low Harmonic/Regen power module in a 600 mm/23.62 in. width cabinet	SF/TS8 VX25	VW3A99BCFAB VW3A99BCFAB01	17.000/ 37.478
Mechanical mounting kit for integration of: ■ 2 Low Harmonic/Regen power modules in a 1,000 mm/39.37 in. width cabinet.	SF/TS8 VX25	VW3A99BCFCD VW3A99BCFCD01	26.000/ 57.320
Removable support for Low Harmonic power module integration	SF/TS8/VX25	VW3A99BR01	16.500/ 36.376
Mechanical mounting kit for integration of: ■ 1 standard power module + 1 mains module	SF/TS8/VX25	VW3A99ACFCBN01	10.000/ 22.000
Mechanical mounting kit for integration of: ■ 2 standard power modules or ■ 1 standard power module + 1 braking module or ■ 2 braking modules architecture	SF/TS8	VW3A99ACFCBM01	9.000/ 19.800
Mechanical mounting kit for integration of: ■ 2 standard power modules or ■ 1 standard power module + 1 braking module or ■ 2 braking modules	VX25	VW3A99ACFCBM02	9.000/ 19.800
Mechanical mounting kit for integration of: ■ 3 standard power modules or ■ 2 standard power modules + 1 braking module	SF/TS8	VW3A99ACFEBN01	12.000/ 26.460
Mechanical mounting kit for integration of: ■ 3 standard power modules or ■ 2 standard power modules + 1 braking module	VX25	VW3A99ACFEBN02	12.000/ 26.460
Mechanical mounting kit for integration of: ■ 1 mains module	SF/TS8/VX25	VW3A99ACFABM	5.500/ 12.130
Top air ducts			
Top outlet cooling air duct for IP54/UL Type 12 integration of: ■ 1 standard power module or ■ 1 braking unit		VW3A99ACA03	1.800/ 3.968
Top outlet cooling air duct for IP54/UL Type 12 integration of: ■ 1 Low Harmonic/Regen power module		VW3A99BCA03	1.700/ 3.747
Top outlet cooling air duct for IP54/UL Type 12 integration of: ■ 1 standard power module or ■ 1 braking module		VW3A99ACA04	3.000/ 6.610
Top outlet cooling air duct for IP54/UL Type 12 integration of: ■ 1 mains module		VW3A99ACA11	2.500/ 5.510
Top outlet cooling air duct for IP54/UL Type 12 integration of: ■ 1 standard power module or ■ 1 braking module in cabinet with an air cooling outlet at the top rear side		VW3A99ACA12	4.000/ 8.820
Top outlet cooling air duct for IP54/UL Type 12 integration of: ■ 1 mains module in cabinet with an air cooling outlet at the top rear side		VW3A99ACA13	3.000/ 6.610

Variable speed drivesAltivar Process Modular
Sub-assemblies and accessories

VW3A99ACA01



VW3A99ACA10



APM1L0LFMY6

Mechanical mounting kits (continued)

Description	Cabinet	Reference	Weight kg/lb
Bottom supports and ducts			
Bottom support for IP21/UL Type 1 integration of: ■ 1 standard power module		VW3A99ACA01	8.000/ 17.637
Bottom support for IP54/UL Type 12 integration of: ■ 1 standard power module		VW3A99ACA02	7.600/ 17.755
Bottom inlet air duct for IP54/UL Type 12 integration of: ■ 1 Low Harmonic/Regen power module		VW3A99BCA02	6.900/ 15.211
Bottom support for IP21/UL Type 1 integration of: ■ 1 standard power module or ■ 1 mains module or ■ 1 braking module	SF/TS8	VW3A99ACA05	3.000/ 6.610
Bottom support for IP54/UL Type 12 integration of: ■ 1 standard power module or ■ 1 mains module or ■ 1 braking module	SF/TS8	VW3A99ACA06	6.000/ 13.230
Bottom support for IP21/UL Type 1 integration of: ■ 1 standard power module or ■ 1 mains module or ■ 1 braking module	VX25	VW3A99ACA09	3.000/ 6.610
Bottom support for IP54/UL Type 12 integration of: ■ 1 standard power module or ■ 1 mains module or ■ 1 braking module	VX25	VW3A99ACA10	6.000/ 13.230
Mechanical mounting kits for liquid-cooled drives			
Connection kit for drive power module and motor protection module in 600mm/23.62 in. width cabinets for 2 to 6 modules		VW3A98LBPC1	15/ 33.069
Mains bar support		VW3A98LTMC1	1.5/ 3.307
Set of tubes for liquid cooling		VW3A98LGHC1	5/ 11.023
Over-pressure valve		VW3A98LGHC2	2.5/ 5.511
Motor terminal extension for box lugs		VW3A98LBPC3	2.5/ 5.511
Braking module interconnection kit including cabinet cooling module adapter		VW3A98LBPC2	27/ 59.524
Module-link cable 10m/32.8ft for braking unit		VW3A83BMR100	0.430/ 0.948
Steel support for Liquid-cooled module		VW3A99LR01	6/ 13.228

Additional modules for liquid-cooled drives

Description	Reference	Weight kg/lb
Line paralleling		
Line paralleling module IP00, 380 ... 480 V ■ 6- or 12-pulse supply ■ 1 x paralleling choke ■ 3 x semiconductor fuses	APM1L0LPN4	40/ 88.185
Line paralleling module IP00, 500 ... 690 V ■ 6- or 12-pulse supply ■ 1 x paralleling choke ■ 3 x semiconductor fuses	APM1L0LPY6	40/ 88.185
Line filter		
Line filter module IP00, 380 ... 480 V ■ EMC filter	APM1L0LFMN4	6.5/ 14.330
Line filter module IP00, 500 ... 690 V ■ EMC filter	APM1L0LFMY6	6.5/ 14.330

Variable speed drives

Altivar Process Modular Sub-assemblies and accessories



ATvM.CP1903B
APMBC0C63Y6



ATvM.CP1904I
APMBC0CTLY6

Additional modules for liquid-cooled drives (continued)

Description	Reference	Weight kg/lb
Line choke		
Line choke module IP00, 380 ... 480 V ■ 6- or 12-pulse supply ■ 2 x three-phase line reactors ■ 6 x semiconductor fuses ■ EMC filter	APM1L0LCMN4	183.5/ 404.55
Line choke module IP00, 500 ... 690 V ■ 6- or 12-pulse supply ■ 2 x three-phase line reactors ■ 6 x semiconductor fuses ■ EMC filter	APM1L0LCMY6	183.5/ 404.55
Motor protection		
Motor protection module IP00, 380 ... 480 V ■ 1 x dv/dt filter and common mode filter ■ Integrated motor terminals	APM1L0MPMN4	32.5/ 71.650
Motor protection module IP00, 500 ... 690 V ■ 1 x dv/dt filter and common mode filter ■ Integrated motor terminals	APM1L0MPMY6	32.5/ 71.650
Cabinet cooling		
Cabinet cooling module IP00, 115 VAC ■ Air/water heat exchanger with fan	APM1L0CCM115	13.5/ 29.762
Cabinet cooling module IP00, 230 VAC ■ Air/water heat exchanger with fan	APM1L0CCM230	13.5/ 29.762

Braking modules

Description	Reference	Weight kg/lb
Braking module for APM 380...480 V:		
■ 1 x power unit ■ 1 x air outlet unit ■ 2 x brackets with nuts for front mechanical connection	APMBC0C50N4	95/ 209.43
Braking module for APM 500...690 V:		
■ 1 x power unit ■ 1 x air outlet unit ■ 2 x brackets with nuts for front mechanical connection	APMBC0C63Y6	95/ 209.43
Overall dimensions		
Reference	W x H x D	
APMBC0C50N4	mm 750 x 1,360 x 700	in. 29.53 x 53.54 x 27.56
APMBC0C63Y6		

Control units for braking unit

Description	Reference	Weight kg/lb
Control unit for braking unit 380...480 V	APMBC0CTLN4	6.750/ 14.881
Control unit for braking unit 500...690 V	APMBC0CTLY6	6.750/ 14.881
Overall dimensions		
Reference	W x H x D	
APMBC0CTLN4	mm 287 x 735 x 178	in. 11.30 x 28.94 x 7.01
APMBC0CTLY6		



ATVW 6554_CPSCT18006
VX5VAM001



SoMove software

Wear parts

Description	Reference	Weight kg/lb
Power fan kit	VX5VAM001	1.420/ 3.130
Drive power fan kit	VX5VAML001	0.7/ 1.543
Cabinet cooling fan kit, 115 V ~	VX5VAML003	1.4/ 3.086
Cabinet cooling fan kit, 230 V ~	VX5VAML002	1.4/ 3.086

SoMove software for Altivar Process Modular

Presentation

SoMove software for PC is used to configure, set up, and maintain Altivar Process drives.

In addition to the standard features offered by SoMove software, such as the oscilloscope function for accurate display of data samples or access to multi-drive applications, the following features are accessible to partners of Altivar Process Modular drives:

- First-time drive setting including architecture identification and validation, main voltage and nominal power range setting, and operational reference creation, which is the identity card of the configuration
- Serial number generation for the built modular drive
- Activation of warranty by registering the built modular drive in the Schneider Electric Partner Database
- Start-up and maintenance of the built modular drive

For more information on SoMove setup software, please consult the SoMove Setup Software catalog.

Variable speed drives

Altivar Process Modular

Options: Graphic display terminal, communication accessory



Graphic display terminal
(example shows dynamic pump operation in relation to its optimum operation)



Instant access to online help



Remote mounting kit for mounting graphic display terminal on enclosure door (front panel)



Remote mounting kit for graphic display terminal (rear panel)

Graphic display terminal (supplied with the drive)

References

Description	Reference	Weight kg/lb
Graphic display terminal	VW3A1111	0.200/0.441

Communication accessory


References

Description	Reference	Weight kg/lb
Wi-Fi dongle Portable battery-powered Wi-Fi access point for Wi-Fi equipment (PC, tablet, smartphone, etc.)	TCSEGWBT31W	0.134/0.295

References

Description	Length m/ft	IP rating	Reference	Weight kg/lb
Remote mounting kit Order with remote-mounting cordset VW3A1104R●●●	–	65/UL Type 12	VW3A1112	–
Tightening tool for remote mounting kit	–	–	ZB5AZ905	0.016/0.035
Remote-mounting cordset equipped with 2 RJ45 connectors	1/3.28	–	VW3A1104R10	0.050/0.110
	3/9.84	–	VW3A1104R30	0.150/0.331
	5/16.4	–	VW3A1104R50	0.250/0.551
	10/33	–	VW3A1104R100	0.500/1.102
IP65 remote mounting kit for Ethernet port (1) Ø 22 RJ45 female/female adapter with seal	–	65	VW3A1115	0.018/0.040

(1) Used to connect a remote PC to the RJ45 port on an IP21 drive mounted in an enclosure.
Drill hole with a standard Ø 22 tool, as used for a pushbutton (requires a remote-mounting cordset VW3A1104R●●● equipped with 2 RJ45 connectors).



Altivar Process Modular Standard architecture from 1 to 6 modules

Modular drives

Modular drive solutions can be built using power modules, control units, and accessories. They cover motor power ratings from 75...2600 kW/125...2600 HP for 380...690 V three-phase voltages.

Three-phase power supply - 380...480 V (-15...10%) Standard

Motor power	Degree of protection	Reference
110...1000 kW	IP00	ATV6A0C11●4...M10●4
150...1400 HP		ATV9A0C11●4...M10●4

Three-phase power supply 500 V (-10...15%), 600...690 V (-15...10%) Standard

Motor power	Degree of protection	Reference
75...1200 kW	IP00	ATV6A0C11●6...M12●6
125...1200 HP		ATV9A0C11●6...M12●6

Three-phase power supply - 380...440 V (-15...10%), 480 V (-10...10%) Low Harmonic

Motor power	Degree of protection	Reference
110...1000 kW	IP00	ATV6B0C11●4...M10●4
150...1400 HP		ATV9B0C11●4...M10●4



Altivar Process Modular Low Harmonic/Regen architecture from 1 to 6 modules

Three-phase power supply 500 V (-10...15%), 600...690 V (-10...10%) Low Harmonic


Motor power	Degree of protection	Reference
75...1200 kW	IP00	ATV6B0C11●6...M12●6
125...1200 HP		ATV9B0C11●6...M12●6

Liquid-cooled three-phase power supply - 380 V...480 V (-15...10%) Standard

Motor power	Degree of protection	Reference
132...1800 kW	IP00	ATV6L0C13●4...M18●4
200...2500 HP		ATV9L0C13●4...M18●4

Liquid-cooled three-phase power supply - 500 V (-10...15%), 600...690 V (-15...10%) Standard

Motor power	Degree of protection	Reference
132...2600 kW	IP00	ATV6L0C20●6...M26●6
200...2600 HP		ATV9L0C20●6...M26●6



Normal duty and Heavy duty modes

Altivar Process Modular variable speed drives are designed for use in two operating modes that can optimize the drive nominal rating according to the system constraints.

These two modes are:

- **Normal duty (ND):** Dedicated mode for applications requiring a slight overload (up to 110% for ATV600 and 120% for ATV900) with a motor power no higher than the drive nominal power
- **Heavy duty (HD):** Dedicated mode for applications requiring a significant overload (up to 150% for both ATV600 and ATV900) with a motor power no higher than the drive nominal power derated by one rating

Architectures


Altivar Process Modular drives can be integrated into cabinets with the following dimensions:

- 2,000 mm/78.7 in. height for standard cabinets or 1,600 mm/63 in., height for Reduced Height cabinets
- 600 mm/23.6 in. depth
- Four different widths: 400 mm/15.7 in., 600 mm/23.6 in., 800 mm/31.5 in., and 1,000 mm/39.4 in.

Examples of different architectures for all Altivar Process Modular power ranges are presented in this chapter for our drives dedicated to 380...480V and 500..690 V line supply. There are four types of architectures:

- Standard
- Reduced Height
- Low Harmonic/Regen
- Liquid cooled.

Please refer to the combinations table (see page 84) to learn more about the possible architectures.



Standard drive solutions without braking - Standard architectures

380...480 V	110 to 160 kW	200 to 315 kW	355 to 500 kW	560 to 630 kW	710 to 800 kW	1000 kW
500...690 V	75 to 200 kW	160 to 400 kW	355 to 630 kW	560 to 800 kW	710 to 1000 kW	800 to 1200 kW


Standard drive solutions with braking - Standard architectures

380...480 V	110 to 160 kW	200 to 315 kW	355 to 500 kW	560 to 630 kW
500...690 V	75 to 200 kW	160 to 400 kW	355 to 630 kW	560 to 800 kW
380...480 V	710 to 800 kW	1000 kW		
500...690 V	710 to 1000 kW	800 to 1200 kW		

Variable speed drives

Altivar Process Modular Architectures

Architectures (continued)




Standard drive solution without braking - Reduced Height architectures

1 x APM 800 mm width	2 x APM 1,200 mm width	3 x APM 1,400 mm width	4 x APM 2,400 mm width
380...480 V	200 to 315 kW	355 to 500 kW	560 to 630 kW
500...690 V	110 to 200 kW	250 to 400 kW	500 to 630 kW
5 x APM 2,600 mm width	6 x APM 2,800 mm width		
380...480 V	710 to 800 kW	1000 kW	
500...690 V	1000 kW	1200 kW	

Standard drive solution with braking - Reduced Height architectures

1 x APM, 1 x BM 1,200 mm width	2 x APM, 1 x BM 1,400 mm width	3 x APM, 1 x BM 1,800 mm width	4 x APM, 2 x BM 3,000 mm width
380...480 V	110 to 160 kW	200 to 315 kW	355 to 500 kW
500...690 V	110 to 200 kW	250 to 400 kW	500 to 630 kW
5 x APM, 2 x BM 3,200 mm width	6 x APM, 2 x BM 3,400 mm width		
380...480 V	710 to 800 kW	1000 kW	
500...690 V	1000 kW	1200 kW	

Architectures (continued)



Required mechanical kits (rear plates, top bar) are not represented


Low Harmonic/Regen drive solutions without braking - Standard architectures

1 x APM 600 mm width	2 x APM 1,000 mm width	3 x APM 1,600 mm width	4 x APM 2,000 mm width
380...480 V 500...690 V	110 to 160 kW 200 to 315 kW 160 to 400 kW	355 to 500 kW 355 to 630 kW	560 to 630 kW 560 to 800 kW
380...480 V 500...690 V	710 to 800 kW 710 to 1000 kW	—	800 to 1200 kW
380...480 V	1000 kW		


Variable speed drives

Altivar Process Modular Architectures

Architectures (continued)




Low Harmonic/Regen drive solutions with braking - Standard architectures



Variable speed drives

Altivar Process Modular Architectures

Architectures (continued)



Liquid-cooled drive solutions – Standard architectures - Compact

1 x STD PM 400 mm width	2 x STD PM 600 mm width	3 x STD PM 800 mm width	4 x STD PM 1,200 mm width	5 x STD PM 1,400 mm width	6 x STD PM 1,600 mm width
380...480 V 132 to 315 kW	400 to 630 kW	800 to 900 kW	1000 to 1200 kW	1500 kW	1800 kW
500...690 V 200 to 450 kW	560 to 900 kW	1200 to 1400 kW	1600 to 1800 kW	2200 kW	2600 kW

Liquid-cooled drive solutions – Standard architectures - Universal

1 x STD PM 600 mm width	2 x STD PM 1,200 mm width	3 x STD PM 1,800 mm width	4 x STD PM 2,400 mm width
380...480 V 132 to 315 kW	400 to 630 kW	800 to 900 kW	1000 to 1200 kW
500...690 V 200 to 450 kW	560 to 900 kW	1200 to 1400 kW	1600 to 1800 kW

5 x STD PM 3,000 mm width	6 x STD PM 3,600 mm width
380...480 V 1500 kW	1800 kW
500...690 V 2200 kW	2600 kW

Motor starters

Schneider Electric offers combinations of circuit breakers and contactors to be able to use Altivar Process Modular drives in optimum conditions (see page 96).

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 400 V 50/60 Hz



ATV6A0C11Q4



ATV6A0C25Q4

400 V (-15...10%) IP00 Standard Modular drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		400 V	400 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 48% at 100% load in Normal duty								
ND	110	—	198	137	50	211	232	ATV6A0C11Q4
HD	90	—	167	116	50	173	260	
ND	132	—	233	161	50	250	275	ATV6A0C13Q4
HD	110	—	198	137	50	211	317	
ND	160	—	278	193	50	302	332	ATV6A0C16Q4
HD	132	—	233	161	50	250	375	
ND	200	—	352	244	50	370	407	ATV6A0C20Q4
HD	160	—	290	201	50	302	453	
ND	250	—	432	299	50	477	525	ATV6A0C25Q4
HD	200	—	353	245	50	370	555	
ND	315	—	538	373	50	590	649	ATV6A0C31Q4
HD	250	—	432	299	50	477	716	
ND	355	—	611	423	50	660	726	ATV6A0C35Q4
HD	280	—	489	339	50	520	780	
ND	400	—	681	472	50	730	803	ATV6A0C40Q4
HD	315	—	545	378	50	590	885	
ND	450	—	764	529	50	830	913	ATV6A0C45Q4
HD	355	—	611	423	50	660	990	
ND	500	—	846	586	50	900	990	ATV6A0C50Q4
HD	400	—	681	472	50	730	1095	
ND	560	—	948	657	50	1020	1122	ATV6A0C56Q4
HD	450	—	767	531	50	830	1245	
ND	630	—	1058	733	50	1140	1254	ATV6A0C63Q4
HD	500	—	849	588	50	900	1350	
ND	710	—	1192	826	50	1260	1386	ATV6A0C71Q4
HD	560	—	951	659	50	1020	1530	
ND	800	—	1335	925	50	1420	1562	ATV6A0C80Q4
HD	630	—	1061	735	50	1140	1710	
ND	1000	—	1692	1172	50	1770	1947	ATV6A0M10Q4
HD	800	—	1362	944	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 400 V 50/60 Hz



ATV9A0C16Q4



ATV9A0C20Q4

400 V (-15...10%) IP00 Standard Modular drives (continued) (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		400 V	400 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 48% at 100% load in Normal duty								
ND	110	—	198	135	50	211	253	ATV9A0C11Q4
HD	90	—	167	114	50	173	260	
ND	132	—	233	161	50	250	300	ATV9A0C13Q4
HD	110	—	198	136	50	211	317	
ND	160	—	278	192	50	302	362	ATV9A0C16Q4
HD	132	—	233	161	50	250	375	
ND	200	—	352	242	50	370	444	ATV9A0C20Q4
HD	160	—	290	198	50	302	453	
ND	250	—	432	299	50	477	572	ATV9A0C25Q4
HD	200	—	353	245	50	370	555	
ND	315	—	538	373	50	590	708	ATV9A0C31Q4
HD	250	—	432	299	50	477	716	
ND	355	—	611	423	50	660	792	ATV9A0C35Q4
HD	280	—	489	339	50	520	780	
ND	400	—	681	472	50	730	876	ATV9A0C40Q4
HD	315	—	545	378	50	590	885	
ND	450	—	764	529	50	830	996	ATV9A0C45Q4
HD	355	—	611	423	50	660	990	
ND	500	—	846	586	50	900	1080	ATV9A0C50Q4
HD	400	—	681	472	50	730	1095	
ND	560	—	948	657	50	1020	1224	ATV9A0C56Q4
HD	450	—	767	531	50	830	1245	
ND	630	—	1058	733	50	1140	1368	ATV9A0C63Q4
HD	500	—	849	588	50	900	1350	
ND	710	—	1192	826	50	1260	1512	ATV9A0C71Q4
HD	560	—	951	659	50	1020	1530	
ND	800	—	1335	925	50	1420	1704	ATV9A0C80Q4
HD	630	—	1061	735	50	1140	1710	
ND	1000	—	1692	1172	50	1770	1947	ATV9A0M10Q4
HD	800	—	1362	944	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 440 V 50/60 Hz



ATV6A0C20R4



ATV6A0C35R4

440 V (-15...10%) IP00 Standard Modular drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line lsc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		440 V	440 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 48% at 100% load in Normal duty								
ND	110	—	183	139	50	211	232	ATV6A0C11R4
HD	90	—	155	118	50	173	260	
ND	132	—	214	163	50	250	275	ATV6A0C13R4
HD	110	—	183	139	50	211	317	
ND	160	—	255	194	50	302	332	ATV6A0C16R4
HD	132	—	214	163	50	250	375	
ND	160	—	325	248	50	370	407	ATV6A0C20R4
HD	160	—	269	205	50	302	453	
ND	250	—	396	302	50	477	525	ATV6A0C25R4
HD	200	—	325	248	50	370	555	
ND	315	—	493	376	50	590	649	ATV6A0C31R4
HD	250	—	396	302	50	477	716	
ND	355	—	559	426	50	660	726	ATV6A0C35R4
HD	280	—	450	343	50	520	780	
ND	400	—	623	475	50	730	803	ATV6A0C40R4
HD	315	—	501	382	50	590	885	
ND	450	—	697	531	50	830	913	ATV6A0C45R4
HD	355	—	559	426	50	660	990	
ND	500	—	771	588	50	900	990	ATV6A0C50R4
HD	400	—	623	475	50	730	1095	
ND	560	—	865	659	50	1020	1122	ATV6A0C56R4
HD	450	—	703	536	50	830	1245	
ND	630	—	965	735	50	1140	1254	ATV6A0C63R4
HD	500	—	776	591	50	900	1350	
ND	710	—	1087	828	50	1260	1386	ATV6A0C71R4
HD	580	—	869	662	50	1020	1530	
ND	800	—	1216	927	50	1420	1562	ATV6A0C80R4
HD	630	—	968	738	50	1140	1710	
ND	1000	—	1542	1175	50	1770	1947	ATV6A0M10R4
HD	800	—	1246	950	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line lsc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 440 V 50/60 Hz



ATV9A0C31R4



ATV9A0C40R4

440 V (-15...10%) IP00 Standard Modular drives (continued) (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		440 V	440 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 48% at 100% load in Normal duty								
ND	110	—	183	136	50	211	253	ATV9A0C11R4
HD	90	—	155	115	50	173	260	
ND	132	—	214	162	50	250	300	ATV9A0C13R4
HD	110	—	183	138	50	211	317	
ND	160	—	255	194	50	302	362	ATV9A0C16R4
HD	132	—	214	162	50	250	375	
ND	160	—	325	245	50	370	444	ATV9A0C20R4
HD	160	—	269	201	50	302	453	
ND	250	—	396	302	50	477	572	ATV9A0C25R4
HD	200	—	325	248	50	370	555	
ND	315	—	493	376	50	590	708	ATV9A0C31R4
HD	250	—	396	302	50	477	716	
ND	355	—	559	426	50	660	792	ATV9A0C35R4
HD	280	—	450	343	50	520	780	
ND	400	—	623	475	50	730	876	ATV9A0C40R4
HD	315	—	501	382	50	590	885	
ND	450	—	697	531	50	830	996	ATV9A0C45R4
HD	355	—	559	426	50	660	990	
ND	500	—	771	588	50	900	1080	ATV9A0C50R4
HD	400	—	623	475	50	730	1095	
ND	560	—	865	659	50	1020	1224	ATV9A0C56R4
HD	450	—	703	536	50	830	1245	
ND	630	—	965	735	50	1140	1368	ATV9A0C63R4
HD	500	—	776	591	50	900	1350	
ND	710	—	1087	828	50	1260	1512	ATV9A0C71R4
HD	580	—	869	662	50	1020	1530	
ND	800	—	1216	927	50	1420	1704	ATV9A0C80R4
HD	630	—	968	738	50	1140	1710	
ND	1000	—	1542	1175	50	1770	1947	ATV9A0M10R4
HD	800	—	1246	950	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives


Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 480 V 50/60 Hz



ATV6A0C56T4



ATV6A0C80T4

ATM_L_OP9051

ATM_L_OP9052

480 V (-15...10%) IP00 Standard Modular drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		480 V	480 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 48% at 100% load in Normal duty								
ND	—	150	168	140	50	211	232	ATV6A0C11T4
HD	—	125	145	121	50	173	260	ATV6A0C13T4
ND	—	200	218	181	50	250	275	ATV6A0C16T4
HD	—	150	168	140	50	211	317	ATV6A0C20T4
ND	—	250	268	223	50	302	332	ATV6A0C25T4
HD	—	200	218	181	50	250	375	ATV6A0C31T4
ND	—	300	328	273	50	370	407	ATV6A0C35T4
HD	—	250	280	233	50	302	453	ATV6A0C40T4
ND	—	400	427	355	50	477	525	ATV6A0C45T4
HD	—	300	328	273	50	370	555	ATV6A0C50T4
ND	—	500	528	439	50	590	649	ATV6A0C56T4
HD	—	400	427	355	50	477	716	ATV6A0C63T4
ND	—	550	586	487	50	660	726	ATV6A0C71T4
HD	—	450	486	404	50	520	780	ATV6A0C80T4
ND	—	600	634	527	50	730	803	ATV6A0M10T4
HD	—	500	536	446	50	590	885	ATV6A0M12T4
ND	—	650	685	569	50	830	913	ATV6A0M15T4
HD	—	550	586	487	50	660	990	ATV6A0M17T4
ND	—	700	736	612	50	900	990	ATV6A0M19T4
HD	—	600	634	527	50	730	1095	ATV6A0M21T4
ND	—	800	842	700	50	1020	1122	ATV6A0M25T4
HD	—	650	690	574	50	830	1245	ATV6A0M27T4
ND	—	900	939	781	50	1140	1254	ATV6A0M31T4
HD	—	700	740	615	50	900	1350	ATV6A0M33T4
ND	—	1000	1044	868	50	1260	1386	ATV6A0M35T4
HD	—	800	846	703	50	1020	1530	ATV6A0M37T4
ND	—	1100	1146	953	50	1420	1562	ATV6A0M39T4
HD	—	900	942	783	50	1140	1710	ATV6A0M41T4
ND	—	1400	1472	1224	50	1770	1947	ATV6A0M43T4
HD	—	1100	1268	1054	50	1420	2130	ATV6A0M45T4

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.


References (continued)

Variable speed drives


Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 480 V 50/60 Hz



ATV9A0C63T4



ATV9A0C80T4

ATV9A0C80T4

480 V (-15...10%) IP00 Standard Modular drives (continued) (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		480 V	480 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 48% at 100% load in Normal duty								
ND	–	150	168	138	50	211	253	ATV9A0C11T4
HD	–	125	145	118	50	173	260	
ND	–	200	218	180	50	250	300	ATV9A0C13T4
HD	–	150	168	140	50	211	317	
ND	–	250	268	223	50	302	362	ATV9A0C16T4
HD	–	200	218	180	50	250	375	
ND	–	300	328	271	50	370	444	ATV9A0C20T4
HD	–	250	280	230	50	302	453	
ND	–	400	427	355	50	477	572	ATV9A0C25T4
HD	–	300	328	273	50	370	555	
ND	–	500	528	439	50	590	708	ATV9A0C31T4
HD	–	400	427	355	50	477	716	
ND	–	550	586	487	50	660	792	ATV9A0C35T4
HD	–	450	486	404	50	520	780	
ND	–	600	634	527	50	730	876	ATV9A0C40T4
HD	–	500	536	446	50	590	885	
ND	–	650	685	569	50	830	996	ATV9A0C45T4
HD	–	550	586	487	50	660	990	
ND	–	700	736	612	50	900	1080	ATV9A0C50T4
HD	–	600	634	527	50	730	1095	
ND	–	800	842	700	50	1020	1224	ATV9A0C56T4
HD	–	650	690	574	50	830	1245	
ND	–	900	939	781	50	1140	1368	ATV9A0C63T4
HD	–	700	740	615	50	900	1350	
ND	–	1000	1044	868	50	1260	1512	ATV9A0C71T4
HD	–	800	846	703	50	1020	1530	
ND	–	1100	1146	953	50	1420	1704	ATV9A0C80T4
HD	–	900	942	783	50	1140	1710	
ND	–	1400	1472	1224	50	1770	1947	ATV9A0M10T4
HD	–	1100	1268	1054	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 500 V 50/60 Hz



ATV6A0C11N6



ATV6A0C25N6

500 V (-10...15%) IP00 Standard Modular drives (1)								
Motor			Line supply			Altivar Process		
Power indicated on rating plate (2)			Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference
			500 V	500 V				
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A	A	
Altivar Process Modular for fluid management								
THDi ≤ 48% at 100% load in Normal duty								
ND	75	—	110	95	50	125	138	ATV6A0C11N6
HD	55	—	83	72	50	105	158	
ND	90	—	129	112	50	145	160	ATV6A0C13N6
HD	75	—	110	95	50	125	188	
ND	110	—	154	133	50	175	193	ATV6A0C16N6
HD	90	—	129	112	50	145	218	
ND	132	—	183	158	50	215	237	ATV6A0C20N6
HD	110	—	154	133	50	175	263	
ND	160	—	225	195	50	275	303	ATV6A0C25N6
HD	132	—	190	165	50	215	323	
ND	220	—	303	262	50	340	374	ATV6A0C31N6
HD	160	—	225	195	50	275	413	
ND	280	—	380	329	50	425	468	ATV6A0C40N6
HD	220	—	303	262	50	340	510	
ND	355	—	484	419	50	520	572	ATV6A0C50N6
HD	280	—	385	333	50	425	638	
ND	450	—	607	526	50	650	715	ATV6A0C63N6
HD	355	—	484	419	50	520	780	
ND	560	—	756	655	50	830	913	ATV6A0C80N6
HD	450	—	610	528	50	650	975	
ND	710	—	954	826	50	1030	1133	ATV6A0M10N6
HD	560	—	758	656	50	830	1245	
ND	800	—	1070	927	50	1230	1353	ATV6A0M12N6
HD	710	—	954	826	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 500 V 50/60 Hz



ATV9A0C11N6



ATV9A0C25N6

500 V (-10...15%) IP00 Standard Modular drives (continued) (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		500 V	500 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 48% at 100% load in Normal duty								
ND	75	—	110	95	50	125	150	ATV9A0C11N6
HD	55	—	83	72	50	105	158	
ND	90	—	129	112	50	145	174	ATV9A0C13N6
HD	75	—	110	95	50	125	188	
ND	110	—	154	133	50	175	210	ATV9A0C16N6
HD	90	—	129	112	50	145	218	
ND	132	—	183	158	50	215	258	ATV9A0C20N6
HD	110	—	154	133	50	175	263	
ND	160	—	225	195	50	275	330	ATV9A0C25N6
HD	132	—	190	165	50	215	323	
ND	220	—	303	262	50	340	408	ATV9A0C31N6
HD	160	—	225	195	50	275	413	
ND	280	—	380	329	50	425	510	ATV9A0C40N6
HD	220	—	303	262	50	340	510	
ND	355	—	484	419	50	520	624	ATV9A0C50N6
HD	280	—	385	333	50	425	638	
ND	450	—	607	526	50	650	780	ATV9A0C63N6
HD	355	—	484	419	50	520	780	
ND	560	—	756	655	50	830	996	ATV9A0C80N6
HD	450	—	610	528	50	650	975	
ND	710	—	954	826	50	1030	1236	ATV9A0M10N6
HD	560	—	758	656	50	830	1245	
ND	800	—	1070	927	50	1230	1476	ATV9A0M12N6
HD	710	—	954	826	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 600 V 50/60 Hz



ATV6A0C50T6



ATV6A0C80T6



600 V (-15...10%) IP00 Standard Modular drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc (4)	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		600 V	600 V	(4)				
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 48% at 100% load in Normal duty								
ND	—	125	112	116	50	125	138	ATV6A0C11T6
HD	—	100	92	96	50	105	158	
ND	—	150	131	136	50	145	160	ATV6A0C13T6
HD	—	125	112	116	50	125	188	
ND	—	175	152	158	50	175	193	ATV6A0C16T6
HD	—	150	131	136	50	145	218	
ND	—	200	172	179	50	215	237	ATV6A0C20T6
HD	—	175	152	158	50	175	263	
ND	—	250	218	227	50	275	303	ATV6A0C25T6
HD	—	200	179	186	50	215	323	
ND	—	350	298	310	50	340	374	ATV6A0C31T6
HD	—	250	218	227	50	275	413	
ND	—	450	379	394	50	425	468	ATV6A0C40T6
HD	—	350	298	310	50	340	510	
ND	—	550	464	482	50	520	572	ATV6A0C50T6
HD	—	450	383	398	50	425	638	
ND	—	650	544	565	50	650	715	ATV6A0C63T6
HD	—	550	464	482	50	520	780	
ND	—	800	670	696	50	830	913	ATV6A0C80T6
HD	—	650	547	568	50	650	975	
ND	—	1000	833	866	50	1030	1133	ATV6A0M10T6
HD	—	800	673	699	50	830	1245	
ND	—	1200	994	1033	50	1230	1353	ATV6A0M12T6
HD	—	1000	835	835	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) For 600V UL certified drives, a higher SCCR is possible under some conditions. Please refer to the Integration Manual PHA2451702 for more details.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives


Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 600 V 50/60 Hz



ATV9A0C50T6



ATV9A0C80T6

ATV9A0P9050

ATV9A0P19051

600 V (-15...10%) IP00 Standard Modular drives (continued) (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc (4)	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		600 V	600 V	(4)				
HD: Heavy duty		kW	HP	A	kVA	kA	A	
Altivar Process Modular for demanding applications								
THDi ≤ 48% at 100% load in Normal duty								
ND	–	125	112	116	50	125	150	ATV9A0C11T6
HD	–	100	92	96	50	105	158	
ND	–	150	131	136	50	145	174	ATV9A0C13T6
HD	–	125	112	116	50	125	188	
ND	–	175	152	158	50	175	210	ATV9A0C16T6
HD	–	150	131	136	50	145	218	
ND	–	200	172	179	50	215	258	ATV9A0C20T6
HD	–	175	152	158	50	175	263	
ND	–	250	218	227	50	275	330	ATV9A0C25T6
HD	–	200	179	186	50	215	323	
ND	–	350	298	310	50	340	408	ATV9A0C31T6
HD	–	250	218	227	50	275	413	
ND	–	450	379	394	50	425	510	ATV9A0C40T6
HD	–	350	298	310	50	340	510	
ND	–	550	464	482	50	520	624	ATV9A0C50T6
HD	–	450	383	398	50	425	638	
ND	–	650	544	565	50	650	780	ATV9A0C63T6
HD	–	550	464	482	50	520	780	
ND	–	800	670	696	50	830	996	ATV9A0C80T6
HD	–	650	547	568	50	650	975	
ND	–	1000	833	866	50	1030	1236	ATV9A0M10T6
HD	–	800	673	699	50	830	1245	
ND	–	1200	994	1033	50	1230	1476	ATV9A0M12T6
HD	–	1000	835	835	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) For 600V UL certified drives, a higher SCCR is possible under some conditions. Please refer to the Integration Manual PHA2451702 for more details.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 690 V 50/60 Hz

ATV6_OP9062



ATV6A0M10Q6

ATV6_OP19053



ATV6A0M12Q6

690 V (-15...10%) IP00 Standard Modular drives (1)

Motor		Line supply			Altivar Process			Reference
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s		
ND:	Normal duty	690 V	690 V					
HD:	Heavy duty							
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDI ≤ 48% at 100% load in Normal duty								
ND	110	—	118	141	50	125	138	ATV6A0C11Q6
HD	90	—	100	120	50	105	158	
ND	132	—	138	165	50	145	160	ATV6A0C13Q6
HD	110	—	118	141	50	125	188	
ND	160	—	163	195	50	175	193	ATV6A0C16Q6
HD	132	—	138	165	50	145	218	
ND	200	—	200	239	50	215	237	ATV6A0C20Q6
HD	160	—	163	195	50	175	263	
ND	250	—	255	305	50	275	303	ATV6A0C25Q6
HD	200	—	211	252	50	215	323	
ND	315	—	316	378	50	340	374	ATV6A0C31Q6
HD	250	—	255	305	50	275	413	
ND	400	—	394	471	50	425	468	ATV6A0C40Q6
HD	315	—	316	378	50	340	510	
ND	500	—	495	592	50	520	572	ATV6A0C50Q6
HD	400	—	401	479	50	425	638	
ND	630	—	615	735	50	650	715	ATV6A0C63Q6
HD	500	—	495	592	50	520	780	
ND	800	—	776	927	50	830	913	ATV6A0C80Q6
HD	630	—	619	740	50	650	975	
ND	1000	—	969	1158	50	1030	1133	ATV6A0M10Q6
HD	800	—	779	931	50	830	1245	
ND	1200	—	1161	1388	50	1230	1353	ATV6A0M12Q6
HD	1000	—	971	1160	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 690 V 50/60 Hz

ATV9AOP19052



ATV9A0M10Q6

ATV9AOP19053



ATV9A0M12Q6

690 V (-15...10%) IP00 Standard Modular drives (continued) (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		690 V	690 V					
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 48% at 100% load in Normal duty								
ND	110	—	118	141	50	125	150	ATV9A0C11Q6
HD	90	—	100	120	50	105	158	
ND	132	—	138	165	50	145	174	ATV9A0C13Q6
HD	110	—	118	141	50	125	188	
ND	160	—	163	195	50	175	210	ATV9A0C16Q6
HD	132	—	138	165	50	145	218	
ND	200	—	200	239	50	215	258	ATV9A0C20Q6
HD	160	—	163	195	50	175	263	
ND	250	—	255	305	50	275	330	ATV9A0C25Q6
HD	200	—	211	252	50	215	323	
ND	315	—	316	378	50	340	408	ATV9A0C31Q6
HD	250	—	255	305	50	275	413	
ND	400	—	394	471	50	425	510	ATV9A0C40Q6
HD	315	—	316	378	50	340	510	
ND	500	—	495	592	50	520	624	ATV9A0C50Q6
HD	400	—	401	479	50	425	638	
ND	630	—	615	735	50	650	780	ATV9A0C63Q6
HD	500	—	495	592	50	520	780	
ND	800	—	776	927	50	830	996	ATV9A0C80Q6
HD	630	—	619	740	50	650	975	
ND	1000	—	969	1158	50	1030	1236	ATV9A0M10Q6
HD	800	—	779	931	50	830	1245	
ND	1200	—	1161	1388	50	1230	1476	ATV9A0M12Q6
HD	1000	—	971	1160	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2451702).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

Note: Altivar Process Modular Standard drives can be designed as Reduced Height versions for integration in 1.6 m/5.25 ft cabinets.

References

Variable speed drives


Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 400 V 50/60 Hz



ATV6B0C11Q4



ATV6B0C20Q4



ATV6B0C11Q4

400 V (-15...10%) IP00 Modular Low Harmonic drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		400 V	400 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 5% at 100% load in Normal duty								
ND	110	—	175	121	50	211	232	ATV6B0C11Q4
HD	90	—	144	100	50	173	260	
ND	132	—	208	144	50	250	275	ATV6B0C13Q4
HD	110	—	174	121	50	211	317	
ND	160	—	252	174	50	302	332	ATV6B0C16Q4
HD	132	—	208	144	50	250	375	
ND	200	—	313	217	50	370	407	ATV6B0C20Q4
HD	160	—	252	174	50	302	453	
ND	250	—	389	270	50	477	525	ATV6B0C25Q4
HD	200	—	313	217	50	370	555	
ND	315	—	491	340	50	590	649	ATV6B0C31Q4
HD	250	—	389	270	50	477	716	
ND	355	—	553	383	50	660	726	ATV6B0C35Q4
HD	280	—	436	302	50	520	780	
ND	400	—	620	429	50	730	803	ATV6B0C40Q4
HD	315	—	491	340	50	590	885	
ND	450	—	697	483	50	830	913	ATV6B0C45Q4
HD	355	—	553	383	50	660	990	
ND	500	—	775	537	50	900	990	ATV6B0C50Q4
HD	400	—	620	429	50	730	1095	
ND	560	—	868	601	50	1020	1122	ATV6B0C56Q4
HD	450	—	697	483	50	830	1245	
ND	630	—	971	673	50	1140	1254	ATV6B0C63Q4
HD	500	—	775	537	50	900	1350	
ND	710	—	1094	758	50	1260	1386	ATV6B0C71Q4
HD	560	—	868	601	50	1020	1530	
ND	800	—	1227	850	50	1420	1562	ATV6B0C80Q4
HD	630	—	971	673	50	1140	1710	
ND	1000	—	1550	1074	50	1770	1947	ATV6B0M10Q4
HD	800	—	1240	859	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 400 V 50/60 Hz

ATVPro_62317_CPMGU00016



ATV9B0C13Q4

ATVPro_OPI0025



ATV9B0C25Q4

400 V (-15...10%) IP00 Modular Low Harmonic/Regen drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		400 V	400 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 5% at 100% load in Normal duty								
ND	110	—	175	121	50	211	253	ATV9B0C11Q4
HD	90	—	144	100	50	173	260	
ND	132	—	208	144	50	250	300	ATV9B0C13Q4
HD	110	—	174	121	50	211	317	
ND	160	—	252	174	50	302	362	ATV9B0C16Q4
HD	132	—	208	144	50	250	375	
ND	200	—	313	217	50	370	444	ATV9B0C20Q4
HD	160	—	252	174	50	302	453	
ND	250	—	389	270	50	477	572	ATV9B0C25Q4
HD	200	—	313	217	50	370	555	
ND	315	—	491	340	50	590	708	ATV9B0C31Q4
HD	250	—	389	270	50	477	716	
ND	355	—	553	383	50	660	792	ATV9B0C35Q4
HD	280	—	436	302	50	520	780	
ND	400	—	620	429	50	730	876	ATV9B0C40Q4
HD	315	—	491	340	50	590	885	
ND	450	—	697	483	50	830	996	ATV9B0C45Q4
HD	355	—	553	383	50	660	990	
ND	500	—	775	537	50	900	1080	ATV9B0C50Q4
HD	400	—	620	429	50	730	1095	
ND	560	—	868	601	50	1020	1224	ATV9B0C56Q4
HD	450	—	697	483	50	830	1245	
ND	630	—	971	673	50	1140	1368	ATV9B0C63Q4
HD	500	—	775	537	50	900	1350	
ND	710	—	1094	758	50	1260	1512	ATV9B0C71Q4
HD	560	—	868	601	50	1020	1530	
ND	800	—	1227	850	50	1420	1704	ATV9B0C80Q4
HD	630	—	971	673	50	1140	1710	
ND	1000	—	1550	1074	50	1770	1947	ATV9B0M10Q4
HD	800	—	1240	859	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 440 V 50/60 Hz



ATV6B0C31R4



ATV6B0C56R4

ATVPro_CP19026

ATVPro_CP19027

440 V (-15...10%) IP00 Modular Low Harmonic drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		440 V	440 V					
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 5% at 100% load in Normal duty								
ND	110	—	159	121	50	211	232	ATV6B0C11R4
HD	90	—	132	100	50	173	260	
ND	132	—	190	145	50	250	275	ATV6B0C13R4
HD	110	—	159	121	50	211	317	
ND	160	—	229	174	50	302	332	ATV6B0C16R4
HD	132	—	190	145	50	250	375	
ND	200	—	285	217	50	370	407	ATV6B0C20R4
HD	160	—	229	174	50	302	453	
ND	250	—	354	270	50	477	525	ATV6B0C25R4
HD	200	—	285	217	50	370	555	
ND	315	—	446	340	50	590	649	ATV6B0C31R4
HD	250	—	354	270	50	477	716	
ND	355	—	503	383	50	660	726	ATV6B0C35R4
HD	280	—	396	302	50	520	780	
ND	400	—	563	429	50	730	803	ATV6B0C40R4
HD	315	—	446	340	50	590	885	
ND	450	—	634	483	50	830	913	ATV6B0C45R4
HD	355	—	503	383	50	660	990	
ND	500	—	704	537	50	900	990	ATV6B0C50R4
HD	400	—	563	429	50	730	1095	
ND	560	—	789	601	50	1020	1122	ATV6B0C56R4
HD	450	—	634	483	50	830	1245	
ND	630	—	883	673	50	1140	1254	ATV6B0C63R4
HD	500	—	704	537	50	900	1350	
ND	710	—	995	758	50	1260	1386	ATV6B0C71R4
HD	560	—	789	601	50	1020	1530	
ND	800	—	1115	850	50	1420	1562	ATV6B0C80R4
HD	630	—	883	673	50	1140	1710	
ND	1000	—	1408	1073	50	1770	1947	ATV6B0M10R4
HD	800	—	1126	858	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise. For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 440 V 50/60 Hz



ATV9B0C40R4



ATV9B0C63R4

440 V IP00 (-15...10%) Modular Low Harmonic/Regen drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		440 V	440 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 5% at 100% load in Normal duty								
ND	110	—	159	121	50	211	253	ATV9B0C11R4
HD	90	—	132	100	50	173	260	
ND	132	—	190	145	50	250	300	ATV9B0C13R4
HD	110	—	159	121	50	211	317	
ND	160	—	229	174	50	302	362	ATV9B0C16R4
HD	132	—	190	145	50	250	375	
ND	200	—	285	217	50	370	444	ATV9B0C20R4
HD	160	—	229	174	50	302	453	
ND	250	—	354	270	50	477	572	ATV9B0C25R4
HD	200	—	285	217	50	370	555	
ND	315	—	446	340	50	590	708	ATV9B0C31R4
HD	250	—	354	270	50	477	716	
ND	355	—	503	383	50	660	792	ATV9B0C35R4
HD	280	—	396	302	50	520	780	
ND	400	—	563	429	50	730	876	ATV9B0C40R4
HD	315	—	446	340	50	590	885	
ND	450	—	634	483	50	830	996	ATV9B0C45R4
HD	355	—	503	383	50	660	990	
ND	500	—	704	537	50	900	1080	ATV9B0C50R4
HD	400	—	563	429	50	730	1095	
ND	560	—	789	601	50	1020	1224	ATV9B0C56R4
HD	450	—	634	483	50	830	1245	
ND	630	—	883	673	50	1140	1368	ATV9B0C63R4
HD	500	—	704	537	50	900	1350	
ND	710	—	995	758	50	1260	1512	ATV9B0C71R4
HD	560	—	789	601	50	1020	1530	
ND	800	—	1115	850	50	1420	1704	ATV9B0C80R4
HD	630	—	883	673	50	1140	1710	
ND	1000	—	1408	1073	50	1770	1947	ATV9B0M10R4
HD	800	—	1126	858	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise. For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)


Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 480 V 50/60 Hz

ATVPro_CP19028



ATV6B0C45T4

ATVPro_CP19023



ATV6B0C71T4

480 V (-10...10%) IP00 Modular Low Harmonic drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power 480 V	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty								
HD: Heavy duty								
KW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 5% at 100% load in Normal duty								
ND	–	150	148	123	50	211	232	ATV6B0C11T4
HD	–	125	125	104	50	173	260	
ND	–	200	197	164	50	250	275	ATV6B0C13T4
HD	–	150	148	123	50	211	317	
ND	–	250	245	203	50	302	332	ATV6B0C16T4
HD	–	200	197	164	50	250	375	
ND	–	300	292	243	50	370	407	ATV6B0C20T4
HD	–	250	245	203	50	302	453	
ND	–	400	387	322	50	477	525	ATV6B0C25T4
HD	–	300	292	243	50	370	555	
ND	–	500	484	402	50	590	649	ATV6B0C31T4
HD	–	400	387	322	50	477	716	
ND	–	550	533	443	50	660	726	ATV6B0C35T4
HD	–	450	436	362	50	520	780	
ND	–	600	578	480	50	730	803	ATV6B0C40T4
HD	–	500	484	402	50	590	885	
ND	–	650	626	520	50	830	913	ATV6B0C45T4
HD	–	550	533	443	50	660	990	
ND	–	700	674	561	50	900	990	ATV6B0C50T4
HD	–	600	578	480	50	730	1095	
ND	–	800	771	641	50	1020	1122	ATV6B0C56T4
HD	–	650	626	520	50	830	1245	
ND	–	900	862	717	50	1140	1254	ATV6B0C63T4
HD	–	700	674	561	50	900	1350	
ND	–	1000	958	797	50	1260	1386	ATV6B0C71T4
HD	–	800	771	641	50	1020	1530	
ND	–	1100	1049	872	50	1420	1562	ATV6B0C80T4
HD	–	900	862	717	50	1140	1710	
ND	–	1400	1348	1121	50	1770	1947	ATV6B0M10T4
HD	–	1100	1156	961	50	1420	2130	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives


Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 480 V 50/60 Hz



ATV9B0C50T4



ATV9B0C80T4

480 V (-10...10%) IP00 Modular Low Harmonic/Regen drives (1)

Motor Power indicated on rating plate (2)	Line supply			Altivar Process			
	Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
	480 V	480 V					
ND: Normal duty							
HD: Heavy duty							
kW HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications							
THDI ≤ 5% at 100% load in Normal duty							
ND – 150	148	123	50	211	253	ATV9B0C11T4	
HD – 125	125	104	50	173	260		ATV9B0C13T4
ND – 200	197	164	50	250	300		ATV9B0C16T4
HD – 150	148	123	50	211	317		ATV9B0C20T4
ND – 250	245	203	50	302	362		ATV9B0C25T4
HD – 200	197	164	50	250	375		ATV9B0C31T4
ND – 300	292	243	50	370	444		ATV9B0C35T4
HD – 250	245	203	50	302	453		ATV9B0C40T4
ND – 400	387	322	50	477	572		ATV9B0C45T4
HD – 300	292	243	50	370	555		ATV9B0C50T4
ND – 500	484	402	50	590	708		ATV9B0C56T4
HD – 400	387	322	50	477	716		ATV9B0C63T4
ND – 550	533	443	50	660	792		ATV9B0C71T4
HD – 450	436	362	50	520	780		ATV9B0C80T4
ND – 600	578	480	50	730	876		ATV9B0M10T4
HD – 500	484	402	50	590	885		ATV9B0M11T4
ND – 650	626	520	50	830	996		ATV9B0M12T4
HD – 550	533	443	50	660	990		ATV9B0M13T4
ND – 700	674	561	50	900	1080		ATV9B0M14T4
HD – 600	578	480	50	730	1095		ATV9B0M15T4
ND – 800	771	641	50	1020	1224		ATV9B0M16T4
HD – 650	626	520	50	830	1245		ATV9B0M17T4
ND – 900	862	717	50	1140	1368		ATV9B0M18T4
HD – 700	674	561	50	900	1350		ATV9B0M19T4
ND – 1000	958	797	50	1260	1512		ATV9B0M20T4
HD – 800	771	641	50	1020	1530		ATV9B0M21T4
ND – 1100	1049	872	50	1420	1704		ATV9B0M22T4
HD – 900	862	717	50	1140	1710		ATV9B0M23T4
ND – 1400	1348	1121	50	1770	1947		ATV9B0M24T4
HD – 1100	1156	961	50	1420	2130		ATV9B0M25T4

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 500 V 50/60 Hz



ATV6B0C11N6



ATV6B0C25N6



ATV6B0C11N6

500 V (-10...15%) IP00 Modular Low Harmonic drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		500 V	500 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 5% at 100% load in Normal duty								
ND	75	—	98	85	50	125	138	ATV6B0C11N6
HD	55	—	72	62	50	105	158	
ND	90	—	117	101	50	145	160	ATV6B0C13N6
HD	75	—	98	85	50	125	188	
ND	110	—	141	122	50	175	193	ATV6B0C16N6
HD	90	—	117	101	50	145	218	
ND	132	—	169	146	50	215	237	ATV6B0C20N6
HD	110	—	141	122	50	175	263	
ND	160	—	204	176	50	275	303	ATV6B0C25N6
HD	132	—	169	146	50	215	323	
ND	220	—	278	241	50	340	374	ATV6B0C31N6
HD	160	—	204	176	50	275	413	
ND	280	—	352	305	50	425	468	ATV6B0C40N6
HD	220	—	278	241	50	340	510	
ND	355	—	446	386	50	520	572	ATV6B0C50N6
HD	280	—	352	305	50	425	638	
ND	450	—	562	487	50	650	715	ATV6B0C63N6
HD	355	—	446	386	50	520	780	
ND	560	—	701	607	50	830	913	ATV6B0C80N6
HD	450	—	564	488	50	650	975	
ND	710	—	884	766	50	1030	1133	ATV6B0M10N6
HD	560	—	701	607	50	830	1245	
ND	800	—	991	859	50	1230	1353	ATV6B0M12N6
HD	710	—	884	766	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives


Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 500 V 50/60 Hz



ATV9B0C11N6



ATV9B0C25N6

500 V (-10...15%) IP00 Modular Low Harmonic/Regen drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		500 V	500 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 5% at 100% load in Normal duty								
ND	75	—	98	85	50	125	150	ATV9B0C11N6
HD	55	—	72	62	50	105	158	
ND	90	—	117	101	50	145	174	ATV9B0C13N6
HD	75	—	98	85	50	125	188	
ND	110	—	141	122	50	175	210	ATV9B0C16N6
HD	90	—	117	101	50	145	218	
ND	132	—	169	146	50	215	258	ATV9B0C20N6
HD	110	—	141	122	50	175	263	
ND	160	—	204	176	50	275	330	ATV9B0C25N6
HD	132	—	169	146	50	215	323	
ND	220	—	278	241	50	340	408	ATV9B0C31N6
HD	160	—	204	176	50	275	413	
ND	280	—	352	305	50	425	510	ATV9B0C40N6
HD	220	—	278	241	50	340	510	
ND	355	—	446	386	50	520	624	ATV9B0C50N6
HD	280	—	352	305	50	425	638	
ND	450	—	562	487	50	650	780	ATV9B0C63N6
HD	355	—	446	386	50	520	780	
ND	560	—	701	607	50	830	996	ATV9B0C80N6
HD	450	—	564	488	50	650	975	
ND	710	—	884	766	50	1030	1236	ATV9B0M10N6
HD	560	—	701	607	50	830	1245	
ND	800	—	991	859	50	1230	1476	ATV9B0M12N6
HD	710	—	884	766	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 600 V 50/60 Hz



ATV6B0C50T6



ATV6B0C80T6

600 V (-10...10%) IP00 Modular Low Harmonic drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3) 600 V	Apparent power 600 V	Maximum prospective line Isc (4)	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 5% at 100% load in Normal duty								
ND	—	125	102	106	50	125	138	ATV6B0C11T6
HD	—	100	82	86	50	105	158	
ND	—	150	121	126	50	145	160	ATV6B0C13T6
HD	—	125	102	106	50	125	188	
ND	—	175	142	147	50	175	193	ATV6B0C16T6
HD	—	150	121	126	50	145	218	
ND	—	200	161	167	50	215	237	ATV6B0C20T6
HD	—	175	142	147	50	175	263	
ND	—	250	199	207	50	275	303	ATV6B0C25T6
HD	—	200	160	166	50	215	323	
ND	—	350	277	288	50	340	374	ATV6B0C31T6
HD	—	250	199	207	50	275	413	
ND	—	450	355	369	50	425	468	ATV6B0C40T6
HD	—	350	277	288	50	340	510	
ND	—	550	434	451	50	520	572	ATV6B0C50T6
HD	—	450	355	369	50	425	638	
ND	—	650	511	531	50	650	715	ATV6B0C63T6
HD	—	550	434	451	50	520	780	
ND	—	800	628	652	50	830	913	ATV6B0C80T6
HD	—	650	513	533	50	650	975	
ND	—	1000	785	815	50	1030	1133	ATV6B0M10T6
HD	—	800	628	652	50	830	1245	
ND	—	1200	937	973	50	1230	1353	ATV6B0M12T6
HD	—	1000	785	815	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise. For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) For 600V UL certified drives, a higher SCCR is possible under some conditions. Please refer to the Integration Manual PHA2452602 for more details.


References (continued)

Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 600 V 50/60 Hz



ATV9B0C50T6



ATV9B0C80T6

600 V (-10...10%) IP00 Modular Low Harmonic/Regen drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power 600 V	Maximum prospective line Isc (4)	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		600 V	600 V	(4)				
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 5% at 100% load in Normal duty								
ND	—	125	102	50	125	150	ATV9B0C11T6	
HD	—	100	82	50	105	158	ATV9B0C13T6	
ND	—	150	121	50	145	174	ATV9B0C16T6	
HD	—	125	102	50	125	188	ATV9B0C20T6	
ND	—	175	142	50	175	210	ATV9B0C25T6	
HD	—	150	121	50	145	218	ATV9B0C31T6	
ND	—	200	161	50	215	258	ATV9B0C40T6	
HD	—	175	142	50	175	263	ATV9B0C50T6	
ND	—	250	199	50	275	330	ATV9B0C63T6	
HD	—	200	160	50	215	323	ATV9B0C80T6	
ND	—	350	277	50	340	408	ATV9B0M10T6	
HD	—	250	199	50	275	413	ATV9B0M12T6	
ND	—	450	355	50	425	510	ATV9B0M15T6	
HD	—	350	277	50	340	510	ATV9B0M18T6	
ND	—	550	434	50	520	624	ATV9B0M20T6	
HD	—	450	355	50	425	638	ATV9B0M25T6	
ND	—	650	511	50	650	780	ATV9B0M30T6	
HD	—	550	434	50	520	780	ATV9B0M35T6	
ND	—	800	628	50	830	996	ATV9B0M40T6	
HD	—	650	513	50	650	975	ATV9B0M45T6	
ND	—	1000	785	50	1030	1236	ATV9B0M50T6	
HD	—	800	628	50	830	1245	ATV9B0M55T6	
ND	—	1200	937	50	1230	1476	ATV9B0M60T6	
HD	—	1000	785	50	1030	1545	ATV9B0M65T6	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) For 600V UL certified drives, a higher SCCR is possible under some conditions. Please refer to the Integration Manual PHA2452602 for more details.

References (continued)


Variable speed drives

Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 690 V 50/60 Hz

ATVPro_CP19028



ATV6B0M10Q6

ATVPro_CP19023



ATV6B0M12Q6

690 V (-10...+10%) IP00 Modular Low Harmonic drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		690 V	690 V					
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for fluid management								
THDi ≤ 5% at 100% load in Normal duty								
ND	110	—	102	122	50	125	138	ATV6B0C11Q6
HD	90	—	85	101	50	105	158	
ND	132	—	122	146	50	145	160	ATV6B0C13Q6
HD	110	—	102	122	50	125	188	
ND	160	—	148	177	50	175	193	ATV6B0C16Q6
HD	132	—	122	146	50	145	218	
ND	200	—	183	219	50	215	237	ATV6B0C20Q6
HD	160	—	148	177	50	175	263	
ND	250	—	228	273	50	275	303	ATV6B0C25Q6
HD	200	—	183	219	50	215	323	
ND	315	—	287	343	50	340	374	ATV6B0C31Q6
HD	250	—	228	273	50	275	413	
ND	400	—	363	434	50	425	468	ATV6B0C40Q6
HD	315	—	287	343	50	340	510	
ND	500	—	453	541	50	520	572	ATV6B0C50Q6
HD	400	—	362	433	50	425	638	
ND	630	—	568	678	50	650	715	ATV6B0C63Q6
HD	500	—	453	541	50	520	780	
ND	800	—	718	859	50	830	913	ATV6B0C80Q6
HD	630	—	569	680	50	650	975	
ND	1000	—	898	1073	50	1030	1133	ATV6B0M10Q6
HD	800	—	718	859	50	830	1245	
ND	1200	—	1078	1288	50	1230	1353	ATV6B0M12Q6
HD	1000	—	898	1073	50	1030	1545	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives


Altivar Process Modular

Drives for cabinet integration

Three-phase supply voltage: 690 V 50/60 Hz



ATV9B0M10Q6



ATV9B0M12Q6

690 V (-10...10%) IP00 Modular Low Harmonic/Regen drives (1)

Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND:	Normal duty	690 V	690 V					
HD:	Heavy duty							
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular for demanding applications								
THDi ≤ 5% at 100% load in Normal duty								
ND	110	—	102	122	50	125	150	ATV9B0C11Q6
HD	90	—	85	101	50	105	158	ATV9B0C13Q6
ND	132	—	122	146	50	145	174	ATV9B0C16Q6
HD	110	—	102	122	50	125	188	ATV9B0C20Q6
ND	160	—	148	177	50	175	210	ATV9B0C25Q6
HD	132	—	122	146	50	145	218	ATV9B0C31Q6
ND	200	—	183	219	50	215	258	ATV9B0C40Q6
HD	160	—	148	177	50	175	263	ATV9B0C50Q6
ND	250	—	228	273	50	275	330	ATV9B0C63Q6
HD	200	—	183	219	50	215	323	ATV9B0C80Q6
ND	315	—	287	343	50	340	408	ATV9B0C10Q6
HD	250	—	228	273	50	275	413	ATV9B0M10Q6
ND	400	—	363	434	50	425	510	ATV9B0M12Q6
HD	315	—	287	343	50	340	510	ATV9B0M12Q6
ND	500	—	453	541	50	520	624	ATV9B0M12Q6
HD	400	—	362	433	50	425	638	ATV9B0M12Q6
ND	630	—	568	678	50	650	780	ATV9B0M12Q6
HD	500	—	453	541	50	520	780	ATV9B0M12Q6
ND	800	—	718	859	50	830	996	ATV9B0M12Q6
HD	630	—	569	680	50	650	975	ATV9B0M12Q6
ND	1000	—	898	1073	50	1030	1236	ATV9B0M12Q6
HD	800	—	718	859	50	830	1245	ATV9B0M12Q6
ND	1200	—	1078	1288	50	1230	1476	ATV9B0M12Q6
HD	1000	—	898	1073	50	1030	1545	ATV9B0M12Q6

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual PHA2452602).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 400 V 50/60 Hz

ATV6L_CP20132



ATV6L0C13Q4

ATV6L_CP20133



ATV6L0C50Q4

400 V (-15...10%) IP00 Modular Liquid-cooled drives (1)							
Motor		Line supply			Altivar Process		
Power indicated on rating plate (2)		Line current (3)	Apparent power 400 V	Maximum prospective line Isc 400 V	Maximum continuous current (2)	Max. transient current for 60 s	Reference
ND: Normal duty							
HD: Heavy duty							
kW	HP	A	kVA	kA	A	A	
Altivar Process Modular Liquid-cooled							
THDi ≤ 48% at 100% load in Normal duty with 6-pulse supply (4)							
ND	132	-	244	169	50	250	275
HD	110	-	210	145	50	211	317
ND	160	-	287	199	50	302	332
HD	132	-	244	169	50	250	375
ND	200	-	350	242	50	370	407
HD	160	-	287	199	50	302	453
ND	250	-	429	297	50	477	525
HD	200	-	350	242	50	370	555
ND	315	-	536	371	50	590	649
HD	250	-	429	297	50	477	716
ND	400	-	684	474	50	730	803
HD	315	-	549	380	50	590	885
ND	500	-	847	587	50	900	990
HD	400	-	684	474	50	730	1095
ND	630	-	1056	732	50	1140	1254
HD	500	-	847	587	50	900	1350
ND	800	-	1335	925	50	1420	1562
HD	630	-	1062	736	50	1140	1710
ND	900	-	1502	1041	50	1600	1760
HD	710	-	1188	823	50	1260	1890
ND	1000	-	1669	1156	50	1770	1947
HD	800	-	1339	928	50	1420	2130
ND	1200	-	2005	1389	50	2140	2354
HD	1000	-	1669	1156	50	1770	2655
ND	1500	-	2513	1741	50	2680	2948
HD	1200	-	2005	1389	50	2140	3210
ND	1800	-	3028	2098	50	3200	3520
HD	1400	-	2341	1622	50	2470	3705

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤ 9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 400 V 50/60 Hz



ATV9L0C13Q4



ATV9L0C50Q4

ATV9L_Cp20132

ATV9L_Cp20133

400 V (-15...10%) IP00 Modular Liquid-cooled drives (1)

Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		400 V	400 V					
HD: Heavy duty								
kW		HP	A	kVA	kA	A	A	
Altivar Process Modular Liquid-cooled								
THDi ≤48% at 100% load in Normal duty with 6-pulse supply (4)								
ND	132	-	244	169	50	250	300	ATV9L0C13Q4
HD	110	-	210	145	50	211	317	
ND	160	-	287	199	50	302	362	ATV9L0C16Q4
HD	132	-	244	169	50	250	375	
ND	200	-	350	242	50	370	444	ATV9L0C20Q4
HD	160	-	287	199	50	302	453	
ND	250	-	429	297	50	477	572	ATV9L0C25Q4
HD	200	-	350	242	50	370	555	
ND	315	-	536	371	50	590	708	ATV9L0C31Q4
HD	250	-	429	297	50	477	716	
ND	400	-	684	474	50	730	876	ATV9L0C40Q4
HD	315	-	549	380	50	590	885	
ND	500	-	847	587	50	900	1080	ATV9L0C50Q4
HD	400	-	684	474	50	730	1095	
ND	630	-	1056	732	50	1140	1368	ATV9L0C63Q4
HD	500	-	847	587	50	900	1350	
ND	800	-	1335	925	50	1420	1704	ATV9L0C80Q4
HD	630	-	1062	736	50	1140	1710	
ND	900	-	1502	1041	50	1600	1920	ATV9L0C90Q4
HD	710	-	1188	823	50	1260	1890	
ND	1000	-	1669	1156	50	1770	2124	ATV9L0M10Q4
HD	800	-	1339	928	50	1420	2130	
ND	1200	-	2005	1389	50	2140	2568	ATV9L0M12Q4
HD	1000	-	1669	1156	50	1770	2655	
ND	1500	-	2513	1741	50	2680	3216	ATV9L0M15Q4
HD	1200	-	2005	1389	50	2140	3210	
ND	1800	-	3028	2098	50	3200	3840	ATV9L0M18Q4
HD	1400	-	2341	1622	50	2470	3705	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 440 V 50/60 Hz

ATVM_CP2014



ATV6L0C80R4

ATVM_CP20135



ATV6L0M10R4

440 V (-15...10%) IP00 Modular Liquid-cooled drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
		440 V	440 V					
ND: Normal duty								
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular Liquid-cooled								
THDi ≤48% at 100% load in Normal duty with 6-pulse supply (4)								
ND	132	-	228	174	50	250	275	ATV6L0C13R4
HD	110	-	198	151	50	211	317	ATV6L0C16R4
ND	160	-	266	203	50	302	332	ATV6L0C20R4
HD	132	-	228	174	50	250	375	
ND	200	-	323	246	50	370	407	ATV6L0C25R4
HD	160	-	266	203	50	302	453	
ND	250	-	394	300	50	477	525	ATV6L0C31R4
HD	200	-	323	246	50	370	555	
ND	315	-	490	373	50	590	649	ATV6L0C40R4
HD	250	-	394	300	50	477	716	
ND	400	-	627	478	50	730	803	ATV6L0C50R4
HD	315	-	506	386	50	590	885	
ND	500	-	774	590	50	900	990	ATV6L0C63R4
HD	400	-	627	478	50	730	1095	
ND	630	-	963	734	50	1140	1254	ATV6L0C80R4
HD	500	-	774	590	50	900	1350	
ND	800	-	1217	927	50	1420	1562	ATV6L0C90R4
HD	630	-	969	738	50	1140	1710	
ND	900	-	1365	1040	50	1600	1760	ATV6L0M10R4
HD	710	-	1083	825	50	1260	1890	
ND	1000	-	1518	1157	50	1770	1947	ATV6L0M12R4
HD	800	-	1220	930	50	1420	2130	
ND	1200	-	1820	1387	50	2140	2354	ATV6L0M15R4
HD	1000	-	1518	1157	50	1770	2655	
ND	1500	-	2279	1737	50	2680	2948	ATV6L0M18R4
HD	1200	-	1820	1387	50	2140	3210	
ND	1800	-	2741	2089	50	3200	3520	ATV6L0M20R4
HD	1400	-	2125	1619	50	2470	3705	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 440 V 50/60 Hz



ATV9L0C80R4



ATV9L0M10R4

ATVM_CFP20134

ATVM_LCP20135

440 V (-15...10%) IP00 Modular Liquid-cooled drives (1)

Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty		440 V	440 V					
HD: Heavy duty								
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular Liquid-cooled								
THDI ≤48% at 100% load in Normal duty with 6-pulse supply (4)								
ND	132	-	228	174	50	250	300	ATV9L0C13R4
HD	110	-	198	151	50	211	317	
ND	160	-	266	203	50	302	362	ATV9L0C16R4
HD	132	-	228	174	50	250	375	
ND	200	-	323	246	50	370	444	ATV9L0C20R4
HD	160	-	266	203	50	302	453	
ND	250	-	394	300	50	477	572	ATV9L0C25R4
HD	200	-	323	246	50	370	555	
ND	315	-	490	373	50	590	708	ATV9L0C31R4
HD	250	-	394	300	50	477	716	
ND	400	-	627	478	50	730	876	ATV9L0C40R4
HD	315	-	506	386	50	590	885	
ND	500	-	774	590	50	900	1080	ATV9L0C50R4
HD	400	-	627	478	50	730	1095	
ND	630	-	963	734	50	1140	1368	ATV9L0C63R4
HD	500	-	774	590	50	900	1350	
ND	800	-	1217	927	50	1420	1704	ATV9L0C80R4
HD	630	-	969	738	50	1140	1710	
ND	900	-	1365	1040	50	1600	1920	ATV9L0C90R4
HD	710	-	1083	825	50	1260	1890	
ND	1000	-	1518	1157	50	1770	2124	ATV9L0M10R4
HD	800	-	1220	930	50	1420	2130	
ND	1200	-	1820	1387	50	2140	2568	ATV9L0M12R4
HD	1000	-	1518	1157	50	1770	2655	
ND	1500	-	2279	1737	50	2680	3216	ATV9L0M15R4
HD	1200	-	1820	1387	50	2140	3210	
ND	1800	-	2741	2089	50	3200	3840	ATV9L0M18R4
HD	1400	-	2125	1619	50	2470	3705	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation. The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDI ≤9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 480 V 50/60 Hz

ATV6L_CP2036



ATV6L0M15T4

ATV6L_CP2037



ATV6L0M18T4

480 V (-15...10%) IP00 Modular Liquid-cooled drives (1)

Motor Power indicated on rating plate (2)	Line supply			Altivar Process			Reference
	Line current (3) 480 V	Apparent power 480 V	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s		
ND: Normal duty							
HD: Heavy duty							
kW	HP	A	kVA	kA	A	A	
Altivar Process Modular Liquid-cooled							
THDi ≤48% at 100% load in Normal duty with 6-pulse supply (4)							
ND -	200	230	191	50	250	275	ATV6L0C13T4
HD -	150	183	152	50	211	317	
ND -	250	278	231	50	302	332	ATV6L0C16T4
HD -	200	230	191	50	250	375	
ND -	300	327	272	50	370	407	ATV6L0C20T4
HD -	250	278	231	50	302	453	
ND -	400	425	353	50	477	525	ATV6L0C25T4
HD -	300	327	272	50	370	555	
ND -	500	527	438	50	590	649	ATV6L0C31T4
HD -	400	425	353	50	477	716	
ND -	600	638	530	50	730	803	ATV6L0C40T4
HD -	500	540	449	50	590	885	
ND -	700	738	614	50	900	990	ATV6L0C50T4
HD -	600	638	530	50	730	1095	
ND -	900	938	780	50	1140	1254	ATV6L0C63T4
HD -	700	738	614	50	900	1350	
ND -	1100	1148	954	50	1420	1562	ATV6L0C80T4
HD -	900	944	785	50	1140	1710	
ND -	1300	1345	1118	50	1600	1760	ATV6L0C90T4
HD -	1000	1045	869	50	1260	1890	
ND -	1400	1451	1206	50	1770	1947	ATV6L0M10T4
HD -	1100	1151	957	50	1420	2130	
ND -	1700	1761	1464	50	2140	2354	ATV6L0M12T4
HD -	1400	1451	1206	50	1770	2655	
ND -	2200	2282	1897	50	2680	2948	ATV6L0M15T4
HD -	1700	1761	1464	50	2140	3210	
ND -	2500	2598	2160	50	3200	3520	ATV6L0M18T4
HD -	2000	2073	1723	50	2470	3705	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 480 V 50/60 Hz

ATV9LCP20136



ATV9LOM15T4

ATV9LCP20137



ATV9LOM18T4

480 V (-15...10%) IP00 Modular Liquid-cooled drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty HD: Heavy duty		480 V	480 V					
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular Liquid-cooled								
THDi ≤48% at 100% load in Normal duty with 6-pulse supply (4)								
ND	-	200	230	191	50	250	300	ATV9L0C13T4
HD	-	150	183	152	50	211	317	
ND	-	250	278	231	50	302	362	ATV9L0C16T4
HD	-	200	230	191	50	250	375	
ND	-	300	327	272	50	370	444	ATV9L0C20T4
HD	-	250	278	231	50	302	453	
ND	-	400	425	353	50	477	572	ATV9L0C25T4
HD	-	300	327	272	50	370	555	
ND	-	500	527	438	50	590	708	ATV9L0C31T4
HD	-	400	425	353	50	477	716	
ND	-	600	638	530	50	730	876	ATV9L0C40T4
HD	-	500	540	449	50	590	885	
ND	-	700	738	614	50	900	1080	ATV9L0C50T4
HD	-	600	638	530	50	730	1095	
ND	-	900	938	780	50	1140	1368	ATV9L0C63T4
HD	-	700	738	614	50	900	1350	
ND	-	1100	1148	954	50	1420	1704	ATV9L0C80T4
HD	-	900	944	785	50	1140	1710	
ND	-	1300	1345	1118	50	1600	1920	ATV9L0C90T4
HD	-	1000	1045	869	50	1260	1890	
ND	-	1400	1451	1206	50	1770	2124	ATV9L0M10T4
HD	-	1100	1151	957	50	1420	2130	
ND	-	1700	1761	1464	50	2140	2568	ATV9L0M12T4
HD	-	1400	1451	1206	50	1770	2655	
ND	-	2200	2282	1897	50	2680	3216	ATV9L0M15T4
HD	-	1700	1761	1464	50	2140	3210	
ND	-	2500	2598	2160	50	3200	3840	ATV9L0M18T4
HD	-	2000	2073	1723	50	2470	3705	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 500 V 50/60 Hz

ATV6-CP20132



ATV6L0C20N6

ATV6-CP20133



ATV6L0C71N6

500 V (-10...15%) IP00 Modular Liquid-cooled drives (1)							
Motor		Line supply			Altivar Process		
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference
ND: Normal duty HD: Heavy duty		500 V	500 V				
kW	HP	A	kVA	kA	A	A	
Altivar Process Modular Liquid-cooled							
THDi ≤ 48% at 100% load in Normal duty with 6-pulse supply (4)							
ND	132	-	196	170	50	215	237
HD	110	-	169	146	50	175	263
ND	200	-	281	243	50	308	339
HD	160	-	230	199	50	240	360
ND	220	-	307	266	50	340	374
HD	180	-	256	222	50	275	413
ND	250	-	344	298	50	425	468
HD	220	-	307	266	50	340	510
ND	315	-	429	372	50	480	528
HD	250	-	344	298	50	384	576
ND	400	-	549	475	50	590	649
HD	315	-	442	383	50	480	720
ND	500	-	679	588	50	740	814
HD	400	-	549	475	50	590	885
ND	630	-	846	733	50	930	1023
HD	500	-	679	588	50	740	1110
ND	800	-	1070	927	50	1230	1353
HD	710	-	957	829	50	1030	1545
ND	1000	-	1335	1156	50	1425	1568
HD	800	-	1070	927	50	1130	1695
ND	1200	-	1603	1388	50	1620	1782
HD	900	-	1204	1043	50	1330	1995
ND	1300	-	1737	1504	50	1820	2002
HD	1000	-	1335	1156	50	1425	2138
ND	1600	-	2141	1854	50	2220	2442
HD	1200	-	1602	1387	50	1720	2580
ND	1900	-	2550	2208	50	2620	2882
HD	1500	-	2005	1736	50	2120	3180

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.
The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤ 9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 500 V 50/60 Hz

ATVM_GP20132



ATV9L0C20N6

ATVM_GP20133



ATV9L0C71N6

500 V (-10...15%) IP00 Modular Liquid-cooled drives (1).

Motor	Line supply			Altivar Process				
	Power indicated on rating plate (2)	Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty HD: Heavy duty	500 V	500 V						
	kW	HP	A	kVA	kA	A	A	
Altivar Process Modular Liquid-cooled								
THDi ≤ 48% at 100% load in Normal duty with 6-pulse supply (4)								
ND	132	-	196	170	50	215	258	ATV9L0C20N6
HD	110	-	169	146	50	175	263	
ND	200	-	281	243	50	308	370	ATV9L0C28N6
HD	160	-	230	199	50	240	360	
ND	220	-	307	266	50	340	408	ATV9L0C31N6
HD	180	-	256	222	50	275	413	
ND	250	-	344	298	50	425	510	ATV9L0C40N6
HD	220	-	307	266	50	340	510	
ND	315	-	429	372	50	480	576	ATV9L0C45N6
HD	250	-	344	298	50	384	576	
ND	400	-	549	475	50	590	708	ATV9L0C56N6
HD	315	-	442	383	50	480	720	
ND	500	-	679	588	50	740	888	ATV9L0C71N6
HD	400	-	549	475	50	590	885	
ND	630	-	846	733	50	930	1116	ATV9L0C90N6
HD	500	-	679	588	50	740	1110	
ND	800	-	1070	927	50	1230	1476	ATV9L0M12N6
HD	710	-	957	829	50	1030	1545	
ND	1000	-	1335	1156	50	1425	1710	ATV9L0M14N6
HD	800	-	1070	927	50	1130	1695	
ND	1200	-	1603	1388	50	1620	1944	ATV9L0M16N6
HD	900	-	1204	1043	50	1330	1995	
ND	1300	-	1737	1504	50	1820	2184	ATV9L0M18N6
HD	1000	-	1335	1156	50	1425	2138	
ND	1600	-	2141	1854	50	2220	2664	ATV9L0M22N6
HD	1200	-	1602	1387	50	1720	2580	
ND	1900	-	2550	2208	50	2620	3144	ATV9L0M26N6
HD	1500	-	2005	1736	50	2120	3180	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 600 V 50/60 Hz

ATV6M.CP20134



ATV6L0M12T6

ATV6M.CP20135



ATV6L0M18T6

600 V (-15...10%) IP00 Modular Liquid-cooled drives (1)							
Motor		Line supply			Altivar Process		
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference
ND: Normal duty HD: Heavy duty		600 V	600 V				
kW	HP	A	kVA	kA	A	A	
Altivar Process Modular Liquid-cooled							
THDi ≤ 48% at 100% load in Normal duty with 6-pulse supply (4)							
ND	-	200	184	191	50	215	237
HD	-	150	146	152	50	175	263
ND	-	300	261	271	50	308	339
HD	-	200	184	191	50	240	360
ND	-	350	302	314	50	340	374
HD	-	250	223	232	50	275	413
ND	-	450	381	396	50	425	468
HD	-	350	302	314	50	340	510
ND	-	500	422	439	50	480	528
HD	-	400	340	353	50	384	576
ND	-	600	512	532	50	590	649
HD	-	500	434	451	50	480	720
ND	-	700	592	615	50	740	814
HD	-	600	512	532	50	590	885
ND	-	900	751	780	50	930	1023
HD	-	700	592	615	50	740	1110
ND	-	1200	996	1035	50	1230	1353
HD	-	1000	838	871	50	1030	1545
ND	-	1400	1159	1204	50	1425	1568
HD	-	1100	919	955	50	1130	1695
ND	-	1600	1325	1377	50	1620	1782
HD	-	1300	1081	1123	50	1330	1995
ND	-	1800	1490	1548	50	1820	2002
HD	-	1400	1162	1208	50	1425	2138
ND	-	2200	1823	1895	50	2220	2442
HD	-	1700	1409	1464	50	1720	2580
ND	-	2600	2156	2241	50	2620	2882
HD	-	2100	1740	1808	50	2120	3180

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 600 V 50/60 Hz

ATV9L_Cp20134



ATV9LOM12T6

ATV9L_Cp20135



ATV9LOM18T6

600 V (-15...10%) IP00 Modular Liquid-cooled drives (1)

Motor	Line supply			Altivar Process			
	Power indicated on rating plate (2)	Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference
ND: Normal duty HD: Heavy duty	600 V	600 V					
kW	HP	A	kVA	kA	A	A	
Altivar Process Modular Liquid-cooled							
THDi ≤ 48% at 100% load in Normal duty with 6-pulse supply (4)							
ND -	200	184	191	50	215	258	ATV9L0C20T6
HD -	150	146	152	50	175	263	
ND -	300	261	271	50	308	370	ATV9L0C28T6
HD -	200	184	191	50	240	360	
ND -	350	302	314	50	340	408	ATV9L0C31T6
HD -	250	223	232	50	275	413	
ND -	450	381	396	50	425	510	ATV9L0C40T6
HD -	350	302	314	50	340	510	
ND -	500	422	439	50	480	576	ATV9L0C45T6
HD -	400	340	353	50	384	576	
ND -	600	512	532	50	590	708	ATV9L0C56T6
HD -	500	434	451	50	480	720	
ND -	700	592	615	50	740	888	ATV9L0C71T6
HD -	600	512	532	50	590	885	
ND -	900	751	780	50	930	1116	ATV9L0C90T6
HD -	700	592	615	50	740	1110	
ND -	1200	996	1035	50	1230	1476	ATV9L0M12T6
HD -	1000	838	871	50	1030	1545	
ND -	1400	1159	1204	50	1425	1710	ATV9L0M14T6
HD -	1100	919	955	50	1130	1695	
ND -	1600	1325	1377	50	1620	1944	ATV9L0M16T6
HD -	1300	1081	1123	50	1330	1995	
ND -	1800	1490	1548	50	1820	2184	ATV9L0M18T6
HD -	1400	1162	1208	50	1425	2138	
ND -	2200	1823	1895	50	2220	2664	ATV9L0M22T6
HD -	1700	1409	1464	50	1720	2580	
ND -	2600	2156	2241	50	2620	3144	ATV9L0M26T6
HD -	2100	1740	1808	50	2120	3180	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤ 9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 690 V 50/60 Hz

ATV6L_CPM20136



ATV6L0M22Q6

ATV6L_CPM20136



ATV6L0M26Q6

690 V (-15...10%) IP00 Modular Liquid-cooled drives (1)								
Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty HD: Heavy duty		690 V	690 V					
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular Liquid-cooled								
THDi ≤ 48% at 100% load in Normal duty with 6-pulse supply (4)								
ND	200	-	218	261	50	215	237	ATV6L0C20Q6
HD	160	-	184	220	50	175	263	
ND	280	-	290	347	50	308	339	ATV6L0C28Q6
HD	220	-	236	282	50	240	360	
ND	315	-	322	385	50	340	374	ATV6L0C31Q6
HD	250	-	262	313	50	275	413	
ND	400	-	399	477	50	425	468	ATV6L0C40Q6
HD	315	-	322	385	50	340	510	
ND	450	-	446	533	50	480	528	ATV6L0C45Q6
HD	355	-	359	429	50	384	576	
ND	560	-	563	673	50	590	649	ATV6L0C56Q6
HD	450	-	462	552	50	480	720	
ND	710	-	700	837	50	740	814	ATV6L0C71Q6
HD	560	-	563	673	50	590	885	
ND	900	-	875	1046	50	930	1023	ATV6L0C90Q6
HD	710	-	700	837	50	740	1110	
ND	1200	-	1260	1506	50	1230	1353	ATV6L0M12Q6
HD	1000	-	976	1166	50	1030	1545	
ND	1400	-	1355	1619	50	1425	1568	ATV6L0M14Q6
HD	1100	-	1070	1279	50	1130	1695	
ND	1600	-	1547	1849	50	1620	1782	ATV6L0M16Q6
HD	1300	-	1262	1508	50	1330	1995	
ND	1800	-	1740	2080	50	1820	2002	ATV6L0M18Q6
HD	1400	-	1357	1622	50	1425	2138	
ND	2200	-	2128	2543	50	2220	2442	ATV6L0M22Q6
HD	1700	-	1644	1965	50	1720	2580	
ND	2600	-	2517	3008	50	2620	2882	ATV6L0M26Q6
HD	2100	-	2030	2426	50	2120	3180	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.
The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.
(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤ 9%.

References (continued)

Variable speed drives

Altivar Process Modular

Modular Liquid-cooled drives

Three-phase supply voltage: 690 V 50/60 Hz

ATV9L_CP20136



ATV9L0M22Q6

ATV9L_CP20136



ATV9L0M26Q6

690 V (-15...10%) IP00 Modular Liquid-cooled drives (1)

Motor		Line supply			Altivar Process			
Power indicated on rating plate (2)		Line current (3)	Apparent power 690 V	Maximum prospective line Isc	Maximum continuous current (2)	Max. transient current for 60 s	Reference	
ND: Normal duty	690 V	HD: Heavy duty	690 V					
kW	HP	A	kVA	kA	A	A		
Altivar Process Modular Liquid-cooled								
THDi ≤ 48% at 100% load in Normal duty with 6-pulse supply (4)								
ND	200	-	218	261	50	215	258	ATV9L0C20Q6
HD	160	-	184	220	50	175	263	
ND	280	-	290	347	50	308	370	ATV9L0C28Q6
HD	220	-	236	282	50	240	360	
ND	315	-	322	385	50	340	408	ATV9L0C31Q6
HD	250	-	262	313	50	275	413	
ND	400	-	399	477	50	425	510	ATV9L0C40Q6
HD	315	-	322	385	50	340	510	
ND	450	-	446	533	50	480	576	ATV9L0C45Q6
HD	355	-	359	429	50	384	576	
ND	560	-	563	673	50	590	708	ATV9L0C56Q6
HD	450	-	462	552	50	480	720	
ND	710	-	700	837	50	740	888	ATV9L0C71Q6
HD	560	-	563	673	50	590	885	
ND	900	-	875	1046	50	930	1116	ATV9L0C90Q6
HD	710	-	700	837	50	740	1110	
ND	1200	-	1260	1506	50	1230	1476	ATV9L0M12Q6
HD	1000	-	976	1166	50	1030	1545	
ND	1400	-	1355	1619	50	1425	1710	ATV9L0M14Q6
HD	1100	-	1070	1279	50	1130	1695	
ND	1600	-	1547	1849	50	1620	1944	ATV9L0M16Q6
HD	1300	-	1262	1508	50	1330	1995	
ND	1800	-	1740	2080	50	1820	2184	ATV9L0M18Q6
HD	1400	-	1357	1622	50	1425	2138	
ND	2200	-	2128	2543	50	2220	2664	ATV9L0M22Q6
HD	1700	-	1644	1965	50	1720	2580	
ND	2600	-	2517	3008	50	2620	3144	ATV9L0M26Q6
HD	2100	-	2030	2426	50	2120	3180	

(1) Integrated motor chokes allowing a shielded motor cable length up to 300 m/984 ft in category C3.

(2) These values are given for a nominal switching frequency of 2.5 kHz for use in continuous operation.

The switching frequency is adjustable from 2 to 4.9 kHz for all ratings.

Above 2.5 kHz, the drive will automatically reduce the switching frequency in the event of an excessive temperature rise.

For continuous operation above the nominal switching frequency, derate the nominal drive current (see the derating curves in the Integration Manual).

(3) Typical value for the indicated motor power and for the maximum prospective line Isc.

(4) APM-L architecture is ready for 12-pulse supply, which allows a THDi ≤ 9%.

Variable speed drives

Altivar Process Modular

Braking units 400 V power supply

Standard drives



MODBUOC16Q4APM

Braking units 400 V power supply										
Drive		Braking unit								
Nominal power		Reference	Power rating		Minimum resistor value	Braking power			Reference	
ND: Normal duty	HD: Heavy duty		kW	HP		Cycle (1)	2	3		
400 V power supply - Standard drives										
ND 110	—	ATV9A0C11Q4	160	—	3x 6.7	198	116.16	75	MODBUOC16Q4APM	
HD 90	—									
ND 132	—	ATV9A0C13Q4								
HD 110	—									
ND 160	—	ATV9A0C16Q4								
HD 132	—									
ND 200	—	ATV9A0C20Q4	315	—	3x 3.35	375	220	130	MODBUOC31Q4APM	
HD 160	—									
ND 250	—	ATV9A0C25Q4								
HD 200	—									
ND 315	—	ATV9A0C31Q4								
HD 250	—									
ND 355	—	ATV9A0C35Q4	500	—	3x 2.23	600	352	225	MODBUOC50Q4APM	
HD 280	—									
ND 400	—	ATV9A0C40Q4								
HD 315	—									
ND 450	—	ATV9A0C45Q4								
HD 355	—									
ND 500	—	ATV9A0C50Q4								
HD 400	—									
ND 560	—	ATV9A0C56Q4	630	—	6x 3.35	750	440	260	MODBUOC63Q4APM	
HD 450	—									
ND 630	—	ATV9A0C63Q4								
HD 500	—									
ND 710	—	ATV9A0C71Q4	800	—	6x 2,68 ou 3x 2,23 +	945	554,4	355	MODBUOC80Q4APM	
HD 560	—									
ND 800	—	ATV9A0C80Q4								
HD 630	—									
ND 1000	—	ATV9A0M10Q4								
HD 800	—									

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)

Variable speed drives

Altivar Process Modular

Braking units 400 V power supply

Low Harmonic/Regenerative drives



ATV9B0C19Q39B

MODBUOC31Q4APM

Braking units 400 V power supply (continued)

Drive		Braking unit			Reference	Power rating	Minimum resistor value	Braking power			Reference
Nominal power		ND: Normal duty	HD: Heavy duty	Cycle (1)				1	2	3	
kW	HP			kW	HP	Ω					
400 V power supply - Low Harmonic/Regenerative drives											
ND	110	–	ATV9B0C11Q4	160	–	3x 6.7	198	116.16	75	MODBUOC16Q4APM	
HD	90	–									
ND	132	–	ATV9B0C13Q4								
HD	110	–									
ND	160	–	ATV9B0C16Q4								
HD	132	–									
ND	200	–	ATV9B0C20Q4	315	–	3x 3.35	375	220	130	MODBUOC31Q4APM	
HD	160	–									
ND	250	–	ATV9B0C25Q4								
HD	200	–									
ND	315	–	ATV9B0C31Q4								
HD	250	–									
ND	355	–	ATV9B0C35Q4	500	–	3x 2.23	600	352	225	MODBUOC50Q4APM	
HD	280	–									
ND	400	–	ATV9B0C40Q4								
HD	315	–									
ND	450	–	ATV9B0C45Q4								
HD	355	–									
ND	500	–	ATV9B0C50Q4								
HD	400	–									
ND	560	–	ATV9B0C56Q4								
HD	450	–									
ND	630	–	ATV9B0C63Q4								
HD	500	–									
ND	710	–	ATV9B0C71Q4								
HD	560	–									
ND	800	–	ATV9B0C80Q4								
HD	630	–									
ND	1000	–	ATV9B0M10Q4								
HD	800	–									

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)

Variable speed drives

Altivar Process Modular

Braking units 400 V power supply

Liquid-cooled drives



ATV9L0C13Q4

MODBUOC50Q4APM

Braking units 400 V power supply (continued)											
Drive		Braking unit									
Nominal power		Reference	Power rating		Minimum resistor value	Braking power			Reference		
ND: Normal duty	HD: Heavy duty		kW	HP		kW	HP	Ω	Cycle (1)		
									1	2	3
400 V power supply - Liquid-cooled drives											
ND	132	-	ATV9L0C13Q4	160	-	3x 6.7	198	116.16	75	MODBUOC16Q4APM	
HD	110	-									
ND	160	-	ATV9L0C16Q4								
HD	132	-									
ND	200	-	ATV9L0C20Q4	315	-	3x 3.35	375	220	130	MODBUOC31Q4APM	
HD	160	-									
ND	250	-	ATV9L0C25Q4								
HD	200	-									
ND	315	-	ATV9L0C31Q4								
HD	250	-									
ND	400	-	ATV9L0C40Q4	500	-	3x 2.23	600	352	225	MODBUOC50Q4APM	
HD	315	-									
ND	500	-	ATV9L0C50Q4								
HD	400	-									
ND	630	-	ATV9L0C63Q4	630	-	6x 3.35	750	440	260	MODBUOC63Q4APM	
HD	500	-									
ND	800	-	ATV9L0C80Q4	800	-	6x 2.68 or 3x 2.23	945	554.4	355	MODBUOC80Q4APM	
HD	630	-									
ND	900	-	ATV9L0C90Q4			+ 3x 3.35					
HD	710	-									
ND	1000	-	ATV9L0M10Q4								
HD	800	-									
ND	1200	-	ATV9L0M12Q4								
HD	1000	-									
ND	1500	-	ATV9L0M15Q4								
HD	1200	-									
ND	1800	-	ATV9L0M18Q4								
HD	1400	-									

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)

Variable speed drives

Altivar Process Modular

Braking units 440 V power supply

Standard drives



ATV9A0C16R4APM

MODBUOC16R4APM

Braking units 440 V power supply										
Drive		Braking unit								
Nominal power		Reference	Power rating		Minimum resistor value	Braking power			Reference	
ND: Normal duty	HD: Heavy duty		kW	HP		Cycle (1)	1	2	3	
					Ω					
440 V power supply - Standard drives										
ND	110	—	ATV9A0C11R4	160	—	3x 6.7	198	116.16	75	MODBUOC16R4APM
HD	90	—								
ND	132	—	ATV9A0C13R4							
HD	110	—								
ND	160	—	ATV9A0C16R4							
HD	132	—								
ND	200	—	ATV9A0C20R4	315	—	3x 3.35	375	220	130	MODBUOC31R4APM
HD	160	—								
ND	250	—	ATV9A0C25R4							
HD	200	—								
ND	315	—	ATV9A0C31R4							
HD	250	—								
ND	355	—	ATV9A0C35R4	500	—	3x 2.23	600	352	225	MODBUOC50R4APM
HD	280	—								
ND	400	—	ATV9A0C40R4							
HD	315	—								
ND	450	—	ATV9A0C45R4							
HD	355	—								
ND	500	—	ATV9A0C50R4							
HD	400	—								
ND	560	—	ATV9A0C56R4	630	—	6x 3.35	750	440	260	MODBUOC63R4APM
HD	450	—								
ND	630	—	ATV9A0C63R4							
HD	500	—								
ND	710	—	ATV9A0C71R4	800	—	6x 2.68 or 3x 2.23	945	554.4	355	MODBUOC80R4APM
HD	580	—								
ND	800	—	ATV9A0C80R4			+ 3x 3.35				
HD	630	—								
ND	1000	—	ATV9A0M10R4							
HD	800	—								

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)

Variable speed drives

Altivar Process Modular

Braking units 440 V power supply

Low Harmonic/Regenerative drives



ATV9B0C19R39B

MODBUOC31R4APM

Braking units 440 V power supply (continued)

Drive		Braking unit					Reference		
Nominal power	Reference	Power rating	Minimum resistor value	Braking power					
ND: Normal duty HD: Heavy duty		kW	HP	kW	HP	Ω			
440 V power supply - Low Harmonic/Regenerative drives									
ND 110	—	ATV9B0C11R4	160	—	3x 6.7	198	116.16	75	MODBUOC16R4APM
HD 90	—								
ND 132	—	ATV9B0C13R4							
HD 110	—								
ND 160	—	ATV9B0C16R4							
HD 132	—								
ND 200	—	ATV9B0C20R4	315	—	3x 3.35	375	220	130	MODBUOC31R4APM
HD 160	—								
ND 250	—	ATV9B0C25R4							
HD 200	—								
ND 315	—	ATV9B0C31R4							
HD 250	—								
ND 355	—	ATV9B0C35R4	500	—	3x 2.23	600	352	225	MODBUOC50R4APM
HD 280	—								
ND 400	—	ATV9B0C40R4							
HD 315	—								
ND 450	—	ATV9B0C45R4							
HD 355	—								
ND 500	—	ATV9B0C50R4							
HD 400	—								
ND 560	—	ATV9B0C56R4							
HD 450	—								
ND 630	—	ATV9B0C63R4							
HD 500	—								
ND 710	—	ATV9B0C71R4							
HD 560	—								
ND 800	—	ATV9B0C80R4							
HD 630	—								
ND 1000	—	ATV9B0M10R4							
HD 800	—								

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)

Variable speed drives

Altivar Process Modular

Braking units 440 V power supply

Liquid-cooled drives



ATV9L0C13R4

MODBUOC50R4APM

Braking units 440 V power supply (continued)											
Drive		Braking unit									
Nominal power		Reference	Power rating		Minimum resistor value	Braking power			Reference		
ND: Normal duty	HD: Heavy duty		kW	HP		kW	HP	Ω	Cycle (1)		
									1	2	3
440 V power supply - Liquid-cooled drives											
ND	132	-	ATV9L0C13R4	160	-	3x 6.7	198	116.16	75	MODBUOC16R4APM	
HD	110	-									
ND	160	-	ATV9L0C16R4								
HD	132	-									
ND	200	-	ATV9L0C20R4	315	-	3x 3.35	375	220	130	MODBUOC31R4APM	
HD	160	-									
ND	250	-	ATV9L0C25R4								
HD	200	-									
ND	315	-	ATV9L0C31R4								
HD	250	-									
ND	400	-	ATV9L0C40R4	500	-	3x 2.23	600	352	225	MODBUOC50R4APM	
HD	315	-									
ND	500	-	ATV9L0C50R4								
HD	400	-									
ND	630	-	ATV9L0C63R4	630	-	6x 3.35	750	440	260	MODBUOC63R4APM	
HD	500	-									
ND	800	-	ATV9L0C80R4	800	-	6x 2.68 or 3x 2.23	945	554.4	355	MODBUOC80R4APM	
HD	630	-									
ND	900	-	ATV9L0C90R4			+ 3x 3.35					
HD	710	-									
ND	1000	-	ATV9L0M10R4								
HD	800	-									
ND	1200	-	ATV9L0M12R4								
HD	1000	-									
ND	1500	-	ATV9L0M15R4								
HD	1200	-									
ND	1800	-	ATV9L0M18R4								
HD	1400	-									

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

Variable speed drives

Altivar Process Modular

Braking units 480 V power supply

Standard drives



MODBUOC80T4APM

ATV9A0P9057

Braking units 480 V power supply										
Drive		Braking unit								
Nominal power		Reference	Power rating	Minimum resistor value	Braking power			Reference		
ND: Normal duty	HD: Heavy duty				Cycle (1)	2	3	1	2	3
kW	HP		kW	Ω						
480 V power supply - Standard drives										
ND	—	150	ATV9A0C11T4	—	250	3x 6.7	198	116.16	75	MODBUOC16T4APM
HD	—	125								
ND	—	200	ATV9A0C13T4							
HD	—	150								
ND	—	250	ATV9A0C16T4							
HD	—	200								
ND	—	300	ATV9A0C20T4	—	500	3x 3.35	375	220	130	MODBUOC31T4APM
HD	—	250								
ND	—	400	ATV9A0C25T4							
HD	—	300								
ND	—	500	ATV9A0C31T4							
HD	—	400								
ND	—	550	ATV9A0C35T4	—	700	3x 2.23	600	352	225	MODBUOC50T4APM
HD	—	450								
ND	—	600	ATV9A0C40T4							
HD	—	500								
ND	—	650	ATV9A0C45T4							
HD	—	550								
ND	—	700	ATV9A0C50T4							
HD	—	600								
ND	—	800	ATV9A0C56T4	—	900	6x 3.35	750	440	260	MODBUOC63T4APM
HD	—	650								
ND	—	900	ATV9A0C63T4							
HD	—	700								
ND	—	1000	ATV9A0C71T4	—	1100	6x 2.68 or 3x 2.23 + 3x 3.35	945	554.4	355	MODBUOC80T4APM
HD	—	800								
ND	—	1100	ATV9A0C80T4							
HD	—	900								
ND	—	1400	ATV9A0M10T4							
HD	—	1100								

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

Variable speed drives

Altivar Process Modular

Braking units 480 V power supply

Low Harmonic/Regenerative drives



MODBUOC50T4APM

Braking units 480 V power supply (continued)										
Drive		Braking unit								
Nominal power		Reference	Power rating		Minimum resistor value	Braking power			Reference	
ND: Normal duty	HD: Heavy duty		kW	HP		kW	HP	Ω		
480 V power supply - Low Harmonic/Regenerative drives										
ND	—	150	ATV9B0C11T4	—	250	3x 6.7	198	116.16	75	MODBUOC16T4APM
HD	—	125								
ND	—	200	ATV9B0C13T4							
HD	—	150								
ND	—	250	ATV9B0C16T4							
HD	—	200								
ND	—	300	ATV9B0C20T4	—	500	3x 3.35	375	220	130	MODBUOC31T4APM
HD	—	250								
ND	—	400	ATV9B0C25T4							
HD	—	300								
ND	—	500	ATV9B0C31T4							
HD	—	400								
ND	—	550	ATV9B0C35T4	—	700	3x 2.23	600	352	225	MODBUOC50T4APM
HD	—	450								
ND	—	600	ATV9B0C40T4							
HD	—	500								
ND	—	650	ATV9B0C45T4							
HD	—	550								
ND	—	700	ATV9B0C50T4							
HD	—	600								
ND	—	800	ATV9B0C56T4							
HD	—	650								
ND	—	900	ATV9B0C63T4							
HD	—	700								
ND	—	1000	ATV9B0C71T4							
HD	—	800								
ND	—	1100	ATV9B0C80T4							
HD	—	900								
ND	—	1400	ATV9B0M10T4							
HD	—	1100								

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)



MODBUOC16T4APM

ATV9L0C16T4APM

Variable speed drives

Altivar Process Modular
Braking units 480 V power supply
Liquid-cooled drives

Braking units 480 V power supply (continued)											
Drive		Braking unit									
Nominal power		Reference	Power rating		Minimum resistor value	Braking power			Reference		
ND: Normal duty	HD: Heavy duty		kW	HP		kW	HP	Ω	1	2	3
480 V power supply - Liquid-cooled drives											
ND	-	200	ATV9L0C13T4	-	250	3x 6.7	198	116.16	75	MODBUOC16T4APM	
HD	-	150									
ND	-	250	ATV9L0C16T4								
HD	-	200									
ND	-	300	ATV9L0C20T4	-	500	3x 3.35	375	220	130	MODBUOC31T4APM	
HD	-	250									
ND	-	400	ATV9L0C25T4								
HD	-	300									
ND	-	500	ATV9L0C31T4								
HD	-	400									
ND	-	600	ATV9L0C40T4	-	700	3x 2.23	600	352	225	MODBUOC50T4APM	
HD	-	500									
ND	-	700	ATV9L0C50T4								
HD	-	600									
ND	-	900	ATV9L0C63T4	-	900	6x 3.35	750	440	260	MODBUOC63T4APM	
HD	-	700									
ND	-	1100	ATV9L0C80T4	-	1100	6x 2.68 or 3x 2.23	945	554.4	355	MODBUOC80T4APM	
HD	-	900									
ND	-	1300	ATV9L0C90T4								
HD	-	1000									
ND	-	1400	ATV9L0M10T4								
HD	-	1100									
ND	-	1700	ATV9L0M12T4								
HD	-	1400									
ND	-	2200	ATV9L0M15T4								
HD	-	1700									
ND	-	2500	ATV9L0M18T4								
HD	-	2000									

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)

Variable speed drives

Altivar Process Modular

Braking units 500 V power supply

Standard and Liquid-cooled drives



ATM-CPR038B

MODBUOC40N6APM

Braking units 500 V power supply										
Drive		Braking unit								
Nominal power		Reference	Braking rating		Minimum resistor value	Braking power			Reference	
ND: Normal duty	HD: Heavy duty		kW	HP		Cycle (1)	1	2	3	
kW	HP		kW	HP	Ω					
500 V power supply - Standard drives										
ND	75	-	ATV9A0C11N6	132	-	3x 11	240	140.8	85	MODBUOC20N6APM
HD	55	-								
ND	90	-	ATV9A0C13N6							
HD	75	-								
ND	110	-	ATV9A0C16N6							
HD	90	-								
ND	132	-	ATV9A0C20N6							
HD	110	-								
ND	160	-	ATV9A0C25N6	280	-	3x 5.5	472.5	277.2	165	MODBUOC40N6APM
HD	132	-								
ND	220	-	ATV9A0C31N6							
HD	160	-								
ND	280	-	ATV9A0C40N6							
HD	220	-								
ND	355	-	ATV9A0C50N6	450	-	3x 3.67	750	440	285	MODBUOC63N6APM
HD	280	-								
ND	450	-	ATV9A0C63N6							
HD	355	-								
ND	560	-	ATV9A0C80N6	560	-	6x 5.5	945	554.4	330	MODBUOC80N6APM
HD	450	-								
ND	710	-	ATV9A0M10N6	710	-	6x 4.4 or 3x 3.67 + 3x 5.5	1200	704	450	MODBUOM10N6APM
HD	560	-								
ND	800	-	ATV9A0M12N6	800	-	6x 3.67	1500	785	550	MODBUOM12N6APM
HD	710	-								
500 V power supply - Liquid-cooled drives										
ND	132	-	ATV9L0C20N6	132	-	3x 11	240	140.8	85	MODBUOC20N6APM
HD	110	-								
ND	200	-	ATV9L0C28N6	280	-	3x 5.5	472.5	277.2	165	MODBUOC40N6APM
HD	160	-								
ND	220	-	ATV9L0C31N6							
HD	180	-								
ND	250	-	ATV9L0C40N6							
HD	220	-								
ND	315	-	ATV9L0C45N6	450	-	3x 3.67	750	440	285	MODBUOC63N6APM
HD	250	-								
ND	400	-	ATV9L0C56N6							
HD	315	-								
ND	500	-	ATV9L0C71N6	560	-	6x 5.5	945	554.4	330	MODBUOC80N6APM
HD	400	-								
ND	630	-	ATV9L0C90N6	710	-	6x 4.4 or 3x 3.67 + 3x 5.5	1200	704	450	MODBUOM10N6APM
HD	500	-								
ND	800	-	ATV9L0M12N6	800	-	6x 3.67	1500	785	550	MODBUOM12N6APM
HD	710	-								
ND	1000	-	ATV9L0M14N6							
HD	800	-								
ND	1200	-	ATV9L0M16N6							
HD	900	-								
ND	1300	-	ATV9L0M18N6							
HD	1000	-								
ND	1600	-	ATV9L0M22N6							
HD	1200	-								
ND	1900	-	ATV9L0M26N6							
HD	1500	-								

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

Variable speed drives

Altivar Process Modular

Braking units 600 V power supply

Standard and Liquid-cooled drives



ATV9M_CPI939B

MODBUOC40T6APM

Braking units 600 V power supply										
Drive		Braking unit								
Nominal power		Reference	Power rating	Minimum resistor value	Braking power			Reference		
ND: Normal duty	HD: Heavy duty				Cycle (1)	2	3	1	2	3
kW	HP		kW	HP	Ω					
600 V power supply - Standard drives										
ND	-	125	ATV9A0C11T6	-	200	3x 11	240	140.8	85	MODBUOC20T6APM
HD	-	100								
ND	-	150	ATV9A0C13T6							
HD	-	125								
ND	-	175	ATV9A0C16T6							
HD	-	150								
ND	-	200	ATV9A0C20T6							
HD	-	175								
ND	-	250	ATV9A0C25T6	-	450	3x 5.5	472.5	277.2	165	MODBUOC40T6APM
HD	-	200								
ND	-	350	ATV9A0C31T6							
HD	-	250								
ND	-	450	ATV9A0C40T6							
HD	-	350								
ND	-	550	ATV9A0C50T6	-	650	3x 3.67	750	440	285	MODBUOC63T6APM
HD	-	450								
ND	-	650	ATV9A0C63T6							
HD	-	550								
ND	-	800	ATV9A0C80T6	-	800	6x 5.5	945	554.4	330	MODBUOC80T6APM
HD	-	650								
ND	-	1000	ATV9A0M10T6	-	1000	6x 4.4 or 3x 3.67 + 3x 5.5	1200	704	450	MODBUOM10T6APM
HD	-	800								
ND	-	1200	ATV9A0M12T6	-	1200	6x 3.67	1500	785	550	MODBUOM12T6APM
HD	-	1000								
600 V power supply - Liquid-cooled drives										
ND	-	200	ATV9L0C20T6	-	200	3x 11	240	140.8	85	MODBUOC20T6APM
HD	-	150								
ND	-	300	ATV9L0C28T6	-	450	3x 5.5	472.5	277.2	165	MODBUOC40T6APM
HD	-	200								
ND	-	350	ATV9L0C31T6							
HD	-	250								
ND	-	450	ATV9L0C40T6							
HD	-	350								
ND	-	500	ATV9L0C45T6	-	650	3x 3.67	750	440	285	MODBUOC63T6APM
HD	-	400								
ND	-	600	ATV9L0C56T6							
HD	-	500								
ND	-	700	ATV9L0C71T6	-	800	6x 5.5	945	554.4	330	MODBUOC80T6APM
HD	-	600								
ND	-	900	ATV9L0C90T6	-	1000	6x 4.4 or 3x 3.67 + 3x 5.5	1200	704	450	MODBUOM10T6APM
HD	-	700								
ND	-	1200	ATV9L0M12T6	-	1200	6x 3.67	1500	785	550	MODBUOM12T6APM
HD	-	1000								
ND	-	1400	ATV9L0M14T6							
HD	-	1100								
ND	-	1600	ATV9L0M16T6							
HD	-	1300								
ND	-	1800	ATV9L0M18T6							
HD	-	1400								
ND	-	2200	ATV9L0M22T6							
HD	-	1700								
ND	-	2600	ATV9L0M26T6							
HD	-	2100								

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

References (continued)

Variable speed drives

Altivar Process Modular

Braking units 690 V power supply

Standard and Liquid-cooled drives



MODBUOM12Q6APM

Braking units 690 V power supply										
Drive		Braking unit								
Nominal power		Reference	Power rating		Minimum resistor value	Braking power			Reference	
ND: Normal duty	HD: Heavy duty		kW	HP		Cycle (1)	2	3		
			kW	HP	Ω					
690 V power supply - Standard drives										
ND	110	—	ATV9A0C11Q6	200	—	3x 11	240	140.8	85	MODBUOC20Q6APM
HD	90	—								
ND	132	—	ATV9A0C13Q6							
HD	110	—								
ND	160	—	ATV9A0C16Q6							
HD	132	—								
ND	200	—	ATV9A0C20Q6							
HD	160	—								
ND	250	—	ATV9A0C25Q6	400	—	3x 5.5	472.5	277.2	165	MODBUOC40Q6APM
HD	200	—								
ND	315	—	ATV9A0C31Q6							
HD	250	—								
ND	400	—	ATV9A0C40Q6							
HD	315	—								
ND	500	—	ATV9A0C50Q6	630	—	3x 3.67	750	440	285	MODBUOC63Q6APM
HD	400	—								
ND	630	—	ATV9A0C63Q6							
HD	500	—								
ND	800	—	ATV9A0C80Q6	800	—	6x 5.5	945	554.4	330	MODBUOC80Q6APM
HD	630	—								
ND	1000	—	ATV9A0M10Q6	1000	—	6x 4.4 or 3x 3.67 + 3x 5.5	1200	704	450	MODBUOM10Q6APM
HD	800	—								
ND	1200	—	ATV9A0M12Q6	1200	—	6x 3.67	1500	785	550	MODBUOM12Q6APM
HD	1000	—								
690 V power supply - Liquid-cooled drives										
ND	200	-	ATV9L0C20Q6	200	—	3x 11	240	140.8	85	MODBUOC20Q6APM
HD	160	-								
ND	280	-	ATV9L0C28Q6	400	—	3x 5.5	472.5	277.2	165	MODBUOC40Q6APM
HD	220	-								
ND	315	-	ATV9L0C31Q6							
HD	250	-								
ND	400	-	ATV9L0C40Q6							
HD	315	-								
ND	450	-	ATV9L0C45Q6	630	—	3x 3.67	750	440	285	MODBUOC63Q6APM
HD	355	-								
ND	560	-	ATV9L0C56Q6							
HD	450	-								
ND	710	-	ATV9L0C71Q6	800	—	6x 5.5	945	554.4	330	MODBUOC80Q6APM
HD	560	-								
ND	900	-	ATV9L0C90Q6	1000	—	6x 4.4 or 3x 3.67 + 3x 5.5	1200	704	450	MODBUOM10Q6APM
HD	710	-								
ND	1200	-	ATV9L0M12Q6	1200	—	6x 3.67	1500	785	550	MODBUOM12Q6APM
HD	1000	-								
ND	1400	-	ATV9L0M14Q6							
HD	1100	-								
ND	1600	-	ATV9L0M16Q6							
HD	1300	-								
ND	1800	-	ATV9L0M18Q6							
HD	1400	-								
ND	2200	-	ATV9L0M22Q6							
HD	1700	-								
ND	2600	-	ATV9L0M26Q6							
HD	2100	-								

(1) Value of the average power that can be dissipated at 50 °C/122 °F. For a 240 s period:

- Cycle 1: 12 s braking at overload (=5%)
- Cycle 2: 120 s braking at overload (=50%)
- Cycle 3: 240 s continuous braking (=100%)

Combinations

Variable speed drives

Altivar Process Modular
Standard architectures without braking unit
380...480 V power supply

Table showing possible combinations to create architectures

Motor (ND/HD)		Drive ATV6/ATV9 (1)	Control units	Power modules	Front covers	Cabinets for IP 20 up to IP 54 integration			
ND: Normal duty	HD: Heavy duty					400 mm width	600 mm width	800 mm width	1,000 mm width
kW	HP	Standard drives three-phase supply voltage: 380...480 V 50/60 Hz							
110/90	150/125	ATV•A0C11•4	1 x APM6A0CTLN401 (ATV6A0) or 1 x APM9A0CTLN401 (ATV9A0)	1 x APM1A0C16N401	—	1	—	—	—
132/110	200/150	ATV•A0C13•4		2 x APM1A0C16N401	1 x VW3A97A01	—	1	—	—
160/132	250/200	ATV•A0C16•4		3 x APM1A0C16N401	2 x VW3A97A01	—	—	1	—
200/160	300/250	ATV•A0C20•4		4 x APM1A0C16N401	3 x VW3A97A01	—	2	—	—
250/200	400/300	ATV•A0C25•4		5 x APM1A0C16N401	4 x VW3A97A01	—	1	1	—
315/250	500/400	ATV•A0C31•4		6 x APM1A0C16N401	5 x VW3A97A01	—	—	2	—
355/280	550/450	ATV•A0C35•4							
400/315	600/500	ATV•A0C40•4							
450/355	650/550	ATV•A0C45•4							
500/400	700/600	ATV•A0C50•4							
560/450	800/650	ATV•A0C56•4							
630/500	900/700	ATV•A0C63•4							
710/560	1000/800	ATV•A0C71•4							
800/630	1100/900	ATV•A0C80•4							
1000/800	1400/1100	ATV•A0M10•4							
Low Harmonic/Regenerative drives three-phase supply voltage: 380...480 V 50/60 Hz									
110/90	150/125	ATV•B0C11•4	1 x APM6B0CTLN401 (ATV6B0) or 1 x APM9B0CTLN401 (ATV9B0)	1 x APM1B0C16N4	—	—	1	—	—
132/110	200/150	ATV•B0C13•4		2 x APM1B0C16N4	1 x VW3A97B01	—	—	—	1
160/132	250/200	ATV•B0C16•4		3 x APM1B0C16N4	2 x VW3A97B01	—	1	—	1
200/160	300/250	ATV•B0C20•4		4 x APM1B0C16N4	3 x VW3A97B01	—	—	—	2
250/200	400/300	ATV•B0C25•4		5 x APM1B0C16N4	4 x VW3A97B01	—	1	—	2
315/250	500/400	ATV•B0C31•4		6 x APM1B0C16N4	5 x VW3A97B01	—	2	—	2
355/280	550/450	ATV•B0C35•4							
400/315	600/500	ATV•B0C40•4							
450/355	650/550	ATV•B0C45•4							
500/400	700/600	ATV•B0C50•4							
560/450	800/650	ATV•B0C56•4							
630/500	900/700	ATV•B0C63•4							
710/560	1000/800	ATV•B0C71•4							
800/630	1100/900	ATV•B0C80•4							
1000/800	1400/1100	ATV•B0M10•4							
Pages									
(1) Replace "•4" with "Q4" for 400V, "R4" for 440V, and "T4" for 480V power supply.									
(2) These cabinet recommendations are for standard integration. For flexible solutions, please contact your Schneider Electric supplier.									
(3) Cabinets must have a minimum depth of 600 mm/23.6 in., and a minimum height of: ■ 2,150 mm/84.6 in. (including the roof-top extension) for IP20/21/23/40/41/43 standard cabinet integration ■ 2,350 mm/92.5 in. (including the plinth and roof-top extension) for IP54 standard cabinet integration									

Combinations (continued)

Variable speed drives

Altivar Process Modular
Standard architectures without braking unit
500...690 V power supply

Table showing possible combinations to create architectures

Motor (ND/HD)		Drive ATV6/ATV9 (1)	Control units	Power modules	Front covers	Cabinets for IP 20 up to IP 54 integration			
ND: Normal duty	HD: Heavy duty					400 mm width	600 mm width	800 mm width	1,000 mm width
kW	HP	Standard drives three-phase supply voltage: 500...690 V 50/60 Hz							
75/55 (500V)	125/100	ATV•A0C11•6	1 x APM6A0CTLY6 (ATV6A0) or 1 x APM9A0CTLY6 (ATV9A0)	1 x APM1A0C20Y6	—	1	—	—	—
110/90 (690V)	150/125	ATV•A0C13•6		2 x APM1A0C20Y6	1 x VW3A97A01	—	1	—	—
90/75 (500V)	175/150	ATV•A0C16•6		3 x APM1A0C20Y6	2 x VW3A97A01	—	—	1	—
132/110 (690V)	200/175	ATV•A0C20•6		4 x APM1A0C20Y6	3 x VW3A97A01	—	2	—	—
110/90 (500V)	250/200	ATV•A0C25•6		5 x APM1A0C20Y6	4 x VW3A97A01	—	1	1	—
160/132 (500V)	350/250	ATV•A0C31•6		6 x APM1A0C20Y6	5 x VW3A97A01	—	—	2	—
220/160 (500V)	450/350	ATV•A0C40•6							
315/250 (690V)	550/450	ATV•A0C50•6							
280/220 (500V)	650/550	ATV•A0C63•6							
400/315 (690V)	800/650	ATV•A0C80•6							
710/560 (500V)	1000/800	ATV•A0M10•6							
800/710 (500V)	1200/1000	ATV•A0M12•6							
Low Harmonic/Regenerative drives three-phase supply voltage: 500...690 V 50/60 Hz									
75/55 (500V)	125/100	ATV•B0C11•6	1 x APM6B0CTLY6 (ATV6B0) or 1 x APM9B0CTLY6 (ATV9B0)	1 x APM1B0C20Y6	—	—	1	—	—
110/90 (690V)	150/125	ATV•B0C13•6		2 x APM1B0C20Y6	1 x VW3A97B01	—	—	—	1
90/75 (500V)	175/150	ATV•B0C16•6		3 x APM1B0C20Y6	2 x VW3A97B01	—	1	—	—
132/110 (690V)	200/175	ATV•B0C20•6		4 x APM1B0C20Y6	3 x VW3A97B01	—	—	2	—
110/90 (500V)	250/200	ATV•B0C25•6		5 x APM1B0C20Y6	4 x VW3A97B01	—	1	—	—
160/132 (500V)	350/250	ATV•B0C31•6		6 x APM1B0C20Y6	5 x VW3A97B01	—	—	—	1
220/160 (500V)	450/350	ATV•B0C40•6							
315/250 (690V)	550/450	ATV•B0C50•6							
280/220 (500V)	650/550	ATV•B0C63•6							
400/315 (690V)	800/650	ATV•B0C80•6							
710/560 (500V)	1000/800	ATV•B0M10•6							
800/710 (500V)	1200/1000	ATV•B0M12•6							

Combinations (continued)

Variable speed drives

Altivar Process Modular
Standard architectures with braking unit
380...480 V power supply

Table showing possible combinations to create architectures

Motor		Braking units	Control units for braking units	Braking unit power modules	Front covers for braking units	Cabinets (drive + braking unit) for IP 20 up to IP 54 integration			
kW	HP					400 mm width	600 mm width	800 mm width	1,000 mm width
Standard drives three-phase supply voltage: 380...480 V 50/60 Hz									
ND 110...160		1 x MODBUOC16Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	-	1	-	-
HD 90...132		1 x MODBUOC16R4APM							
	ND 150...250	1 x MODBUOC16T4APM							
ND 200...315		1 x MODBUOC31Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	-	-	1	-
HD 160...250		1 x MODBUOC31R4APM							
	ND 300...500	1 x MODBUOC31T4APM							
ND 355...500		1 x MODBUOC50Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	1	-	1	-
HD 280...400		1 x MODBUOC50R4APM							
	ND 550...700	1 x MODBUOC50T4APM							
ND 560...630		2 x MODBUOC63Q4APM	1 x APMBC0CTLN4	2 x APMBC0C50N4	1 x VW3A97A01	-	-	2	-
HD 450...500		2 x MODBUOC63R4APM							
	ND 800...900	2 x MODBUOC63T4APM							
ND 710...1000		2 x MODBUOC80Q4APM	1 x APMBC0CTLN4	2 x APMBC0C50N4	1 x VW3A97A01	-	2	1	-
HD 560...800		2 x MODBUOC80R4APM							
	ND 1000...1400	2 x MODBUOC80T4APM							
Low Harmonic/Regenerative drives three-phase supply voltage: 380...480 V 50/60 Hz									
ND 110...160		1 x MODBUOC16Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	1	1	-	-
HD 90...132		1 x MODBUOC16R4APM							
	ND 150...250	1 x MODBUOC16T4APM							
ND 200...315		1 x MODBUOC31Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	1	-	-	1
HD 160...250		1 x MODBUOC31R4APM							
	ND 300...500	1 x MODBUOC31T4APM							
ND 355...500		1 x MODBUOC50Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	1	1	-	1
HD 280...400		1 x MODBUOC50R4APM							
	ND 550...700	1 x MODBUOC50T4APM							
ND 560...630		1 x MODBUOC50Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	1	-	-	2
HD 450...500		1 x MODBUOC50R4APM							
	ND 800...900	1 x MODBUOC50T4APM							
ND 710...1000		1 x MODBUOC50Q4APM	1 x APMBC0CTLN4	1 x APMBC0C50N4	-	1	1	-	2
HD 560...800		1 x MODBUOC50R4APM							
	ND 1000...1400	1 x MODBUOC50T4APM							
Pages		72	20	20	21	(1) (2)			

(1) These cabinet recommendations are for standard integration. For flexible solutions, please contact your Schneider Electric supplier.

(2) Cabinets must have a minimum depth of 600 mm/23.6 in., and a minimum height of:

- 2,150 mm/84.6 in. (including the roof-top extension) for IP20/21/23/40/41/43 standard cabinet integration
- 2,350 mm/92.5 in. (including the plinth and roof-top extension) for IP54 standard cabinet integration

Combinations (continued)

Variable speed drives

Altivar Process Modular
Standard architectures with braking unit
500...690 V power supply

Table showing possible combinations to create architectures

Motor		Braking units	Control units for braking units	Braking unit power modules	Front covers for braking units	Cabinets (drive + braking unit) for IP 20 up to IP 54 integration			
kW	HP					400 mm width	600 mm width	800 mm width	1,000 mm width
Standard drives three-phase supply voltage: 500...690 V 50/60 Hz									
ND 75...132		1 x MODBUOC20N6APM	1 x APMBC0CTL6	1 x APMBC0C63Y6	-	-	1	-	-
HD 55...110		1 x MODBUOC20Q6APM							
ND 110...200		ND 175...200 HD 150...175	1 x MODBUOC20T6APM						
HD 90...160									
ND 160...280		1 x MODBUOC40N6APM	1 x APMBC0CTL6	1 x APMBC0C63Y6	-	-	1	-	-
HD 132...220		1 x MODBUOC40Q6APM							
ND 250...400		ND 250...450 HD 200...350	1 x MODBUOC40T6APM						
HD 200...315									
ND 355...450		1 x MODBUOC63N6APM	1 x APMBC0CTL6	1 x APMBC0C63Y6	-	1	-	1	-
HD 280...355		1 x MODBUOC63Q6APM							
ND 500...630		ND 550...650 HD 450...550	1 x MODBUOC63T6APM						
HD 400...500									
ND 560		2 x MODBUOC80N6APM	2 x APMBC0CTL6	2 x APMBC0C63Y6	1 x VW3A97A01	-	-	2	-
HD 450		2 x MODBUOC80Q6APM							
ND 800		ND 800 HD 650	2 x MODBUOC80T6APM						
HD 630									
ND 710		2 x MODBUOM10N6APM	1 x APMBC0CTL6	2 x APMBC0C63Y6	1 x VW3A97A01	-	2	1	-
HD 560		2 x MODBUOM10Q6APM							
ND 1000		ND 1000 HD 800	2 x MODBUOM10T6APM						
HD 800									
ND 800		2 x MODBUOM12N6APM	1 x APMBC0CTL6	2 x APMBC0C63Y6	1 x VW3A97A01	-	1	2	-
HD 710		2 x MODBUOM12Q6APM							
ND 1200		ND 1200 HD 1000	2 x MODBUOM12T6APM						
HD 1000									
Pages		75	20	20	21				

Combinations (continued)

Variable speed drives

Altivar Process Modular

Reduced height architectures without braking unit

Table showing possible combinations to create architectures

Motor (ND/HD)		Drive ATV6/ATV9 (1)	Control units	Power modules	Mains module	Front covers	Cabinets for IP 20 up to IP 54 integration	
kW	HP						600 mm width	800 mm width
Standard drives three-phase supply voltage: 380...480 V 50/60 Hz - Reduced Height version								
110/90	150/125	ATV•A0C11•4	1 x APM6A0CTLN401 (ATV6A0) or 1 x APM9A0CTLN401 (ATV9A0)	1 x APM1A0C16N4RH	1 x APMCA01LCN4RH	—	—	1
132/110	200/150	ATV•A0C13•4		2 x APM1A0C16N4RH	1 x APMCA02LCN4RH	1 x VW3A97A01	2	—
160/132	250/200	ATV•A0C16•4		3 x APM1A0C16N4RH	1 x APMCA03LCN4RH	2 x VW3A97A01	1	1
200/160	300/250	ATV•A0C20•4		4 x APM1A0C16N4RH	2 x APMCA02LCN4RH	3 x VW3A97A01	4	—
250/200	400/300	ATV•A0C25•4		5 x APM1A0C16N4RH	1 x APMCA02LCN4RH + 1 x APMCA03LCN4RH	4 x VW3A97A01	3	1
315/250	500/400	ATV•A0C31•4		6 x APM1A0C16N4RH	1 x APMCA03LCN4RH + 1 x APMCA03LCN4RH	5 x VW3A97A01	2	2
355/280	550/450	ATV•A0C35•4						
400/315	600/500	ATV•A0C40•4						
450/355	650/550	ATV•A0C45•4						
500/400	700/600	ATV•A0C50•4						
560/450	800/650	ATV•A0C56•4						
630/500	900/700	ATV•A0C63•4						
710/560	1000/800	ATV•A0C71•4						
800/630	1100/900	ATV•A0C80•4						
1000/800	1400/1100	ATV•A0M10•4						
Standard drives three-phase supply voltage: 500...690 V 50/60 Hz - Reduced Height version								
75/55 (500V)	125/100	ATV•A0C11•6	1 x APM6A0CTLY6 (ATV6A0) or 1 x APM9A0CTLY6 (ATV9A0)	1 x APM1A0C20Y6RH	1 x APMCA01LCY6RH	—	—	1
110/90 (690V)				2 x APM1A0C20Y6RH	1 x APMCA02LCY6RH	1 x VW3A97A01	2	—
90/75 (500V)	150/125	ATV•A0C13•6		3 x APM1A0C20Y6RH	1 x APMCA03LCY6RH	2 x VW3A97A01	1	1
132/110 (690V)	175/150	ATV•A0C16•6		4 x APM1A0C20Y6RH	2 x APMCA02LCY6RH	3 x VW3A97A01	4	—
132/110 (500V)	200/175	ATV•A0C20•6		5 x APM1A0C20Y6RH	1 x APMCA02LCY6RH + 1 x APMCA03LCY6RH	4 x VW3A97A01	3	1
160/132 (500V)	250/200	ATV•A0C25•6		6 x APM1A0C20Y6RH	2 x APMCA03LCY6RH	5 x VW3A97A01	2	2
250/200 (690V)								
220/160 (500V)	350/250	ATV•A0C31•6						
315/250 (690V)								
280/220 (500V)	450/350	ATV•A0C40•6						
400/315 (690V)								
355/280 (500V)	550/450	ATV•A0C50•6						
500/400 (690V)								
450/355 (500V)	650/550	ATV•A0C63•6						
630/500 (690V)								
560/450 (500V)	800/650	ATV•A0C80•6						
800/630 (690V)								
710/560 (500V)	1000/800	ATV•A0M10•6						
1000/800 (690V)								
800/710 (500V)	1200/1000	ATV•A0M12•6						
1200/1000 (690V)								
Pages	36	20	20	21	21	(2) (3)		

(1) Replace "•4" with "Q4" for 400V, "R4" for 440V, and "T4" for 480V power supply. Replace "•6" with "N6" for 500V, "Q6" for 600V, and "Y6" for 690V power supply.

(2) These cabinet recommendations are for standard integration. For flexible solutions, please contact your Schneider Electric supplier.

(3) Cabinets must have a minimum depth of 600 mm/23.6 in., and a minimum height of:

- 2,150 mm/84.6 in. (including the roof-top extension) for IP20/21/23/40/41/43 standard cabinet integration
- 2,350 mm/92.5 in. (including the plinth and roof-top extension) for IP54 standard cabinet integration

Combinations (continued)

Variable speed drives

Altivar Process Modular

Reduced height architectures with braking unit

Table showing possible combinations to create architectures

Motor		Braking units	Control units for braking units	Braking unit power modules	Front covers for braking units	Cabinets (drive + braking unit) for IP 20 up to IP 54 integration	
kW	HP					600 mm width	800 mm width
Standard drives three-phase supply voltage: 380...480 V 50/60 Hz - reduced height version							
ND 110...160		1 x MODBUOC16Q4APM	1 x APMB0CTLN4	1 x APMB0C50N4	—	2	—
HD 90...132		1 x MODBUOC16R4APM					
		ND 150...250 HD 125...200	1 x MODBUOC16T4APM				
ND 200...315		1 x MODBUOC31Q4APM	1 x APMB0CTLN4	1 x APMB0C50N4	—	1	1
HD 160...250		1 x MODBUOC31R4APM					
		ND 300...500 HD 250...400	1 x MODBUOC31T4APM				
ND 355...500		1 x MODBUOC50Q4APM	1 x APMB0CTLN4	1 x APMB0C50N4	—	3	—
HD 280...400		1 x MODBUOC50R4APM					
		ND 550...700 HD 450...600	1 x MODBUOC50T4APM				
ND 560...630		2 x MODBUOC63Q4APM	1 x APMB0CTLN4	2 x APMB0C50N4	1 x VW3A97A01	5	—
HD 450...500		2 x MODBUOC63R4APM					
		ND 800...900 HD 650...700	2 x MODBUOC63T4APM				
ND 710...1000		2 x MODBUOC80Q4APM	1 x APMB0CTLN4	2 x APMB0C50N4	1 x VW3A97A01	4	1
HD 560...800		2 x MODBUOC80R4APM					
		ND 1000...1400 HD 800...1100	2 x MODBUOC80T4APM				
Standard drives three-phase supply voltage: 500...690 V 50/60 Hz - reduced height version							
ND 75...132		1 x MODBUOC20N6APM	1 x APMB0CTLY6	1 x APMB0C63Y6	—	2	—
HD 55...110		1 x MODBUOC20Q6APM					
		ND 175...200 HD 150...175	1 x MODBUOC20T6APM				
ND 160...280		1 x MODBUOC40N6APM	1 x APMB0CTLY6	1 x APMB0C63Y6	—	1	1
HD 132...220		1 x MODBUOC40Q6APM					
		ND 250...450 HD 200...350	1 x MODBUOC40T6APM				
ND 355...450		1 x MODBUOC63N6APM	1 x APMB0CTLY6	1 x APMB0C63Y6	—	3	—
HD 280...355		1 x MODBUOC63Q6APM					
		ND 550...650 HD 450...550	1 x MODBUOC63T6APM				
ND 560		2 x MODBUOC80N6APM	1 x APMB0CTLY6	2 x APMB0C63Y6	1 x VW3A97A01	5	—
HD 450		2 x MODBUOC80Q6APM					
		ND 800	2 x MODBUOC80T6APM				
ND 710		2 x MODBUOM10N6APM	1 x APMB0CTLY6	2 x APMB0C63Y6	1 x VW3A97A01	4	1
HD 560		2 x MODBUOM10Q6APM					
		ND 1000	2 x MODBUOM10T6APM				
ND 800		2 x MODBUOM12N6APM	1 x APMB0CTLY6	2 x APMB0C63Y6	1 x VW3A97A01	3	2
HD 710		2 x MODBUOM12Q6APM					
		ND 1200	2 x MODBUOM				

Variable speed drives

Altivar Process Modular

Standard liquid-cooled architectures without braking unit

Universal version

Table showing possible combinations to create architectures

Motor (ND/HD)		Drive ATV6/ATV9 (1)	Control units	Power modules	Line choke module	Motor protection module	Cabinet cooling module (2)	Cabinets for IP 20 up to IP 66 integration	
kW	HP							600 mm width	
Standard liquid-cooled drives three-phase supply voltage: 380...480 V 50/60 Hz - Universal version									
132/110	200/150	ATV•L0C13•4	1 x APM6L0CTLN (ATV6L0) or 1 x APM6L0CTLN (ATV9L0)	1 x APM1L0C20N4	1 x APM1L0LCMN4	1 x APM1L0MPMN4	1 x APM1L0CCM230 (230V) or 1 x APM1L0CCM115 (115V)	1	
160/132	250/200	ATV•L0C16•4		1 x APM1L0C31N4					
200/160	300/250	ATV•L0C20•4		2 x APM1L0C20N4	2 x APM1L0LCMN4	2 x APM1L0MPMN4		2	
250/200	400/300	ATV•L0C25•4		2 x APM1L0C31N4					
315/250	500/400	ATV•L0C31•4		3 x APM1L0C31N4	3 x APM1L0LCMN4	3 x APM1L0MPMN4		3	
400/315	600/500	ATV•L0C40•4		4 x APM1L0C31N4	4 x APM1L0LCMN4	4 x APM1L0MPMN4		4	
500/400	700/600	ATV•L0C50•4		5 x APM1L0C31N4	5 x APM1L0LCMN4	5 x APM1L0MPMN4		5	
630/500	900/700	ATV•L0C63•4		6 x APM1L0C31N4	6 x APM1L0LCMN4	6 x APM1L0MPMN4		6	
800/630	1100/900	ATV•L0C80•4							
900/710	1300/1000	ATV•L0C90•4							
1000/800	1400/1100	ATV•L0M10•4	1 x APM6L0CTLN (ATV6L0) or 1 x APM6L0CTLN (ATV9L0)						
1200/1000	1700/1400	ATV•L0M12•4							
1500/1200	2200/1700	ATV•L0M15•4							
1800/1400	2500/2000	ATV•L0M18•4							
Standard liquid-cooled drives three-phase supply voltage: 500...690 V 50/60 Hz - Universal version									
132/110 (500V)	200/150	ATV•L0C20•6		1 x APM1L0C28Y6	1 x APM1L0LCMY6	1 x APM1L0MPMY6	1 x APM1L0CCM230 (230V) or 1 x APM1L0CCM115 (115V)	1	
200/160 (690V)	300/200	ATV•L0C28•6		1 x APM1L0C45Y6					
200/160 (500V)	300/200	ATV•L0C31•6		2 x APM1L0C28Y6	2 x APM1L0LCMY6	2 x APM1L0MPMY6		2	
280/220 (690V)	350/250	ATV•L0C40•6		2 x APM1L0C45Y6					
315/250 (690V)	450/350	ATV•L0C45•6		3 x APM1L0C45Y6	3 x APM1L0LCMY6	3 x APM1L0MPMY6		3	
315/250 (500V)	500/400	ATV•L0C56•6		4 x APM1L0C45Y6	4 x APM1L0LCMY6	4 x APM1L0MPMY6		4	
450/355 (690V)	600/500	ATV•L0C71•6		5 x APM1L0C45Y6	5 x APM1L0LCMY6	5 x APM1L0MPMY6		5	
400/315 (500V)	700/600	ATV•L0M12•6		6 x APM1L0C45Y6	6 x APM1L0LCMY6	6 x APM1L0MPMY6		6	
560/450 (690V)	900/700	ATV•L0M14•6	1 x APM6L0CTLN (ATV6L0) or 1 x APM6L0CTLN (ATV9L0)	7 x APM1L0C45Y6	7 x APM1L0LCMY6	7 x APM1L0MPMY6	1 x APM1L0CCM230 (230V) or 1 x APM1L0CCM115 (115V)	7	
500/400 (500V)	1200/1000	ATV•L0M16•6		8 x APM1L0C45Y6	8 x APM1L0LCMY6	8 x APM1L0MPMY6		8	
710/560 (690V)	1400/1100	ATV•L0M18•6		9 x APM1L0C45Y6	9 x APM1L0LCMY6	9 x APM1L0MPMY6		9	
630/500 (500V)	1600/1300	ATV•L0M22•6		10 x APM1L0C45Y6	10 x APM1L0LCMY6	10 x APM1L0MPMY6		10	
1300/1000 (500V)	1800/1400	ATV•L0M26•6		11 x APM1L0C45Y6	11 x APM1L0LCMY6	11 x APM1L0MPMY6		11	
1800/1400 (690V)	2200/1700	ATV•L0M26•6		12 x APM1L0C45Y6	12 x APM1L0LCMY6	12 x APM1L0MPMY6		12	
1600/1200 (500V)	2600/2100	ATV•L0M26•6		13 x APM1L0C45Y6	13 x APM1L0LCMY6	13 x APM1L0MPMY6		13	
2200/1700 (690V)	2600/2100	ATV•L0M26•6		14 x APM1L0C45Y6	14 x APM1L0LCMY6	14 x APM1L0MPMY6		14	
1900/1500 (500V)	2600/2100	ATV•L0M26•6		15 x APM1L0C45Y6	15 x APM1L0LCMY6	15 x APM1L0MPMY6		15	
2600/2100 (690V)	2600/2100	ATV•L0M26•6		16 x APM1L0C45Y6	16 x APM1L0LCMY6	16 x APM1L0MPMY6		16	
Pages	60	22	20	26	26	26	26	(3) (4)	

(1) Replace "•4" with "Q4" for 400V, "R4" for 440V, and "T4" for 480V power supply. Replace "•6" with "N6" for 500V, "Q6" for 600V, and "Y6" for 690V power supply.

(2) Depending on the available control voltage, a module with 115 VAC or 230 VAC can be used.

(3) These cabinet recommendations are for standard integration. For flexible solutions, please contact your Schneider Electric supplier.

(4) Cabinets must have a minimum depth of 600 mm/23.6 in., and a minimum height of:

- 2,150 mm/84.6 in. (including the roof-top extension) for IP20/21/23/40/41/43 standard cabinet integration
- 2,350 mm/92.5 in. (including the plinth and roof-top extension) for IP54 standard cabinet integration

Variable speed drives

Altivar Process Modular

Standard liquid-cooled architectures without braking unit

Compact version

Table showing possible combinations to create architectures

Motor (ND/HD)		Drive ATV6/ATV9 (1)	Control units	Power modules	Line filter module	Line paralleling module	Motor protection module	Cabinets for IP 20 up to IP 66 integration		
ND: Normal duty	HD: Heavy duty							400 mm width	600 mm width	800 mm width
Standard liquid-cooled drives three-phase supply voltage: 380...480 V 50/60 Hz - Compact version										
132/110	200/150	ATV•L0C13•4	1 x APM6L0CTLN (ATV6L0) or 1 x APM6L0CTLN (ATV9L0)	1 x APM1L0C20N4	1 x APM1L0LFMN4	1 x APM1L0LPMN4	1 x APM1L0MPMN4	1	-	-
160/132	250/200	ATV•L0C16•4		1 x APM1L0C31N4						
200/160	300/250	ATV•L0C20•4		2 x APM1L0C20N4	1 x APM1L0LFMN4	2 x APM1L0LPMN4	2 x APM1L0MPMN4	-	1	-
250/200	400/300	ATV•L0C25•4		2 x APM1L0C31N4						
315/250	500/400	ATV•L0C31•4		3 x APM1L0C31N4	1 x APM1L0LFMN4	3 x APM1L0LPMN4	3 x APM1L0MPMN4	-	-	1
400/315	600/500	ATV•L0C40•4		4 x APM1L0C31N4	2 x APM1L0LFMN4	4 x APM1L0LPMN4	4 x APM1L0MPMN4	-	2	-
500/400	700/600	ATV•L0C50•4		5 x APM1L0C31N4	2 x APM1L0LFMN4	5 x APM1L0LPMN4	5 x APM1L0MPMN4	-	1	1
630/500	900/700	ATV•L0C63•4		6 x APM1L0C31N4	2 x APM1L0LFMN4	6 x APM1L0LPMN4	6 x APM1L0MPMN4	-	-	2
800/630	1100/900	ATV•L0C80•4								
900/710	1300/1000	ATV•L0C90•4								
1000/800	1400/1100	ATV•L0M10•4								
1200/1000	1700/1400	ATV•L0M12•4								
1500/1200	2200/1700	ATV•L0M15•4								
1800/1400	2500/2000	ATV•L0M18•4								
Standard liquid-cooled drives three-phase supply voltage: 500...690 V 50/60 Hz - Compact version										
132/110 (500V)	200/150	ATV•L0C20•6	1 x APM6L0CTLN (ATV6L0) or 1 x APM6L0CTLN (ATV9L0)	1 x APM1L0C28Y6	1 x APM1L0LFMY6	1 x APM1L0LPMY6	1 x APM1L0MPMY6	1		
200/160 (690V)	300/200	ATV•L0C28•6		1 x APM1L0C45Y6						
200/160 (500V)	300/200	ATV•L0C28•6		2 x APM1L0C28Y6	1 x APM1L0LFMY6	2 x APM1L0LPMY6	2 x APM1L0MPMY6	2		
280/220 (690V)	350/250	ATV•L0C31•6		2 x APM1L0C45Y6						
220/180 (500V)	350/250	ATV•L0C31•6		3 x APM1L0C45Y6	1 x APM1L0LFMY6	3 x APM1L0LPMY6	3 x APM1L0MPMY6	3		
315/250 (690V)	450/350	ATV•L0C40•6		4 x APM1L0C45Y6	2 x APM1L0LFMY6	4 x APM1L0LPMY6	4 x APM1L0MPMY6	4		
250/220 (500V)	450/350	ATV•L0C40•6		5 x APM1L0C45Y6	2 x APM1L0LFMY6	5 x APM1L0LPMY6	5 x APM1L0MPMY6	5		
400/315 (690V)	500/400	ATV•L0C45•6		6 x APM1L0C45Y6	2 x APM1L0LFMY6	6 x APM1L0LPMY6	6 x APM1L0MPMY6	6		
315/250 (500V)	500/400	ATV•L0C45•6								
450/355 (690V)	500/400	ATV•L0C45•6								
400/315 (500V)	600/500	ATV•L0C56•6								
560/450 (690V)	700/600	ATV•L0C71•6								
500/400 (500V)	700/600	ATV•L0C71•6								
710/560 (690V)	900/700	ATV•L0C90•6								
630/500 (500V)	900/700	ATV•L0C90•6								
800/710 (500V)	1200/1000	ATV•L0M12•6								
1200/1000(690V)	1400/1100	ATV•L0M14•6								
1000/800 (500V)	1400/1100	ATV•L0M14•6								
1400/1100 (690V)	1600/1300	ATV•L0M16•6								
1200/900 (500V)	1600/1300 (690V)	ATV•L0M16•6								
1300/1000 (500V)	1800/1400	ATV•L0M18•6								
1800/1400 (690V)	2200/1700	ATV•L0M22•6								
1600/1200 (500V)	2200/1700 (690V)	ATV•L0M22•6								
1900/1500 (500V)	2600/2100	ATV•L0M26•6								
2600/2100 (690V)										
Pages	60	22	20	26	26	26	26	(2) (3)		

(1) Replace "•4" with "Q4" for 400V, "R4" for 440V, and "T4" for 480V power supply. Replace "•6" with "N6" for 500V, "Q6" for 600V, and "Y6" for 690V power supply.

(2) These cabinet recommendations are for standard integration. For flexible solutions, please contact your Schneider Electric supplier.

(3) Cabinets must have a minimum depth of 600 mm/23.6 in., and a minimum height of:

- 2,150 mm/84.6 in. (including the roof-top extension) for IP20/21/23/40/41/43 standard cabinet integration
- 2,350 mm/92.5 in. (including the plinth and roof-top extension) for IP54 standard cabinet integration

Variable speed drives

Altivar Process Modular
Compatibility table

Module compatibility table

Safety module			
Description	Reference	Compatibility	Slot
Safety module	VW3A3802	ATV900	C (2)
Encoder interface modules			
Description	Reference	Compatibility	Slot
Digital encoder interface module	VW3A3420	ATV900	B
Analog encoder interface module	VW3A3422	ATV900	B
Resolver interface module	VW3A3423	ATV900	B
HTL encoder interface module	VW3A3424	ATV900	B
Additional I/O modules			
Description	Reference	Compatibility	Slot
Extended I/O module (1)	VW3A3203	ATV600 and ATV900	A or B or C (2)
Extended relay module (1)	VW3A3204	ATV600 and ATV900	A or B or C (2)
Fieldbus modules			
Description	Reference	Compatibility	Slot
EtherNet/IP and Modbus TCP dual port	VW3A3720	ATV600	A
EtherNet/IP, Modbus TCP, and MD-Link dual port	VW3A3721	ATV600	A
CANopen daisy chain	VW3A3608	ATV600 and ATV900	A
CANopen SUB-D	VW3A3618	ATV600 and ATV900	A
CANopen screw terminal block	VW3A3628	ATV600 and ATV900	A
PROFINET	VW3A3627	ATV600 and ATV900	A
PROFIBUS DP V1	VW3A3607	ATV600 and ATV900	A
POWERLINK Network	VW3A3619	ATV600 and ATV900	A
BACnet MS/TP	VW3A3725	ATV600	A
EtherCAT	VW3A3601	ATV900	A
DeviceNet	VW3A3609	ATV600 and ATV900	A

(1) These references can only be used once per drive, e.g. VW3A3203 in slot A and VW3A3204 in slot B.

(2) The Altivar 900 drive must be equipped with an additional module support VW3A3800 to be able to insert the safety module VW3A3802.



Altivar Process drives slots

For more information on compatible options and accessories, please contact your Schneider Electric supplier or consult the product selector available on our [partner portal](#).

For more details on I/O, encoder, and communication modules, please refer to the Altivar Process ATV600 and ATV900 catalogs:



Altivar Process catalogs
Click to open the documents

Applications

Circuit breaker/contactor/drive combinations help to ensure continuity of service in the installation.

The type of circuit breaker/contactor coordination selected can reduce maintenance costs in the event of a motor short-circuit on the drive input by minimizing the time required to make the necessary repairs and the cost of replacement equipment. The suggested combinations provide coordination according to the drive rating.

The selection according to IEC considers loading of components with max. 80% up to 1600A nominal current, to avoid thermal test requirement according IEC 61439-1.

The selection according to UL considers the requirement for disconnect switches not carrying full load currents more than 80% of their nominal current.

The drive controls the motor, provides a monitoring function against short-circuits between the drive and the motor, and helps protect the motor cable against overloads. Overload monitoring is provided by the drive's motor thermal monitoring function if this has been enabled. Otherwise, an external monitoring device such as a probe or thermal overload relay must be provided.

Selecting short-circuit protection devices (fuses or circuit breakers) is key to helping to protect the overall installation against potential damage caused by short-circuits. It is recommended to refer to the APM Integration Manuals



NS1250N Micrologic 5.0

+



LC1F1400••

+



ATV6A0C71Q4

IEC standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker Type (2)	Rating @50°C		Line contactor	
			kW	HP	I ₁	Reference (3)
Three-phase supply voltage: 400 V 50/60 Hz						
ND 110	—	ATV•A0C11Q4	NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F225•• 280
HD 90			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F185•• 240
ND 132	—	ATV•A0C13Q4	NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F265•• 300
HD 110			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F225•• 280
ND 160	—	ATV•A0C16Q4	NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F330•• 360
HD 132			NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F265•• 300
ND 200	—	ATV•A0C20Q4	NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
HD 160			NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F400•• 430
ND 250	—	ATV•A0C25Q4	NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
HD 200			NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
ND 315	—	ATV•A0C31Q4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630•• 850
HD 250			NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
ND 355	—	ATV•A0C35Q4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630•• 850
HD 280			NS630N Micrologic 5.0	630	1260 (5)	LC1F630•• 850
ND 400	—	ATV•A0C40Q4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
HD 315			NS800N Micrologic 5.0	800	1600 (5)	LC1F630•• 850
ND 450	—	ATV•A0C45Q4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
HD 355			NS800N Micrologic 5.0	800	1600 (5)	LC1F630•• 850
ND 500	—	ATV•A0C50Q4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1250•• 1060
HD 400			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
ND 560	—	ATV•A0C56Q4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400•• 1190
HD 450			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
ND 630	—	ATV•A0C63Q4	NS1600N Micrologic 5.0	1600	3200 (5)	LC1F1700•• 1450
HD 500			NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400•• 1190
ND 710	—	ATV•A0C71Q4	NS1600N Micrologic 5.0	1600	3200 (5)	LC1F2100•• 1750
HD 560			NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400•• 1190
ND 800	—	ATV•A0C80Q4	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (5)	LC1F2100•• 1750
HD 630			NS1600N Micrologic 5.0	1600	3200 (5)	LC1F1700•• 1450
ND 1000	—	ATV•A0M10Q4	2x NS1250N Micrologic 5.0	1250	2500 (5)	2x LC1F1250•• 1060
HD 800			2x NS1000N Micrologic 5.0	1000	2000 (5)	2x LC1F1250•• 1060

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current I₁: fixed.

(5) Rated instantaneous short-circuit current I₁: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular

Motor starters

IEC 440 V Standard drives



NS800N Micrologic 5.0

+



LC1F630••

+



ATV9A0C45R4

IEC standard motor starters								
Nominal power		Drive	Circuit breaker			Line contactor		
ND: Normal duty	HD: Heavy duty	Reference (1)	Type (2)	Rating @50°C	li	Reference (3)	Rating @60°C	
KW	HP				A	A	A	
Three-phase supply voltage: 440 V 50/60 Hz								
ND 110	—	ATV•A0C11R4	NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F180••	240	
HD 90			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1D115••	200	
ND 132	—	ATV•A0C13R4	NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F225••	280	
HD 110			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F185••	240	
ND 160	—	ATV•A0C16R4	NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F330••	360	
HD 132			NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F225••	280	
ND 200	—	ATV•A0C20R4	NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F400••	430	
HD 160			NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F330••	360	
ND 250	—	ATV•A0C25R4	NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580	
HD 200			NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F400••	430	
ND 315	—	ATV•A0C31R4	NS630bN Micrologic 5.0	630	1260 (5)	LC1F630••	850	
HD 250			NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580	
ND 355	—	ATV•A0C35R4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850	
HD 280			NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580	
ND 400	—	ATV•A0C40R4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850	
HD 315			NS630bN Micrologic 5.0	630	1260 (5)	LC1F630••	850	
ND 450	—	ATV•A0C45R4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060	
HD 355			NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850	
ND 500	—	ATV•A0C50R4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060	
HD 400			NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850	
ND 560	—	ATV•A0C56R4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400••	1190	
HD 450			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060	
ND 630	—	ATV•A0C63R4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1700••	1450	
HD 500			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060	
ND 710	—	ATV•A0C71R4	NS1600N Micrologic 5.0	1600	3200 (5)	LC1F1700••	1450	
HD 560			NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400••	1190	
ND 800	—	ATV•A0C80R4	NS1600N Micrologic 5.0	1600	3200 (5)	LC1F2100••	1750	
HD 630			NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1700••	1450	
ND 1000	—	ATV•A0M10R4	2x NS1000N Micrologic 5.0	1000	2000 (5)	2x LC1F1250••	1060	
HD 800			2x NS800N Micrologic 5.0	800	1600 (5)	2x LC1F630••	850	

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: fixed.

(5) Rated instantaneous short-circuit current li: setting 2.



LLL36600U31X

+



LC1F400••

+



ATV9A0C25T4

UL standard motor starters							
Nominal power		Drive Reference (1)		Circuit breaker		Line contactor	
ND: Normal duty HD: Heavy duty				Type (2)	Rating @50°C	li	Reference (3)
kW HP					A	A	A
Three-phase supply voltage: 480 V 50/60 Hz							
ND	—	150	ATV•A0C11T4	JLL36250U31X	250	500 (4)	LC1F185••
HD	—	125		JLL36250U31X	250	500 (4)	LC1D115••
ND	—	200	ATV•A0C13T4	LLL36400U31X	400	800 (4)	LC1F225••
HD	—	150		JLL36250U31X	250	500 (4)	LC1F185••
ND	—	250	ATV•A0C16T4	LLL36400U31X	400	800 (4)	LC1F330••
HD	—	200		LLL36400U31X	400	800 (4)	LC1F225••
ND	—	300	ATV•A0C20T4	LLL36600U31X	600	1200 (4)	LC1F400••
HD	—	250		LLL36400U31X	400	800 (4)	LC1F330••
ND	—	400	ATV•A0C25T4	LLL36600U31X	600	1200 (4)	LC1F500••
HD	—	300		LLL36600U31X	600	1200 (4)	LC1F400••
ND	—	500	ATV•A0C31T4	PLL34080U31A	736	1600 (4)	LC1F630••
HD	—	400		LLL36600U31X	600	1200 (4)	LC1F500••
ND	—	550	ATV•A0C35T4	PLL34080U31A	736	1600 (4)	LC1F630••
HD	—	450		PLL34080U31A	736	1600 (4)	LC1F630••
ND	—	600	ATV•A0C40T4	PLL34100U44A	920	2000 (4)	LC1F630••
HD	—	500		PLL34080U31A	736	1600 (4)	LC1F630••
ND	—	650	ATV•A0C45T4	PLL34100U44A	920	2000 (4)	LC1F1250••
HD	—	550		PLL34080U31A	736	1600 (4)	LC1F630••
ND	—	700	ATV•A0C50T4	PLL34100U44A	920	2000 (4)	LC1F1250••
HD	—	600		PLL34100U44A	920	2000 (4)	LC1F630••
ND	—	800	ATV•A0C56T4	PLL34120U44A	1104	2400 (4)	LC1F1250••
HD	—	650		PLL34100U44A	920	2000 (4)	LC1F1250••
ND	—	900	ATV•A0C63T4	RLF36160U44A	1472	3200 (4)	LC1F1400••
HD	—	700		PLL34120U44A	1104	2400 (4)	LC1F1250••
ND	—	1000	ATV•A0C71T4	RLF36160U44A	1472	3200 (4)	LC1F1700••
HD	—	800		PLL34120U44A	1104	2400 (4)	LC1F1250••
ND	—	1100	ATV•A0C80T4	RLF36160U44A	1472	3200 (4)	LC1F1700••
HD	—	900		RLF36160U44A	1472	3200 (4)	LC1F1400••
ND	—	1400	ATV•A0M10T4	2x PLL34100U44A	920	2000 (4)	2x LC1F1250••
HD	—	1100		2x PLL34100U44A	920	2000 (4)	2x LC1F630••

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for lcu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: fixed.

(5) Rated instantaneous short-circuit current li: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular

Motor starters

IEC 500 V and UL 600V Standard drives



JRL36250U31X

+



LC1D115••

+



ATV6A0C13T6

IEC and UL standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker			Line contactor	
		Type (2)	Rating @50°C	I _i	Reference (3)	Rating @60°C
KW HP			A	A	A	A
Three-phase supply voltage: 500 V 50/60 Hz						
ND 75	—	ATV•A0C11N6	NSX160L Micrologic 2.2 160	160	2400 (4)	LC1D115•• 200
HD 55			NSX160L Micrologic 2.2 160	160	2400 (4)	LC1D80•• 125
ND 90	—	ATV•A0C13N6	NSX250L Micrologic 2.2 250	250	3000 (4)	LC1D115•• 200
HD 75			NSX160L Micrologic 2.2 160	160	2400 (4)	LC1D115•• 200
ND 110	—	ATV•A0C16N6	NSX250L Micrologic 2.2 250	250	3000 (4)	LC1D115•• 200
HD 90			NSX250L Micrologic 2.2 250	250	3000 (4)	LC1D115•• 200
ND 132	—	ATV•A0C20N6	NSX250L Micrologic 2.2 250	250	3000 (4)	LC1F185•• 240
HD 110			NSX250L Micrologic 2.2 250	250	3000 (4)	LC1D115•• 200
ND 160	—	ATV•A0C25N6	NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F265•• 300
HD 132			NSX250L Micrologic 2.2 250	250	3000 (4)	LC1F185•• 240
ND 220	—	ATV•A0C31N6	NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F400•• 430
HD 160			NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F265•• 300
ND 280	—	ATV•A0C40N6	NSX630L Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
HD 220			NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F400•• 430
ND 355	—	ATV•A0C50N6	NS630bH Micrologic 5.0	630	1260 (5)	LC1F630•• 850
HD 280			NSX630L Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
ND 450	—	ATV•A0C63N6	NS800H Micrologic 5.0	800	1600 (5)	LC1F630•• 850
HD 355			NS630bH Micrologic 5.0	630	1260 (5)	LC1F630•• 850
ND 560	—	ATV•A0C80N6	NS1000H Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
HD 450			NS800H Micrologic 5.0	800	1600 (5)	LC1F630•• 850
ND 710	—	ATV•A0M10N6	NS1250H Micrologic 5.0	1250	2500 (5)	LC1F1700•• 1450
HD 560			NS1000H Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
ND 800	—	ATV•A0M12N6	NS1600H Micrologic 5.0	1600	3200 (5)	LC1F1700•• 1450
HD 710			NS1250H Micrologic 5.0	1250	2500 (5)	LC1F1700•• 1450
Three-phase supply voltage: 600 V 50/60 Hz						
ND —	125	ATV•A0C11T6	HRL36150U31X	150	300 (4)	LC1D115•• 200
HD	100		HRL36150U31X	150	300 (4)	LC1D80•• 125
ND —	150	ATV•A0C13T6	JRL36250U31X	250	500 (4)	LC1D115•• 200
HD	125		HRL36150U31X	150	300 (4)	LC1D115•• 200
ND —	175	ATV•A0C16T6	JRL36250U31X	250	500 (4)	LC1D115•• 200
HD	150		JRL36250U31X	250	500 (4)	LC1D115•• 200
ND —	200	ATV•A0C20T6	JRL36250U31X	250	500 (4)	LC1F185•• 240
HD	175		JRL36250U31X	250	500 (4)	LC1D115•• 200
ND —	250	ATV•A0C25T6	LRL36400U31X	400	800 (4)	LC1F225•• 280
HD	200		JRL36250U31X	250	500 (4)	LC1F185•• 240
ND —	350	ATV•A0C31T6	LRL36400U31X	400	800 (4)	LC1F400•• 430
HD	250		LRL36400U31X	400	800 (4)	LC1F225•• 280
ND —	450	ATV•A0C40T6	LRL36600U31X	600	1200 (4)	LC1F500•• 580
HD	350		LRL36400U31X	400	800 (4)	LC1F400•• 430
ND —	550	ATV•A0C50T6	LRL36600U31X	600	1200 (4)	LC1F500•• 580
HD	450		LRL36600U31X	600	1200 (4)	LC1F500•• 580
ND —	650	ATV•A0C63T6	MTZ2 08L Micrologic 3.0 X	736	1600 (4)	LC1F630•• 850
HD	550		LRL36600U31X	600	1200 (4)	LC1F500•• 580
ND —	800	ATV•A0C80T6	MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F630•• 850
HD	650		MTZ2 08L Micrologic 3.0 X	736	1600 (4)	LC1F630•• 850
ND —	1000	ATV•A0M10T6	MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F1250•• 1060
HD	800		MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F630•• 850
ND —	1200	ATV•A0M12T6	MTZ2 16L Micrologic 6.0 X	1472	3200 (4)	LC1F1700•• 1450
HD	1000		MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F1250•• 1060

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for I_c min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current I_i: fixed.

(5) Rated instantaneous short-circuit current I_i: setting 2.



NSX400HB1 Micrologic 2.3 400

+



LC1F330••

+



ATV9A0C25Q6

IEC standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker			Line contactor		
		Type (2)	Rating @50°C	I _i	Reference (3)	Rating @60°C	
KW HP		A	A	A	A	A	
Three-phase supply voltage: 690 V 50/60 Hz							
ND 110 –	ATV•A0C11Q6	NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D115••	200	
HD 90		NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D80••	125	
ND 132 –	ATV•A0C13Q6	NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1D115••	200	
HD 110		NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D115••	200	
ND 160 –	ATV•A0C16Q6	NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1F185••	240	
HD 132		NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1D115••	200	
ND 200 –	ATV•A0C20Q6	NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1F225••	280	
HD 160		NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1F185••	240	
ND 250 –	ATV•A0C25Q6	NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F330••	360	
HD 200		NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F225••	280	
ND 315 –	ATV•A0C31Q6	NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F400••	430	
HD 250		NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F330••	360	
ND 400 –	ATV•A0C40Q6	NSX630HB1 Micrologic 2.3 630	600	6900 (4)	LC1F500••	580	
HD 315		NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F400••	430	
ND 500 –	ATV•A0C50Q6	NS630bLB Micrologic 5.0	630	1260 (5)	LC1F630••	850	
HD 400		NSX630HB1 Micrologic 2.3 630	600	6900 (4)	LC1F500••	580	
ND 630 –	ATV•A0C63Q6	NS800LB Micrologic 5.0	800	1600 (5)	LC1F630••	850	
HD 500		NS630bLB Micrologic 5.0	630	1260 (5)	LC1F630••	850	
ND 800 –	ATV•A0C80Q6	MTZ2 10H1 Micrologic 5.0 X	1000	2000 (5)	LC1F1250••	1060	
HD 630		NS800LB Micrologic 5.0	800	1600 (5)	LC1F630••	850	
ND 1000 –	ATV•A0M10Q6	MTZ2 12H1 Micrologic 5.0 X	1250	2500 (5)	LC1F1700••	1450	
HD 800		MTZ2 10H1 Micrologic 5.0 X	1000	2000 (5)	LC1F1250••	1060	
ND 1200 –	ATV•A0M12Q6	MTZ2 16H1 Micrologic 5.0 X	1600	3200 (5)	LC1F2100••	1750	
HD 1000		MTZ2 12H1 Micrologic 5.0 X	1250	2500 (5)	LC1F1700••	1450	

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for I_{cu} min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current I_i: fixed.

(5) Rated instantaneous short-circuit current I_i: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular
Motor starters
IEC 400 V Low harmonic/Regen drives



NSX630N Micrologic 2.3 630

+



LC1F500••

+



ATV9B0C25Q4

IEC standard motor starters							
Nominal power		Drive	Circuit breaker			Line contactor	
ND: Normal duty	HD: Heavy duty	Reference (1)	Type (2)	Rating @50°C	li	Reference (3)	Rating @60°C
KW	HP			A	A	A	A
Three-phase supply voltage: 400 V 50/60 Hz							
ND 110	—	ATV•B0C11Q4	NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F225••	280
HD 90			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F185••	240
ND 132	—	ATV•B0C13Q4	NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F265••	300
HD 110			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F225••	280
ND 160	—	ATV•B0C16Q4	NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F330••	360
HD 132			NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F265••	300
ND 200	—	ATV•B0C20Q4	NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
HD 160			NSX400N Micrologic 2.3 400	400	4800 (4)	LC1F400••	430
ND 250	—	ATV•B0C25Q4	NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
HD 200			NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
ND 315	—	ATV•B0C31Q4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
HD 250			NSX630N Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
ND 355	—	ATV•B0C35Q4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
HD 280			NS630bN Micrologic 5.0	630	1260 (5)	LC1F630••	850
ND 400	—	ATV•B0C40Q4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
HD 315			NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
ND 450	—	ATV•B0C45Q4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
HD 355			NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
ND 500	—	ATV•B0C50Q4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1250••	1060
HD 400			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
ND 560	—	ATV•B0C56Q4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400••	1190
HD 450			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
ND 630	—	ATV•B0C63Q4	NS1600N Micrologic 5.0	1600	3200 (5)	LC1F1700••	1450
HD 500			NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400••	1190
ND 710	—	ATV•B0C71Q4	NS1600N Micrologic 5.0	1600	3200 (5)	LC1F2100••	1750
HD 560			NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400••	1190
ND 800	—	ATV•B0C80Q4	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (5)	LC1F2100••	1750
HD 630			NS1600N Micrologic 5.0	1600	3200 (5)	LC1F1700••	1450
ND 1000	—	ATV•B0M10Q4	2x NS1250N Micrologic 5.0	1250	2500 (5)	2x LC1F1250••	1060
HD 800			2x NS1000N Micrologic 5.0	1000	2000 (5)	2x LC1F1250••	1060

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for lcu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: fixed.

(5) Rated instantaneous short-circuit current li: setting 2.



NSX250N Micrologic 2.2 250

+



LC1D115••

+



ATV6B0C11R4

IEC standard motor starters							
Nominal power		Drive Reference (1)	Circuit breaker		Line contactor		
ND: Normal duty	HD: Heavy duty		Type (2)	Rating @50°C	li	Reference (3)	Rating @60°C
kW	HP				A	A	A
Three-phase supply voltage: 440 V 50/60 Hz							
ND 110	—	ATV•B0C11R4	NSX250N Micrologic 2.2 250	250	3000 (4)	LC1D115••	200
HD 90			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1D115••	200
ND 132	—	ATV•B0C13R4	NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F185••	240
HD 110			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1D115••	200
ND 160	—	ATV•B0C16R4	NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F265••	300
HD 132			NSX250N Micrologic 2.2 250	250	3000 (4)	LC1F185••	240
ND 200	—	ATV•B0C20R4	NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F330••	360
HD 160			NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F265••	300
ND 250	—	ATV•B0C25R4	NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
HD 200			NSX400H Micrologic 2.3 400	400	4800 (4)	LC1F330••	360
ND 315	—	ATV•B0C31R4	NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
HD 250			NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
ND 355	—	ATV•B0C35R4	NS630bN Micrologic 5.0	630	1260 (5)	LC1F630••	850
HD 280			NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
ND 400	—	ATV•B0C40R4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
HD 315			NSX630H Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
ND 450	—	ATV•B0C45R4	NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
HD 355			NS630bN Micrologic 5.0	630	1260 (5)	LC1F630••	850
ND 500	—	ATV•B0C50R4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
HD 400			NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
ND 560	—	ATV•B0C56R4	NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
HD 450			NS800N Micrologic 5.0	800	1600 (5)	LC1F630••	850
ND 630	—	ATV•B0C63R4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400••	1190
HD 500			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
ND 710	—	ATV•B0C71R4	NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1700••	1450
HD 560			NS1000N Micrologic 5.0	1000	2000 (5)	LC1F1250••	1060
ND 800	—	ATV•B0C80R4	NS1600N Micrologic 5.0	1600	3200 (5)	LC1F1700••	1450
HD 630			NS1250N Micrologic 5.0	1250	2500 (5)	LC1F1400••	1190
ND 1000	—	ATV•B0M10R4	2x NS1000N Micrologic 5.0	1000	2000 (5)	2x LC1F1250••	1060
HD 800			2x NS800N Micrologic 5.0	800	1600 (5)	2x LC1F630••	850

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: fixed.

(5) Rated instantaneous short-circuit current li: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular

Motor starters

UL 480 V Low harmonic/Regen drives




RLF36160U44A

+



LC1F1700••

+



ATV9B0C80T4

UL standard motor starters							
Nominal power		Drive	Circuit breaker			Line contactor	
ND: Normal duty		Reference (1)	Type (2)	Rating @50°C	li	Reference (3)	Rating @60°C
KW	HP			A	A	A	A
Three-phase supply voltage: 480 V 50/60 Hz							
ND	—	150	ATV•B0C11T4	JLL36250U31X	250	500 (4)	LC1D115••
HD	—	125		JLL36250U31X	250	500 (4)	LC1D115••
ND	—	200	ATV•B0C13T4	JLL36250U31X	250	500 (4)	LC1F225••
HD	—	150		JLL36250U31X	250	500 (4)	LC1D115••
ND	—	250	ATV•B0C16T4	LLL36400U31X	400	800 (4)	LC1F330••
HD	—	200		LLL36400U31X	250	500 (4)	LC1F225••
ND	—	300	ATV•B0C20T4	LLL36400U31X	400	800 (4)	LC1F400••
HD	—	250		LLL36400U31X	400	800 (4)	LC1F330••
ND	—	400	ATV•B0C25T4	LLL36600U31X	600	1200 (4)	LC1F500••
HD	—	300		LLL36600U31X	400	800 (4)	LC1F400••
ND	—	500	ATV•B0C31T4	PLL34080U31A	736	1600 (4)	LC1F630••
HD	—	400		PLL36600U31X	600	1200 (4)	LC1F500••
ND	—	550	ATV•B0C35T4	PLL34080U31A	736	1600 (4)	LC1F630••
HD	—	450		PLL36600U44X	600	1200 (4)	LC1F500••
ND	—	600	ATV•B0C40T4	PLL34080U31A	736	1600 (4)	LC1F630••
HD	—	500		PLL34080U31A	736	1600 (4)	LC1F630••
ND	—	650	ATV•B0C45T4	PLL34100U44A	920	2000 (4)	LC1F630••
HD	—	550		PLL34080U31A	736	1600 (4)	LC1F630••
ND	—	700	ATV•B0C50T4	PLL34100U44A	920	2000 (4)	LC1F630••
HD	—	600		PLL34080U31A	736	1600 (4)	LC1F630••
ND	—	800	ATV•B0C56T4	PLL34120U44A	1104	2400 (4)	LC1F1250••
HD	—	650		PLL34100U44A	920	2000 (4)	LC1F630••
ND	—	900	ATV•B0C63T4	PLL34120U44A	1104	2400 (4)	LC1F1400••
HD	—	700		PLL34100U44A	920	2000 (4)	LC1F630••
ND	—	1000	ATV•B0C71T4	RLF36160U44A	1472	3200 (4)	LC1F1700••
HD	—	800		PLL34120U44A	1104	2400 (4)	LC1F1250••
ND	—	1100	ATV•B0C80T4	RLF36160U44A	1472	3200 (4)	LC1F1700••
HD	—	900		PLL34120U44A	1104	2400 (4)	LC1F1400••
ND	—	1400	ATV•B0M10T4	2x PLL34100U44A	920	2000 (4)	2x LC1F630••
HD	—	1100		2x PLL34080U31A	736	1600 (4)	2x LC1F630••

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for lcu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: fixed.

(5) Rated instantaneous short-circuit current li: setting 2.



LRL36600U31X

+



LC1F500•

+



ATV6A0C50T6

IEC and UL standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker Type (2)	Rating @50°C		Line contactor	
			kW HP	li	Reference (3)	Rating @60°C
Three-phase supply voltage: 500 V 50/60 Hz						
ND 75	—	ATV•B0C11N6	NSX160L Micrologic 2.2 160	160	2400 (4)	LC1D80•• 125
HD 55			NSX100L Micrologic 2.2 100	100	1500 (4)	LC1D80•• 125
ND 90	—	ATV•B0C13N6	NSX160L Micrologic 2.2 160	160	2400 (4)	LC1D115•• 200
HD 75			NSX160L Micrologic 2.2 160	160	2400 (4)	LC1D80•• 125
ND 110	—	ATV•B0C16N6	NSX250L Micrologic 2.2 250	250	3000 (4)	LC1D115•• 200
HD 90			NSX160L Micrologic 2.2 160	160	2400 (4)	LC1D115•• 200
ND 132	—	ATV•B0C20N6	NSX250L Micrologic 2.2 250	250	3000 (4)	LC1F185•• 240
HD 110			NSX250L Micrologic 2.2 250	250	3000 (4)	LC1D115•• 200
ND 160	—	ATV•B0C25N6	NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F225•• 280
HD 132			NSX250L Micrologic 2.2 250	250	3000 (4)	LC1F185•• 240
ND 220	—	ATV•B0C31N6	NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F330•• 360
HD 160			NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F225•• 280
ND 280	—	ATV•B0C40N6	NSX630L Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
HD 220			NSX400L Micrologic 2.3 400	400	4800 (4)	LC1F330•• 360
ND 355	—	ATV•B0C50N6	NSX630L Micrologic 2.3 630	600	6900 (4)	LC1F630•• 850
HD 280			NSX630L Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
ND 450	—	ATV•B0C63N6	NS800H Micrologic 5.0	800	1600 (5)	LC1F630•• 850
HD 355			NSX630L Micrologic 2.3 630	600	6900 (4)	LC1F500•• 580
ND 560	—	ATV•B0C80N6	NS1000H Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
HD 450			NS800H Micrologic 5.0	800	1600 (5)	LC1F630•• 850
ND 710	—	ATV•B0M10N6	NS1250H Micrologic 5.0	1250	2500 (5)	LC1F1400•• 1190
HD 560			NS1000H Micrologic 5.0	1000	2000 (5)	LC1F1250•• 1060
ND 800	—	ATV•B0M12N6	NS1250H Micrologic 5.0	1250	2500 (5)	LC1F1700•• 1450
HD 710			NS1250H Micrologic 5.0	1250	2500 (5)	LC1F1400•• 1190
Three-phase supply voltage: 600 V 50/60 Hz						
ND —	125	ATV•B0C11T6	HRL36150U31X	150	300 (4)	LC1D115•• 200
HD	100		HRL36150U31X	150	300 (4)	LC1D80•• 125
ND —	150	ATV•B0C13T6	JRL36250U31X	250	500 (4)	LC1D115•• 200
HD	125		HRL36150U31X	150	300 (4)	LC1D115•• 200
ND —	175	ATV•B0C16T6	JRL36250U31X	250	500 (4)	LC1D115•• 200
HD	150		JRL36250U31X	250	500 (4)	LC1D115•• 200
ND —	200	ATV•B0C20T6	JRL36250U31X	250	500 (4)	LC1F185•• 240
HD	175		JRL36250U31X	250	500 (4)	LC1D115•• 200
ND —	250	ATV•B0C25T6	JRL36250U31X	250	500 (4)	LC1F225•• 280
HD	200		JRL36250U31X	250	500 (4)	LC1D115•• 200
ND —	350	ATV•B0C31T6	LRL36400U31X	400	800 (4)	LC1F330•• 360
HD	250		JRL36250U31X	250	500 (4)	LC1F225•• 280
ND —	450	ATV•B0C40T6	LRL36600U31X	600	1200 (4)	LC1F500•• 580
HD	350		LRL36400U31X	400	800 (4)	LC1F330•• 360
ND —	550	ATV•B0C50T6	LRL36600U31X	600	1200 (4)	LC1F500•• 580
HD	450		LRL36600U31X	600	1200 (4)	LC1F500•• 580
ND —	650	ATV•B0C63T6	MTZ2 08L Micrologic 3.0 X	736	1600 (4)	LC1F630•• 850
HD	550		LRL36600U31X	600	1200 (4)	LC1F500•• 580
ND —	800	ATV•B0C80T6	MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F630•• 850
HD	650		MTZ2 08L Micrologic 3.0 X	736	1600 (4)	LC1F630•• 850
ND —	1000	ATV•B0M10T6	MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F1250•• 1060
HD	800		MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F630•• 850
ND —	1200	ATV•B0M12T6	MTZ2 16L Micrologic 6.0 X	1472	3200 (4)	LC1F1400•• 1190
HD	1000		MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F1250•• 1060

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: fixed.

(5) Rated instantaneous short-circuit current li: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular

Motor starters

IEC 690 V Low harmonic/Regen drives




MTZ2 16H1

+



LC1F1700••

+



ATV6B0M10Q6

IEC standard motor starters

Nominal power		Drive Reference (1)	Circuit breaker			Line contactor	
ND: Normal duty	HD: Heavy duty		Type (2)	Rating @50°C	I _{li}	Reference (3)	Rating @60°C
kW	HP		A	A	A	A	A
Three-phase supply voltage: 690 V 50/60 Hz							
ND 110	—	ATV•B0C11Q6	NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D115••	200
HD 90			NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D80••	125
ND 132	—	ATV•B0C13Q6	NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D115••	200
HD 110			NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D115••	200
ND 160	—	ATV•B0C16Q6	NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1D115••	200
HD 132			NSX250HB1 Micrologic 2.2 160	160	2400 (4)	LC1D115••	200
ND 200	—	ATV•B0C20Q6	NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1F185••	240
HD 160			NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1D115••	200
ND 250	—	ATV•B0C25Q6	NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F265••	300
HD 200			NSX250HB1 Micrologic 2.2 250	250	3000 (4)	LC1F185••	240
ND 315	—	ATV•B0C31Q6	NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F330••	360
HD 250			NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F265••	300
ND 400	—	ATV•B0C40Q6	NSX630HB1 Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
HD 315			NSX400HB1 Micrologic 2.3 400	400	4800 (4)	LC1F330••	360
ND 500	—	ATV•B0C50Q6	NSX630HB1 Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
HD 400			NSX630HB1 Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
ND 630	—	ATV•B0C63Q6	NS800LB Micrologic 5.0	800	1600 (5)	LC1F630••	850
HD 500			NSX630HB1 Micrologic 2.3 630	600	6900 (4)	LC1F500••	580
ND 800	—	ATV•B0C80Q6	MTZ2 10H1 Micrologic 5.0 X	1000	2000 (5)	LC1F1250••	1060
HD 630			NS800LB Micrologic 5.0	800	1600 (5)	LC1F630••	850
ND 1000	—	ATV•B0M10Q6	MTZ2 12H1 Micrologic 5.0 X	1250	2500 (5)	LC1F1400••	1190
HD 800			MTZ2 10H1 Micrologic 5.0 X	1000	2000 (5)	LC1F1250••	1060
ND 1200	—	ATV•B0M12Q6	MTZ2 16H1 Micrologic 5.0 X	1600	3200 (5)	LC1F1700••	1450
HD 1000			MTZ2 12H1 Micrologic 5.0 X	1250	2500 (5)	LC1F1400••	1190

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current I_{li}: fixed.

(5) Rated instantaneous short-circuit current I_{li}: setting 2.



NS1000N Micrologic 5.0

+



LC1F1250••

+



ATV9L0C50Q4

IEC standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker			Line contactor		
		Type (2)	Rating @50°C	I _i	Reference (3)	Rating @60°C	
KW	HP		A	A	A	A	
Three-phase supply voltage: 400 V 50/60 Hz							
ND 132	—	ATV•L0C13Q4	NSX400N Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
HD 110			NSX400N Micrologic 2.3 400	400	4800 (5)	LC1F225••	280
ND 160	—	ATV•L0C16Q4	NSX400N Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
HD 132			NSX400N Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
ND 200	—	ATV•L0C20Q4	NSX630N Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
HD 160			NSX400N Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
ND 250	—	ATV•L0C25Q4	NSX630N Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
HD 200			NSX630N Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
ND 315	—	ATV•L0C31Q4	NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
HD 250			NSX630N Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
ND 400	—	ATV•L0C40Q4	NS1000N Micrologic 5.0	1000	2000 (6)	LC1F1250••	1060
HD 315			NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
ND 500	—	ATV•L0C50Q4	NS1250N Micrologic 5.0	1250	2500 (6)	LC1F1250••	1060
HD 400			NS1000N Micrologic 5.0	1000	2000 (6)	LC1F1250••	1060
ND 630	—	ATV•L0C63Q4	NS1600N Micrologic 5.0	1600	3200 (6)	LC1F1700••	1450
HD 500			NS1250N Micrologic 5.0	1250	2500 (6)	LC1F1250••	1060
ND 800	—	ATV•L0C80Q4	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••	1750
HD 630			NS1600N Micrologic 5.0	1600	3200 (6)	LC1F1700••	1450
ND 900	—	ATV•L0C90Q4	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
HD 710			NS1600N Micrologic 5.0	1600	3200 (6)	LC1F2100••	1750
ND 1000	—	ATV•L0M10Q4 (4)	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••	1750
HD 800	ATV•L0M10Q4		MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••	1750
ND 1200	—	ATV•L0M12Q4 (4)	MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••	2600
HD 1000			MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••	1750
ND 1500	—	ATV•L0M15Q4 (4)	MTZ2 32H1 Micrologic 5.0 X	3200	6400 (6)	LC1F2600••	2600
HD 1200			MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••	2600
ND 1800	—	ATV•L0M18Q4 (4)	MTZ2 32H1 Micrologic 5.0 X	3200	6400 (6)	3 x LC1F1700••	3262
HD 1400			MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••	2600

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) A thermal test is required to fulfill IEC 61439-1.

(5) Rated instantaneous short-circuit current I_i: fixed.

(6) Rated instantaneous short-circuit current I_i: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular

Motor starters

IEC 440 V - 6 pulse Liquid-cooled drives



NSX400H Micrologic 2.3 400



LC1F265••



ATV9LOC13R4

IEC standard motor starters

Nominal power		Drive	Circuit breaker			Line contactor	
ND: Normal duty	HD: Heavy duty	Reference (1)	Type (2)	Rating @50°C	li	Reference (3)	Rating @60°C
kW	HP			A	A	A	A
Three-phase supply voltage: 440 V 50/60 Hz							
ND 132	—	ATV•LOC13R4	NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F265••	300
HD 110			NSX250N Micrologic 2.2 250	250	3000 (5)	LC1F225••	280
ND 160	—	ATV•LOC16R4	NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
HD 132			NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F265••	300
ND 200	—	ATV•LOC20R4	NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F400••	430
HD 160			NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
ND 250	—	ATV•LOC25R4	NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
HD 200			NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F400••	430
ND 315	—	ATV•LOC31R4	NS630bN Micrologic 5.0	630	1260 (6)	LC1F630••	850
HD 250			NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
ND 400	—	ATV•LOC40R4	NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
HD 315			NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
ND 500	—	ATV•LOC50R4	NS1000N Micrologic 5.0	1000	2000 (6)	LC1F1250••	1060
HD 400			NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
ND 630	—	ATV•LOC63R4	NS1250N Micrologic 5.0	1250	2500 (6)	LC1F1700••	1450
HD 500			NS1000N Micrologic 5.0	1000	2000 (6)	LC1F1250••	1060
ND 800	—	ATV•LOC80R4	NS1600N Micrologic 5.0	1600	3200 (6)	LC1F2100••	1750
HD 630			NS1250N Micrologic 5.0	1250	2500 (6)	LC1F1700••	1450
ND 900	—	ATV•LOC90R4	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••	1750
HD 710			NS1600N Micrologic 5.0	1600	3200 (6)	LC1F1700••	1450
ND 1000	—	ATV•LOM10R4 (4)	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
HD 800		ATV•LOM10R4	NS1600N Micrologic 5.0	1600	3200 (6)	LC1F2100••	1750
ND 1200	—	ATV•LOM12R4 (4)	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
HD 1000		ATV•LOM12R4	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
ND 1500	—	ATV•LOM15R4 (4)	MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••	2600
HD 1200			MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
ND 1800	—	ATV•LOM18R4 (4)	MTZ2 32H1 Micrologic 5.0 X	3200	6400 (6)	3 x LC1F1700••	3262
HD 1400			MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••	2600

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) A thermal test is required to fulfill IEC 61439-1.

(5) Rated instantaneous short-circuit current li: fixed.

(6) Rated instantaneous short-circuit current li: setting 2.



RLF36160U44A

+



LC1F1400••

+



ATV6LOC80T4

UL standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker Type (2)	Rating @50°C li		Line contactor Reference (3)	Rating @60°C
			kW	HP		
Three-phase supply voltage: 480 V 50/60 Hz						
ND – 200	ATV•L0C13T4	LLL36400U31X	400	800 (4)	LC1F265••	300
HD 150		JLL36250U31X	250	500 (4)	LC1F185••	240
ND – 250	ATV•L0C16T4	LLL36400U31X	400	800 (4)	LC1F330••	360
HD 200		LLL36400U31X	400	800 (4)	LC1F265••	300
ND – 300	ATV•L0C20T4	LLL36600U31X	600	1200 (4)	LC1F400••	430
HD 250		LLL36400U31X	400	800 (4)	LC1F330••	360
ND – 400	ATV•L0C25T4	LLL36600U31X	600	1200 (4)	LC1F500••	580
HD 300		LLL36600U31X	600	1200 (4)	LC1F400••	430
ND – 500	ATV•L0C31T4	PLL34080U31A	736	1600 (4)	LC1F630••	850
HD 400		LLL36600U31X	600	1200 (4)	LC1F500••	580
ND – 600	ATV•L0C40T4	PLL34100U44A	920	2000 (4)	LC1F630••	850
HD 500		PLL34080U31A	736	1600 (4)	LC1F630••	850
ND – 700	ATV•L0C50T4	PLL34120U44A	1104	2400 (4)	LC1F1250••	1060
HD 600		PLL34100U44A	920	2000 (4)	LC1F630••	850
ND – 900	ATV•L0C63T4	RLF36160U44A	1472	3200 (4)	LC1F1400••	1190
HD 700		PLL34120U44A	1104	2400 (4)	LC1F1250••	1060
ND – 1100	ATV•L0C80T4	RLF36160U44A	1472	3200 (4)	LC1F1700••	1450
HD 900		RLF36160U44A	1472	3200 (4)	LC1F1400••	1190
ND – 1300	ATV•L0C90T4	RLF36200U44A	1840	4000 (4)	LC1F2100••	1750
HD 1000		RLF36160U44A	1472	3200 (4)	LC1F1700••	1450
ND – 1400	ATV•L0M10T4	RLF36200U44A	1840	4000 (4)	LC1F2600••	2600
HD 1100		RLF36160U44A	1472	3200 (4)	LC1F1700••	1450
ND – 1700	ATV•L0M12T4	RLF36250U44A	2300	5000 (4)	LC1F2600••	2600
HD 1400		RLF36200U44A	1840	4000 (4)	LC1F2600••	2600
ND – 2200	ATV•L0M15T4	MTZ3 40H Micrologic 6.0 X	3680	8000 (4)	3 x LC1F1700••	3262
HD 1700		RLF36250U44A	2300	5000 (4)	LC1F2600••	2600
ND – 2500	ATV•L0M18T4	MTZ3 40H Micrologic 6.0 X	3680	8000 (4)	3 x LC1F1700••	3262
HD 2000		RLF36300U44A	2760	6000 (4)	LC1F2600••	2600

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular

Motor starters

IEC 500 V - 6 pulse Liquid-cooled drives



MTZ2 20H1



LC1F2600••



ATV6LOM18N6

IEC standard motor starters

Nominal power		Drive Reference (1)	Circuit breaker			Line contactor	
ND: Normal duty	HD: Heavy duty		Type (2)	Rating @50°C	li	Reference (3)	Rating @60°C
kW	HP			A	A	A	A
Three-phase supply voltage: 500 V 50/60 Hz							
ND 132	—	ATV•L0C20N6	NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F265••	300
HD 110			NSX250N Micrologic 2.2 250	250	3000 (5)	LC1F225••	280
ND 200	—	ATV•L0C28N6	NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
HD 160			NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F265••	300
ND 220	—	ATV•L0C31N6	NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F400••	430
HD 180			NSX400H Micrologic 2.3 400	400	4800 (5)	LC1F330••	360
ND 250	—	ATV•L0C40N6	NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
HD 220			NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F400••	430
ND 315	—	ATV•L0C45N6	NS630bN Micrologic 5.0	630	1260 (5)	LC1F630••	850
HD 250			NSX630H Micrologic 2.3 630	600	6900 (5)	LC1F500••	580
ND 400	—	ATV•L0C56N6	NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
HD 315			NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
ND 500	—	ATV•L0C71N6	NS1000N Micrologic 5.0	1000	2000 (6)	LC1F1250••	1060
HD 400			NS800N Micrologic 5.0	800	1600 (6)	LC1F630••	850
ND 630	—	ATV•L0C90N6	NS1250N Micrologic 5.0	1250	2500 (6)	LC1F1700••	1450
HD 500			NS1000N Micrologic 5.0	1000	2000 (6)	LC1F1250••	1060
ND 800	—	ATV•L0M12N6	NS1600N Micrologic 5.0	1600	3200 (6)	LC1F2100••	1750
HD 710			NS1250N Micrologic 5.0	1250	2500 (6)	LC1F1700••	1450
ND 1000	—	ATV•L0M14N6	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••	1750
HD 800			NS1600N Micrologic 5.0	1600	3200 (6)	LC1F1700••	1450
ND 1200	—	ATV•L0M16N6 (4)	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
HD 900		ATV•L0M16N6	NS1600N Micrologic 5.0	1600	3200 (6)	LC1F2100••	1750
ND 1300	—	ATV•L0M18N6 (4)	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
HD 1000		ATV•L0M18N6	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
ND 1600	—	ATV•L0M22N6 (4)	MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••	2600
HD 1200			MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••	2600
ND 1900	—	ATV•L0M26N6 (4)	MTZ2 32H1 Micrologic 5.0 X	3200	6400 (6)	3 x LC1F1700••	3262
HD 1500			MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••	2600

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) A thermal test is required to fulfill IEC 61439-1.

(5) Rated instantaneous short-circuit current li: fixed.

(6) Rated instantaneous short-circuit current li: setting 2.



MTZ2 12L

+



LC1F1250••

+



ATV6L0M12T6

UL standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker Type (2)	Rating @50°C li		Line contactor Reference (3)	Rating @60°C
			kW HP	A		
Three-phase supply voltage: 600 V 50/60 Hz						
ND — 200	ATV•L0C20T6	JRL36250U31X	250	500 (4)	LC1F185••	240
HD 150		JRL36250U31X	250	500 (4)	LC1D115••	200
ND — 300	ATV•L0C28T6	LRL36400U31X	400	800 (4)	LC1F330••	360
HD 200		JRL36250U31X	250	500 (4)	LC1F185••	240
ND — 350	ATV•L0C31T6	LRL36400U31X	400	800 (4)	LC1F400••	430
HD 250		LRL36400U31X	400	800 (4)	LC1F225••	280
ND — 450	ATV•L0C40T6	LRL36600U31X	600	1200 (4)	LC1F500••	580
HD 350		LRL36600U31X	400	800 (4)	LC1F400••	430
ND — 500	ATV•L0C45T6	LRL36600U31X	600	1200 (4)	LC1F500••	580
HD 400		LRL36600U31X	600	1200 (4)	LC1F400••	430
ND — 600	ATV•L0C56T6	MTZ2 08L Micrologic 3.0 X	736	1600 (4)	LC1F630••	850
HD 500		LRL36600U31X	600	1200 (4)	LC1F500••	580
ND — 700	ATV•L0C71T6	MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F630••	850
HD 600		MTZ2 08L Micrologic 3.0 X	736	1600 (4)	LC1F630••	850
ND — 900	ATV•L0C90T6	MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F1250	1060
HD 700		MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F630••	850
ND — 1200	ATV•L0M12T6	MTZ2 16L Micrologic 6.0 X	1472	3200 (4)	LC1F1700••	1450
HD 1000		MTZ2 12L Micrologic 6.0 X	1104	2400 (4)	LC1F1250••	1060
ND — 1400	ATV•L0M14T6	MTZ2 16L Micrologic 6.0 X	1472	3200 (4)	LC1F1700••	1450
HD 1100		MTZ2 16L Micrologic 6.0 X	1472	3200 (4)	LC1F1400••	1190
ND — 1600	ATV•L0M16T6	MTZ2 20L Micrologic 6.0 X	1840	4000 (4)	LC1F2100••	1750
HD 1300		MTZ2 16L Micrologic 6.0 X	1472	3200 (4)	LC1F1700••	1450
ND — 1800	ATV•L0M18T6	MTZ2 25L Micrologic 6.0 X	2300	5000 (4)	LC1F2600••	2600
HD 1400		MTZ2 16L Micrologic 6.0 X	1472	3200 (4)	LC1F2100••	1750
ND — 2200	ATV•L0M22T6	MTZ2 25L Micrologic 6.0 X	2300	5000 (4)	LC1F2600••	2600
HD 1700		MTZ2 20L Micrologic 6.0 X	1840	4000 (4)	LC1F2600••	2600
ND — 2600	ATV•L0M26T6	MTZ2 30L Micrologic 6.0 X	2760	6000 (4)	3 x LC1F1700••	3262
HD 2100		MTZ2 25L Micrologic 6.0 X	2300	5000 (4)	LC1F2600••	2600

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.

(4) Rated instantaneous short-circuit current li: setting 2.

Combinations for customer assembly (continued)

Variable speed drives

Altivar Process Modular

Motor starters

IEC 690 V - 6 pulse Liquid-cooled drives



MTZ2 32H1



LC1F2600••



ATV6L0M26Q6

IEC standard motor starters

Nominal power ND: Normal duty HD: Heavy duty	Drive Reference (1)	Circuit breaker			Line contactor	
		Type (2)	Rating @50°C	I _{li}	Reference (3)	Rating @60°C
kW HP				A A	A	A
Three-phase supply voltage: 690 V 50/60 Hz						
ND 200	—	ATV•L0C20Q6	NSX400HB1 Micrologic 2.3 400	400	4800 (5)	LC1F225••
HD 160			NSX250HB1 Micrologic 2.2 250	250	3000 (5)	LC1F185••
ND 280	—	ATV•L0C28Q6	NSX400HB1 Micrologic 2.3 400	400	4800 (5)	LC1F400••
HD 220			NSX400HB1 Micrologic 2.3 400	400	4800 (5)	LC1F265••
ND 315	—	ATV•L0C31Q6	NSX630HB1 Micrologic 2.3 630	600	6900 (5)	LC1F400••
HD 250			NSX400HB1 Micrologic 2.3 400	400	4800 (5)	LC1F330••
ND 400	—	ATV•L0C40Q6	NSX630HB1 Micrologic 2.3 630	600	6900 (5)	LC1F500••
HD 315			NSX630HB1 Micrologic 2.3 630	600	6900 (5)	LC1F400••
ND 450	—	ATV•L0C45Q6	NSX630HB1 Micrologic 2.3 630	600	6900 (5)	LC1F500••
HD 355			NSX630HB1 Micrologic 2.3 630	600	6900 (5)	LC1F500••
ND 560	—	ATV•L0C56Q6	NS800LB Micrologic 5.0	800	1600 (6)	LC1F630••
HD 450			NSX630HB1 Micrologic 2.3 630	600	6900 (5)	LC1F500••
ND 710	—	ATV•L0C71Q6	MTZ2 10H1 Micrologic 5.0 X	1000	2000 (6)	LC1F1250••
HD 560			NS800LB Micrologic 5.0	800	1600 (6)	LC1F630••
ND 900	—	ATV•L0C90Q6	MTZ2 12H1 Micrologic 5.0 X	1250	2500 (6)	LC1F1400••
HD 710			MTZ2 10H1 Micrologic 5.0 X	1000	2000 (6)	LC1F1250••
ND 1200	—	ATV•L0M12Q6	MTZ2 16H1 Micrologic 5.0 X	1600	3200 (6)	LC1F2100••
HD 1000			MTZ2 12H1 Micrologic 5.0 X	1250	2500 (6)	LC1F1700••
ND 1400	—	ATV•L0M14Q6	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••
HD 1100			MTZ2 16H1 Micrologic 5.0 X	1600	3200 (6)	LC1F1700••
ND 1600	—	ATV•L0M16Q6	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2600••
HD 1300			MTZ2 16H1 Micrologic 5.0 X	1600	3200 (6)	LC1F2100••
ND 1800	—	ATV•L0M18Q6 (4)	MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••
HD 1400	ATV•L0M18Q6		MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••
ND 2200	—	ATV•L0M22Q6 (4)	MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••
HD 1700			MTZ2 20H1 Micrologic 5.0 X	2000	4000 (6)	LC1F2100••
ND 2600	—	ATV•L0M26Q6 (4)	MTZ2 32H1 Micrologic 5.0 X	3200	6400 (6)	LC1F2600••
HD 2100			MTZ2 25H1 Micrologic 5.0 X	2500	5000 (6)	LC1F2600••
						2600

(1) Replace the dot • with «6» for ATV6A0 or «9» for ATV9A0.

(2) The type of circuit breaker is selected for Icu min. 50 kA.

(3) Replace the dots •• with the control circuit voltage code indicated in the documentation for the contactor.


(4) A thermal test is required to fulfill IEC 61439-1.

(5) Rated instantaneous short-circuit current I_{li}: fixed.

(6) Rated instantaneous short-circuit current I_{li}: setting 2.

Variable speed drives and soft starters

A whole world of Services for your drives and soft starters by Schneider Electric



Support and services offer by Schneider Electric

Variable speed drives and soft starters are an important part of your operation, with downtime having a significant impact on your business. Protecting that investment through comprehensive services means that you can continue to deliver optimally throughout the lifecycle of your drive and soft starter. Our range of services is designed to help you get more out of your drives and soft starters, your operation, and to improve your environmental impact.



Install

- **Extended Warranty** service helps you control your maintenance costs. Schneider Electric will provide a replacement drive and soft starter or repair the product on site during a period of one or three years more than the standard warranty, in all conditions covered by the extended warranty.
- **Start-up** service is the first essential step in maintenance and optimal operational performance of the drive or soft starter. Our comprehensive review checks up to 100 parameters and is especially designed for drives and soft starters in simple applications.
- **Commissioning** service ensures a reliable start for operations with more complex applications and drive systems. The unique requirements of your process need to be carefully considered to ensure efficient operations.



Operate

- **Preventive Maintenance** service performs predetermined maintenance actions according to a product-specific schedule. The work is carried out by certified technical experts following Schneider Electric instructions. This service minimizes unplanned downtime and extends your equipment lifetime.
- **Remote Technical Support** brings you expert product assistance over the phone, email, chat, or web for any technical questions relating to your drives and soft starters, including configuration, diagnostics, and maintenance. Our global support team is multi-lingual with support available up to R&D level experts if needed.
- **On-Site Expert Assistance** service offers you highly skilled field service experts to troubleshoot and resolve drive or soft starter equipment-related matters at your site, as a back-up source of expertise for your personnel.
- **Spare Part Management** service identifies and manages your critical spare parts either on your site or offsite. This service ensures that you have access to the spares you need without having to invest in capital to maintain the stock.

(1) Services available in countries that have the right structure and capabilities.



Support and services offer by Schneider Electric (continued)

Optimize

- **Training** service offers eLearning, classroom, and onsite training provision to enhance the technical installation, commissioning, and maintenance competencies of your personnel. Added competence translates into further process efficiency and reliability, as well as employee satisfaction.
- **EcoStruxure Asset Advisor** service enables you to move from reactive to predictive maintenance and access actionable insight provided by the advisor. The service predicts drive- and motor-related actions through connected devices and advanced algorithms monitored by Schneider Electric's experts.



Renew

- **Drive Revitalization** is an excellent choice if you prefer to use your aging drives longer and want to extend their service life with affordable and comprehensive inspection and replacement of all critical parts.
- **Drive and soft starter replacement** involves modernizing equipment by replacing the previous aged or obsolete product with a new one matched to the purpose. The service can be extended with engineering in case the device and process requires more advanced engineering.



Circular economy

- **Spare Parts** are available from our local, regional, and global stocks. Original equipment parts from Schneider Electric are reliable and easily available. They will help to keep your product in operation for longer.
- **Repair** allows you to extend the life of your drive or soft starter. The affected product can be replaced, or repaired on site or at our repair centers, depending on the type of product in question.
- **Fast Exchange by refurbished drive or soft starter (1)** gives a second life to inoperative drives or soft starters. In this case, we offer an immediate exchange with a replacement refurbished drive or soft starter and take back the product, repair it, and keep it ready for the next exchange.
- **Take-back and recycling (1)** is the last step to improve your environmental impact. Unrepairable products are dismantled, raw materials are collected and given a second life. Up to 85% of the product components can be recycled.



Service contracts secure recovery, availability, and outcome

Service contracts manage the safety and performance of your assets through well-defined maintenance plans tailored to your operational needs. The predefined service contract – Advantage Service Plan – and fully customizable “à la carte” service contract are built from the services in the “Operate” and “Optimize” phases and service levels defining availability, response, and lead times matching your particular needs. You will enjoy priority access to Schneider Electric support when you need it, as well as having an expert partner to plan the long-term evolution of your drives and soft starters.

mySchneider app

With the mySchneider app you have easy 24/7 access to product information and expert support. All registered users have access to additional features, such as real-time notifications, order tracking, product pricing, and availability. The mySchneider app is available for download from the IOS and Android app store.



Schneider Electric – helping you succeed

Schneider Electric, the leader in digital transformation of energy management and automation, has operations in more than 100 countries. With this global footprint we have certified field service representatives, regional expert and advanced level support up to product R&D to provide you the right support across the lifecycle of your drives and soft starters. Furthermore, we offer an extensive network of local and global repair centers and a logistics chain that underpins our ability to respond to your needs.

To order services or find out more, please contact your local Schneider Electric service center.

(1) Services available in countries that have the right structure and capabilities.

ATV9A0C20T4	41	ATV9A0C63R4	39	ATV9B0C20T6	57	ATV9B0C80T4	53	ATV9L0C45Q6	71
	78		75	ATV9B0C25N6	55		79		83
ATV9A0C20T6	45	ATV9A0C63T4	41	ATV9B0C25Q4	49	ATV9B0C80T6	57	ATV9L0C45T6	69
	82		78		73	ATV9B0M10N6	55		82
ATV9A0C25N6	43	ATV9A0C63T6	45	ATV9B0C25Q6	59	ATV9B0M10Q4	49	ATV9L0C50Q4	61
	81		82	ATV9B0C25R4	51		73		74
ATV9A0C25Q4	37	ATV9A0C71Q4	37		76	ATV9B0M10Q6	59	ATV9L0C50R4	63
	72		72	ATV9B0C25T4	53	ATV9B0M10R4	51		77
ATV9A0C25Q6	47	ATV9A0C71R4	39		79	ATV9B0M10T4	53	ATV9L0C50T4	65
	83		75	ATV9B0C25T6	57	ATV9B0M10T6	57	ATV9L0C56N6	67
ATV9A0C25R4	39	ATV9A0C71T4	41	ATV9B0C31N6	55	ATV9B0M12N6	55	ATV9L0C56Q6	71
	75		78	ATV9B0C31Q4	49	ATV9B0M12Q6	59		83
ATV9A0C25T4	41	ATV9A0C80N6	43	ATV9B0C31Q6	59	ATV9B0M12T6	57	ATV9L0C56T6	69
	78		81	ATV9B0C31R4	51	ATV9L0C13Q4	61		82
ATV9A0C25T6	45	ATV9A0C80Q4	37		76		74	ATV9L0C63Q4	61
	82		72	ATV9B0C31T4	53	ATV9L0C13R4	63		74
ATV9A0C31N6	43	ATV9A0C80Q6	47		79	ATV9L0C13T4	65	ATV9L0C63R4	63
	81		83	ATV9B0C31T6	57	ATV9L0C16Q4	61		77
ATV9A0C31Q4	37	ATV9A0C80R4	39	ATV9B0C35Q4	49	ATV9L0C16R4	63	ATV9L0C63T4	65
	72		75	ATV9B0C35R4	51		77	ATV9L0C71N6	67
ATV9A0C31Q6	47	ATV9A0C80T4	41	ATV9B0C35T4	53	ATV9L0C16T4	65	ATV9L0C71Q6	71
	83		78	ATV9B0C40N6	55	ATV9L0C20Q4	61		83
ATV9A0C31R4	39	ATV9A0C80T6	45	ATV9B0C40Q4	49	ATV9L0C20Q6	71	ATV9L0C71T6	69
	75		82	ATV9B0C40T4	53	ATV9L0C20R4	63		82
ATV9A0C31T4	41	ATV9A0M10N6	43	ATV9B0C45R4	51	ATV9L0C20T4	65	ATV9L0C80Q4	61
	78		81	ATV9B0C45Q4	49		80	ATV9L0C80R4	74
ATV9A0C31T6	45	ATV9A0M10Q4	37	ATV9B0C45T4	53	ATV9L0C25Q4	61		77
	82		72	ATV9B0C50N6	55	ATV9L0C25R4	63	ATV9L0C80T4	65
ATV9A0C35Q4	37	ATV9A0M10Q6	47	ATV9B0C50Q4	49	ATV9L0C25T4	65	ATV9L0C90N6	67
	72		83	ATV9B0C40R4	51	ATV9L0C28N6	67	ATV9L0C90Q4	61
ATV9A0C35R4	39	ATV9A0M10R4	39	ATV9B0C40R4	51	ATV9L0C28Q6	71	ATV9L0C90Q6	71
	75		75	ATV9B0C40T4	53		83		83
ATV9A0C35T4	41	ATV9A0M10T4	41	ATV9B0C40T6	57	ATV9L0C28T6	69	ATV9L0C90R4	63
	78		78	ATV9B0C45Q4	49		82		77
ATV9A0C40N6	43	ATV9A0M10T6	45	ATV9B0C45R4	51	ATV9L0C31N6	67	ATV9L0C90T4	65
	81		82	ATV9B0C45T4	53	ATV9L0C31Q4	61		80
ATV9A0C40Q4	37	ATV9A0M12N6	43	ATV9B0C50N6	55	ATV9L0C31Q6	71	ATV9L0M10R4	63
	72		81	ATV9B0C50Q4	49	ATV9L0C31R4	63		77
ATV9A0C40Q6	47	ATV9A0M12Q6	47	ATV9B0C50R4	51	ATV9L0M10T4	65	ATV9L0M10T4	65
	83		83	ATV9B0C55R4	53	ATV9L0M12N6	67		80
ATV9A0C40R4	39	ATV9A0M12T6	45	ATV9B0C55T4	53	ATV9L0M12Q4	61	ATV9L0M12Q4	61
	75		82	ATV9B0C55Q4	51	ATV9L0M12T6	65		74
ATV9A0C40T4	41	ATV9A0M11Q4	49	ATV9B0C55R4	53	ATV9L0M12R4	63	ATV9L0M12R4	63
	78		73	ATV9B0C56Q4	49	ATV9L0M12T4	65		77
ATV9A0C40T6	45	ATV9A0M11T6	45	ATV9B0C56R4	51	ATV9L0M12T6	69	ATV9L0M12T6	69
	82		82	ATV9B0C56T4	53	ATV9L0M14N6	67		82
ATV9A0C45Q4	37	ATV9A0M11T6	55	ATV9B0C56T6	57	ATV9L0M14Q4	61	ATV9L0M14Q4	61
	72		55	ATV9B0C56Q4	49	ATV9L0M14T6	69		81
ATV9A0C45R4	39	ATV9A0M11Q4	49	ATV9B0C57T4	53	ATV9L0M14T6	69	ATV9L0M14T6	69
	75		73	ATV9B0C57Q4	49	ATV9L0M15Q4	61		82
ATV9A0C45T4	41	ATV9A0M11R4	51	ATV9B0C57R4	51	ATV9L0M15Q4	61	ATV9L0M15Q4	61
	78		76	ATV9B0C58T4	53	ATV9L0M15R4	63		74
ATV9A0C50N6	43	ATV9A0M13Q4	49	ATV9B0C58Q4	49	ATV9L0M15R4	63	ATV9L0M15R4	63
	81		73	ATV9B0C59T4	53	ATV9L0M15T4	65		77
ATV9A0C50Q4	37	ATV9A0M13T6	57	ATV9B0C59Q4	49	ATV9L0M15T4	69	ATV9L0M15T4	80
	72		57	ATV9B0C60T4	53		82		80
ATV9A0C50Q6	47	ATV9A0M16N6	55	ATV9B0C60Q4	49	ATV9L0M16T6	69	ATV9L0M16T6	69
	83		76	ATV9B0C61T4	53	ATV9L0M16T6	82		82
ATV9A0C50R4	39	ATV9A0M16Q4	49	ATV9B0C61Q4	49	ATV9L0M17N6	67	ATV9L0M17N6	67
	75		73	ATV9B0C61R4	51	ATV9L0M17Q4	61		81
ATV9A0C50T4	41	ATV9A0M16T4	53	ATV9B0C61T4	53	ATV9L0M17T6	69	ATV9L0M17T6	69
	78		79	ATV9B0C62T4	53	ATV9L0M18N6	67		82
ATV9A0C50T6	45	ATV9A0M17Q4	59	ATV9B0C62Q4	49	ATV9L0M18Q4	61	ATV9L0M18Q4	61
	82		59	ATV9B0C63T4	53	ATV9L0M18T6	69		74
ATV9A0C55Q4	37	ATV9A0M17T6	57	ATV9B0C63Q4	49	ATV9L0M19N6	67	ATV9L0M19N6	67
	72		57	ATV9B0C64T4	53	ATV9L0M19Q4	61		81
ATV9A0C56R4	39	ATV9A0M18N6	55	ATV9B0C64Q4	49	ATV9L0M19T6	69	ATV9L0M19T6	69
	75		76	ATV9B0C65T4	53	ATV9L0M19T6	82		82
ATV9A0C56T4	41	ATV9A0M18Q4	51	ATV9B0C65Q4	49	ATV9L0M20N6	67	ATV9L0M20N6	67
	78		76	ATV9B0C66T4	53	ATV9L0M20Q4	61		81
ATV9A0C63N6	43	ATV9A0M19Q4	51	ATV9B0C66Q4	49	ATV9L0M20T6	69	ATV9L0M20T6	69
	81		76	ATV9B0C67T4	53	ATV9L0M21N6	67		82
ATV9A0C63Q4	37	ATV9A0M20T4	51	ATV9B0C67Q4	49	ATV9L0M21Q4	61	ATV9L0M21Q4	61
	72		76	ATV9B0C68T4	53	ATV9L0M21T6	65		74
ATV9A0C63Q6	47	ATV9A0M20T4	53	ATV9B0C68Q4	49	ATV9L0M21T6	65	ATV9L0M21T6	65
	83		79	ATV9B0C69T4	53	ATV9L0M22N6	67		83

ATV9L0M16N6	67	MODBUOC16R4APM	75	MODBUOC80N6APM	81	VW3A97A01	23
	81		76		87		84
ATV9L0M16Q6	71		77		89		85
	83		86				
ATV9L0M16T6	69		89	MODBUOC80Q4APM	72		86
	82	MODBUOC16T4APM	78		74		87
ATV9L0M18N6	67		79		86		88
	81		80	MODBUOC80Q6APM	83	VW3A97B01	23
ATV9L0M18Q4	61		86		87		84
	74		89		89		85
ATV9L0M18Q6	71	MODBUOC20N6APM	81	MODBUOC80R4APM	75	VW3A98ABMAAA	24
	83		87		77	VW3A98ABMCAB	24
ATV9L0M18R4	63		89		86	VW3A98ABMCAC	24
	77	MODBUOC20Q6APM	83	MODBUOC80T4APM	78	VW3A98ABMDCE	24
ATV9L0M18T4	65		87		80	VW3A98ABMDCF	24
	80		89	MODBUOC80T6APM	82	VW3A98ABPC1	24
ATV9L0M18T6	69	MODBUOC20T6APM	82		86	VW3A98ABPDCE1	24
	82		87		89	VW3A98ABPDCF	24
ATV9L0M22N6	67		89	MODBUOM10N6APM	81	VW3A98BBMAAB	24
	81	MODBUOC31Q4APM	72		87	VW3A98BBMCAD	24
ATV9L0M22Q6	71		73		89	VW3A98BBMDCG	24
	83		74	MODBUOM10Q6APM	81	VW3A98BBPC	24
ATV9L0M22T6	69		86		87	VW3A98BBPDCG	24
	82		89	MODBUOM10T6APM	82	VW3A98BBPDCK	24
ATV9L0M26N6	67	MODBUOC31R4APM	75		89	VW3A98CF3169	24
	81		76	MODBUOM12N6APM	81	VW3A98CF4040	24
ATV9L0M26Q6	71		77		87	VW3A98CTM01	24
	83		86	MODBUOM12Q6APM	83	VW3A98CTM02	24
ATV9L0M26T6	69		89		89	VW3A98CTM03	25
	82	MODBUOC31T4APM	78	MODBUOM12T6APM	82	VW3A98CTM04	25
H			79		87	VW3A98LBPC1	26
HRL36150U31X	99		80		89	VW3A98LBPC2	26
	104		86	MODBUOM12Q6APM	83	VW3A98LBPC3	26
J			89		87	VW3A98LGHC1	26
JLL36250U31X	98	MODBUOC40N6APM	81		89	VW3A98LGHC2	26
	99		87	MODBUOM12T6APM	82	VW3A98LTMC1	26
	103		89		87	VW3A99ACA01	26
	104	MODBUOC40Q6APM	83		89	VW3A99ACA02	26
	110		87	MODBUOM12T6APM	82	VW3A99ACA03	25
L			89		87	VW3A99ACA04	25
LLL36400U31X	98	MODBUOC40T6APM	82	T	29	VW3A99ACA05	26
	103		87	TCSEGWB131W	29	VW3A99ACA06	26
	108		89	V		VW3A99ACA07	26
LLL36600U31X	98	MODBUOC50Q4APM	72	VW3A1104R10	29	VW3A99ACA08	26
	103		73	VW3A1104R100	29	VW3A99ACA09	26
	108		74	VW3A1104R30	29	VW3A99ACA10	26
LLL36600U44X	103		86	VW3A1104R50	29	VW3A99ACA11	25
LRL36400U31X	99	MODBUOC50R4APM	75	VW3A1111	29	VW3A99ACA12	25
	104		76	VW3A1112	29	VW3A99ACA13	25
	110		77	VW3A1115	29	VW3A99ACFAA	25
LRL36600U31X	99	MODBUOC50T4APM	78	VW3A3203	94	VW3A99ACFAA01	25
	104		79	VW3A3204	94	VW3A99ACFABM	25
	110		86	VW3A3420	94	VW3A99ACFCB	25
P			89	VW3A3422	94	VW3A99ACFCB01	25
PLL34080U31A	98	MODBUOC50T4APM	78	VW3A3423	94	VW3A99ACFCBM01	25
	103		79	VW3A3424	94	VW3A99ACFCBM02	25
	108		86	VW3A3601	94	VW3A99ACFCBN01	25
PLL34100U44A	98	MODBUOC50T4APM	78	VW3A3607	94	VW3A99ACFEBN01	25
	103		79	VW3A3608	94	VW3A99ACFEBN02	25
	108		87	VW3A3609	94	VW3A99ACFEC	25
PLL34120U44A	98	MODBUOC63N6APM	81	VW3A3618	94	VW3A99ACFEC01	25
	103		87	VW3A3619	94	VW3A99AR01	25
	108		89	VW3A3627	94	VW3A99BCA02	26
R			89	VW3A3628	94	VW3A99BCA03	25
RLF36160U44A	98	MODBUOC63Q6APM	83	VW3A3720	94	VW3A99BCFAB	25
	103		87	VW3A3721	94	VW3A99BCFAB01	25
	108		89	VW3A3725	94	VW3A99BCFC	25
RLF36200U44A	108	MODBUOC63Q4APM	72	VW3A3800	94	VW3A99BCFC01	25
RLF36300U44A	108		74	VW3A3802	94	VW3A99BR01	25
M			86	VW3A83BMR015	23	VW3A99BCA02	26
MODBUOC16Q4APM	72		86	VW3A83BMR050	23	VW3A99BCA03	25
	73	MODBUOC63R4APM	75	VW3A83CDG020	23	VW3A99BCFAB	25
	74		77	VW3A83CDG030	23	VW3A99BCFAB01	25
	86		86	VW3A83CDG050	23	VW3A99BCFC	25
	89	MODBUOC63T4APM	78	VW3A83CDG100	23	VW3A99BCFC01	25
			80			VW3A99BCFC02	25
			86			VW3A99BCFC03	25
			89			VW3A99BCFC04	25
		MODBUOC63T6APM	82			VW3A99BCFC05	25
			87			VZ5VAM001	28
			89			VZ5VAM002	28
			89			VZ5VAM003	28
			89			ZB5AZ905	29

Life Is On



Learn more about our products at
www.se.com/drives

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier - CS 30323
F-92500 Rueil-Malmaison Cedex
France

DIA2ED2180301EN
October 2022 - V8.0