

# Product data sheet

Specifications



## APC Smart-UPS C, Line Interactive, 3kVA, Rackmount 2U, 230V, 8x IEC C13+1x IEC C19 outlets, USB and Serial communication, AVR, Graphic LCD

SMC3000R2I-RS

### Overview

<b>Presentation</b>	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Main Output Voltage</b>	230 V
<b>Rated power in W</b>	2100 W
<b>Rated power in VA</b>	3000 VA
<b>Input Connection Type</b>	IEC 320 C20
<b>Nb of power socket outlets</b>	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
<b>Number of rack unit</b>	2U
<b>Number of cables</b>	1
<b>Battery type</b>	Lead-acid battery
<b>Provided equipment</b>	Installation guide Rack mounting brackets USB cable

### General

<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Product web sub-family</b>	Entry level
<b>Redundant</b>	No

### Physical

<b>Colour</b>	Grey
<b>Height</b>	8.9 cm
<b>Width</b>	48 cm
<b>Depth</b>	67 cm

Net weight	41 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

## Input

Input voltage limits	180...287 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
Transfer time	8 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50 Hz sync to mains

## Conformance

Product certifications	EAC
------------------------	-----

## Environmental

Acoustic level	42 dBA
Heat dissipation	81 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Batteries & Runtime

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Battery power in VAh	490 VAh runtime

---

Battery charger power	163 W rated
-----------------------	-------------

---

## Communications & Management

---

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
-------	---

---

---

Control panel	Multifunction LCD status and control console
---------------	--

---

---

Free slots	0
------------	---

---

## Surge Protection and Filtering

---

Surge energy rate	300 J
-------------------	-------

---

---

Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
-------------------	--

---

## Packing Units

---

Package 1 Weight	50.9 kg
------------------	---------

---

---

Package 1 Height	25.4 cm
------------------	---------

---

---

Package 1 width	60 cm
-----------------	-------

---

---

Package 1 Length	98 cm
------------------	-------

---

---

Number of Units in Package 3	16
------------------------------	----

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

---

Mercury free	Yes
--------------	-----

---

---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

---

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

---

---

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

---

---

Take-back	Take-back program available
-----------	-----------------------------

---

## Contractual warranty

---

Warranty	1 year repair or replace
----------	--------------------------

---