

BeneHeart R12

Electrocardiograph



Technical Specifications

Physical

Height:	128 mm
Width:	365 mm
Depth:	305 mm
Weight:	4.9 Kg

Processing

ECG sampling rate:	1000 samples/second/channel
Pacer detection sampling rate:	16,000 samples/second/channel
ECG amplifier:	DC-coupled
Acquisition mode:	Pre- or post-acquisition, provide 10 seconds of instantaneous ECG acquisition
Dynamic range:	AC differential ± 10 mV, DC offset ± 600 mV
Resolution:	1 μ V/LSB
Frequency response:	-3 dB @ 0.05 to 150 Hz
Baseline drift filter:	0.05 Hz, Baseline Drift Removal (BDR)
Artifact filter:	20 Hz, 35 Hz
AC filter:	50/60 Hz
Common mode rejection:	≥ 110 dB (with AC filter switched off)
ADC:	24 bits
Input impedance:	> 50 M Ω @ 10 Hz, defibrillator protected
Time Constant	≥ 3.2 s
Noise Level	≤ 15 μ V
Patient leakage:	< 10 μ A
Heart rate meter:	30 to 300 BPM $\pm 10\%$ or ± 5 BPM, whichever is greater
Sensitivity/gain:	2.5, 5, 10, 20, L=10 C=5, L=20 C=10 mm/mV, Auto
Boot time:	< 7 s

Display

Display type:	8-inch 24-bit color, TFT LCD with LED graphics backlit
Display resolution:	800x480 pixels
Display data:	Patient ID, Patient name, gender, age, heart rate, clock, battery power indicator, waveforms, lead labels, speed, gain, filter settings, warning messages, information messages, network, USB status

Power

Power supply:	AC input (without external power adaptor) or battery operation
---------------	--

AC Power

Input voltage:	100 to 240 VAC $\pm 10\%$
Input power:	100 VA
AC frequency:	50/60 Hz ± 3 Hz

Battery

Battery type:	Rechargeable Lithium ion battery, 4500 mAh
Charge time:	≤ 6 h to 90% and ≤ 7 h to 100% with device off
Battery Capacity:	More than 3.5 hours of continuous operation or 400 ECGs recording

Writer		
Writer technology:	Thermal dot array	
Writer speed:	5, 12.5, 25, 50 mm/s	
Number of traces:	12 leads	
Writer speed accuracy:	±5%	
Writer amplitude accuracy:	±5%	
Writer resolution:	Horizontal 40 dots/mm @ 25 mm/s, Vertical 8 dots/mm	
Paper type:	Thermal Z-fold A4 paper (210 mm x 295 mm)	US
	Letter 8.5x11 in (215 mm x 280 mm)	
Software		
Measurement and interpretation:	Supports the University of Glasgow 12-lead ECG analysis program for adults and pediatrics	
Resting ECG mode:	Records and prints 12-lead resting ECG with 10-second duration as a standard feature	
Supported patient information:	Name, patient ID, secondary ID, name, age, date of birth, gender, race, medication, class, V3 electrode Placement.	
Internal storage:	800 ECGs in internal memory	
ECG Storage format:	XML, PDF, Mindray	
Report Formats:	3x4+1R, 3x4+3R, 6x2, 6x2+1R, 12x1	
Extensional Function		
Preview and review full ECG report on screen		
Reanalyze ECG automatically after changing patient's demographics		
Touch screen (Optional)		
Connect to external printer directly (Optional)		
Upload XML or PDF reports through FTP protocol (Optional)		
Barcode scanner (Optional)		
Wifi (Optional)		
USB flash drive storage of PDF and XML outputs (Optional)		
Accessories		
ECG patient cable with banana plugs, Limb Clamps, Chest Bulbs (IEC/AHA)		
ECG cable with Electrode clips (IEC/AHA)		
ECG patient cable with banana plugs, banana to tab lead adapters, ECG tab electrodes		
Country-specific power cords		
Z-fold thermal paper (Letter or A4)		
Trolley		

Mindray Building, Keji 12th Road South,
High-tech Industrial Park, Nanshan, Shenzhen 518057, P.R. China
Tel: +86 755 8188 8998 Fax: +86 755 26582680
E-mail: intl-market@mindray.com www.mindray.com

Mindray is listed on the NYSE under the symbol "MR"

mindray [healthcare within reach] BeneHeart are registered trademarks or trademarks owned by Shenzhen Mindray Bio-medical Electronics Co., LTD.
© 2013 Shenzhen Mindray Bio-Medical Electronics Co., Ltd. All rights reserved. Specifications subject to changes without prior notice.
P/N:ENG-BeneHeart R12-210285x2P-20141110



mindray