

# ENGINE DRIVEN WELDER TS 405 EVO

The images are for reference

## WELDING PROCESS



SMAW Shielded Metal Arc welding (STICK)



Gas Tungsten Arc Welding (TIG)



## FEATURES

- D.C. Arc welding source
- Electronic regulation of welding current and arc force
- Welding control panel "EVO CONTROL"
- A.C. generator, single-phase and three-phase also available while welding
- Engine control digital module
- Bunded base
- Base plate with forklift pockets
- Canopy with large opening to allow easy maintenance (replacement of air, oil, fuel filters)
- Large fuel tank
- Fuel level sensor
- External plugs for oil and water drainage
- Emergency stop button
- Central lifting eye
- Wide access for easy maintenance
- Meets EC/UE directives



water cooled



diesel



electric starter

## DEFINITIONS

### EVO CONTROL



Welding current regulation  
Welding arc regulation  
Welding scale selection

### EVO INSTRUMENT



Welding current regulation  
Welding arc regulation  
Welding scale selection  
Digital ammeter - welding current  
Digital voltmeter - welding voltage

## ENGINE 3000 RPM

4 STROKE, NATURAL ASPIRATED	
Model	KOHLER KDW1003
Stand-By net power	17.2 kW (23.4 hp)
PRP net power	15.5 kW (21.1 hp)
COP net power	/
Cylinders / Displacement	3 / 1028 cm <sup>3</sup> (1.028 lt.)
Bore / Stroke	75 / 77.6 (mm)
Compression ratio	22.8 :1
BMEP (Brake Mean Effective Pressure : LTP - PRP)	/
Speed governor type	Mechanical
<b>FUEL CONSUMPTION</b>	
110 % (Stand-by power)	5.4 lt./h
100 % to PRP	4.9 lt./h
75 % to PRP	3.7 lt./h
50 % to PRP	2.7 lt./h
<b>COOLING SYSTEM</b>	
Total system cap. - only engine	- / 1.3l
Fan air flow	93 m <sup>3</sup> /min.
<b>LUBRICATION SYSTEM</b>	
Total oil system capacity	/
Oil capacity in sump	2.4 lt
Oil consumption at full load	/

<b>EXHAUST SYSTEM</b>	
Maximum exhaust gas flow	3.2 m <sup>3</sup> /min.
Max. exhaust gas temp.	540 °C
Maximum back pressure	8 kPa (0.08 bar)
External diameter exhaust pipe	/
<b>ELECTRICAL SYSTEM</b>	
12 Vdc	12 Vdc
Starter motor power	1.6 kW
Battery charging alternator cap.	40 A
Cold start	- 10 °C
With cold start aid	/
<b>AIR FILTER</b>	
AIR FILTER	Dry
Combustion air flow	1.54 m <sup>3</sup> /min.
<b>HEAT REJECTED AT FULL LOAD</b>	
To exhaust system	/
To water and oil	/
Radiated to room	/
To charge cooler	/



# WELDING AND GENERATION

## C.C. WELDING

CONSTANT CURRENT SMAW COATED ELECTRODE (STICK)	
Current range	20A / 20.8V ÷ 400A / 20V
Type of regulation	Continue on 2 step 20A ÷ 200A / 20A ÷ 400A
Duty cycle	330A @ 33.2V / 60% 300A @ 32V / 100%
Open circuit voltage	75 Vcc (79 Vcc to peak)
Reduced open circuit voltage with VRD	< 13 Vcc / Vdc
Arc force control	Yes

## C.C. WELDING

CONSTANT CURRENT GTAW TUNGSTEN ELECTRODE (TIG)	
Current range	20A / 10.8V ÷ 400A / 20V
Type of regulation	Continue on 2 step 20A ÷ 200A / 20A ÷ 400A
Duty cycle	380A @ 25.2V / 35% 330A @ 23.2V / 60% 300A @ 22V / 100%
Open circuit voltage	75 Vcc (79 Vcc to peak)
Reduced open circuit voltage with VRD	< 13 Vcc / Vdc

## SIMULTANEOUS LOAD CHARACTERISTIC

WELDING CURRENT	≥ 200 A	175 A	150 A	125 A	100 A	50 A
POW. IN THREE PHASE 400V cosφ 0.8	0 kVA	2.5 kVA	4 kVA	6 kVA	7.5 kVA	11 kVA
POW. IN SINGLE PHASE 230V cosφ 0.8	0 kVA	2.5 kVA	4 kVA	5 kVA	6 kVA	8 kVA

## SIMULTANEOUS LOAD CHARACTERISTIC

WELDING CURRENT	≥ 200 A	175 A	150 A	125 A	100 A	50 A
POW. IN THREE PHASE 400V cosφ 1	0 kW	5 kW	8 kW	10 kW	11 kW	11 kW
POW. IN SINGLE PHASE 230V cosφ 1	0 kW	2.5 kW	4 kW	5 kW	6 kW	8 kW
POW. IN SINGLE PHASE 110V cosφ 1	0 kW	1.5 kW	kW	2.5 kW	3 kW	4 kW

## ALTERNATOR

Fuel tank capacity	38 l
Starter battery	12 Vdc -50Ah / 420A CCA(EN)
Fuel consumption (welding 60%)	3.3 l/h
Running time (welding 60%)	11.5 h
IP protection degree	IP 23

Guaranteed acoustic power LwA (pressure LpA)	96 dB(A) (71 dB(A) @ 7 m)
Measured acoustic power LwA (pressure LpA)	94.7 dB(A) (69.7 dB(A) @ 7 m)
Max. ambient temperature	40 °C

## A.C. GENERATION

### ALTERNATOR ASYNCHRONOUS THREE-PHASE, SELF-EXCITED, SELF-REGULATED, BRUSHLESS

Insulation class	H
------------------	---

## AUXILIARY GENERATION

OUTPUT 1	
Type of source	3-phase
Frequency	50Hz
Power kVA (Power kW) Max	14 kVA (11.2 kW)
Cos φ	0.8
Voltage	400V
Current	20.2 A

OUTPUT 2	
Type of source	1-phase
Frequency	50Hz
Power kVA (Power kW) Max	8 kVA/kW
Cos φ	0.8/1
Voltage	230V
Current	34.8 A

OUTPUT 3	
Type of source	1-phase
Frequency	50Hz
Power kVA (Power kW) Max	4 kVA/kW
Cos φ	0.8/1
Voltage	110V CTE
Current	36.4A

OUTPUT 4	
Type of source	1-phase
Frequency	50Hz
Power kVA (Power kW) Max	5 kVA/kW
Cos φ	1
Voltage	48V
Current	104A

# CONTROL PANEL

## ENGINE

- Controller RGK420SA
- Engine protector thermal circuit breaker: 1x30A
- Engine protector thermal circuit breaker: 1x5A
- Siren
- Emergency stop button



FEATURES CONTROLLER RGK420SA	
Operating Mode	<ul style="list-style-type: none"> <li>• MAN - REMOTE</li> </ul>
Display	<ul style="list-style-type: none"> <li>• Graphic back-light LCD display</li> <li>• Buttons: START ▼ - ▲</li> <li>• Key</li> </ul>
Measures generator	<ul style="list-style-type: none"> <li>• Voltage L1-L2 / L2-L3 / L3-L1 - N-L1/N-L2/N-L3</li> <li>• Frequency Hz</li> </ul>
Measures engine	<ul style="list-style-type: none"> <li>• Fuel level</li> <li>• rpm meter</li> <li>• Hours meter</li> <li>• Battery voltage</li> </ul>
Protections generator	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Undervoltage</li> <li>• Overfrequency</li> <li>• Underfrequency</li> </ul>
Protections engine	<ul style="list-style-type: none"> <li>• Overspeed</li> <li>• Underspeed</li> <li>• High temperature shutdown</li> <li>• Low oil pressure shutdown</li> <li>• Low fuel level warning</li> <li>• Low fuel level shutdown</li> <li>• Battery voltage</li> <li>• Battery flat</li> <li>• Battery charge alternator failure</li> <li>• Arresto d'emergenza / Emergency stop</li> <li>• Mancato avviamento / Start failure</li> <li>• Mancato arresto / Stop failure</li> <li>• Manutenzione / Maintenance</li> </ul>
Features	<ul style="list-style-type: none"> <li>• Operator interface via symbols, codes and texts</li> <li>• Setpoints adjustable via controller buttons or PC</li> <li>• Remote Start and Stop</li> <li>• Configurable inputs and outputs</li> <li>• Operation temperature : -30°C -+70°C</li> <li>• NFC interface for wireless programming</li> </ul>

## GENERATION (VERS. AUS)

- ELCB-GFI (Ground Fault Interruptor) (400V/230V)
- Circuit breaker for 230V sockets
- Output sockets : 1x 400V 32A 3P+N+T IP67 AUS  
 1x 230V 32A 2P+T IP67 AUS  
 1x 230V 15A 2P+T IP67 AUS
- Earth terminal (PE)

## WELDING

- **EVO CONTROL:**
  - Continuous control of the welding current
  - Welding range switch
  - Continuous control of the arc force
  - Connection of remote control with automatic "local / remote" switch at the insertion of the plug
  - Welding output sockets:  
 1x Welding (+) 400A  
 1x Welding (-) 400A



- **EVO INSTRUMENT:**
  - Continuous control of the welding current
  - Welding range switch
  - Continuous control of the arc force
  - Connection of remote control with automatic "local / remote" switch at the insertion of the plug
  - Welding output sockets:  
 1x Welding (+) 400A  
 1x Welding (-) 400A
  - 2x Display - 4 Digit
  - Set the welding current
  - Current and voltage Measurement during the welding process
  - VRD ON/OFF switch (only with EVO Instrument panel)
  - Connector for connection to Box PL400



## GENERATION (VERS. 400V / 230V / 48V)

- ELCB-GFI (Ground Fault Interruptor) (400V/230V)
- Circuit breaker for 230V sockets
- Thermal circuit breakers for sockets: 1x 16A for socket 230V 16A 2P+T CEE
- Output sockets : 1x 400V 32A 3P+N+T CEE  
 1x 230V 32A 2P+T CEE  
 1x 230V 16A 2P+T CEE  
 N°2 output terminals 200A (for 48V)
- Earth terminal (PE)

## GENERATION (VERS. 400V/230V/110V CTE)

- ELCB-GFI (Ground Fault Interruptor) (400V/230V)
- Circuit breaker for 230V sockets
- Circuit breaker for 110V sockets
- Thermal circuit breakers for sockets: 1x 16A for socket 110V 16A 2P+T CEE
- Output sockets : 1x 400V 32A 3P+N+T CEE  
 1x 230V 32A 2P+T CEE  
 1x 110V 32A 2P+T CEE  
 1x 110V 16A 2P+T CEE
- Earth terminal (PE)



# WEIGHT - DIMENSIONS ACCESSORIES

TS 405 EVO





**DRY WEIGHT:**  
• 455 Kg

The welding machine pictured may include optional accessories.



**DIMENSION PICTURE**



## OPTIONS ON REQUEST

- Remote control RC2
- Remote control RCE PL - (Remote control for polarity change)
- Remote control extension cord (30m)
- Box PL 400 - External polarity change - max. 400A (only with EVO INSTRUMENT panel)
- Welding cables K500 (20+15 m, 50 mm<sup>2</sup>)
- Welding kit (mask gloves, etc.)
- Site tow CTL255
- Road tow running gear CTV4
- Earthing kit



## AVAILABLE VERSION

C1KS1020	400/230/110 - EVO CONTROL
C1KS1060	400/230/48 - EVO CONTROL
C1KS1020BKP	400/230/110 - EVO INSTRUMENT <ul style="list-style-type: none"> <li>• Gauges - water temperature and oil pressure</li> <li>• Oil pressure Indicator</li> <li>• Main battery switch</li> </ul>
C1KS1060BKP	400/230/48 - EVO INSTRUMENT <ul style="list-style-type: none"> <li>• Gauges - water temperature and oil pressure</li> <li>• Oil pressure Indicator</li> <li>• Main battery switch</li> </ul>
C1KS1040BKP	400/230 - EVO INSTRUMENT (AUSTRALIA) <ul style="list-style-type: none"> <li>• Gauges - water temperature and oil pressure</li> <li>• Oil pressure Indicator</li> <li>• Main battery switch</li> </ul>

## GENERAL INFORMATIONS

EC Directives and Standards Compliance  
 2006/42 / EC (Machinery Directive)  
 2014/35 / EU (Low Voltage Directive)  
 2014/30 / EU (EMC Directive)  
 2000/14 / EC (Directive Acoustic Emission for machines for use outdoors)  
 ISO 8528 (Reciprocating internal combustion engine driven alternating current generating sets)



ISO 9001:2015 - Cert. 0192

### WARRANTY

All devices are covered by the manufacturer's warranty.

Specifications subject to change without notice. For further information please contact the sales department.

© MOSA - Viale Europa, 59 - 20090 Cusago (Milano) - Italy - phone +39-0290352.1 - fax + 39-0290390466 E-mail: info@mosa.it Web site: www.mosa.it

