

SPECIFICATIONS

Panel	
Panel Type	IPS
Panel Size	27.0"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.311 mm
Brightness	250 cd/m ²
Contrast Ratio	20,000,000 (DCR)
Viewing Angle (H/V)	178°/178°
Display Colour	16.7M
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 25%), 3H Hard Coating
Frequency	
Frequency (H)	30 kHz-112 kHz
Frequency (V)	56 Hz-100 Hz
Signal Input	
DisplayPort	x 1
HDMI	1.4 x 1
Audio	
Audio Out	Stereo Audio Jack (3.5 mm)
Internal Speakers	2W x 2
Power	
Power Supply	External
Power Requirements	DC 12V, 5.0A
On Mode	20W (On)
Standby Mode	< 0.5W
Off Mode	< 0.3W
Operating Conditions	
Temperature	0°C-40°C (32°F-104°F)
Humidity	10%-85% (non-condensing)
Storage Conditions	
Temperature	-20°C-60°C (-4°F-140°F)
Humidity	5%-95% (non-condensing)
Mounting	
VESA FPM/PMI	Yes (100 x 100 mm)
Stand	
Tilt	-5° to 20°
Pivot	0° to 90°
Swivel	± 45°
Height Adjustment	0-120 mm
Security	
Kensington Security Slot	Yes
Dimensions	
Product with Base (W x H x D)	612.2 x 557.0 x 190.0 mm (24.1" x 21.9" x 7.5")
Product w/o Base (W x H x D)	612.2 x 336.3 x 46.7 mm (24.1" x 13.2" x 1.8")
Packaging (W x H x D)	696.0 x 437.0 x 188.0 mm (27.4" x 17.2" x 7.4")
Weight	
Product with Base	6.2 kg (13.7 lb)
Product w/o Base	3.9 kg (8.6 lb)
Packaging	7.9 kg (17.4 lb)
Regulation Approval	
Certifications & Compliance	CE, LVD, WEEE, RoHS, REACH
Power Adaptor Certifications	CE, BSMI, CCC, CB, WEEE, cUL, FCC, PSE, IEC/EN 60601-1, IEC/EN 60601-1-2
Accessories	
Supplied	HDMI Cable, Power Adaptor, Power Cord, Quick Start Guide
Optional Accessories	
Ceiling Mount	CMP-01 + WMK-03
Wall Mount	WMA-01, WMK-01, WMK-03, PMK-01
Desk Mount	DMC-01, DMC-02D, DMS-01D, ES-02

