

RFQ nr.: **RFQ/MOL/CO/24/39** from **14.08.2024**

The object of the acquisition: **Fire emergency tools**

| Item/Service | Model | Country of Origin | Manufacturer | Full Technical Specification Requested by Contracting Authority | Full Technical Specification Proposed by Tenderer | Reference Standards |
|--|--|-------------------|-------------------|---|--|---------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| Fire emergency ladder (3 story) | 1047154 THREE-STORY PORTABLE FIRE ESCAPE LADDER, 24 FEET | Mexico | BRK Brands, Inc., | Ladder | <p>Model 1047154 Product Height 24 ft Product Length 13.3 in Product Width 4.5 in Product Weight 30 lb</p> <p>The First Alert Three-Story Portable Fire Escape Ladder helps prepare you for fires and other emergencies by giving you a vital, dependable means of escape through a window. This 24-foot ladder can hold up to 375 pounds at a time. This durable emergency escape ladder features a steel and nylon construction. The fire safety ladder can be used on standard windowsills, can be stored under a bed or in a closet for easy access, and comes fully assembled.</p> <p>Fully assembled 24-foot fire escape ladder offers a dependable means of escape to safety from third story windows Durable steel and nylon construction can</p> | |

| | | | | | | |
|---|------------------------|--------|--------------------------------|-------------------|--|--|
| | | | | | <p>safely hold up to 375 pounds at a time</p> <p>Slip-resistant rungs and steel stabilizers provide a steady foothold</p> <p>Extra-wide hooks work with almost any windowsill measuring at least 20 inches wide, 32 inches high, and 6 to 13 inches deep</p> <p>Tested to ASTM standards</p> | |
| Fire extinguisher (OP8, Type ABCE) | Fire extinguisher OP-8 | Russia | MELANTI OOO | Fire extinguisher | <p>The OP-8 fire extinguisher is used to equip cars and premises with a small area. These powder fire extinguishers are charged with extinguishing powder and pumped under pressure with displacing gas up to 16 atmospheres. It is intended for extinguishing fires of ABCE classes (A - solids, B - liquids, C - flammable gases, E - electrical equipment with voltage up to 1000V).</p> <p>The fire extinguisher must be recharged immediately after use or at least once every 5 years. When using the fire extinguisher in vehicles, it must be recharged at least once every 1 year.</p> <p>Additional information: Brand Melanti Type OP-8 powder fire extinguisher Weight of extinguishing agent 8,0±0,4 kg Gross weight, not more than 10,3±0,5 kg Fire extinguishing agent jet length not less than 4.0 m class B 144 B Class A 4 A Assembly height 555 mm Length 195 mm Width 159 mm Colour Red</p> | |
| Emergency light (for stairs) | EL-2-W-BBx2 | USA | Light Fixture Industries, Inc. | Emergency light | <p>FEATURES</p> <p>UL 924, NEC, OSHA and NFPA 101 Life Safety Code</p> <p>Listed for damp location</p> <p>Two fully adjustable, glare-free LED lighting heads</p> <p>LED indicator light with push-to-test switch</p> | |

| | | | | | |
|---|-----------------------|---------|-------------|-------------------|--|
| | | | | | Lightweight, injection molded, 5VA flame retardant thermoplastic housing 120/277 VAC operation Universal mounting plate Short circuit, voltage surge, brown out and low battery voltage disconnect protected Dimensions Height 4.5" Depth 3.125" Length 12.312" Weight 6.00 lb |
| Left exit sign - 15 pcs Right exit sign - 15 pcs Fire extinguisher sign - 35 pcs | Signs | Moldova | Soling SA | Fire safety signs | Left exit sign - 15 pcs Right exit sign - 15 pcs Fire extinguisher sign - 35 pcs |
| Fire blanket | Fire blanket(1.5m*2m) | Russia | MELANTI OOO | Fire blanket | Fire blankets, are a reliable means of extinguishing fires and providing safety in a variety of situations. The fire blanket is designed to extinguish different classes of fires including hot solids (Class A), flammable liquids (Class B), combustible gases (Class C) and electrical equipment energised up to 1000 volts (Class E). It is a versatile means of extinguishing fire quickly and effectively in a variety of scenarios. It is important to note that the blanket does not contain carcinogenic or harmful to health asbestos fibres. It also does not conduct electricity, is not subject to shrinkage when exposed to high temperatures and is resistant to aggressive environments. The operating temperature is an impressive 600°C. |

Tax ID (Codul fiscal): 1003600087058

VAT ID (TVA): 0500350

Bank Details:

Bank Name: 'FinComBank' SA, suc. Nr.1 Chisinau

Bank Code: FTMDMD2X735

IBAN: MD19FT222450100004920498 (in MDL)

Legal Address: MD-2071, Moldova, Chisinau, str. Alba-Iulia 77/16-ap.59

Contact Information:

Phone: 022 800 830

Email: moldova_soling@mail.ru

Director: Ruslan Dubic

Website: www.soling.md

Semnat _____ Numele, Prenumele: **Dubic Ruslan**. In calitate de: **Director**

Ofertantul: Soling SA, Adresa: or. Chisinau, str. Alba-Iulia 77/16-ap.59

