



AZUR INSULATION
Smart Supply

DECLARATION OF PERFORMANCE

Performans Beyanı

No: 02

1. Unique identification code of the product type / Ürün tipi kimlik kodu	AZURFLEX – Thermal Insulation Products AZURFLEX – Isı Yalıtım Mamülleri Non Faced Products / Kaplamasız Ürünler AZURFLEX PIPE / AZURFLEX BORU
2. Intended use/es / Kullanım amacı/ amaçları	Thermal insulation products for building equipment and industrial installations – factory made flexible elastomeric foam (FEF) products. Tesisat ve endüstriyel uygulamalar için ısı yalıtım mamülleri – Fabrika yapımı esnek elastomeric (FEF) ürünler.
3. Manufacturer/ İmalatçı	AZUR YALITIM SANAYİ VE TİCARET A.Ş. Saray Mahallesi Küçüksu Caddesi No:64/A Antasya Residence Daire:90 Ümraniye / İstanbul
4. Authorised representative / Yetkili Temsilci	Not applicable / Yok
5. System/s of AVCP / Performansın Değişmezliğinin Değerlendirilmesi ve Doğrulanması Sistemi/Sistemleri	System 1 / Sistem 1
6a. Harmonized standard / Uyumlaştırılmış Standart Notified body/ies/ Onaylanmış Kuruluş(lar)	EN 14304:2009+A1:2013 Technický a Zkušební Ústav Stavební Praha, s. p. -TZÚS NB - 1020

7. Declared Performance/s Beyan Edilen Performanslar

Essential characteristics Temel Karakteristikler	Performance Performans					Harmonized Technical Specification Uyumlaştırılmış Teknik Şartname
Product / Ürün	AZURFLEX					EN 14304:2009+ A1:2013
Thermal Conductivity / Isıl İletkenlik (EN ISO 8497)	-20°C	0°C	25°C	50°C	75°C	
	0,034 λ	0,036 λ	0,039 λ	0,040 λ	0,041 λ	
Reaction to Fire / Yangına Tepki (EN 13501-1)	B ₁ - s2 - d0					
Length / Boy (EN 13467)	± 1.5%					
Thickness / Kalınlık (EN 13467)	dD ≤ 8 ; ± 1 8 < dD ≤ 18 ; ± 1.5 18 < dD ≤ 31 ; ± 2.5 dD > 31 ; ± 3					
Squareness / Gönyeden Sapma (EN 13467)	dD ≤ 8 ; 3.0 mm					
Water Absorption / Su Emme (EN 13472)	NPD					
Water Vapor Diffusion Resistance / Su Buharı Difüzyon Direnci (EN 13469)	7000					
Trace quantities of water soluble ions and ph value Eser Miktarla Suda Çözünabilir İyon ve PH değeri (EN 13468)	CL500 - pH8					
Sound Absorption / Ses Absorpsiyonu (EN ISO 354)	NPD					
Release of dangerous substances / Tehlikeli Maddeler	NPD					
Continuous glow ing combustion / Sürekli Alevli Yanma	NPD					

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. / Yukarıda tanımlanan yapı malzemesi beyan edilen performanslar grubuna sahiptir. Yapı Malzemeleri Yönetmeliği (305/2011/AB) uyarınca hazırlanan bu performans beyanı sadece yukarıda tanımlanan imalatçının sorumluluğu altında yayımlanır.

Signed for and on behalf of the manufacturer by İmalatçı / İmalatçı adına imzalayan

Name And Function - İsim Ve Görevi: Okan Murat ERENOĞLU / General Manager

Place And Date Of Issue - Düzenlenen Yer Ve Tarih :08.01.2020 ISTANBUL

Signature – İmza

AZUR YALITIM SANAYİ ve TİCARET A.Ş.
SARAY MH. KÜÇÜKSU CD. B BLOK APT. NO.: 64A / B
ÜMRANİYE - İSTANBUL
ALEMDAĞ VERGİ DAİRESİ - 127 030 0407
MERSİS NO: 017105040700011
T.C. SİCİL NO: 196410-5