

TIRE SIZE	PR	TT/TL	LOAD / SPEED INDEX	RIMS		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS(W/LOAD)			
				RECOMMENDED (INCH)	PERMITTED (INCH)	OUTER DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOADED RADIUS (MM)	DYNAMIC ROLLING CIRCUMFERENCE (MM)		
10.0/75-15.3	10 - 10 R/F	TT	123/A8	9.00	-	760	264	352	2368		
10.0/75-15.3	12 R/F	TL	126/A8	9.00	-	760	264	352	2368		
10.0/75-15.3	14	TL	130	9.00	-	760	264	352	2368		
11.5/80-15.3	12R/F	TT/ TL	135/A8	9.00	-	845	290	382	2600		
INFLATION PRESSURE (PSI/BAR)	LOAD CAPACITY PER TIRE, KG										
	SPEED (KM/H)										
	20	25	30	40	50						
	49 / 3.4	2335	2205	2075	1855	1670					
	55 / 3.8	2530	2390	2245	2005	1805					
	60 / 4.1	2750	2595	2440	2180	1960					
	58 / 4,0	2600	2460	2315	2065	1840					
64 / 4,4	2785	2630	2475	2210	1970						
69 / 4.8	3060	2890	2720	2430	2160						
11.5/80-15.3	14	TT/ TL	139/A8	9.00	-	845	290	382	2600		
12.5/80-15.3	12	TL	139/A8	9.00	-	889	307	378	2571		
12.5/80-15.3	16	TL	144/A8	9.00	-	889	307	378	2571		